

# [MS-OXCICAL]: iCalendar to Appointment Object Conversion Algorithm

---

## Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting [iplg@microsoft.com](mailto:iplg@microsoft.com).
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

## Revision Summary

Date	Revision History	Revision Class	Comments
04/04/2008	0.1		Initial Availability.
04/25/2008	0.2		Revised and updated property names and other technical content.
06/27/2008	1.0		Initial Release.
08/06/2008	1.01		Revised and edited technical content.
09/03/2008	1.02		Revised and edited technical content.
10/01/2008	1.03		Revised and edited technical content.
12/03/2008	1.04		Updated IP notice.
03/04/2009	1.05		Revised and edited technical content.
04/10/2009	2.0		Updated technical content and applicable product releases.
07/15/2009	3.0	Major	Revised and edited for technical content.
11/04/2009	4.0.0	Major	Updated and revised the technical content.
02/10/2010	4.0.0	None	Version 4.0.0 release
05/05/2010	4.1.0	Minor	Updated the technical content.
08/04/2010	4.2	Minor	Clarified the meaning of the technical content.
11/03/2010	4.3	Minor	Clarified the meaning of the technical content.
03/18/2011	5.0	Major	Significantly changed the technical content.
08/05/2011	5.1	Minor	Clarified the meaning of the technical content.
10/07/2011	6.0	Major	Significantly changed the technical content.
01/20/2012	7.0	Major	Significantly changed the technical content.
04/27/2012	7.1	Minor	Clarified the meaning of the technical content.
07/16/2012	7.1	No change	No changes to the meaning, language, or formatting of the technical content.
10/08/2012	8.0	Major	Significantly changed the technical content.

# Table of Contents

<b>1 Introduction</b>	<b>7</b>
1.1 Glossary	7
1.2 References	8
1.2.1 Normative References	8
1.2.2 Informative References	9
1.3 Overview	9
1.4 Relationship to Protocols and Other Algorithms	9
1.5 Applicability Statement	10
1.6 Standards Assignments	10
<b>2 Algorithm Details</b>	<b>11</b>
2.1 Common Algorithm Details	11
2.1.1 Abstract Data Model	11
2.1.2 Initialization	11
2.1.3 Processing Rules	11
2.1.3.1 Hierarchy of Components, Properties, and Parameters	16
2.1.3.1.1 Component: VCALENDAR	16
2.1.3.1.1.1 Property: METHOD	16
2.1.3.1.1.2 Property: PRODID	17
2.1.3.1.1.3 Property: VERSION	17
2.1.3.1.1.4 Property: X-CALEND	18
2.1.3.1.1.4.1 Parameter: TZID	18
2.1.3.1.1.5 Property: X-CALSTART	18
2.1.3.1.1.5.1 Parameter: TZID	19
2.1.3.1.1.6 Property: X-CLIPEND	19
2.1.3.1.1.6.1 Parameter: TZID	19
2.1.3.1.1.7 Property: X-CLIPSTART	20
2.1.3.1.1.7.1 Parameter: TZID	20
2.1.3.1.1.8 Property: X-MICROSOFT-CALSCALE	20
2.1.3.1.1.9 Property: X-MS-OLK-FORCEINSPECTOROPEN	23
2.1.3.1.1.10 Property: X-MS-WKHRDAYS	23
2.1.3.1.1.11 Property: X-MS-WKHREND	23
2.1.3.1.1.11.1 Parameter: TZID	24
2.1.3.1.1.12 Property: X-MS-WKHRSTART	24
2.1.3.1.1.12.1 Parameter: TZID	24
2.1.3.1.1.13 Property: X-OWNER	25
2.1.3.1.1.13.1 Parameter: CN	25
2.1.3.1.1.14 Property: X-PRIMARY-CALENDAR	25
2.1.3.1.1.15 Property: X-PUBLISHED-TTL	26
2.1.3.1.1.16 Property: X-WR-CALDESC	26
2.1.3.1.1.17 Property: X-WR-CALNAME	26
2.1.3.1.1.18 Property: X-WR-RELCALID	27
2.1.3.1.1.19 Component: VTIMEZONE	27
2.1.3.1.1.19.1 Property: TZID	29
2.1.3.1.1.19.2 Component: STANDARD	30
2.1.3.1.1.19.2.1 Property: DTSTART	30
2.1.3.1.1.19.2.2 Property: RRULE	32
2.1.3.1.1.19.2.3 Property: TZNAME	33
2.1.3.1.1.19.2.4 Property: TZOFFSETFROM	33
2.1.3.1.1.19.2.5 Property: TZOFFSETTO	34

2.1.3.1.1.19.3	Component: DAYLIGHT	34
2.1.3.1.1.19.3.1	Property: DTSTART	35
2.1.3.1.1.19.3.2	Property: RRULE	35
2.1.3.1.1.19.3.3	Property: TZNAME	35
2.1.3.1.1.19.3.4	Property: TZOFFSETFROM	35
2.1.3.1.1.19.3.5	Property: TZOFFSETTO	36
2.1.3.1.1.20	Component: VEVENT	36
2.1.3.1.1.20.1	Property: ATTACH	36
2.1.3.1.1.20.1.1	Parameter: ENCODING	39
2.1.3.1.1.20.1.2	Parameter: FMTTYPE	39
2.1.3.1.1.20.1.3	Parameter: VALUE	39
2.1.3.1.1.20.1.4	Parameter: X-FILENAME	40
2.1.3.1.1.20.2	Property: ATTENDEE	40
2.1.3.1.1.20.2.1	Parameter: CN	43
2.1.3.1.1.20.2.2	Parameter: CUTYPE	43
2.1.3.1.1.20.2.3	Parameter: PARTSTAT	44
2.1.3.1.1.20.2.4	Parameter: ROLE	45
2.1.3.1.1.20.2.5	Parameter: RSVP	45
2.1.3.1.1.20.2.6	Parameter: X-MS-OLK-RESPTIME	46
2.1.3.1.1.20.3	Property: CATEGORIES	46
2.1.3.1.1.20.4	Property: CLASS	47
2.1.3.1.1.20.5	Property: COMMENT	47
2.1.3.1.1.20.6	Property: CONTACT	47
2.1.3.1.1.20.7	Property: CREATED	48
2.1.3.1.1.20.8	Property: DTEND	48
2.1.3.1.1.20.8.1	Parameter: TZID	49
2.1.3.1.1.20.8.2	Parameter: VALUE	50
2.1.3.1.1.20.9	Property: DTSTAMP	50
2.1.3.1.1.20.9.1	Parameter: TZID	51
2.1.3.1.1.20.10	Property: DTSTART	51
2.1.3.1.1.20.10.1	Parameter: TZID	52
2.1.3.1.1.20.10.2	Parameter: VALUE	52
2.1.3.1.1.20.11	Property: DESCRIPTION	53
2.1.3.1.1.20.11.1	Parameter: LANGUAGE	53
2.1.3.1.1.20.12	Property: DURATION	53
2.1.3.1.1.20.13	Property: EXDATE	54
2.1.3.1.1.20.13.1	Parameter: TZID	55
2.1.3.1.1.20.13.2	Parameter: VALUE	55
2.1.3.1.1.20.14	Property: LAST-MODIFIED	55
2.1.3.1.1.20.15	Property: LOCATION	56
2.1.3.1.1.20.15.1	Parameter: ALTREP	56
2.1.3.1.1.20.15.2	Parameter: LANGUAGE	56
2.1.3.1.1.20.16	Property: ORGANIZER	57
2.1.3.1.1.20.16.1	Parameter: CN	58
2.1.3.1.1.20.17	Property: PRIORITY	58
2.1.3.1.1.20.18	Property: RDATE	59
2.1.3.1.1.20.18.1	Parameter: TZID	62
2.1.3.1.1.20.18.2	Parameter: VALUE	62
2.1.3.1.1.20.19	Property: RRULE	62
2.1.3.1.1.20.20	Property: RECURRENCE-ID	62
2.1.3.1.1.20.20.1	Parameter: TZID	64
2.1.3.1.1.20.20.2	Parameter: VALUE	65
2.1.3.1.1.20.21	Property: RESOURCES	65

2.1.3.1.1.20.22	Property: SEQUENCE .....	66
2.1.3.1.1.20.23	Property: STATUS.....	66
2.1.3.1.1.20.24	Property: SUMMARY.....	66
2.1.3.1.1.20.24.1	Parameter: LANGUAGE .....	67
2.1.3.1.1.20.25	Property: TRANSP.....	67
2.1.3.1.1.20.26	Property: UID .....	68
2.1.3.1.1.20.27	Property: X-ALT-DESC .....	71
2.1.3.1.1.20.27.1	Parameter: FMTTYPE .....	71
2.1.3.1.1.20.28	Property: X-MICROSOFT-CDO-ALLDAYEVENT .....	72
2.1.3.1.1.20.29	Property: X-MICROSOFT-CDO-APPT-SEQUENCE .....	72
2.1.3.1.1.20.30	Property: X-MICROSOFT-CDO-ATTENDEE-CRITICAL-CHANGE ....	72
2.1.3.1.1.20.31	Property: X-MICROSOFT-CDO-BUSYSTATUS .....	73
2.1.3.1.1.20.32	Property: X-MICROSOFT-CDO-IMPORTANCE .....	73
2.1.3.1.1.20.33	Property: X-MICROSOFT-CDO-INSTTYPE .....	74
2.1.3.1.1.20.34	Property: X-MICROSOFT-CDO-INTENDEDSTATUS .....	74
2.1.3.1.1.20.35	Property: X-MICROSOFT-CDO-OWNERAPPTID .....	74
2.1.3.1.1.20.36	Property: X-MICROSOFT-CDO-OWNER-CRITICAL-CHANGE .....	75
2.1.3.1.1.20.37	Property: X-MICROSOFT-CDO-REPLYTIME .....	75
2.1.3.1.1.20.38	Property: X-MICROSOFT-DISALLOW-COUNTER .....	75
2.1.3.1.1.20.39	Property: X-MICROSOFT-EXDATE .....	76
2.1.3.1.1.20.39.1	Parameter: VALUE .....	76
2.1.3.1.1.20.40	Property: X-MICROSOFT-ISDRAFT .....	76
2.1.3.1.1.20.41	Property: X-MICROSOFT-MSNCALENDAR-ALLDAYEVENT.....	77
2.1.3.1.1.20.42	Property: X-MICROSOFT-MSNCALENDAR-BUSYSTATUS .....	77
2.1.3.1.1.20.43	Property: X-MICROSOFT-MSNCALENDAR-IMPORTANCE .....	77
2.1.3.1.1.20.44	Property: X-MICROSOFT-MSNCALENDAR-INTENDEDSTATUS.....	78
2.1.3.1.1.20.45	Property: X-MICROSOFT-RRULE .....	78
2.1.3.1.1.20.45.1	Parameter: VALUE .....	78
2.1.3.1.1.20.45.2	Parameter: X-MICROSOFT-ISLEAPMONTH.....	79
2.1.3.1.1.20.46	Property: X-MS-OLK-ALLOWEXTERNCHECK .....	79
2.1.3.1.1.20.47	Property: X-MS-OLK-APPTLASTSEQUENCE.....	79
2.1.3.1.1.20.48	Property: X-MS-OLK-APPTSEQTIME .....	80
2.1.3.1.1.20.48.1	Parameter: TZID.....	80
2.1.3.1.1.20.49	Property: X-MS-OLK-AUTOFILLLOCATION.....	80
2.1.3.1.1.20.50	Property: X-MS-OLK-AUTOSTARTCHECK.....	80
2.1.3.1.1.20.51	Property: X-MS-OLK-COLLABORATEDOC .....	81
2.1.3.1.1.20.52	Property: X-MS-OLK-CONFCHK .....	81
2.1.3.1.1.20.53	Property: X-MS-OLK-CONFTYPE.....	81
2.1.3.1.1.20.54	Property: X-MS-OLK-DIRECTORY.....	81
2.1.3.1.1.20.55	Property: X-MS-OLK-MWSURL.....	82
2.1.3.1.1.20.56	Property: X-MS-OLK-NETSHOWURL .....	82
2.1.3.1.1.20.57	Property: X-MS-OLK-ONLINEPASSWORD .....	82
2.1.3.1.1.20.58	Property: X-MS-OLK-ORGALIAS .....	82
2.1.3.1.1.20.59	Property: X-MS-OLK-ORIGALEND .....	83
2.1.3.1.1.20.60	Property: X-MS-OLK-ORIGINALSTART .....	83
2.1.3.1.1.20.61	Property: X-MS-OLK-SENDER.....	83
2.1.3.1.1.20.61.1	Parameter: CN .....	84
2.1.3.1.1.20.62	Component: VALARM .....	84
2.1.3.1.1.20.62.1	Property: TRIGGER .....	85
2.1.3.1.1.20.62.2	Property: ACTION .....	86
2.1.3.1.1.20.62.3	Property: DESCRIPTION .....	86
2.1.3.2	Additional Information on Recurrences .....	86
2.1.3.2.1	iCalendar Recurrence Syntax .....	86

2.1.3.2.1.1	Recurrence Part: FREQ.....	86
2.1.3.2.1.2	Recurrence Part: INTERVAL.....	87
2.1.3.2.1.3	Recurrence Part: BYMINUTE.....	87
2.1.3.2.1.4	Recurrence Part: BYHOUR.....	87
2.1.3.2.1.5	Recurrence Part: BYMONTHDAY.....	88
2.1.3.2.1.6	Recurrence Part: BYDAY.....	88
2.1.3.2.1.7	Recurrence Part: BYMONTH.....	89
2.1.3.2.1.8	Recurrence Part: BYSETPOS.....	89
2.1.3.2.1.9	Recurrence Part: WKST.....	89
2.1.3.2.1.10	Recurrence Part: UNTIL.....	90
2.1.3.2.1.11	Recurrence Part: COUNT.....	90
2.1.3.2.2	Recurrence Templates.....	90
2.1.3.2.2.1	Template: Daily Recurrences.....	91
2.1.3.2.2.2	Template: Weekly Recurrences.....	95
2.1.3.2.2.3	Template: Monthly Recurrences.....	98
2.1.3.2.2.4	Template: Monthly Nth Recurrences.....	101
2.1.3.2.2.5	Template: Yearly Recurrences.....	103
2.1.3.2.2.6	Template: Yearly Nth Recurrences.....	106
2.1.3.2.3	End-of-Month Concerns.....	108
2.1.3.2.4	Legacy UNTIL Concerns.....	108
2.1.3.3	Additional Rules for MIME Messages.....	108
2.2	Calendar Object Properties.....	109
2.2.1	PidLidInboundICalStream.....	109
2.2.2	PidLidSingleBodyICal.....	109
2.2.3	PidNameLocationUrl.....	109
<b>3</b>	<b>Algorithm Examples.....</b>	<b>110</b>
3.1	Birthday Calendar for 2008.....	110
3.2	Schedule for the Week of June 16, 2008.....	138
3.3	Single Meeting Scenario.....	177
3.3.1	Organizer's Meeting Request.....	177
3.3.2	Attendee's Meeting Acceptance.....	187
3.3.3	Organizer's Cancellation.....	191
3.4	Recurring Meeting Scenario.....	202
3.4.1	Organizer's Meeting Request.....	202
3.4.2	Organizer's Cancellation of an Instance.....	213
3.4.3	Organizer's Location Change of an Instance.....	223
3.4.4	Attendee's Tentative Acceptance of the Series.....	235
<b>4</b>	<b>Security.....</b>	<b>241</b>
4.1	Security Considerations for Implementers.....	241
4.2	Index of Security Parameters.....	241
<b>5</b>	<b>Appendix A: Product Behavior.....</b>	<b>242</b>
<b>6</b>	<b>Change Tracking.....</b>	<b>262</b>
<b>7</b>	<b>Index.....</b>	<b>271</b>

# 1 Introduction

The iCalendar file format, as described in [\[RFC2445\]](#), describes an extensible text structure that is capable of serializing a wide variety of calendar data, including **meeting requests**, task items, **free/busy status**, and exported calendars.

The iCalendar to Appointment Object Conversion Algorithm describes how applications can import appointments in the iCalendar file format to a **Calendar object**, as described in [\[MS-OXOCAL\]](#), and export Calendar objects to appointments in the iCalendar file format.

Section 2 of this specification is normative and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in RFC 2119. Section 1.6 is also normative but cannot contain those terms. All other sections and examples in this specification are informative.

## 1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

**Augmented Backus-Naur Form (ABNF)**  
**code page**  
**common name (CN)**  
**Coordinated Universal Time (UTC)**

The following terms are defined in [\[MS-OXGLOS\]](#):

**address book**  
**Address Book object**  
**Attachment object**  
**attachments table**  
**base64 encoding**  
**binary large object (BLOB)**  
**calendar**  
**Calendar object**  
**contact**  
**counter proposal**  
**delegate**  
**floating**  
**Folder object**  
**free/busy status**  
**Hypertext Markup Language (HTML)**  
**meeting**  
**meeting request**  
**Meeting Workspace**  
**Message object**  
**MIME message**  
**MIME part**  
**Multipurpose Internet Mail Extensions (MIME)**  
**one-off EntryID**  
**organizer**  
**recipient**  
**recipient table**  
**recurrence part**  
**recurrence pattern**  
**Recurring Calendar object**  
**reminder**

**Rich Text Format (RTF)**  
**signal time**  
**Simple Mail Transfer Protocol (SMTP)**  
**store**  
**Uniform Resource Identifier (URI)**  
**Uniform Resource Locator (URL)**  
**Web Distributed Authoring and Versioning Protocol (WebDAV)**

The following terms are specific to this document:

**primary calendar:** The calendar that contains free/busy information for a specific user or resource. It enables a user or resource to schedule their appointments and other types of events, and the Calendar objects within it are used to process and respond to meeting requests.

**week independent:** A BYDAY recurrence part that does not specify any week numbers.

**MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

## 1.2 References

References to Microsoft Open Specifications documentation do not include a publishing year because links are to the latest version of the technical documents, which are updated frequently. References to other documents include a publishing year when one is available.

### 1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com). We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[MS-LCID] Microsoft Corporation, "[Windows Language Code Identifier \(LCID\) Reference](#)".

[MS-OXCDATA] Microsoft Corporation, "[Data Structures](#)".

[MS-OXCMAIL] Microsoft Corporation, "[RFC2822 and MIME to E-Mail Object Conversion Algorithm](#)".

[MS-OXOABK] Microsoft Corporation, "[Address Book Object Protocol Specification](#)".

[MS-OXOCAL] Microsoft Corporation, "[Appointment and Meeting Object Protocol Specification](#)".

[MS-OXPROPS] Microsoft Corporation, "[Exchange Server Protocols Master Property List](#)".

[MS-OXRTFCP] Microsoft Corporation, "[Rich Text Format \(RTF\) Compression Algorithm](#)".

[MS-OXRTFEX] Microsoft Corporation, "[Rich Text Format \(RTF\) Extensions Algorithm](#)".

[RFC1766] Alvestrand, H., "Tags for the Identification of Languages", RFC 1766, March 1995, <http://www.ietf.org/rfc/rfc1766.txt>

[RFC2045] Freed, N., and Borenstein, N., "Multipurpose Internet Mail Extensions (MIME) Part One: Format of Internet Message Bodies", RFC 2045, November 1996, <http://ietf.org/rfc/rfc2045.txt>



[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC2368] Hoffman, P., Masinter, L., and Zawinski, J., "The mailto URL scheme", RFC 2368, July 1998, <http://www.rfc-editor.org/rfc/rfc2368.txt>

[RFC2392] Levinson, E., "Content-ID and Message-ID Uniform Resource Locators", RFC 2392, August 1998, <http://www.rfc-editor.org/rfc/rfc2392.txt>

[RFC2445] Dawson, F., and Stenerson, D., "Internet Calendaring and Scheduling Core Object Specification (iCalendar)", RFC 2445, November 1998, <http://www.rfc-editor.org/rfc/rfc2445.txt>

[RFC2446] Silverberg, S., Mansour, S., Dawson, F., and Hopson, R., "iCalendar Transport-Independent Interoperability Protocol (iTIP) Scheduling Events, BusyTime, To-Dos, and Journal Entries", RFC 2446, November 1998, <http://www.ietf.org/rfc/rfc2446.txt>

[RFC3986] Berners-Lee, T., Fielding, R., and Masinter, L., "Uniform Resource Identifier (URI): Generic Syntax", STD 66, RFC 3986, January 2005, <http://www.ietf.org/rfc/rfc3986.txt>

[RFC5234] Crocker, D., Ed., and Overell, P., "Augmented BNF for Syntax Specifications: ABNF", STD 68, RFC 5234, January 2008, <http://www.rfc-editor.org/rfc/rfc5234.txt>

### 1.2.2 Informative References

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MS-OXCMMSG] Microsoft Corporation, "[Message and Attachment Object Protocol Specification](#)".

[MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)".

[MS-OXOMSG] Microsoft Corporation, "[E-Mail Object Protocol Specification](#)".

[MS-OXPROTO] Microsoft Corporation, "[Exchange Server Protocols System Overview](#)".

[RFC2447] Dawson, F., Mansour, S., and Silverberg, S., "iCalendar Message-Based Interoperability Protocol (iMIP)", RFC 2447, November 1998, <http://www.rfc-editor.org/rfc/rfc2447.txt>

### 1.3 Overview

This algorithm enables the iCalendar file format to be used by a Calendar object application, as described in [\[MS-OXOCAL\]](#), to communicate with other calendaring systems over transports that do not support Calendar objects. More specifically, the algorithm enables iCalendar data to be imported into a Calendar object and Calendar objects to be exported as iCalendar data.

### 1.4 Relationship to Protocols and Other Algorithms

This algorithm enables a mapping between the iCalendar file format (as described in [\[RFC2445\]](#)) and a Calendar object (as described in [\[MS-OXOCAL\]](#)), which can be updated and sent using the protocols described in [\[MS-OXCMMSG\]](#) and [\[MS-OXOMSG\]](#).

When used as a meeting request, the iCalendar file format can be embedded as a **MIME** part in an e-mail as described in [\[RFC2447\]](#) and [\[MS-OXCMAIL\]](#).

For conceptual background information and overviews of the relationships and interactions between this and other protocols, see [\[MS-OXPROTO\]](#).

## 1.5 Applicability Statement

This algorithm is applicable for scenarios where **calendar** data needs to be transported between a Calendar object source and a non-Calendar object or indeterminate destination. This algorithm is best avoided if 100 percent fidelity is required when transporting calendar data between a Calendar object source and a Calendar object destination.

## 1.6 Standards Assignments

None.

## 2 Algorithm Details

The structure of the iCalendar text stream is specified in [\[RFC2445\]](#) section 4.1.

### 2.1 Common Algorithm Details

#### 2.1.1 Abstract Data Model

None.

#### 2.1.2 Initialization

None.

#### 2.1.3 Processing Rules

Section [2.1.3.1](#) specifies over 100 components, properties, and parameters that can be converted between the iCalendar and Calendar object. The following table provides recommendations regarding the actual relevance of each component, property, and parameter to the scenarios defined by five values of the METHOD property: 'PUBLISH' (PUB), 'REQUEST' (REQ), 'REPLY' (REP), 'COUNTER' (COU), and 'CANCEL' (CAN) (as specified in [\[RFC2446\]](#)).

For clarity, 'No's are represented by a blank space. The '•' symbol is used to indicate hierarchy placement.

Component/Property/Parameter	Section	PUB	REQ	REP	COU	CAN
<b>VCALENDAR</b>	<a href="#">2.1.3.1.1</a>	Yes	Yes	Yes	Yes	Yes
• <b>METHOD</b>	<a href="#">2.1.3.1.1.1</a>	Yes	Yes	Yes	Yes	Yes
• <b>PRODID</b>	<a href="#">2.1.3.1.1.2</a>	Yes	Yes	Yes	Yes	Yes
• <b>VERSION</b>	<a href="#">2.1.3.1.1.3</a>	Yes	Yes	Yes	Yes	Yes
• <b>X-CALEND</b>	<a href="#">2.1.3.1.1.4</a>	Yes				
• • <b>TZID</b>	<a href="#">2.1.3.1.1.4.1</a>	Yes				
• <b>X-CALSTART</b>	<a href="#">2.1.3.1.1.5</a>	Yes				
• • <b>TZID</b>	<a href="#">2.1.3.1.1.5.1</a>	Yes				
• <b>X-CLIPEND</b>	<a href="#">2.1.3.1.1.6</a>	Yes				
• • <b>TZID</b>	<a href="#">2.1.3.1.1.6.1</a>	Yes				
• <b>X-CLIPSTART</b>	<a href="#">2.1.3.1.1.7</a>	Yes				
• • <b>TZID</b>	<a href="#">2.1.3.1.1.7.1</a>	Yes				
• <b>X-MICROSOFT-CALSCALE</b>	<a href="#">2.1.3.1.1.8</a>	Yes	Yes	Yes	Yes	Yes
• <b>X-MS-OLK-FORCEINSPECTOROPEN</b>	<a href="#">2.1.3.1.1.9</a>	Yes				
• <b>X-MS-WKHRDAYS</b>	<a href="#">2.1.3.1.1.10</a>	Yes				

Component/Property/Parameter	Section	PUB	REQ	REP	COU	CAN
• X-MS-WKHREND	<a href="#">2.1.3.1.1.11</a>	Yes				
• • TZID	<a href="#">2.1.3.1.1.11.1</a>	Yes				
• X-MS-WKHRSTART	<a href="#">2.1.3.1.1.12</a>	Yes				
• • TZID	<a href="#">2.1.3.1.1.12.1</a>	Yes				
• X-OWNER	<a href="#">2.1.3.1.1.13</a>	Yes				
• • CN	<a href="#">2.1.3.1.1.13.1</a>	Yes				
• X-PRIMARY-CALENDAR	<a href="#">2.1.3.1.1.14</a>	Yes				
• X-PUBLISHED-TTL	<a href="#">2.1.3.1.1.15</a>	Yes				
• X-WR-CALDESC	<a href="#">2.1.3.1.1.16</a>	Yes				
• X-WR-CALNAME	<a href="#">2.1.3.1.1.17</a>	Yes				
• X-WR-RELCALID	<a href="#">2.1.3.1.1.18</a>	Yes				
• VTIMEZONE	<a href="#">2.1.3.1.1.19</a>	Yes	Yes	Yes	Yes	Yes
• • TZID	<a href="#">2.1.3.1.1.19.1</a>	Yes	Yes	Yes	Yes	Yes
• • STANDARD	<a href="#">2.1.3.1.1.19.2</a>	Yes	Yes	Yes	Yes	Yes
• • • DTSTART	<a href="#">2.1.3.1.1.19.2.1</a>	Yes	Yes	Yes	Yes	Yes
• • • RRULE	<a href="#">2.1.3.1.1.19.2.2</a>	Yes	Yes	Yes	Yes	Yes
• • • TZNAME	<a href="#">2.1.3.1.1.19.2.3</a>	Yes	Yes	Yes	Yes	Yes
• • • TZOFFSETFROM	<a href="#">2.1.3.1.1.19.2.4</a>	Yes	Yes	Yes	Yes	Yes
• • • TZOFFSETTO	<a href="#">2.1.3.1.1.19.2.5</a>	Yes	Yes	Yes	Yes	Yes
• • DAYLIGHT	<a href="#">2.1.3.1.1.19.3</a>	Yes	Yes	Yes	Yes	Yes
• • • DTSTART	<a href="#">2.1.3.1.1.19.3.1</a>	Yes	Yes	Yes	Yes	Yes
• • • RRULE	<a href="#">2.1.3.1.1.19.3.2</a>	Yes	Yes	Yes	Yes	Yes
• • • TZNAME	<a href="#">2.1.3.1.1.19.3.3</a>	Yes	Yes	Yes	Yes	Yes
• • • TZOFFSETFROM	<a href="#">2.1.3.1.1.19.3.4</a>	Yes	Yes	Yes	Yes	Yes
• • • TZOFFSETTO	<a href="#">2.1.3.1.1.19.3.5</a>	Yes	Yes	Yes	Yes	Yes
• VEVENT	<a href="#">2.1.3.1.1.20</a>	Yes	Yes	Yes	Yes	Yes
• • ATTACH	<a href="#">2.1.3.1.1.20.1</a>	Yes				
• • • ENCODING	<a href="#">2.1.3.1.1.20.1.1</a>	Yes				
• • • FMTTYPE	<a href="#">2.1.3.1.1.20.1.2</a>	Yes				
• • • VALUE	<a href="#">2.1.3.1.1.20.1.3</a>	Yes				

Component/Property/Parameter	Section	PUB	REQ	REP	COU	CAN
••• X-FILENAME	<a href="#">2.1.3.1.1.20.1.4</a>	Yes				
•• ATTENDEE	<a href="#">2.1.3.1.1.20.2</a>	Yes	Yes	Yes	Yes	Yes
••• CN	<a href="#">2.1.3.1.1.20.2.1</a>	Yes	Yes	Yes	Yes	Yes
••• CUTYPE	<a href="#">2.1.3.1.1.20.2.2</a>	Yes	Yes	Yes	Yes	Yes
••• PARTSTAT	<a href="#">2.1.3.1.1.20.2.3</a>			Yes	Yes	
••• ROLE	<a href="#">2.1.3.1.1.20.2.4</a>	Yes	Yes	Yes	Yes	Yes
••• RSVP	<a href="#">2.1.3.1.1.20.2.5</a>	Yes	Yes			Yes
•• CATEGORIES	<a href="#">2.1.3.1.1.20.3</a>	Yes	Yes	Yes	Yes	Yes
•• CLASS	<a href="#">2.1.3.1.1.20.4</a>	Yes	Yes	Yes	Yes	Yes
•• COMMENT	<a href="#">2.1.3.1.1.20.5</a>			Yes	Yes	
•• CONTACT	<a href="#">2.1.3.1.1.20.6</a>	Yes	Yes	Yes	Yes	Yes
•• CREATED	<a href="#">2.1.3.1.1.20.7</a>					
•• DTEND	<a href="#">2.1.3.1.1.20.8</a>	Yes	Yes	Yes	Yes	Yes
••• TZID	<a href="#">2.1.3.1.1.20.8.1</a>	Yes	Yes	Yes	Yes	Yes
••• VALUE	<a href="#">2.1.3.1.1.20.8.2</a>	Yes	Yes	Yes	Yes	Yes
•• DTSTAMP	<a href="#">2.1.3.1.1.20.9</a>	Yes	Yes	Yes	Yes	Yes
••• TZID	<a href="#">2.1.3.1.1.20.9.1</a>					
•• DTSTART	<a href="#">2.1.3.1.1.20.10</a>	Yes	Yes	Yes	Yes	Yes
••• TZID	<a href="#">2.1.3.1.1.20.10.1</a>	Yes	Yes	Yes	Yes	Yes
••• VALUE	<a href="#">2.1.3.1.1.20.10.2</a>	Yes	Yes	Yes	Yes	Yes
•• DESCRIPTION	<a href="#">2.1.3.1.1.20.11</a>	Yes	Yes	Yes	Yes	Yes
••• LANGUAGE	<a href="#">2.1.3.1.1.20.11.1</a>	Yes	Yes	Yes	Yes	Yes
•• DURATION	<a href="#">2.1.3.1.1.20.12</a>					
•• EXDATE	<a href="#">2.1.3.1.1.20.13</a>	Yes	Yes	Yes	Yes	Yes
••• TZID	<a href="#">2.1.3.1.1.20.13.1</a>	Yes	Yes	Yes	Yes	Yes
••• VALUE	<a href="#">2.1.3.1.1.20.13.2</a>	Yes	Yes	Yes	Yes	Yes
•• LAST-MODIFIED	<a href="#">2.1.3.1.1.20.14</a>					
•• LOCATION	<a href="#">2.1.3.1.1.20.15</a>	Yes	Yes	Yes	Yes	Yes
••• ALTREP	<a href="#">2.1.3.1.1.20.15.1</a>	Yes	Yes	Yes	Yes	Yes
••• LANGUAGE	<a href="#">2.1.3.1.1.20.15.2</a>	Yes	Yes	Yes	Yes	Yes

Component/Property/Parameter	Section	PUB	REQ	REP	COU	CAN
• • ORGANIZER	<a href="#">2.1.3.1.1.20.16</a>	Yes	Yes	Yes	Yes	Yes
• • • CN	<a href="#">2.1.3.1.1.20.16.1</a>	Yes	Yes	Yes	Yes	Yes
• • PRIORITY	<a href="#">2.1.3.1.1.20.17</a>	Yes	Yes	Yes	Yes	Yes
• • RDATE	<a href="#">2.1.3.1.1.20.18</a>	Yes	Yes	Yes	Yes	Yes
• • • TZID	<a href="#">2.1.3.1.1.20.18.1</a>	Yes	Yes	Yes	Yes	Yes
• • • VALUE	<a href="#">2.1.3.1.1.20.18.2</a>	Yes	Yes	Yes	Yes	Yes
• • RRULE	<a href="#">2.1.3.1.1.20.19</a>	Yes	Yes	Yes	Yes	Yes
• • RECURRENCE-ID	<a href="#">2.1.3.1.1.20.20</a>	Yes	Yes	Yes	Yes	Yes
• • • TZID	<a href="#">2.1.3.1.1.20.20.1</a>	Yes	Yes	Yes	Yes	Yes
• • • VALUE	<a href="#">2.1.3.1.1.20.20.2</a>	Yes	Yes	Yes	Yes	Yes
• • RESOURCES	<a href="#">2.1.3.1.1.20.21</a>	Yes	Yes	Yes	Yes	Yes
• • SEQUENCE	<a href="#">2.1.3.1.1.20.22</a>	Yes	Yes	Yes	Yes	Yes
• • STATUS	<a href="#">2.1.3.1.1.20.23</a>					
• • SUMMARY	<a href="#">2.1.3.1.1.20.24</a>	Yes	Yes	Yes	Yes	Yes
• • • LANGUAGE	<a href="#">2.1.3.1.1.20.24.1</a>	Yes	Yes	Yes	Yes	Yes
• • TRANSP	<a href="#">2.1.3.1.1.20.25</a>	Yes	Yes	Yes	Yes	Yes
• • UID	<a href="#">2.1.3.1.1.20.26</a>	Yes	Yes	Yes	Yes	Yes
• • X-ALT-DESC	<a href="#">2.1.3.1.1.20.27</a>	Yes				
• • • FMTTYPE	<a href="#">2.1.3.1.1.20.27.1</a>	Yes				
• • X-MICROSOFT-CDO-ALLDAYEVENT	<a href="#">2.1.3.1.1.20.28</a>	Yes	Yes	Yes	Yes	Yes
• • X-MICROSOFT-CDO-APPT-SEQUENCE	<a href="#">2.1.3.1.1.20.29</a>					
• • X-MICROSOFT-CDO-ATTENDEE-CRITICAL-CHANGE	<a href="#">2.1.3.1.1.20.30</a>		Yes	Yes	Yes	Yes
• • X-MICROSOFT-CDO-BUSYSTATUS	<a href="#">2.1.3.1.1.20.31</a>	Yes	Yes	Yes	Yes	Yes
• • X-MICROSOFT-CDO-IMPORTANCE	<a href="#">2.1.3.1.1.20.32</a>					
• • X-MICROSOFT-CDO-INSTTYPE	<a href="#">2.1.3.1.1.20.33</a>					
• • X-MICROSOFT-CDO-INTENDEDSTATUS	<a href="#">2.1.3.1.1.20.34</a>	Yes	Yes	Yes	Yes	Yes
• • X-MICROSOFT-CDO-OWNERAPPTID	<a href="#">2.1.3.1.1.20.35</a>	Yes	Yes	Yes	Yes	Yes
• • X-MICROSOFT-CDO-OWNER-CRITICAL-CHANGE	<a href="#">2.1.3.1.1.20.36</a>	Yes	Yes	Yes	Yes	Yes

Component/Property/Parameter	Section	PUB	REQ	REP	COU	CAN
• • X-MICROSOFT-CDO-REPLYTIME	<a href="#">2.1.3.1.1.20.37</a>	Yes	Yes	Yes	Yes	Yes
• • X-MICROSOFT-DISALLOW-COUNTER	<a href="#">2.1.3.1.1.20.38</a>	Yes	Yes	Yes	Yes	Yes
• • X-MICROSOFT-EXDATE	<a href="#">2.1.3.1.1.20.39</a>	Yes	Yes	Yes	Yes	Yes
• • • VALUE	<a href="#">2.1.3.1.1.20.39.1</a>	Yes	Yes	Yes	Yes	Yes
• • X-MICROSOFT-ISDRAFT	<a href="#">2.1.3.1.1.20.40</a>	Yes				
• • X-MICROSOFT-MSNCALENDAR-ALLDAYEVENT	<a href="#">2.1.3.1.1.20.41</a>					
• • X-MICROSOFT-MSNCALENDAR-BUSYSTATUS	<a href="#">2.1.3.1.1.20.42</a>					
• • X-MICROSOFT-MSNCALENDAR-IMPORTANCE	<a href="#">2.1.3.1.1.20.43</a>					
• • X-MICROSOFT-MSNCALENDAR-INTENDEDSTATUS	<a href="#">2.1.3.1.1.20.44</a>					
• • X-MICROSOFT-RRULE	<a href="#">2.1.3.1.1.20.45</a>	Yes	Yes	Yes	Yes	Yes
• • • VALUE	<a href="#">2.1.3.1.1.20.45.1</a>	Yes	Yes	Yes	Yes	Yes
• • • X-MICROSOFT-ISLEAPMONTH	<a href="#">2.1.3.1.1.20.45.2</a>	Yes	Yes	Yes	Yes	Yes
• • X-MS-OLK-ALLOWEXTERNCHECK	<a href="#">2.1.3.1.1.20.46</a>					
• • X-MS-OLK-APPTLASTSEQUENCE	<a href="#">2.1.3.1.1.20.47</a>					
• • X-MS-OLK-APPTSEQTIME	<a href="#">2.1.3.1.1.20.48</a>					
• • • TZID	<a href="#">2.1.3.1.1.20.48.1</a>					
• • X-MS-OLK-AUTOFILLLOCATION	<a href="#">2.1.3.1.1.20.49</a>					
• • X-MS-OLK-AUTOSTARTCHECK	<a href="#">2.1.3.1.1.20.50</a>					
• • X-MS-OLK-COLLABORATEDOC	<a href="#">2.1.3.1.1.20.51</a>					
• • X-MS-OLK-CONFCHK	<a href="#">2.1.3.1.1.20.52</a>					
• • X-MS-OLK-CONFTYPE	<a href="#">2.1.3.1.1.20.53</a>					
• • X-MS-OLK-DIRECTORY	<a href="#">2.1.3.1.1.20.54</a>					
• • X-MS-OLK-MWSURL	<a href="#">2.1.3.1.1.20.55</a>					
• • X-MS-OLK-NETSHOWURL	<a href="#">2.1.3.1.1.20.56</a>					
• • X-MS-OLK-ONLINEPASSWORD	<a href="#">2.1.3.1.1.20.57</a>					
• • X-MS-OLK-ORGALIAS	<a href="#">2.1.3.1.1.20.58</a>					
• • X-MS-OLK-ORIGALEND	<a href="#">2.1.3.1.1.20.59</a>				Yes	
• • X-MS-OLK-ORIGINALSTART	<a href="#">2.1.3.1.1.20.60</a>				Yes	

Component/Property/Parameter	Section	PUB	REQ	REP	COU	CAN
• • X-MS-OLK-SENDER	<a href="#">2.1.3.1.1.20.61</a>	Yes				
• • • CN	<a href="#">2.1.3.1.1.20.61.1</a>	Yes				
• • VALARM	<a href="#">2.1.3.1.1.20.62</a>	Yes	Yes			Yes
• • • TRIGGER	<a href="#">2.1.3.1.1.20.62.1</a>	Yes	Yes			Yes
• • • ACTION	<a href="#">2.1.3.1.1.20.62.2</a>	Yes	Yes			Yes
• • • DESCRIPTION	<a href="#">2.1.3.1.1.20.62.3</a>	Yes	Yes			Yes

### 2.1.3.1 Hierarchy of Components, Properties, and Parameters

This section enumerates all iCalendar components, properties, and parameters that can be mapped to Calendar objects. The hierarchy presented in the header specifies all parent-child relationships between these components, properties, and parameters. Any components, properties, and parameters not specified in this document SHOULD be ignored.

Unless otherwise specified, if the Calendar object property being exported is not set, then the corresponding property SHOULD NOT be exported. Similarly, unless otherwise specified, if the property being imported is not present, then the corresponding Calendar object property SHOULD be left unset.

#### 2.1.3.1.1 Component: VCALENDAR

RFC Reference: [\[RFC2445\]](#) section 4.4

Number of Instances Allowed: 1+

Brief Description: The root component of a valid iCalendar file.

##### Importing to and Exporting from Calendar objects

A valid iCalendar file SHOULD [<1>](#) have exactly one VCALENDAR component as its root.

#### 2.1.3.1.1.1 Property: METHOD

RFC Reference: [\[RFC2445\]](#) section 4.7.2

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Distinguishes normal appointments from meeting requests, responses, and cancellations.

##### Importing to Calendar objects

The METHOD property SHOULD [<2>](#) be imported as the **PidTagMessageClass** ([\[MS-OXPROPS\]](#) section 2.855) and **PidLidAppointmentCounterProposal** ([\[MS-OXPROPS\]](#) section 2.10) of all imported Calendar objects, as specified in the table later in this section. In the case where the METHOD property is set to 'REPLY', the **PidTagMessageClass** has several possible values depending on the PARTSTAT parameter of the ATTENDEE property of the VEVENT component. If the



METHOD property is set to 'REPLY' or 'COUNTER', the iCalendar MUST have exactly one ATTENDEE property and exactly one such PARTSTAT parameter.

In the case where the METHOD property is set to 'REQUEST', 'REPLY', or 'CANCEL', the VCALENDAR file MUST define exactly one appointment.<3>

METHOD	PARTSTAT	PidLidAppointmentCounterProposal	PidTagMessageClass
(default)		FALSE or unset	IPM.Appointment
PUBLISH		FALSE or unset	IPM.Appointment
REQUEST		FALSE or unset	IPM.Schedule.Meeting.Request
REPLY	ACCEPTED	FALSE or unset	IPM.Schedule.Meeting.Resp.Pos
REPLY	TENTATIVE	FALSE or unset	IPM.Schedule.Meeting.Resp.Tent
REPLY	DECLINED	FALSE or unset	IPM.Schedule.Meeting.Resp.Neg
COUNTER	TENTATIVE	TRUE	IPM.Schedule.Meeting.Resp.Tent
CANCEL		FALSE or unset	IPM.Schedule.Meeting.Canceled

### Exporting from Calendar objects

For exports of calendars, the METHOD property MUST be left unset or set to 'PUBLISH'. For exports of individual Calendar objects, the **PidTagMessageClass** and **PidLidAppointmentCounterProposal** of the Calendar object SHOULD<4> be exported as the METHOD property as specified in the table earlier in this section.

#### 2.1.3.1.1.2 Property: PROID

RFC Reference: [\[RFC2445\]](#) section 4.7.3

Number of Instances Allowed: 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Identifies the application that generated the iCalendar file.

### Importing to Calendar objects

When parsing an iCalendar file, if the value of the PROID property begins with the substring '-//Microsoft Corporation//Outlook<SP>' and ends with the substring '<SP>MIMEDIR//EN', where '<SP>' represents the space character (U+0020), and if the integer part of the version number between the two substrings is between 1 and 11 (inclusive), then some behavior changes SHOULD be made as described in section [2.1.3.2.4](#).

### Exporting from Calendar objects

The value assigned to PROID MUST be unique for different implementations and different versions of an iCalendar converter.

#### 2.1.3.1.1.3 Property: VERSION

RFC Reference: [\[RFC2445\]](#) section 4.7.4

Number of Instances Allowed: 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Identifies the version of an iCalendar file.

### **Importing to and Exporting from Calendar objects**

The value of this property MUST be set to '2.0'.

#### **2.1.3.1.1.4 Property: X-CALEND**

RFC Reference: N/A

Number of Instances Allowed: 0, 1, 2

Format: Date-Time ([\[RFC2445\]](#) section 4.3.5)

Brief Description: Identifies the end time of the last instance of an appointment in the iCalendar file.

### **Importing to Calendar objects**

This property SHOULD be ignored.

### **Exporting from Calendar objects**

This property SHOULD<5> be computed as the end time of the last instance of an appointment in the iCalendar file. If the iCalendar contains appointments with **floating** and non-floating end times in such a way that the calendar's end time is dependent on the **recipient's (1)** time zone, the X-CALEND property SHOULD<6> be declared twice: once with a floating calendar end time, and once with a non-floating calendar end time.

#### **2.1.3.1.1.4.1 Parameter: TZID**

RFC Reference: [\[RFC2445\]](#) section 4.2.19

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: In conjunction with a matching VTIMEZONE, specifies the time zone of a Date-Time property provided in local time.

Refer to [\[RFC2445\]](#) section 4.2.19 for additional details on the TZID parameter.

#### **2.1.3.1.1.5 Property: X-CALSTART**

RFC Reference: N/A

Number of Instances Allowed: 0, 1, 2

Format: Date-Time ([\[RFC2445\]](#) section 4.3.5)

Brief Description: Identifies the start time of the first instance of an appointment in the iCalendar file.

### **Importing to Calendar objects**

This property SHOULD be ignored.

#### **Exporting from Calendar objects**

This property SHOULD<7> be computed as the start time of the first instance of an appointment in the iCalendar file. If the iCalendar contains appointments with floating and non-floating start times in such a way that the calendar's start time is dependent on the recipient's (1) time zone, the X-CALSTART property SHOULD<8> be declared twice: once with a floating calendar start time, and once with a non-floating calendar start time.

##### **2.1.3.1.1.5.1 Parameter: TZID**

RFC Reference: [\[RFC2445\]](#) section 4.2.19

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: In conjunction with a matching VTIMEZONE, specifies the time zone of a Date-Time property provided in local time.

Refer to [\[RFC2445\]](#) section 4.2.19 for additional details on the TZID parameter.

##### **2.1.3.1.1.6 Property: X-CLIPEND**

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Date-Time ([\[RFC2445\]](#) section 4.3.5)

Brief Description: Indicates the end of the date range that the user selected for export during the creation of the iCalendar file.

#### **Importing to Calendar objects**

This property SHOULD<9> be ignored.

#### **Exporting from Calendar objects**

This property SHOULD<10> be the end of the date range that the user selected for export. If this iCalendar does not represent a calendar export, this property MUST be omitted.

##### **2.1.3.1.1.6.1 Parameter: TZID**

RFC Reference: [\[RFC2445\]](#) section 4.2.19

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: In conjunction with a matching VTIMEZONE, specifies the time zone of a Date-Time property provided in local time.

Refer to [\[RFC2445\]](#) section 4.2.19 for additional details on the TZID parameter.

### 2.1.3.1.1.7 Property: X-CLIPSTART

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Date-Time ([\[RFC2445\]](#) section 4.3.5)

Brief Description: Indicates the start of the date range that the user selected for export during the creation of the iCalendar file.

#### Importing to Calendar objects

This property SHOULD [<11>](#) be ignored.

#### Exporting from Calendar objects

This property SHOULD [<12>](#) be the start of the date range that the user selected for export. If this iCalendar does not represent a calendar export, this property MUST be omitted.

### 2.1.3.1.1.7.1 Parameter: TZID

RFC Reference: [\[RFC2445\]](#) section 4.2.19

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: In conjunction with a matching VTIMEZONE, specifies the time zone of a Date-Time property provided in local time.

Refer to [\[RFC2445\]](#) section 4.2.19 for additional details on the TZID parameter.

### 2.1.3.1.1.8 Property: X-MICROSOFT-CALSCALE

RFC Reference: N/A

Number of Instances Allowed: 0,1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Identifies the calendar type of a non-Gregorian recurring appointment.

#### Importing to Calendar objects

If this property is specified, then it SHOULD [<13>](#) be imported for every VEVENT that declares an X-MICROSOFT-RRULE.

This property SHOULD [<14>](#) set the **CalendarType** field of the **RecurrencePattern** field of the **AppointmentRecurrencePattern** structure ([\[MS-OXOCAL\]](#) section 2.2.1.44.5) in the **PidLidAppointmentRecur** property ([\[MS-OXOCAL\]](#) section 2.2.1.44). See also sections [2.1.3.2.2.1](#), [2.1.3.2.2.2](#), [2.1.3.2.2.3](#), [2.1.3.2.2.4](#), [2.1.3.2.2.5](#), and [2.1.3.2.2.6](#).

X-MICROSOFT-CALSCALE Value	CalendarType
Not present or empty	0x0000

<b>X-MICROSOFT-CALSCALE Value</b>	<b>CalendarType</b>
string (default)	
Gregorian	0x0001
Gregorian_us	0x0002
Japan	0x0003
Taiwan	0x0004
Korea	0x0005
Hijri	Either 0x0000 or 0x0006, as specified in the table for Hijri calendars that follows (the PatternType field SHOULD <a href="#">&lt;15&gt;</a> also be overwritten as specified in the table for Hijri calendars that follows).
Thai	0x0007
Hebrew	0x0008
GregorianMeFrench	0x0009
GregorianArabic	0x000A
GregorianXlitEnglish	0x000B
GregorianXlitFrench	0x000C
JapanLunar	0x000E
ChineseLunar	0x000F
Saka	0x0010
LunarEtoChn	0x0011
LunarEtoKor	0x0012
LunarRokuyou	0x0013
KoreaLunar	0x0014
Umalqura	0x0017

For appointments with an X-MICROSOFT-CALSCALE value of "Hijri", the value for **PatternType** and **CalendarType** depend upon the imported value of **PatternType**. **PatternType** SHOULD be determined as specified in section [2.1.3.2.2](#). The resulting value SHOULD then be overwritten as specified in the following table.

<b>Imported PatternType Value</b>	<b>Hijri PatternType Value</b>	<b>Hijri CalendarType Value</b>
0x0000	0x0000	0x0006
0x0001	0x0001	0x0006
0x0002	0x000A	0x0000

Imported PatternType Value	Hijri PatternType Value	Hijri CalendarType Value
0x0003	0x000B	0x0000

### Exporting from Calendar objects

Since this property is a child of the VCALENDAR, a VCALENDAR MUST NOT contain any two VEVENTs that would result in different values of X-MICROSOFT-CALSCALE.

If the **CalendarType** field of the **RecurrencePattern** field of the **AppointmentRecurrencePattern** structure is nonzero, then this property SHOULD [<16>](#) be exported as specified in the following table.

CalendarType Value	X-MICROSOFT-CALSCALE Value
0x0001	Gregorian
0x0002	Gregorian_us
0x0003	Japan
0x0004	Taiwan
0x0005	Korea
0x0006	Hijri
0x0007	Thai
0x0008	Hebrew
0x0009	GregorianMeFrench
0x000A	GregorianArabic
0x000B	GregorianXlitEnglish
0x000C	GregorianXlitFrench
0x000E	JapanLunar
0x000F	ChineseLunar
0x0010	Saka
0x0011	LunarEtoChn
0x0012	LunarEtoKor
0x0013	LunarRokuyou
0x0014	KoreaLunar
0x0017	Umalqura

Additionally, for certain values of the **PatternType** field of the **RecurrencePattern** field of the **AppointmentRecurrencePattern** structure, this property SHOULD [<17>](#) be exported as specified in the following table.

Special PatternType Value	X-MICROSOFT-CALSCALE Value
0x000A	Hijri
0x000B	Hijri

### 2.1.3.1.1.9 Property: X-MS-OLK-FORCEINSPECTOROPEN

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Boolean ([RFC2445] section 4.3.2)

Brief Description: Specifies whether or not the iCalendar file only contains one appointment.

#### Importing to Calendar objects

If this property is set to TRUE, the iCalendar stream SHOULD<18> be imported as a single Calendar object, regardless of the number of VEVENT components present in the iCalendar. Note that it is possible for an iCalendar file containing multiple VEVENT components to represent a single appointment through the use of the RECURRENCE-ID property specified in section [2.1.3.1.1.20.20](#).

#### Exporting from Calendar objects

This property SHOULD<19> be set to 'TRUE' if the iCalendar file represents a single appointment rather than a calendar export.

### 2.1.3.1.1.10 Property: X-MS-WKHRDAYS

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Text ([RFC2445] section 4.3.11)

Brief Description: Specifies the days of the week in the calendar owner's workweek.

#### Importing to Calendar objects

This property SHOULD<20> be ignored.

#### Exporting from Calendar objects

If this iCalendar does not represent the **primary calendar** of the owner, this property SHOULD be omitted. Otherwise, this property SHOULD<21> be a comma-delimited list containing any number of the character codes for days of the week specified in section [2.1.3.2.1.6](#).

Each element MUST NOT appear more than once, but the order of the elements does not matter. The syntax of this format is the same as the syntax of a **week independent** BYDAY **recurrence part** specified in [2.1.3.2.1.6](#).

### 2.1.3.1.1.11 Property: X-MS-WKHREND

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Local Time ([\[RFC2445\]](#) section 4.3.12)

Brief Description: Specifies the end time of the calendar owner's workday.

#### **Importing to Calendar objects**

This property SHOULD [<22>](#) be ignored.

#### **Exporting from Calendar objects**

If this iCalendar does not represent the primary calendar of the owner, this property SHOULD be omitted. Otherwise, this property SHOULD [<23>](#) be the end time of the calendar owner's workday, specified as a local time with the TZID parameter (section [2.1.3.1.1.11.1](#)).

### **2.1.3.1.1.11.1 Parameter: TZID**

RFC Reference: [\[RFC2445\]](#) section 4.2.19

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: In conjunction with a matching VTIMEZONE, specifies the time zone of a Date-Time property provided in local time.

Refer to [\[RFC2445\]](#) section 4.2.19 for additional details on the TZID parameter.

### **2.1.3.1.1.12 Property: X-MS-WKHRSTART**

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Local Time ([\[RFC2445\]](#) section 4.3.12)

Brief Description: Specifies the starting time of the calendar owner's workday.

#### **Importing to Calendar objects**

This property SHOULD [<24>](#) be ignored.

#### **Exporting from Calendar objects**

If this iCalendar does not represent the primary calendar of the owner, this property SHOULD be omitted. Otherwise, this property SHOULD [<25>](#) be the start time of the calendar owner's workday, specified as a local time with the TZID parameter (section [2.1.3.1.1.12.1](#)).

### **2.1.3.1.1.12.1 Parameter: TZID**

RFC Reference: [\[RFC2445\]](#) section 4.2.19

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: In conjunction with a matching VTIMEZONE, specifies the time zone of a Date-Time property provided in local time.



Refer to [\[RFC2445\]](#) section 4.2.19 for additional details on the TZID parameter.

#### **2.1.3.1.1.13 Property: X-OWNER**

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: calendar User Address ([\[RFC2445\]](#) section 4.3.3)

Brief Description: Specifies the calendar owner of a primary calendar.

##### **Importing to Calendar objects**

This property SHOULD [<26>](#) be ignored.

##### **Exporting from Calendar objects**

If this iCalendar does not represent the primary calendar of the owner, this property SHOULD be omitted. Otherwise, this property SHOULD [<27>](#) be the e-mail address of the owner.

#### **2.1.3.1.1.13.1 Parameter: CN**

RFC Reference: [\[RFC2445\]](#) section 4.2.2

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Specifies the display name of the owner of a primary calendar.

##### **Importing to Calendar objects**

This parameter SHOULD [<28>](#) be ignored.

##### **Exporting from Calendar objects**

If this iCalendar does not represent the primary calendar of the owner, this parameter SHOULD be omitted. Otherwise, this parameter SHOULD [<29>](#) be the display name of the owner.

#### **2.1.3.1.1.14 Property: X-PRIMARY-CALENDAR**

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Boolean ([\[RFC2445\]](#) section 4.3.2)

Brief Description: Specifies whether or not the iCalendar file represents a primary calendar.

##### **Importing to Calendar objects**

This property SHOULD [<30>](#) be ignored.

##### **Exporting from Calendar objects**

If this iCalendar does not represent the primary calendar of the owner, this property SHOULD be omitted. Otherwise, this property SHOULD [<31>](#) be set to 'TRUE'.

### 2.1.3.1.1.15 Property: X-PUBLISHED-TTL

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Duration ([\[RFC2445\]](#) section 4.3.6)

Brief Description: Specifies a suggested iCalendar file download frequency for clients and servers with sync capabilities.

#### Importing to Calendar objects

This property SHOULD [<32>](#) be ignored.

#### Exporting from Calendar objects

If this iCalendar is being automatically published to a remote location at regular intervals, this property SHOULD [<33>](#) be set to that interval with a minimum granularity of minutes.

### 2.1.3.1.1.16 Property: X-WR-CALDESC

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Specifies the description of the calendar.

#### Importing to Calendar objects

This property SHOULD [<34>](#) be ignored.

#### Exporting from Calendar objects

If this iCalendar represents an export of a calendar, and if the owner has provided a description of the calendar, this property SHOULD [<35>](#) be set to the owner's specified text, which SHOULD [<36>](#) be truncated to a length of 255 WCHARs if the length exceeds 255 WCHARs. The truncation SHOULD NOT [<37>](#) split surrogate pairs.

### 2.1.3.1.1.17 Property: X-WR-CALNAME

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Specifies the name of the calendar.

#### Importing to Calendar objects

This property SHOULD [<38>](#) be imported directly into the **PidTagDisplayName** ([\[MS-OXPROPS\]](#) section 2.745) of the **Folder object** representing the newly-created destination of the imported appointments. Implementations MAY truncate the value to 255 characters and MAY remove carriage return (U+000D) and line feed (U+000A) characters.

## Exporting from Calendar objects

This property MUST be omitted if the iCalendar represents a single appointment or **meeting**.

If this iCalendar represents a calendar export, this property SHOULD [<39>](#) be set to the value of **PidTagDisplayName** on the Folder object representing the calendar being exported.

If the calendar is the owner's primary calendar, this property SHOULD [<40>](#) instead be set to a more descriptive locale-dependent string containing the owner's name (e.g. 'Elizabeth Andersen calendar').

### 2.1.3.1.1.18 Property: X-WR-RELCALID

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Specifies a globally unique identifier for the calendar.

## Importing to Calendar objects

This property SHOULD [<41>](#) be used and persisted by the iCalendar renderer to decide whether the import overwrites an existing calendar or creates a new calendar.

## Exporting from Calendar objects

This property MUST be omitted if the iCalendar represents a single appointment or meeting.

If this iCalendar represents a calendar export, this property SHOULD [<42>](#) be set to a value that will be globally unique for different calendars, but consistent across multiple exports of the same calendar.

### 2.1.3.1.1.19 Component: VTIMEZONE

RFC Reference: [\[RFC2445\]](#) section 4.6.5

Number of Instances Allowed: 0+ [<43>](#)

Brief Description: Specifies any time zones referenced by TZID parameters.

## Importing to Calendar objects

Since TZIDs can be referenced by many properties, including several x-props in the root component, VTIMEZONEs MUST be used to resolve all local times in the iCalendar file, even if the TZID reference occurs before the VTIMEZONE definition. This section discusses how to import a VTIMEZONE into a **PidLidTimeZoneStruct** structure ([\[MS-OXOCAL\]](#) section 2.2.1.39).

Field of the PidLidTimeZoneStruct structure	Value
<b>IBias</b>	See section <a href="#">2.1.3.1.1.19.2.5</a>
<b>IStandardBias</b>	Set to 0x00000000
<b>IDaylightBias</b>	See section <a href="#">2.1.3.1.1.19.3.5</a>
<b>stStandardDate</b>	See sections <a href="#">2.1.3.1.1.19.2.1</a> and <a href="#">2.1.3.1.1.19.2.2</a>

Field of the <b>PidLidTimeZoneStruct</b> structure	Value
<b>stDaylightDate</b>	See sections <a href="#">2.1.3.1.1.19.3.1</a> and <a href="#">2.1.3.1.1.19.3.2</a>
<b>wStandardYear</b>	Set to the <b>wYear</b> field of <b>stStandardDate</b>
<b>wDaylightYear</b>	Set to the <b>wYear</b> field of <b>stDaylightDate</b>

If this VTIMEZONE is imported as **PidLidAppointmentTimeZoneDefinitionRecur** ([\[MS-OXPROPS\]](#) section 2.33), **PidLidAppointmentTimeZoneDefinitionStartDisplay** ([\[MS-OXPROPS\]](#) section 2.34), and/or **PidLidAppointmentTimeZoneDefinitionEndDisplay** ([\[MS-OXPROPS\]](#) section 2.32), [<44>](#) then the following table specifies the contents of the resulting **BLOB** (the structure of this BLOB is specified in [\[MS-OXOCAL\]](#)). See section [2.1.3.1.1.20.8.1](#) and section [2.1.3.1.1.20.10.1](#) for more information.

Field of the <b>BLOB</b>	Value
<b>Major Version</b>	Constant specified by <a href="#">[MS-OXOCAL]</a>
<b>Minor Version</b>	Constant specified by <a href="#">[MS-OXOCAL]</a>
<b>cbHeader</b>	Set to (0x0006 + 0x0002 * <b>cchKeyName</b> )
<b>Reserved</b>	Constant specified by <a href="#">[MS-OXOCAL]</a>
<b>cchKeyName</b>	Set to the number of characters in <b>KeyName</b>
<b>KeyName</b>	See section <a href="#">2.1.3.1.1.19.1</a>
<b>cRules</b>	Set to the number of <b>TZRule</b> structures (as specified in <a href="#">[MS-OXOCAL]</a> section 2.2.1.41.1) in the <b>TZRules</b> field. This value is equal to the number of time zone rules generated by parsing the STANDARD and DAYLIGHT subcomponents.

The following table specifies the contents of each **TZRule** structure in the **TZRules** field.

<b>TZRule</b> structure field	Value
<b>Major Version</b>	Constant specified by <a href="#">[MS-OXOCAL]</a>
<b>Minor Version</b>	Constant specified by <a href="#">[MS-OXOCAL]</a>
<b>Reserved</b>	Constant specified by <a href="#">[MS-OXOCAL]</a>
<b>TZRule flags</b>	Set to 0x0002 for <b>PidLidAppointmentTimeZoneDefinitionStartDisplay</b> and <b>PidLidAppointmentTimeZoneDefinitionEndDisplay</b> . Set to 0x0003 for <b>PidLidAppointmentTimeZoneDefinitionRecur</b> .
<b>wYear</b>	For the first <b>TZRule</b> structure in the array, this field SHOULD be set to 0x0641 but MAY <a href="#">&lt;45&gt;</a> be set to 0x0001. For subsequent <b>TZRule</b> structures, this field MUST be set to the year that corresponds to the time zone rule.
<b>X</b>	Constant specified by <a href="#">[MS-OXOCAL]</a>
<b>IBias</b>	Import the same as the <b>IBias</b> field of a <b>PidLidTimeZoneStruct</b> structure
<b>IStandardBias</b>	Import the same as the <b>IStandardBias</b> field of a <b>PidLidTimeZoneStruct</b> structure

<b>TZRule structure field</b>	<b>Value</b>
<b>IDaylightBias</b>	Import the same as the <b>IDaylightBias</b> field of a <b>PidLidTimeZoneStruct</b> structure
<b>stStandardDate</b>	Import the same as the <b>stStandardDate</b> field of a <b>PidLidTimeZoneStruct</b> structure
<b>stDaylightDate</b>	Import the same as the <b>stDaylightDate</b> field of a <b>PidLidTimeZoneStruct</b> structure

### Exporting from Calendar objects

A VTIMEZONE component MUST be declared for each unique value of any TZID parameters in the iCalendar. Note that the comparison used to match TZID parameters to VTIMEZONE components SHOULD [<46>](#) be case-insensitive.

If exporting a VTIMEZONE from a **PidLidAppointmentTimeZoneDefinitionRecur**, **PidLidAppointmentTimeZoneDefinitionStartDisplay**, or **PidLidAppointmentTimeZoneDefinitionEndDisplay**, the **IBias**, **IStandardBias**, **IDaylightBias**, **stStandardDate**, and **stDaylightDate** subfields of the **TZRule** entry with the TZRULE\_FLAG\_EFFECTIVE\_TZREG (0x0002) bit set in the **TZRule flags** field MUST be exported as a **PidLidTimeZoneStruct** structure as specified in the following subsections. [<47>](#)

#### 2.1.3.1.1.19.1 Property: TZID

RFC Reference: [\[RFC2445\]](#) section 4.8.3.1

Number of Instances Allowed: 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: The name of the time zone. This string will be compared (case-insensitive) [<48>](#) to TZID parameters in the rest of the iCalendar to identify the time zone being referenced by the parameter's parent property.

#### Importing to Calendar objects

This property SHOULD be imported as specified in section [2.1.3.1.1.20.8.1](#) and section [2.1.3.1.1.20.10.1](#).

#### Exporting from Calendar objects

If the system's local time zone is being exported as a VTIMEZONE, then this name MUST be derived from the system API that supplied the time zone.

If the **PidLidTimeZoneStruct** property is being exported as a VTIMEZONE, this name SHOULD be derived from **PidLidTimeZoneDescription** ([\[MS-OXOCAL\]](#) section 2.2.1.40), but MAY be set to any unique string.

If the **PidLidAppointmentTimeZoneDefinitionRecur**, **PidLidAppointmentTimeZoneDefinitionStartDisplay**, or **PidLidAppointmentTimeZoneDefinitionEndDisplay** property is being exported as a VTIMEZONE, then the value of TZID MUST [<49>](#) be derived from the **KeyName** field of the **PidLidAppointmentTimeZoneDefinitionRecur** structure ([\[MS-OXOCAL\]](#) section 2.2.1.41) contained in the property.

In all cases, TZIDs for different time zones MUST be unique, and each unique TZID MUST NOT be defined more than once.

### 2.1.3.1.1.19.2 Component: STANDARD

RFC Reference: [\[RFC2445\]](#) section 4.6.5

Number of Instances Allowed: 1+

Brief Description: A specification of the Standard portion of the time zone.

#### Importing to Calendar objects

If more than one STANDARD component is defined in the VTIMEZONE, only the STANDARD component with the largest DTSTART SHOULD<50> be parsed. Alternatively, implementers MAY<51> parse the first STANDARD component found within the VTIMEZONE, MAY<52> parse all STANDARD components found within the VTIMEZONE that have unique years in their DTSTART subcomponents, or MAY<53> fail to parse the iCalendar stream if more than one STANDARD component is defined in the VTIMEZONE.

#### Exporting from Calendar objects

Exactly one STANDARD component SHOULD be exported for each VTIMEZONE.

### 2.1.3.1.1.19.2.1 Property: DTSTART

RFC Reference: [\[RFC2445\]](#) section 4.8.2.4

Number of Instances Allowed: 1

Format: Date-Time ([\[RFC2445\]](#) section 4.3.5)

Brief Description: The effective start date of this onset of Standard time.

#### Importing to Calendar objects

If this VTIMEZONE component has no DAYLIGHT sub-component, all the bytes in the **stStandardDate** field of the **PidLidTimeZoneStruct** structure MUST be set to 0x00.

If the VTIMEZONE being imported contains one or more DAYLIGHT sub-components and the STANDARD component contains an RRULE property, the fields of the **stStandardDate** field of the **PidLidTimeZoneStruct** structure are set according to the following table.

Field of <b>PidLidTimeZoneStruct.stStandardDate</b>	Value
<b>wYear</b>	Set as specified in section <a href="#">2.1.3.1.1.19.2.2</a> .
<b>wMonth</b>	Set as specified in section <a href="#">2.1.3.1.1.19.2.2</a> .
<b>wDayOfWeek</b>	Set as specified in section <a href="#">2.1.3.1.1.19.2.2</a> .
<b>wDay</b>	Set as specified in section <a href="#">2.1.3.1.1.19.2.2</a> .
<b>wHour</b>	The hour portion of DTSTART
<b>wMinute</b>	The minute portion of DTSTART
<b>wSecond</b>	The second portion of DTSTART

Field of PidLidTimeZoneStruct.stStandardDate	Value
wMilliseconds	Set to 0x0000

If an RRULE property is not specified for this component, the **stStandardDate** field of the **PidLidTimeZoneStruct** structure SHOULD [<54>](#) be imported as specified in the following table. Alternatively, implementers MAY [<55>](#) convert the value of the RDATE property to a SYSTEMTIME and import the resulting value to the **stStandardDate** field, or MAY [<56>](#) convert the value of the DTSTART property to a SYSTEMTIME and import the resulting value to the **stStandardDate** field.

Field of PidLidTimeZoneStruct.stStandardDate	Value
wYear	Set to 0x0000
wMonth	The month portion of DTSTART
wDayOfWeek	The day of the week of the date specified by DTSTART. Possible values are specified later in this section.
wDay	The occurrence of the day of week in the month for the date specified by DTSTART (if this is the 2nd Monday of May, wDay is set to 2). If this is the last occurrence of the day of the week in the month, wDay is set to 0x0005. Possible values are specified later in this section.
wHour	The hour portion of DTSTART
wMinute	The minute portion of DTSTART
wSecond	The second portion of DTSTART
wMilliseconds	Set to 0x0000

The following table lists the possible values of the **wDayOfWeek** subfield of the **stStandardDate** field in the **PidLidTimeZoneStruct** structure.

wDayOfWeek	Meaning
0x0000	Sunday
0x0001	Monday
0x0002	Tuesday
0x0003	Wednesday
0x0004	Thursday
0x0005	Friday
0x0006	Saturday

The following table lists the possible values of the **wDay** subfield of the **stStandardDate** field in the **PidLidTimeZoneStruct** structure.

<b>wDay</b>	<b>Meaning</b>
0x0001	First occurrence of the day of the week
0x0002	Second occurrence of the day of the week
0x0003	Third occurrence of the day of the week
0x0004	Fourth occurrence of the day of the week
0x0005	Last occurrence of the day of the week

### Exporting from Calendar objects

This MUST be set to the onset of the Standard portion of the time zone for some year before the first appointment in the iCalendar. <57> This property is specified in the local time of the VTIMEZONE component, but the TZID parameter of this property is omitted.

#### 2.1.3.1.1.19.2.2 Property: RRULE

RFC Reference: [\[RFC2445\]](#) section 4.8.5.4

Number of Instances Allowed: 0,1

Format: Recurrence rule ([\[RFC2445\]](#) section 4.3.10)

Brief Description: A rule describing the onset of Standard time for years following DTSTART.

### Importing to Calendar objects

If this VTIMEZONE component has no DAYLIGHT sub-component, all the bytes in the **stStandardDate** field of the **PidLidTimeZoneStruct** structure MUST be set to 0x00 (as specified in [2.1.3.1.1.19.2.1](#)). The remainder of this subsection only pertains to the case where the VTIMEZONE being imported contains one or more DAYLIGHT sub-components.

For basic information regarding the Recurrence rule format, see [\[RFC2445\]](#) section 4.3.10 and section [2.1.3.2.1](#) of this document.

Time zone recurrences MUST be of frequency YEARLY and MUST specify either a BYDAY or a BYMONTHDAY, but not both.

If a BYDAY is specified, it MUST specify a single occurrence of a single day of the week (e.g. BYDAY=2MO, but not BYDAY=MO or BYDAY=1MO,3MO). The recurrence is imported into the **stStandardDate** field of the **PidLidTimeZoneStruct** structure using the following table.

<b>Field of PidLidTimeZoneStruct.stStandardDate</b>	<b>Value</b>
<b>wYear</b>	Set to 0x0000
<b>wMonth</b>	The value of the BYMONTH recurrence part, or, if not present, the month portion of DTSTART property.
<b>wDayOfWeek</b>	The day of the week specified by the BYDAY recurrence part. See section <a href="#">2.1.3.1.1.19.2.1</a> and section <a href="#">2.1.3.2.1.6</a> .
<b>wDay</b>	The occurrence of the day of the week specified by the BYDAY recurrence part. See section <a href="#">2.1.3.1.1.19.2.1</a> and



Field of PidLidTimeZoneStruct.stStandardDate	Value
	section <a href="#">2.1.3.2.1.6</a> .

If a BYMONTHDAY is specified, it MUST specify a single day of the month (BYMONTHDAY=12, but not BYMONTHDAY=14,15). The recurrence SHOULD [<58>](#) be imported into the **stStandardDate** field of the **PidLidTimeZoneStruct** structure as specified in the following table.

Field of PidLidTimeZoneStruct.stStandardDate	Value
<b>wYear</b>	Set to 0x0001
<b>wMonth</b>	The value of the BYMONTH recurrence part, or, if not present, the month portion of DTSTART property.
<b>wDayOfWeek</b>	Set to 0x0000.
<b>wDay</b>	The value of the BYMONTHDAY recurrence part.

### Exporting from Calendar objects

For basic information regarding the Recurrence rule format, see [\[RFC2445\]](#) section 4.3.10 and section [2.1.3.2.1](#) of this document.

If the time zone does not observe Daylight Saving Time (DST), this property MUST be omitted.

If the time zone transitions between Daylight Saving Time and Standard Time based on an occurrence of a day of the week, this property MUST be of the form  
FREQ=YEARLY;BYDAY=byday;BYMONTH=bymonth.

If the time zone transitions between Daylight Saving Time and Standard Time based on a specific day of the month, this property SHOULD [<59>](#) be of the form  
FREQ=YEARLY;BYMONTHDAY=bymonthday;BYMONTH=bymonth.

#### 2.1.3.1.1.19.2.3 Property: TZNAME

RFC Reference: [\[RFC2445\]](#) section 4.8.3.2

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: The name of the standard portion of the time zone.

#### Importing to Calendar objects

This property SHOULD be ignored on import.

#### Exporting from Calendar objects

This property SHOULD [<60>](#) be omitted.

#### 2.1.3.1.1.19.2.4 Property: TZOFFSETFROM

RFC Reference: [\[RFC2445\]](#) section 4.8.3.3

Number of Instances Allowed: 1

Format: UTC-Offset ([\[RFC2445\]](#) section 4.3.14)

Brief Description: The UTC-offset of the Daylight portion of the time zone.

#### **Importing to Calendar objects**

This property SHOULD be ignored on import.

#### **Exporting from Calendar objects**

This property MUST be the UTC-Offset representation of  $(-1 * (\text{PidLidTimeZoneStruct.IBias} + \text{PidLidTimeZoneStruct.IDaylightBias}))$ .

### **2.1.3.1.1.19.2.5 Property: TZOFFSETTO**

RFC Reference: [\[RFC2445\]](#) section 4.8.3.4

Number of Instances Allowed: 1

Format: UTC-Offset ([\[RFC2445\]](#) section 4.3.14)

Brief Description: The UTC-offset of the Standard portion of the time zone.

#### **Importing to Calendar objects**

The **IBias** field of the **PidLidTimeZoneStruct** structure MUST be set to  $(-1 * \text{offsetMinutes})$ , where **offsetMinutes** is the value of **TZOFFSETTO** in minutes.

#### **Exporting from Calendar objects**

This property MUST be the UTC-Offset representation of  $(-1 * (\text{PidLidTimeZoneStruct.IBias} + \text{PidLidTimeZoneStruct.IStandardBias}))$ .

### **2.1.3.1.1.19.3 Component: DAYLIGHT**

RFC Reference: [\[RFC2445\]](#) section 4.6.5

Number of Instances Allowed: 0+

Brief Description: A specification of the Daylight portion of the time zone.

#### **Importing to Calendar objects**

If more than one DAYLIGHT component is defined in the VTIMEZONE, only the DAYLIGHT component with the largest DTSTART SHOULD [<61>](#) be parsed. Alternatively, implementers MAY [<62>](#) parse the first DAYLIGHT component found within the VTIMEZONE, MAY [<63>](#) parse all STANDARD components found within the VTIMEZONE that have unique years in their DTSTART subcomponents, or MAY [<64>](#) fail to parse the iCalendar stream if more than one DAYLIGHT component is defined in the VTIMEZONE.

If no DAYLIGHT components are defined in the VTIMEZONE then all the bytes in the **IDaylightBias**, **IStandardBias**, **stDaylightDate**, and **stStandardDate** fields of the **PidLidTimeZoneStruct** MUST be set to 0x00.

#### **Exporting from Calendar objects**

If this time zone observes Daylight Saving Time, exactly one DAYLIGHT component MUST be exported for each VTIMEZONE.

If this time zone does not observe DST, this component SHOULD [<65>](#) be omitted.

#### **2.1.3.1.1.19.3.1 Property: DTSTART**

RFC Reference: [\[RFC2445\]](#) section 4.8.2.4

Number of Instances Allowed: 1

Format: Date-Time ([\[RFC2445\]](#) section 4.3.5)

Brief Description: The effective start date of this onset of Daylight Saving Time.

##### **Importing to and Exporting from Calendar objects**

The behavior of this property is identical to the behavior of the DTSTART property of the STANDARD component (section [2.1.3.1.1.19.2.1](#)) with the exception that **stDaylightDate** is modified instead of **stStandardDate**.

#### **2.1.3.1.1.19.3.2 Property: RRULE**

RFC Reference: [\[RFC2445\]](#) section 4.8.5.4

Number of Instances Allowed: 0,1

Format: Recurrence rule ([\[RFC2445\]](#) section 4.3.10)

Brief Description: A rule describing the onset of Daylight Saving Time for years following DTSTART.

##### **Importing to and Exporting from Calendar objects**

The behavior of this property is identical to the behavior of the RRULE property of the STANDARD component (section [2.1.3.1.1.19.2.2](#)) with the exception that **stDaylightDate** is modified instead of **stStandardDate**.

#### **2.1.3.1.1.19.3.3 Property: TZNAME**

RFC Reference: [\[RFC2445\]](#) section 4.8.3.2

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: The name of the daylight portion of the time zone.

##### **Importing to Calendar objects**

This property MUST be ignored on import.

##### **Exporting from Calendar objects**

This property SHOULD [<66>](#) be omitted.

#### **2.1.3.1.1.19.3.4 Property: TZOFFSETFROM**

RFC Reference: [\[RFC2445\]](#) section 4.8.3.3

Number of Instances Allowed: 1

Format: UTC-Offset ([\[RFC2445\]](#) section 4.3.14)

Brief Description: The UTC-offset of the Standard portion of the time zone.

#### **Importing to Calendar objects**

This property SHOULD be ignored on import.

#### **Exporting from Calendar objects**

This property MUST be the UTC-Offset representation of  $(-1 * (\text{PidLidTimeZoneStruct.IBias} + \text{PidLidTimeZoneStruct.IStandardBias}))$ .

### **2.1.3.1.1.19.3.5 Property: TZOFFSETTO**

RFC Reference: [\[RFC2445\]](#) section 4.8.3.4

Number of Instances Allowed: 1

Format: UTC-Offset ([\[RFC2445\]](#) section 4.3.14)

Brief Description: The UTC-Offset of the Daylight portion of the time zone.

#### **Importing to Calendar objects**

The **IDaylightBias** field of **PidLidTimeZoneStruct** structure MUST be set to  $(-1 * \text{offsetMinutes} - \text{IBias})$ , where `offsetMinutes` is the value of `TZOFFSETTO` measured in minutes.

#### **Exporting from Calendar objects**

This property MUST be the UTC-Offset representation of  $(-1 * (\text{PidLidTimeZoneStruct.IBias} + \text{PidLidTimeZoneStruct.IDaylightBias}))$ .

### **2.1.3.1.1.20 Component: VEVENT**

RFC Reference: [\[RFC2445\]](#) section 4.6.1

Number of Instances Allowed: 1+

Brief Description: A specification of an appointment or an exception to a recurring appointment.

#### **Importing to Calendar objects**

With the exception of those containing `RECURRENCE-ID` properties (section [2.1.3.1.1.20.20](#)), all `VEVENT` components MUST map to a new Calendar object.

#### **Exporting from Calendar objects**

Each Calendar object MUST be exported to its own `VEVENT` component. Certain exceptions to recurring appointments can also be exported as separate `VEVENT` components as specified in section [2.1.3.1.1.20.20](#).

### **2.1.3.1.1.20.1 Property: ATTACH**

RFC Reference: [\[RFC2445\]](#) section 4.8.1.1

Number of Instances Allowed: 0+

Format: **URI** ([\[RFC2445\]](#) section 4.3.13), Binary ([\[RFC2445\]](#) section 4.3.1)

Brief Description: An attachment to the appointment.

### Importing to Calendar objects

If the VALUE parameter of this property is BINARY, then this property SHOULD [<67>](#) be parsed as a stream encoded with **base64 encoding** (as specified in [\[RFC2045\]](#) section 6.8), decoded into its raw binary form, and stored in **PidTagAttachDataBinary** ([\[MS-OXPROPS\]](#) section 2.659) of a new **Attachment object** with properties specified in the following table.

Attachment object property	Value
<b>PidTagAttachDataBinary</b>	See the preceding paragraph
<b>PidTagAttachEncoding</b> ( <a href="#">[MS-OXPROPS]</a> section 2.661)	Set to an empty <b>PtypBinary</b>
<b>PidTagAttachExtension</b> ( <a href="#">[MS-OXPROPS]</a> section 2.662)	Set to the substring following the last instance of a '.' character (U+002E) in X-FILENAME (section <a href="#">2.1.3.1.1.20.1.4</a> ). If no instances of a period exist in X-FILENAME, set to a zero-length string ("").
<b>PidTagAttachFilename</b> ( <a href="#">[MS-OXPROPS]</a> section 2.663)	Set to the value of X-FILENAME (section <a href="#">2.1.3.1.1.20.1.4</a> )
<b>PidTagAttachFlags</b> ( <a href="#">[MS-OXPROPS]</a> section 2.664)	Set to 0x00000000
<b>PidTagAttachLongFilename</b> ( <a href="#">[MS-OXPROPS]</a> section 2.665)	Set to the value of X-FILENAME (section <a href="#">2.1.3.1.1.20.1.4</a> )
<b>PidTagAttachMethod</b> ( <a href="#">[MS-OXPROPS]</a> section 2.671)	Set to 0x00000001
<b>PidTagAttachMimeType</b> ( <a href="#">[MS-OXPROPS]</a> section 2.672)	Imported from FMTTYPE (section <a href="#">2.1.3.1.1.20.1.2</a> )
<b>PidTagAttachmentContactPhoto</b> ( <a href="#">[MS-OXPROPS]</a> section 2.667)	Set to FALSE
<b>PidTagAttachmentFlags</b> ( <a href="#">[MS-OXPROPS]</a> section 2.668)	Set to 0x00000000
<b>PidTagAttachmentHidden</b> ( <a href="#">[MS-OXPROPS]</a> section 2.669)	Set to FALSE
<b>PidTagAttachmentLinkId</b> ( <a href="#">[MS-OXPROPS]</a> section 2.670)	Set to 0x00000000
<b>PidTagDisplayName</b>	Set to the value of X-FILENAME (section <a href="#">2.1.3.1.1.20.1.4</a> )
<b>PidTagExceptionEndTime</b> ( <a href="#">[MS-OXPROPS]</a> section 2.753)	Set to 0x0CB34557A3DD4000
<b>PidTagExceptionStartTime</b> ( <a href="#">[MS-OXPROPS]</a> section 2.755)	Set to 0x0CB34557A3DD4000

Attachment object property	Value
<b>PidTagRenderingPosition</b> ([MS-OXPROPS] section 2.979)	Set to 0xFFFFFFFF

If the VALUE parameter of this property is "URI" or not defined, then this property SHOULD<68> be parsed as a URI. CID URIs (as specified in [RFC2392]) SHOULD<69> be used, for the case in which the iCalendar is embedded in a multi-part MIME e-mail to determine which attachments from the MIME will be imported into the Calendar object. Other URIs SHOULD<70> be imported into a new Attachment object with properties specified in the following table.

Attachment object property	Value
<b>PidTagAttachDataBinary</b>	Set to an 8-bit text stream, containing the following text encoded in the active <b>code page</b> (line breaks are encoded as 0x0D followed by 0x0A):  [InternetShortcut] URL=urivalue
<b>PidTagAttachEncoding</b>	Set to an empty <b>PtypBinary</b>
<b>PidTagAttachExtension</b>	Set to ".url"
<b>PidTagAttachFilename</b>	Set to the filename parsed from the URI with a.url extension added. With respect to [RFC3986], the filename is the last segment in the hier-part of the URI.
<b>PidTagAttachFlags</b>	Set to 0x00000000
<b>PidTagAttachLongFilename</b>	Same as <b>PidTagAttachFilename</b>
<b>PidTagAttachMethod</b>	Set to 0x00000001
<b>PidTagAttachMimeTag</b>	Set to the value of FMTTYPE (section 2.1.3.1.1.20.1.2)
<b>PidTagAttachmentContactPhoto</b>	Set to FALSE
<b>PidTagAttachmentFlags</b>	Set to 0x00000000
<b>PidTagAttachmentHidden</b>	Set to FALSE
<b>PidTagAttachmentLinkId</b>	Set to 0x00000000
<b>PidTagDisplayName</b>	Same as <b>PidTagAttachFilename</b>
<b>PidTagExceptionEndTime</b>	Set to 0x0CB34557A3DD4000
<b>PidTagExceptionStartTime</b>	Set to 0x0CB34557A3DD4000
<b>PidTagRenderingPosition</b>	Set to 0xFFFFFFFF

### Exporting from Calendar objects

If this iCalendar is being generated as part of a MIME meeting request, all attachments in the **attachments table** that meet the constraints in the following table SHOULD<71> be exported as a CID URI (as specified in [RFC2392]). In this case, the value of this property MUST be a CID URI generated by treating **PidTagAttachContentId** ([MS-OXPROPS] section 2.657) as a CID. If

**PidTagAttachContentId** does not exist, an [\[RFC2392\]](#)-compliant CID SHOULD [<72>](#) be generated and stored in **PidTagAttachContentId**.

If this iCalendar is being generated as part of a calendar export, all attachments in the attachments table that meet the constraints in the following table SHOULD [<73>](#) be exported as binary streams encoded with base64 encoding. The value of this property MUST be the base64 encoding of **PidTagAttachDataBinary** (base64 encoding is specified in [\[RFC2045\]](#) section 6.8).

Attachment Object Property	Constraint
<b>PidTagAttachmentFlags</b>	MUST NOT have any bits set to 1 in the bit mask 0x00000007
<b>PidTagAttachmentHidden</b>	MUST be unset or, if set, MUST be FALSE
<b>PidTagAttachMethod</b>	MUST be 0x00000001

#### 2.1.3.1.1.20.1.1 Parameter: ENCODING

RFC Reference: [\[RFC2445\]](#) section 4.2.7

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Specifies the encoding of a binary attachment.

##### Importing to and Exporting from Calendar objects

If the VALUE parameter of this ATTACH is BINARY, then the value of this parameter MUST be "base64". Otherwise, this parameter MUST be omitted.

#### 2.1.3.1.1.20.1.2 Parameter: FMTTYPE

RFC Reference: [\[RFC2445\]](#) section 4.2.8

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Specifies the MIME content type of an attachment.

##### Importing to Calendar objects

This parameter SHOULD [<74>](#) be imported as **PidTagAttachMimeTag**.

##### Exporting from Calendar objects

This parameter MAY take the value of **PidTagAttachMimeTag**.

#### 2.1.3.1.1.20.1.3 Parameter: VALUE

RFC Reference: [\[RFC2445\]](#) section 4.2.20

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Distinguishes encoded binary attachments from URI attachments.

#### **Importing to Calendar objects**

This parameter distinguishes attachments encoded in the iCalendar from URIs referencing resources outside the iCalendar. See section [2.1.3.1.1.20.1](#).

#### **Exporting from Calendar objects**

If this iCalendar is being generated as part of a MIME meeting request, this parameter SHOULD be omitted.

If this iCalendar is being generated as part of a calendar export, this parameter SHOULD be BINARY.

### **2.1.3.1.1.20.1.4 Parameter: X-FILENAME**

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Supplies a filename for an encoded binary attachment.

#### **Importing to Calendar objects**

If the VALUE parameter of this ATTACH is BINARY, this X-FILENAME parameter SHOULD [<75>](#) be sanitized as specified in [\[MS-OXCMAIL\]](#) section 2.2.3.4.1.1 and imported as **PidTagAttachFilename**, **PidTagAttachLongFilename**, and **PidTagDisplayName**. The filename extension parsed from this parameter is imported as **PidTagAttachExtension** as specified in section [2.1.3.1.1.20.1](#).

Otherwise, the X-FILENAME parameter is ignored.

#### **Exporting from Calendar objects**

If the VALUE parameter of this ATTACH is BINARY, then this parameter SHOULD [<76>](#) take the value of **PidTagAttachLongFilename**.

Otherwise, this parameter SHOULD be omitted.

### **2.1.3.1.1.20.2 Property: ATTENDEE**

RFC Reference: [\[RFC2445\]](#) section 4.8.4.1

Number of Instances Allowed: 0+

Format: Calendar User Address ([\[RFC2445\]](#) section 4.3.3)

Brief Description: An attendee for a meeting.

#### **Importing to Calendar objects**

If this property has the special value 'invalid:nomail', then the **CN** of this attendee SHOULD [<77>](#) be added to a list delimited by "; " (U+003B followed by U+0020) in the appropriate string property, as specified in the following table. If an attendee matches more than one row in the following table, the first matching row applies.



CUTYPE	ROLE	Append CN to...
RESOURCE	(any)	<b>PidLidNonSendableBcc</b> ([MS-OXPROPS] section 2.177)
ROOM	(any)	<b>PidLidNonSendableBcc</b>
(any)	OPT-PARTICIPANT	<b>PidLidNonSendableCc</b> ([MS-OXPROPS] section 2.178)
(any)	NON-PARTICIPANT	SHOULD<78> import to <b>PidLidNonSendableBcc</b> , MAY<79> import to <b>PidLidNonSendableCc</b>
(any)	(any)	<b>PidLidNonSendableTo</b> ([MS-OXPROPS] section 2.179)

If this property is not 'invalid:nomail', it SHOULD<80> be parsed as a valid mailto URI (as specified in [RFC2368]). The resulting SMTP address SHOULD<81> be resolved against the **address book** [MS-OXOABK]. If no match was found, a **one-off EntryID** ([MS-OXCDATA] section 2.2.5.1) MUST be created using the SMTP address and the CN parameter. The **Address Book object** MUST be added to the **recipient table** of the Calendar object with properties specified in the following table.

Recipient Table Property	Value								
<b>PidTagAddressType</b> ([MS-OXPROPS] section 2.646)	Resolved from the address book (see above). In the case of a one-off, set to 'SMTP'.								
<b>PidTagDisplayName</b>	Resolved from the address book (see above). In the case of a one-off, set to the value of the CN parameter.								
<b>PidTagDisplayType</b> ([MS-OXPROPS] section 2.748)	Set to 0x00000000<82>								
<b>PidTagEmailAddress</b> ([MS-OXPROPS] section 2.750)	Resolved from the address book (see above). In the case of a one-off, set to the SMTP address parsed from the mailto URI.								
<b>PidTagEntryId</b> ([MS-OXPROPS] section 2.752)	Resolved from the address book (see above). In the case of a one-off, use the one-off EntryID.								
<b>PidTagRecipientDisplayName</b> ([MS-OXPROPS] section 2.964)	Copy of <b>PidTagDisplayName</b> <83>								
<b>PidTagRecipientEntryId</b> ([MS-OXPROPS] section 2.965)	Copy of <b>PidTagEntryId</b> <84>								
<b>PidTagRecipientFlags</b> ([MS-OXPROPS] section 2.966)	Set to 0x00000001<85>								
<b>PidTagRecipientType</b> ([MS-OXPROPS] section 2.975)	See the next table.<86>								
<b>PidTagRecipientTrackStatus</b> ([MS-OXPROPS] section 2.973)	Import from PARTSTAT as follows:<87> <table border="1" data-bbox="727 1480 1328 1690"> <thead> <tr> <th>PARTSTAT</th> <th>PidTagRecipientTrackStatus</th> </tr> </thead> <tbody> <tr> <td>ACCEPTED</td> <td>0x00000003</td> </tr> <tr> <td>DECLINED</td> <td>0x00000004</td> </tr> <tr> <td>TENTATIVE</td> <td>0x00000002</td> </tr> </tbody> </table>	PARTSTAT	PidTagRecipientTrackStatus	ACCEPTED	0x00000003	DECLINED	0x00000004	TENTATIVE	0x00000002
PARTSTAT	PidTagRecipientTrackStatus								
ACCEPTED	0x00000003								
DECLINED	0x00000004								
TENTATIVE	0x00000002								

Recipient Table Property	Value		
	<table border="1"> <tr> <td>(Any other value)</td> <td>0x00000000</td> </tr> </table>	(Any other value)	0x00000000
(Any other value)	0x00000000		
<b>PidTagRecipientTrackStatusTime</b> ( <a href="#">[MS-OXPROPS]</a> section 2.974)	Import from X-MS-OLK-RESPTIME if present.<88>		

The correct value of **PidTagRecipientType** SHOULD be determined based on the CUTYPE and ROLE parameters as specified in the following table. If an attendee matches more than one row in the following table, the first matching row applies.

CUTYPE	ROLE	PidTagRecipientType
RESOURCE	(Any)	0x00000003
ROOM	(Any)	0x00000003
(any)	NON-PARTICIPANT	SHOULD<89> set to 0x00000003, MAY<90> set to 0x00000002
(any)	OPT-PARTICIPANT	0x00000002
(any)	(Any)	0x00000001

Implementations MAY<91> use the following table to determine the correct value of **PidTagRecipientType** for an attendee. If an attendee matches more than one row in the following table, the first matching row applies.

CUTYPE	ROLE	PidTagRecipientType
(Any)	CHAIR	0x00000001
(Any)	REQ-PARTICIPANT	0x00000001
(Any)	OPT-PARTICIPANT	0x00000002
RESOURCE	(Any)	0x00000003
ROOM	(Any)	0x00000003
(Any)	NON-PARTICIPANT	0x00000002
(Any)	(Any)	0x00000001

### Exporting from Calendar objects

If the 0x00000001 flag of **PidLidAppointmentStateFlags** ([\[MS-OXPROPS\]](#) section 2.30) is 0, then attendee properties SHOULD NOT<92> be exported.

Each row in the recipient table of the Calendar object that satisfies the constraints in the following table MUST be exported as an attendee property. The value of the property MUST be a mailto URI (as specified in [\[RFC2368\]](#)) with the SMTP address of the recipient (1) from the address book [MS-OXOABK]. If the recipient does not have an SMTP address, then the value of the property SHOULD<93> be set to 'invalid:nomail'.

Recipient Table Property	Constraint
<b>PidTagRecipientFlags</b>	The bit denoted by 0x00000020 MUST be 0 and the bit denoted by 0x00000002 MUST be 0
<b>PidTagRecipientType</b>	MUST NOT be 0x00000000

In addition, each of the semicolon-delimited entries in **PidLidNonSendableTo** and **PidLidNonSendableCc** SHOULD [<94>](#) be exported with a URI of 'invalid:nomail'. For handling of **PidLidNonSendableBcc**, see [2.1.3.1.1.20.21](#).

### 2.1.3.1.1.20.2.1 Parameter: CN

RFC Reference: [\[RFC2445\]](#) section 4.2.2

Number of Instances Allowed: 0,1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: The display name of an attendee.

#### Importing to Calendar objects

See section [2.1.3.1.1.20.2.2](#).

#### Exporting from Calendar objects

For attendees exported from the recipient table, this parameter SHOULD be exported from the **PidTagDisplayName** from the Address Book object (falling back on the **PidTagDisplayName** from the recipient table, if necessary).

For attendees exported from **PidLidNonSendableTo** and **PidLidNonSendableCc**, this parameter SHOULD [<95>](#) be taken from the semicolon-delimited lists.

### 2.1.3.1.1.20.2.2 Parameter: CUTYPE

RFC Reference: [\[RFC2445\]](#) section 4.2.3

Number of Instances Allowed: 0,1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: The type of attendee.

#### Importing to Calendar objects

See section [2.1.3.1.1.20.2](#).

#### Exporting from Calendar objects

For attendees exported from the recipient table, this parameter SHOULD [<96>](#) only be exported if the **PidTagRecipientType** is 0x00000003. In this case, the CUTYPE SHOULD [<97>](#) be set to "RESOURCE".

For attendees exported from **PidLidNonSendableTo** and **PidLidNonSendableCc**, this parameter SHOULD be omitted.

### 2.1.3.1.1.20.2.3 Parameter: PARTSTAT

RFC Reference: [\[RFC2445\]](#) section 4.2.12

Number of Instances Allowed: 0,1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: The attendee's response status.

#### Importing to Calendar objects

Import behavior for the PARTSTAT parameter into the recipient table is specified in section [2.1.3.1.1.20.2](#).

For calendars with a METHOD of COUNTER or REPLY, the PARTSTAT parameter is used in conjunction with the METHOD property to determine the **PidTagMessageClass** of the Calendar object. See section [2.1.3.1.1.1](#).

For calendars with a METHOD of PUBLISH, if the attendee is the user, the PARTSTAT parameter SHOULD [<98>](#) also be imported to the **PidLidResponseStatus** ([\[MS-OXPROPS\]](#) section 2.232) of the Calendar object as follows.

PARTSTAT	PidLidResponseStatus
ACCEPTED	0x00000003
DECLINED	0x00000004
TENTATIVE	0x00000002
(Any other value)	Not imported

#### Exporting from Calendar objects

For calendars with a METHOD of COUNTER or REPLY, the PARTSTAT parameter MUST be exported based on the **PidTagMessageClass** of the Calendar object. See section [2.1.3.1.1.1](#).

For calendars with a METHOD of publish, if the attendee is being exported from a row in the recipient table, the PARTSTAT parameter SHOULD [<99>](#) be exported from the **PidTagRecipientTrackStatus** of the recipient (1) as specified in the following table. If **PidTagRecipientTrackStatus** could not be exported because it is unset or 0 and the attendee is the user, then the **PidLidResponseStatus** of the Calendar object SHOULD [<100>](#) be exported instead as specified in the following table.

PidTagRecipientTrackStatus or PidLidResponseStatus	PARTSTAT
0x00000003	ACCEPTED
0x00000004	DECLINED
0x00000002	TENTATIVE
(Other)	(Not exported)

### 2.1.3.1.1.20.2.4 Parameter: ROLE

RFC Reference: [\[RFC2445\]](#) section 4.2.16

Number of Instances Allowed: 0,1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: The participation role of the attendee.

#### Importing to Calendar objects

See section [2.1.3.1.1.20.2](#).

#### Exporting from Calendar objects

For ATTENDEES exported from the recipient table, this parameter SHOULD be exported based on the **PidTagRecipientType**, as specified in the following table.

<b>PidTagRecipientType</b>	<b>ROLE</b>
0x00000002	OPT-PARTICIPANT
0x00000003	NON-PARTICIPANT
(otherwise)	(omit) <a href="#">&lt;101&gt;</a>

For ATTENDEES exported from **PidLidNonSendableTo**, this parameter SHOULD be omitted.

For ATTENDEES exported from **PidLidNonSendableCc**, this parameter SHOULD [<102>](#) be exported as OPT-PARTICIPANT.

### 2.1.3.1.1.20.2.5 Parameter: RSVP

RFC Reference: [\[RFC2445\]](#) section 4.2.17

Number of Instances Allowed: 0,1

Format: Boolean ([\[RFC2445\]](#) section 4.3.2)

Brief Description: To specify whether there is an expectation of a reply from this attendee.

#### Importing to Calendar objects

If any ATTENDEE property in the VEVENT has its RSVP parameter set to TRUE or if the VEVENT is being imported with a **PidTagMessageClass** of "IPM.Appointment", then **PidTagResponseRequested** ([\[MS-OXPROPS\]](#) section 2.994) and **PidTagReplyRequested** ([\[MS-OXPROPS\]](#) section 2.982) on the Calendar object MUST both be set to TRUE. Otherwise, **PidTagResponseRequested** and **PidTagReplyRequested** MUST both be set to FALSE.

#### Exporting from Calendar objects

For ATTENDEES exported from the recipient table, this parameter MUST be exported from **PidTagResponseRequested** on the Calendar object.

For ATTENDEES exported from **PidLidNonSendableTo** and **PidLidNonSendableCc**, this parameter SHOULD be omitted.

### 2.1.3.1.1.20.2.6 Parameter: X-MS-OLK-RESPTIME

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Date-Time ([\[RFC2445\]](#) section 4.3.5), Date ([\[RFC2445\]](#) section 4.3.4)

Brief Description: The time that the ATTENDEE responded to the meeting request.

#### Importing to Calendar objects

Section [2.1.3.1.1.20.2](#) specifies how X-MS-OLK-RESPTIME is imported into the recipient table.

For calendars with a METHOD of PUBLISH, if the attendee is the user, the X-MS-OLK-RESPTIME parameter SHOULD also be imported to the **PidLidAppointmentReplyTime** ([\[MS-OXPROPS\]](#) section 2.24) of the Calendar object. [<103>](#)

#### Exporting from Calendar objects

For calendars with a METHOD of PUBLISH, if the attendee is being exported from a row in the recipient table, the X-MS-OLK-RESPTIME parameter MAY be exported in **UTC** format from the **PidTagRecipientTrackStatusTime** of the recipient (1). If **PidTagRecipientTrackStatus** could not be exported as specified in section [2.1.3.1.1.20.2.3](#) because it is unset or 0 and the attendee is the user, the **PidLidAppointmentReplyTime** of the Calendar object SHOULD be exported in UTC format instead. [<104>](#)

### 2.1.3.1.1.20.3 Property: CATEGORIES

RFC Reference: [\[RFC2445\]](#) section 4.8.1.2

Number of Instances Allowed: 0+

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: A list of categories assigned to the appointment.

#### Importing to Calendar objects

All instances of the CATEGORIES property SHOULD be parsed into a single array of strings. Several rules apply to the import of categories:

- All separator characters, semicolon (U+003B), comma (U+002C), arabic semicolon (U+061B), small semicolon (U+FE54), full-width semicolon (U+FF1B), SHOULD [<105>](#) be removed.
- All contiguous sequences of whitespace [<106>](#) characters SHOULD [<107>](#) be truncated to a single space (U+0020) character.
- Whitespace at the start and end of each string SHOULD be trimmed.
- Strings SHOULD [<108>](#) be truncated to a length of 255 WCHARs if the length exceeds 255 WCHARs, but the truncation SHOULD NOT [<109>](#) split surrogate pairs.
- All case-insensitive duplicate occurrences and zero-length strings in the array SHOULD [<110>](#) be removed.

The resulting string array is stored in **PidNameKeywords** ([\[MS-OXPROPS\]](#) section 2.495).

## Exporting from Calendar objects

**PidNameKeywords** SHOULD be exported as a comma-delimited list in the CATEGORIES property.

### 2.1.3.1.1.20.4 Property: CLASS

RFC Reference: [\[RFC2445\]](#) section 4.8.1.3

Number of Instances Allowed: 0,1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: The privacy or classification level of an appointment.

#### Importing to and Exporting from Calendar objects

The CLASS property MUST map to **PidTagSensitivity** ([\[MS-OXPROPS\]](#) section 2.1074) as specified in the following table.

CLASS	PidTagSensitivity
PRIVATE	0x00000002
CONFIDENTIAL	0x00000003
PUBLIC	0x00000000
X-PERSONAL< <a href="#">111</a> >	0x00000001< <a href="#">112</a> >

### 2.1.3.1.1.20.5 Property: COMMENT

RFC Reference: [\[RFC2445\]](#) section 4.8.1.4 and [\[RFC2446\]](#) section 3.2.3

Number of Instances Allowed: 0,1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: In a meeting response, this property represents an optional plain-text message from the attendee intended for the **organizer**.

#### Importing to and Exporting from Calendar objects

If the METHOD property of the VCALENDAR component is set to 'REPLY' or 'COUNTER', this property SHOULD<[113](#)> be mapped directly to **PidTagBody** ([\[MS-OXPROPS\]](#) section 2.688). The COMMENT property SHOULD be ignored for other values of METHOD.

Also see the documentation for DESCRIPTION in section [2.1.3.1.1.20.11](#).

### 2.1.3.1.1.20.6 Property: CONTACT

RFC Reference: [\[RFC2445\]](#) section 4.8.4.2

Number of Instances Allowed: 0+

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: A **contact (3)** for an appointment.

## Importing to Calendar objects

All instances of the CONTACT property SHOULD [<114>](#) be appended to single array of strings. Several rules apply to the import of contacts (3).

- All semicolons (U+003B) SHOULD [<115>](#) be removed.
- All contiguous sequences of whitespace [<116>](#) characters SHOULD [<117>](#) be truncated to a single space (U+0020) character.
- Whitespace at the start and end of each string SHOULD [<118>](#) be trimmed.
- Strings SHOULD [<119>](#) be truncated to a length of 500 WCHARs if their length exceeds 500 WCHARs, but the truncation SHOULD NOT [<120>](#) split surrogate pairs.
- All case-insensitive duplicate occurrences and zero-length strings in the array SHOULD [<121>](#) be removed.

The resulting string array is stored in **PidLidContacts** ([\[MS-OXPROPS\]](#) section 2.77).

## Exporting from Calendar objects

Each string in the array of strings in **PidLidContacts** SHOULD [<122>](#) be exported as a new CONTACT property.

### 2.1.3.1.1.20.7 Property: CREATED

RFC Reference: [\[RFC2445\]](#) section 4.8.7.1

Number of Instances Allowed: 0, 1

Format: Date-Time ([\[RFC2445\]](#) section 4.3.5)

Brief Description: The creation time of an appointment.

#### Importing to Calendar objects

This property SHOULD be ignored.

#### Exporting from Calendar objects

The **PidTagCreationTime** ([\[MS-OXPROPS\]](#) section 2.724) of a Calendar object SHOULD [<123>](#) be exported as a CREATED property, specified in UTC.

### 2.1.3.1.1.20.8 Property: DTEND

RFC Reference: [\[RFC2445\]](#) section 4.8.2.2

Number of Instances Allowed: 1

Format: Date-Time ([\[RFC2445\]](#) section 4.3.5), Date ([\[RFC2445\]](#) section 4.3.4)

Brief Description: The end time of an appointment. If the item is a **counter proposal**, then this is the proposed end time of the meeting.

#### Importing to Calendar objects



If the METHOD property of the VCALENDAR component is set to 'COUNTER', then this property SHOULD be imported as **PidLidAppointmentProposedEndWhole** ([MS-OXPROPS] section 2.20).<124>

If the METHOD property of the VCALENDAR component is not set to 'COUNTER', or if either X-MS-OLK-ORIGINALEND or X-MS-OLK-ORIGINALSTART is not specified, then this property SHOULD<125> be imported as **PidLidAppointmentEndWhole** ([MS-OXPROPS] section 2.14), and **PidLidAppointmentDuration** ([MS-OXPROPS] section 2.11) SHOULD<126> be set to the number of minutes between DTSTART and DTEND.

If DTSTART and DTEND are both specified in floating time, and if both occur at midnight of their respective days, then the appointment SHOULD<127> be imported as an all-day appointment: **PidLidAppointmentSubType** ([MS-OXPROPS] section 2.31) MUST be set to 0x00000001. Note that this logic SHOULD<128> also be triggered by X-MICROSOFT-CDO-ALLDAYEVENT (section 2.1.3.1.1.20.28) and X-MICROSOFT-MSNCALENDAR-ALLDAYEVENT (section 2.1.3.1.1.20.41).

### Exporting from Calendar objects

If the METHOD property of the VCALENDAR component is set to 'COUNTER', then **PidLidAppointmentProposedEndWhole** SHOULD<129> be exported as a new DTEND property. For other values of METHOD, the **PidLidAppointmentEndWhole** of a Calendar object SHOULD<130> be exported as a new DTEND property.

If this is an all-day appointment, then this property SHOULD<131> be exported in floating time with the Date format ([RFC2445] section 4.3.4).

If this is a recurring non-all-day appointment, then this property MUST be specified as a local time with a TZID parameter.

Non-recurring non-all-day appointments SHOULD<132> be specified as a local time with a TZID parameter.

#### 2.1.3.1.1.20.8.1 Parameter: TZID

RFC Reference: [RFC2445] section 4.2.19

Number of Instances Allowed: 0, 1

Format: Text ([RFC2445] section 4.3.11)

Brief Description: In conjunction with a matching VTIMEZONE, specifies the time zone of a Date-Time property provided in local time.

### Importing to Calendar objects

If this appointment is recurring, and if there is a TZID parameter, and if neither **PidLidTimeZoneStruct** nor **PidLidTimeZoneDescription** has been imported from DTSTART (section 2.1.3.1.1.20.10), then **PidLidTimeZoneStruct** MUST be imported from the VTIMEZONE referenced by the TZID parameter, **PidLidTimeZoneDescription** MUST be imported from the TZID parameter, and **PidLidAppointmentTimeZoneDefinitionRecur** SHOULD<133> be imported from the VTIMEZONE referenced by the TZID parameter. Otherwise, this parameter SHOULD be ignored.

Furthermore, **PidLidAppointmentTimeZoneDefinitionEndDisplay** SHOULD<134> be imported from the VTIMEZONE referenced by the TZID parameter.

Refer to [RFC2445] section 4.2.19 for additional details on the TZID parameter.

## Exporting from Calendar objects

If this is a recurring non-all-day appointment, then the DTEND property MUST be specified as a local time. It MUST be accompanied by a TZID parameter that is equal to the TZID property of the VTIMEZONE described by **PidLidAppointmentTimeZoneDefinitionRecur**<135> or the combination of **PidLidTimeZoneDescription** and **PidLidTimeZoneStruct**.

If this is a non-recurring non-all-day appointment and if **PidLidAppointmentTimeZoneDefinitionEndDisplay** is set, then the DTEND property SHOULD<136> be specified as a local time. It MUST be accompanied by a TZID parameter that is equal to the TZID property of the VTIMEZONE described by **PidLidAppointmentTimeZoneDefinitionEndDisplay**.

### 2.1.3.1.1.20.8.2 Parameter: VALUE

RFC Reference: [\[RFC2445\]](#) section 4.2.20

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Specifies the format of this property.

## Importing to Calendar objects

This parameter SHOULD<137> be ignored since a parser can determine whether a property is in the Date format ([\[RFC2445\]](#) section 4.3.4) or Date-Time format ([\[RFC2445\]](#) section 4.3.5) without an explicit declaration in the VALUE parameter.

## Exporting from Calendar objects

If the DTEND property is specified in the Date format ([\[RFC2445\]](#) section 4.3.4), the VALUE parameter MUST be exported as 'DATE'. If the DTEND property is specified in the Date-Time format ([\[RFC2445\]](#) section 4.3.5), the VALUE parameter SHOULD be omitted, but MAY be exported as 'DATE-TIME'.

### 2.1.3.1.1.20.9 Property: DTSTAMP

RFC Reference: [\[RFC2445\]](#) section 4.8.7.2

Number of Instances Allowed: 1

Format: Date-Time ([\[RFC2445\]](#) section 4.3.5), Date ([\[RFC2445\]](#) section 4.3.4)

Brief Description: The creation time of the iCalendar.

## Importing to Calendar objects

If the METHOD (specified in section [2.1.3.1.1.1](#)) is 'REPLY' or 'COUNTER', then this property SHOULD be imported as **PidLidAttendeeCriticalChange** ([\[MS-OXPROPS\]](#) section 2.37).<138>

If the METHOD is not 'REPLY' or 'COUNTER', then this property MUST be imported as **PidLidOwnerCriticalChange** ([\[MS-OXPROPS\]](#) section 2.199).

## Exporting from Calendar objects

If the METHOD (specified in section [2.1.3.1.1.1](#)) is 'REPLY' or 'COUNTER', then **PidLidAttendeeCriticalChange** MUST be exported as DTSTAMP.

If the METHOD is not 'REPLY' or 'COUNTER', then **PidLidOwnerCriticalChange** MUST be exported as DTSTAMP. If **PidLidOwnerCriticalChange** is undefined, the current system time SHOULD be used.

#### 2.1.3.1.1.20.9.1 Parameter: TZID

RFC Reference: [\[RFC2445\]](#) section 4.2.19

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: In conjunction with a matching VTIMEZONE, specifies the time zone of a Date-Time property provided in local time.

Refer to [\[RFC2445\]](#) section 4.2.19 for additional details on the TZID parameter.

#### 2.1.3.1.1.20.10 Property: DTSTART

RFC Reference: [\[RFC2445\]](#) section 4.8.2.4

Number of Instances Allowed: 1

Format: Date-Time ([\[RFC2445\]](#) section 4.3.5), Date ([\[RFC2445\]](#) section 4.3.4)

Brief Description: The start time of an appointment. If the item is a counter proposal, this is the proposed start time of the meeting.

##### Importing to Calendar objects

If the METHOD property of the VCALENDAR component is set to 'COUNTER', then this property SHOULD<[139](#)> be imported as **PidLidAppointmentProposedStartWhole** ([\[MS-OXPROPS\]](#) section 2.21).

If the METHOD property of the VCALENDAR component is not set to 'COUNTER' or if either X-MS-OLK-ORIGALEND or X-MS-OLK-ORIGINALSTART is not specified, then this property SHOULD<[140](#)> be imported as **PidLidAppointmentStartWhole** ([\[MS-OXPROPS\]](#) section 2.29), and **PidLidAppointmentDuration** SHOULD<[141](#)> be set to the number of minutes between DTSTART and DTEND.

If DTSTART and DTEND are both specified in floating time, and if both occur at midnight of their respective days, then the appointment SHOULD<[142](#)> be imported as an all-day appointment: **PidLidAppointmentSubType** MUST be set to 0x00000001. Note that this logic SHOULD<[143](#)> also be triggered by X-MICROSOFT-CDO-ALLDAYEVENT (section [2.1.3.1.1.20.28](#)) and X-MICROSOFT-MSNCALENDAR-ALLDAYEVENT (section [2.1.3.1.1.20.41](#)).

If the DTEND and DURATION properties are not specified in the VEVENT, the value of DTSTART MAY<[144](#)> be used to derive the end time based on the format of the DTSTART property based on the following rules.

- If the format of the DTSTART property is a Date-Time, the end time is treated as being equal to the value of DTSTART, and is imported as specified in section [2.1.3.1.1.20.8](#).
- If the format of the DTSTART property is a Date, the end time is treated as being equal to the value of DTSTART + 1 day, and is imported as specified in section [2.1.3.1.1.20.8](#).

##### Exporting from Calendar objects

If the METHOD property of the VCALENDAR component is set to 'COUNTER', then **PidLidAppointmentProposedStartWhole** SHOULD [<145>](#) be exported as a new DTSTART property. For other values of METHOD, the **PidLidAppointmentStartWhole** of a Calendar object SHOULD [<146>](#) be exported as a DTSTART property.

If this is an all-day appointment, then this property SHOULD [<147>](#) be exported in floating time with the Date format.

If this is a recurring non-all-day appointment, then this property MUST be specified as a local time with a TZID parameter.

Non-recurring non-all-day appointments SHOULD [<148>](#) be specified as a local time with a TZID parameter.

#### 2.1.3.1.1.20.10.1 Parameter: TZID

RFC Reference: [\[RFC2445\]](#) section 4.2.19

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: In conjunction with a matching VTIMEZONE, specifies the time zone of a Date-Time property provided in local time.

##### Importing to Calendar objects

If this appointment is recurring, and if there is a TZID parameter, then **PidLidTimeZoneStruct** MUST be imported from the VTIMEZONE referenced by the TZID parameter, **PidLidTimeZoneDescription** MUST be imported from the TZID parameter, and **PidLidAppointmentTimeZoneDefinitionRecur** SHOULD [<149>](#) be imported from the VTIMEZONE referenced by the TZID parameter.

Furthermore, **PidLidAppointmentTimeZoneDefinitionStartDisplay** SHOULD [<150>](#) be imported from the VTIMEZONE referenced by the TZID parameter.

Refer to [\[RFC2445\]](#) section 4.2.19 for additional details on the TZID parameter.

##### Exporting from Calendar objects

If this is a recurring non-all-day appointment, then the DTSTART property MUST be specified as a local time. It MUST be accompanied by a TZID parameter referencing the VTIMEZONE described by **PidLidAppointmentTimeZoneDefinitionRecur** [<151>](#) or the combination of **PidLidTimeZoneDescription** and **PidLidTimeZoneStruct**.

If this is a non-recurring non-all-day appointment and if **PidLidAppointmentTimeZoneDefinitionStartDisplay** is set, then the DTSTART property SHOULD [<152>](#) be specified as a local time. It MUST be accompanied by a TZID parameter referencing the VTIMEZONE described by **PidLidAppointmentTimeZoneDefinitionStartDisplay**.

#### 2.1.3.1.1.20.10.2 Parameter: VALUE

RFC Reference: [\[RFC2445\]](#) section 4.2.20

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Specifies the format of this property.

### **Importing to Calendar objects**

This parameter SHOULD<153> be ignored since a parser can determine whether a property is in the Date format ([RFC2445] section 4.3.4) or Date-Time format ([RFC2445] section 4.3.5) without an explicit declaration in the VALUE parameter.

### **Exporting from Calendar objects**

If the DTSTART property is specified in the Date format ([RFC2445] section 4.3.4), the VALUE parameter MUST be exported as 'DATE'. If the DTSTART property is specified in the Date-Time format ([RFC2445] section 4.3.4), the VALUE parameter SHOULD be omitted, but MAY be exported as 'DATE-TIME'.

## **2.1.3.1.1.20.11 Property: DESCRIPTION**

RFC Reference: [RFC2445] section 4.8.1.5

Number of Instances Allowed: 0, 1

Format: Text ([RFC2445] section 4.3.11)

Brief Description: Specifies the plain-text body of an appointment.

### **Importing to and Exporting from Calendar objects**

If the METHOD property of the VCALENDAR component is set to 'REPLY' or 'COUNTER', this property SHOULD<154> be ignored. For other values of METHOD, this property MUST be mapped directly to **PidTagBody**.

Also see the documentation for COMMENT in section [2.1.3.1.1.20.5](#).

## **2.1.3.1.1.20.11.1 Parameter: LANGUAGE**

RFC Reference: [RFC2445] section 4.2.10

Number of Instances Allowed: 0, 1

Format: Text ([RFC2445] section 4.3.11)

Brief Description: Specifies the language of the property.

### **Importing to Calendar objects**

This parameter SHOULD<155> be interpreted as a language tag as specified in [RFC1766] and stored in **PidTagMessageLocaleId** ([MS-OXPROPS] section 2.861) as the corresponding language code identifier, as specified in [MS-LCID].

### **Exporting from Calendar objects**

This parameter SHOULD NOT be exported (see section [2.1.3.1.1.20.24.1](#)).

## **2.1.3.1.1.20.12 Property: DURATION**

RFC Reference: [RFC2445] section 4.8.2.5

Number of Instances Allowed: 0, 1

Format: Duration ([\[RFC2445\]](#) section 4.3.6)

Brief Description: Specifies the duration of an appointment.

### Importing to Calendar objects

If only one of DTSTART and DTEND is present, the DURATION property SHOULD [<156>](#) be used to compute the missing property.

### Exporting from Calendar objects

This parameter SHOULD NOT be exported.

## 2.1.3.1.1.20.13 Property: EXDATE

RFC Reference: [\[RFC2445\]](#) section 4.8.5.1

Number of Instances Allowed: 0+

Format: Date-Time ([\[RFC2445\]](#) section 4.3.5), Date ([\[RFC2445\]](#) section 4.3.4)

Brief Description: Specifies the original start time of instances of the recurring appointment which have been deleted.

### Importing to Calendar objects

If this property is specified, an RRULE MUST also be specified in the same VEVENT.

All valid EXDATES SHOULD [<157>](#) be gathered into the **DeletedInstanceDates** field of the **RecurrencePattern** structure embedded within the **AppointmentRecurrencePattern** structure ([\[MS-OXOCAL\]](#) section 2.2.1.44.5) in the **PidLidAppointmentRecur** property ([\[MS-OXOCAL\]](#) section 2.2.1.44) after the following validation:

- All EXDATES SHOULD [<158>](#) be converted to the time zone specified by **PidLidTimeZoneStruct**.
- The time information MUST be stripped off (all entries MUST fall on midnight).
- All duplicate entries MUST be removed.
- All entries that do not have a date matching the start date of an instance in the **recurrence pattern** MUST be removed.
- The **DeletedInstanceDates** field of the **RecurrencePattern** structure MUST be sorted chronologically with the earliest dates at the start.

Note that additional EXDATES could be derived from the RECURRENCE-IDs of other VEVENTs (see section [2.1.3.1.1.20.20](#)).

### Exporting from Calendar objects

The EXDATE property MUST NOT be exported for non-recurring appointments or exceptions of recurring appointments.

In certain cases, an X-MICROSOFT-EXDATE SHOULD [<159>](#) be exported in place of an EXDATE. See section [2.1.3.1.1.20.39](#).

If there are entries in the **DeletedInstanceDates** field, the date-times of each day specified by the **DeletedInstanceDates** field SHOULD [<160>](#) be added with the time specified by the

**StartTimeOffset** field of the **RecurrencePattern** structure and exported in a multi-valued EXDATE property. However, exceptions exported as a separate VEVENT with a RECURRENCE-ID (see section [2.1.3.1.1.20.20](#)) SHOULD NOT also be exported as an EXDATE.

If the recurrence is an all-day recurrence, the EXDATES MUST be specified in the Date format.

#### **2.1.3.1.1.20.13.1 Parameter: TZID**

RFC Reference: [\[RFC2445\]](#) section 4.2.19

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: In conjunction with a matching VTIMEZONE, specifies the time zone of a Date-Time property provided in local time.

Refer to [\[RFC2445\]](#) section 4.2.19 for additional details on the TZID parameter.

#### **2.1.3.1.1.20.13.2 Parameter: VALUE**

RFC Reference: [\[RFC2445\]](#) section 4.2.20

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Specifies the format of this property.

#### **Importing to Calendar objects**

This parameter SHOULD [<161>](#) be ignored since a parser can determine whether a property is in the Date format ([\[RFC2445\]](#) section 4.3.4) or Date-Time format ([\[RFC2445\]](#) section 4.3.5) without an explicit declaration in the VALUE parameter.

#### **Exporting from Calendar objects**

If the EXDATE property is specified in the Date format ([\[RFC2445\]](#) section 4.3.4), the VALUE parameter MUST be exported as 'DATE'. If the EXDATE property is specified in the Date-Time format ([\[RFC2445\]](#) section 4.3.5), the VALUE parameter SHOULD be omitted, but MAY be exported as 'DATE-TIME'.

#### **2.1.3.1.1.20.14 Property: LAST-MODIFIED**

RFC Reference: [\[RFC2445\]](#) section 4.8.7.3

Number of Instances Allowed: 0, 1

Format: Date-Time ([\[RFC2445\]](#) section 4.3.5)

Brief Description: The last modification time of an appointment.

#### **Importing to Calendar object**

This property SHOULD be ignored. [<162>](#)

#### **Exporting from Calendar objects**

The **PidTagLastModificationTime** ([\[MS-OXPROPS\]](#) section 2.832) of a Calendar object SHOULD [<163>](#) be exported as a LAST-MODIFIED property, specified in UTC.

### 2.1.3.1.1.20.15 Property: LOCATION

RFC Reference: [\[RFC2445\]](#) section 4.8.1.7

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Specifies the location of an appointment.

#### Importing to Calendar objects

This property SHOULD [<164>](#) be stripped of all carriage returns (U+000D) and line feeds (U+000A), and SHOULD [<165>](#) be truncated to a length of 255 WCHARs if its length exceeds 255 WCHARs. The truncation SHOULD NOT [<166>](#) split surrogate pairs. This property MUST be stored in **PidLidLocation** ([\[MS-OXPROPS\]](#) section 2.159).

#### Exporting from Calendar objects

**PidLidLocation** MUST be exported as a LOCATION property.

### 2.1.3.1.1.20.15.1 Parameter: ALTREP

RFC Reference: [\[RFC2445\]](#) section 4.2.1

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Specifies an alternate text representation of the property value.

#### Importing to Calendar objects

This parameter MAY [<167>](#) be imported to the **PidNameLocationUrl** (section [2.2.3](#)) property.

#### Exporting to Calendar objects

This parameter MAY [<168>](#) be exported from the **PidNameLocationUrl** property.

### 2.1.3.1.1.20.15.2 Parameter: LANGUAGE

RFC Reference: [\[RFC2445\]](#) section 4.2.10

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Specifies the language of the property.

#### Importing to Calendar objects

This parameter SHOULD [<169>](#) be interpreted as a language tag as specified in [\[RFC1766\]](#) and stored in **PidTagMessageLocaleId** as the corresponding language code identifier, as specified in [\[MS-LCID\]](#).



## Exporting from Calendar objects

This parameter SHOULD NOT be exported. See section [2.1.3.1.1.20.24.1](#).

### 2.1.3.1.1.20.16 Property: ORGANIZER

RFC Reference: [\[RFC2445\]](#) section 4.8.4.3

Number of Instances Allowed: 0, 1

Format: Calendar User Address ([\[RFC2445\]](#) section 4.3.3)

Brief Description: The organizer of a meeting.

## Importing to Calendar objects

This property SHOULD [<170>](#) be parsed as a valid mailto URI as specified in [\[RFC2368\]](#). The resulting SMTP address SHOULD be resolved against the address book, as specified in [\[MS-OXOABK\]](#). If no match was found, a one-off EntryID ([\[MS-OXCDATA\]](#) section 2.2.5.1) MUST be created using the SMTP address and the CN parameter. The Address Book object MUST be added to the recipient table of the Calendar object with properties specified in the following table.

Recipient Table Property	Value
<b>PidTagAddressType</b>	Resolved from the address book (see previous paragraph).
<b>PidTagDisplayName</b>	Resolved from the address book (see previous paragraph).
<b>PidTagDisplayType</b>	Set to 0x00000000 <a href="#">&lt;171&gt;</a>
<b>PidTagEmailAddress</b>	Resolved from the address book (see previous paragraph).
<b>PidTagEntryId</b>	Resolved from the address book (see previous paragraph).
<b>PidTagRecipientDisplayName</b>	Copy of <b>PidTagDisplayName</b> <a href="#">&lt;172&gt;</a>
<b>PidTagRecipientEntryId</b>	Copy of <b>PidTagEntryId</b> <a href="#">&lt;173&gt;</a>
<b>PidTagRecipientFlags</b>	Set to 0x00000003.
<b>PidTagRecipientType</b>	Set to 0x00000001.

## Exporting from Calendar objects

If the 0x00000001 flag of **PidLidAppointmentStateFlags** is 0, then an ORGANIZER property MUST NOT be exported.

The row in the recipient table of the Calendar object that satisfies the constraints in the following table SHOULD [<174>](#) be exported as an ORGANIZER property. The value of the property MUST be a mailto URI as specified in [\[RFC2368\]](#) with the SMTP address of the recipient (1) from the address book, as specified in [\[MS-OXOABK\]](#). If the recipient does not have an SMTP address, then the value of the property SHOULD [<175>](#) be set to 'invalid:nomail'.

Recipient Table Property	Constraint
<b>PidTagRecipientFlags</b>	The bit denoted by 0x00000020 MUST be 0
<b>PidTagRecipientFlags</b>	The bit denoted by 0x00000002 of <b>PidTagRecipientFlags</b> MUST be 1

Recipient Table Property	Constraint
or <b>PidTagRecipientType</b>	or The <b>PidTagRecipientType</b> MUST be 0x00000000

### 2.1.3.1.1.20.16.1 Parameter: CN

RFC Reference: [\[RFC2445\]](#) section 4.2.2

Number of Instances Allowed: 0,1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: The display name of the organizer.

#### Importing to Calendar objects

See section [2.1.3.1.1.20.16](#).

#### Exporting from Calendar objects

This parameter SHOULD be exported from the **PidTagDisplayName** from the Address Book object (falling back on the **PidTagDisplayName** from the recipient table, if necessary).

### 2.1.3.1.1.20.17 Property: PRIORITY

RFC Reference: [\[RFC2445\]](#) section 4.8.1.9

Number of Instances Allowed: 0, 1

Format: Integer ([\[RFC2445\]](#) section 4.3.8)

Brief Description: Specifies the importance of an appointment.

#### Importing to Calendar objects

If **PidTagImportance** ([\[MS-OXPROPS\]](#) section 2.805) cannot be imported from X-MICROSOFT-CDO-IMPORTANCE (section [2.1.3.1.1.20.32](#)) or X-MICROSOFT-MSNCALENDAR-IMPORTANCE (section [2.1.3.1.1.20.43](#)), then this property MUST be imported into **PidTagImportance** as specified by the following table.

PRIORITY	PidTagImportance
0	(unset)
1	0x00000002
2	0x00000002
3	0x00000002
4	0x00000002
5	0x00000001
6	0x00000000
7	0x00000000

PRIORITY	PidTagImportance
8	0x00000000
9	0x00000000

### Exporting from Calendar objects

**PidTagImportance** MUST be exported as the PRIORITY property as specified by the following table.

PidTagImportance	PRIORITY
0x00000002	1
0x00000001	5
0x00000000	9

### 2.1.3.1.1.20.18 Property: RDATE

RFC Reference: [\[RFC2445\]](#) section 4.8.5.3

Number of Instances Allowed: 0+

Format: Date-Time ([\[RFC2445\]](#) section 4.3.5), Date ([\[RFC2445\]](#) section 4.3.4), Period of Time ([\[RFC2445\]](#) section 4.3.9)

Brief Description: Specifies the start time of additional instances of the recurring appointment which have been created by the organizer.

### Importing to Calendar objects

If this property is specified, an RRULE MUST also be specified in the same VEVENT.

RDATEs in Period of Time format SHOULD be ignored. All valid RDATEs SHOULD [<176>](#) be gathered into the **ModifiedInstanceDates** field of the **RecurrencePattern** structure ([\[MS-OXOCAL\]](#) section 2.2.1.44.1) embedded within the **AppointmentRecurrencePattern** structure ([\[MS-OXOCAL\]](#) section 2.2.1.44.5) in the **PidLidAppointmentRecur** property ([\[MS-OXOCAL\]](#) section 2.2.1.44), after the following validation:

- All RDATEs MUST be converted to the time zone specified by **PidLidTimeZoneStruct**.
- The time-of-day information MUST be stripped off (all entries MUST fall on midnight).
- All duplicate entries MUST be removed.
- Each RDATE MUST be pairable with an EXDATE to represent a moved instance of a recurring appointment. The moved instance obeys the following rules:
  - An instance MUST NOT be moved before the previous instance or after the next instance.
  - An instance MUST NOT be moved such that the intersection of its span with the span of any other instance of the appointment has a non-zero duration.
  - An instance MUST NOT be moved such that its start time falls on the same calendar day as that of another instance.

- The **ModifiedInstanceDates** field in the **RecurrencePattern** structure MUST be sorted chronologically with the earliest dates at the start.

In addition, all valid RDATEs SHOULD [<177>](#) be stored in the **ExceptionInfo** field of the **AppointmentRecurrencePattern** structure. The contents of each **ExceptionInfo** block MUST be set as specified in the following table.

ExceptionInfo Field	Value
<b>StartDateTime</b>	Set to the RDATE value, in the time zone specified by <b>PidLidTimeZoneStruct</b>
<b>EndDateTime</b>	Set to <b>StartDateTime</b> + the duration of the appointment
<b>OriginalStartDate</b>	Set to the paired EXDATE value, in the time zone specified by <b>PidLidTimeZoneStruct</b>
<b>OverrideFlags</b>	Set to 0x00000000
<b>SubjectLength/Subject</b>	(unset)
<b>MeetingType</b>	(unset)
<b>ReminderDelta</b>	(unset)
<b>ReminderSet</b>	(unset)
<b>LocationLength/Location</b>	(unset)
<b>BusyStatus</b>	(unset)
<b>Attachment</b>	(unset)
<b>SubType</b>	(unset)
<b>AppointmentColor</b>	(unset)

Note that additional RDATEs could be derived from the DTSTARTs of other VEVENTs. See section [2.1.3.1.1.20.20](#). For exceptions generated by RECURRENCE-IDs, fields in the **ExceptionInfo** structure MUST be set according to the following table.

ExceptionInfo Field	Value
<b>StartDateTime</b>	Set to <b>PidLidAppointmentStartWhole</b> from the exception Calendar object, in the time zone specified by <b>PidLidTimeZoneStruct</b>
<b>EndDateTime</b>	Set to <b>PidLidAppointmentEndWhole</b> from the exception Calendar object, in the time zone specified by <b>PidLidTimeZoneStruct</b>
<b>OriginalStartDate</b>	Set to <b>PidLidExceptionReplaceTime</b> ( <a href="#">[MS-OXPROPS]</a> section 2.117) from the exception Calendar object, in the time zone specified by <b>PidLidTimeZoneStruct</b>
<b>OverrideFlags</b>	Set the appropriate flags specified in the next table.
<b>SubjectLength/Subject</b>	Set to <b>PidTagSubject</b> ( <a href="#">[MS-OXPROPS]</a> section 2.1096) from the exception Calendar object, leave unset if <b>PidTagSubject</b> is not present
<b>MeetingType</b>	(unset)

ExceptionInfo Field	Value
<b>ReminderDelta</b>	Set to <b>PidLidReminderDelta</b> ( <a href="#">[MS-OXPROPS]</a> section 2.219) from the exception Calendar object, leave unset if <b>PidLidReminderDelta</b> is not present
<b>ReminderSet</b>	Set to FALSE if <b>PidLidReminderDelta</b> is not present, leave unset otherwise
<b>LocationLength/Location</b>	Set to <b>PidLidLocation</b> from the exception Calendar object, leave unset if <b>PidLidLocation</b> is not present
<b>BusyStatus</b>	Set to <b>PidLidBusyStatus</b> ( <a href="#">[MS-OXPROPS]</a> section 2.47) from the exception Calendar object, leave unset if <b>PidLidBusyStatus</b> is not present
<b>Attachment</b>	(unset)
<b>SubType</b>	Set to <b>PidLidAppointmentSubType</b> from the exception Calendar object, leave unset if <b>PidLidAppointmentSubType</b> is not present
<b>AppointmentColor</b>	(unset)

The following table specifies the valid values for the **OverrideFlags** field of the **ExceptionInfo** structure.

OverrideFlags Flag	Meaning
0x0001	<b>SubjectLength</b> and <b>Subject</b> are set.
0x0004	<b>ReminderDelta</b> is set.
0x0008	<b>ReminderSet</b> is set.
0x0010	<b>LocationLength</b> and <b>Location</b> are set.
0x0020	<b>BusyStatus</b> is set.
0x0080	<b>SubType</b> is set.
0x0200	<b>PidTagRtfCompressed</b> ( <a href="#">[MS-OXPROPS]</a> section 2.1005) or <b>PidTagBody</b> from the exception Calendar object is present.

### Exporting from Calendar objects

The RDATE property MUST NOT be exported for non-recurring appointments or exceptions of recurring appointments.

If there are entries in the **ModifiedInstanceDates** field in the **RecurrencePattern** structure embedded within the **AppointmentRecurrencePattern** structure, the date-times of all instances of the recurrence pattern falling on the days specified by the **ModifiedInstanceDates** field in the **RecurrencePattern** structure SHOULD [<178>](#) be exported in an RDATE, but exceptions exported as a separate VEVENT with a RECURRENCE-ID (see section [2.1.3.1.1.20.20](#)) MUST NOT also be exported as an RDATE.

If the exception is an all-day appointment, the RDATE MUST be specified in the Date format.

### **2.1.3.1.1.20.18.1 Parameter: TZID**

RFC Reference: [\[RFC2445\]](#) section 4.2.19

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: In conjunction with a matching VTIMEZONE, specifies the time zone of a Date-Time property provided in local time.

Refer to [\[RFC2445\]](#) section 4.2.19 for additional details on the TZID parameter.

### **2.1.3.1.1.20.18.2 Parameter: VALUE**

RFC Reference: [\[RFC2445\]](#) section 4.2.20

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Specifies the format of this property.

#### **Importing to Calendar objects**

This parameter SHOULD<179> be ignored since a parser can determine whether a property is in the Date format ([\[RFC2445\]](#) section 4.3.4) or Date-Time format ([\[RFC2445\]](#) section 4.3.5) without an explicit declaration in the VALUE parameter.

#### **Exporting from Calendar objects**

If the RDATE property is specified in the Date format ([\[RFC2445\]](#) section 4.3.4), the VALUE parameter MUST be exported as 'DATE'. If the RDATE property is specified in the Date-Time format ([\[RFC2445\]](#) section 4.3.5), the VALUE parameter SHOULD be omitted, but MAY be exported as 'DATE-TIME'.

### **2.1.3.1.1.20.19 Property: RRULE**

RFC Reference: [\[RFC2445\]](#) section 4.8.5.4

Number of Instances Allowed: 0, 1

Format: Recurrence rule ([\[RFC2445\]](#) section 4.3.10)

Brief Description: Specifies the recurrence pattern of a recurring appointment.

#### **Importing to and Exporting from Calendar objects**

Section [2.1.3.2.2](#) specifies how the RRULE property is imported and exported.

### **2.1.3.1.1.20.20 Property: RECURRENCE-ID**

RFC Reference: [\[RFC2445\]](#) section 4.8.4.4

Number of Instances Allowed: 0, 1

Format: Date-Time ([\[RFC2445\]](#) section 4.3.5), Date ([\[RFC2445\]](#) section 4.3.4)

Brief Description: The original starting time of a moved exception of a recurring appointment.

### Importing to Calendar objects

This property MUST be imported into **PidLidExceptionReplaceTime**, in UTC.

In addition, if the VCALENDAR contains a recurring VEVENT with the same UID, but no RECURRENCE-ID, this entire VEVENT SHOULD [<180>](#) be treated as an exception of the recurring VEVENT. In particular:

- Instead of creating a new Calendar object in the Folder object for this VEVENT, a new Attachment object in the **Recurring Calendar object** SHOULD [<181>](#) be created (with properties specified in the following table), and **PidTagAttachDataObject** ([\[MS-OXPROPS\]](#) section 2.660) SHOULD [<182>](#) be opened as a Calendar object and used to import this VEVENT.
- The **PidTagMessageClass** of this Calendar object SHOULD [<183>](#) be overwritten to 'IPM.OLE.CLASS.{00061055-0000-0000-C000-000000000046}'.
- The recurring VEVENT SHOULD [<184>](#) treat this VEVENT's RECURRENCE-ID as an EXDATE, and this VEVENT's DTSTART as an RDATE. See section [2.1.3.1.1.20.18](#) for the effect of this exception on **PidLidAppointmentRecur**.

Attachment Object Property	Value
<b>PidTagAttachDataObject</b>	Open this property as a Calendar object interface and import the VEVENT
<b>PidTagAttachMethod</b>	Set to 0x00000005
<b>PidTagRenderingPosition</b>	Set to 0xFFFFFFFF
<b>PidTagDisplayName</b>	Set to the <b>PidTagSubject</b> of this Calendar object.
<b>PidTagExceptionStartTime</b>	Set to the <b>PidLidAppointmentStartWhole</b> of this Calendar object, local to the time zone specified by <b>PidLidTimeZoneStruct</b> of this Calendar object.
<b>PidTagAttachEncoding</b>	Set to an empty <b>PtypBinary</b>
<b>PidTagExceptionEndTime</b>	Set to the <b>PidLidAppointmentEndWhole</b> of this Calendar object, local to the time zone specified by <b>PidLidTimeZoneStruct</b> of this Calendar object.
<b>PidTagAttachmentFlags</b>	Set to 0x00000002
<b>PidTagAttachmentLinkId</b>	Set to 0x00000000
<b>PidTagAttachFlags</b>	Set to 0x00000000
<b>PidTagAttachmentHidden</b>	Set to TRUE
<b>PidTagAttachmentContactPhoto</b>	Set to FALSE

### Exporting from Calendar objects

If **PidLidExceptionReplaceTime** is set, then it MUST be exported as a RECURRENCE-ID. Otherwise, if an InstanceDate can be parsed from the 17th, 18th, 19th, and 20th bytes of **PidLidGlobalObjectId** ([\[MS-OXPROPS\]](#) section 2.142) as specified in section [2.1.3.1.1.20.26](#), then

that date combined with the time in **PidLidStartRecurrenceTime** ([MS-OXPROPS] section 2.305) in the time zone specified by **PidLidTimeZoneStruct** MUST be exported as a RECURRENCE-ID.

In addition, exceptions to recurring appointments SHOULD<185> be exported as a separate VEVENTs with a RECURRENCE-ID under either of the conditions below. Exceptions that do not fit either of these conditions MAY instead be exported as an RDATE (see section 2.1.3.1.1.20.18).

- Exceptions stored as an Attachment object with **PidTagAttachMethod** set to 0x00000005 and with the bit denoted by 0x00000002 set to 1 in **PidTagAttachmentFlags**.
- Exceptions which do anything other than, or in addition to, moving the start time of an instance without changing the duration.

The RECURRENCE-ID of new VEVENTs MUST be exported from the **OriginalStartDate** field of the corresponding **ExceptionInfo** block. Furthermore, the new VEVENTs MUST export the same UID as the recurring VEVENT. The remaining properties MUST be exported from the Calendar object embedded in **PidTagAttachDataObject** of the Attachment object. If no Attachment object exists for this exception, then the **ExceptionInfo's** fields MUST be exported as properties of the new VEVENT as specified in the following table.

ExceptionInfo Field	Export as...
<b>StartDateTime / MeetingType</b>	Export as DTSTART (see section 2.1.3.1.1.20.10)
<b>EndDateTime / MeetingType</b>	Export as DTEND (see section 2.1.3.1.1.20.8)
<b>fOriginalStartDate</b>	Export as RECURRENCE-ID
<b>SubjectLength / Subject</b>	Export as SUMMARY (see section 2.1.3.1.1.20.24), if <b>Subject</b> is set
<b>ReminderDelta / ReminderSet</b>	Export as a VALARM sub-component (see section 2.1.3.1.1.20.62), if <b>ReminderDelta</b> is set and if <b>ReminderSet</b> is not FALSE
<b>LocationLength / Location</b>	Export as LOCATION (see section 2.1.3.1.1.20.15), if <b>Location</b> is set
<b>BusyStatus</b>	Export as TRANSP (see section 2.1.3.1.1.20.25) and X-MICROSOFT-CDO-BUSYSTATUS (see section 2.1.3.1.1.20.31), if <b>BusyStatus</b> is set

If RECURRENCE-ID is exported (as specified above) and the recurring parent is not all-day, RECURRENCE-ID MUST be specified local to the time zone specified in **PidLidTimeZoneStruct**.

If RECURRENCE-ID is exported (as specified above) and the recurring parent is all-day, then the RECURRENCE-ID MUST be specified in the Date format ([RFC2445] section 4.3.4).

### 2.1.3.1.1.20.20.1 Parameter: TZID

RFC Reference: [RFC2445] section 4.2.19

Number of Instances Allowed: 0, 1

Format: Text ([RFC2445] section 4.3.11)

Brief Description: In conjunction with a matching VTIMEZONE, specifies the time zone of a Date-Time property provided in local time.



Refer to [\[RFC2445\]](#) section 4.2.19 for additional details on the TZID parameter.

### **2.1.3.1.1.20.20.2 Parameter: VALUE**

RFC Reference: [\[RFC2445\]](#) section 4.2.20

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Specifies the format of this property.

#### **Importing to Calendar objects**

This parameter SHOULD<[186](#)> be ignored since a parser can determine whether a property is in the Date format ([\[RFC2445\]](#) section 4.3.4) or Date-Time format ([\[RFC2445\]](#) section 4.3.5) without an explicit declaration in the VALUE parameter.

#### **Exporting from Calendar objects**

If the RECURRENCE-ID property is specified in the Date format ([\[RFC2445\]](#) section 4.3.4), the VALUE parameter MUST be exported as 'DATE'. If the RECURRENCE-ID property is specified in the Date-Time format ([\[RFC2445\]](#) section 4.3.5), the VALUE parameter SHOULD be omitted, but MAY be exported as 'DATE-TIME'.

### **2.1.3.1.1.20.21 Property: RESOURCES**

RFC Reference: [\[RFC2445\]](#) section 4.8.1.10

Number of Instances Allowed: 0+

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: A resource (such as rooms or equipment) for a meeting.

#### **Importing to Calendar objects**

All instances of the RESOURCES property SHOULD<[187](#)> be parsed as a comma-delimited list of strings into a string array. For each string in the array:

- All semicolons (U+003B) MUST be filtered out.
- All adjacent sequences of whitespace<[188](#)> MUST be compressed to a single space (U+0020).
- All whitespace<[189](#)> at the beginning and end of the string MUST be filtered out.
- Zero-length strings MUST be ignored.

All remaining strings in the array SHOULD<[190](#)> be added to a list delimited by ";" (U+003B) followed by U+0020) in **PidLidNonSendableBcc**.

#### **Exporting from Calendar objects**

The semicolon-delimited entries in **PidLidNonSendableBcc** SHOULD<[191](#)> be exported as a comma-delimited list in a RESOURCES property.

### 2.1.3.1.1.20.22 Property: SEQUENCE

RFC Reference: [\[RFC2445\]](#) section 4.8.7.4

Number of Instances Allowed: 0, 1

Format: Integer ([\[RFC2445\]](#) section 4.3.8)

Brief Description: Specifies the revision sequence number of the meeting request.

#### Importing to Calendar objects

If **PidLidAppointmentSequence** ([\[MS-OXPROPS\]](#) section 2.25) cannot be imported from X-MICROSOFT-CDO-APPT-SEQUENCE (section [2.1.3.1.1.20.29](#)), then this property MUST be imported into **PidLidAppointmentSequence**. If no SEQUENCE property exists, **PidLidAppointmentSequence** SHOULD [<192>](#) be left unset.

#### Exporting from Calendar objects

**PidLidAppointmentSequence** MUST be exported as the SEQUENCE property. If **PidLidAppointmentSequence** is not set, the SEQUENCE property MUST be exported as 0.

### 2.1.3.1.1.20.23 Property: STATUS

RFC Reference: [\[RFC2445\]](#) section 4.8.1.11

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Specifies the confirmation level of the appointment.

#### Importing to Calendar objects

If **PidLidBusyStatus** cannot be imported from TRANSP (section [2.1.3.1.1.20.25](#)), X-MICROSOFT-CDO-BUSYSTATUS (section [2.1.3.1.1.20.31](#)), or X-MICROSOFT-MSNCALENDAR-BUSYSTATUS (section [2.1.3.1.1.20.42](#)), this property SHOULD [<193>](#) be imported into **PidLidBusyStatus** as specified in the following table.

STATUS	PidLidBusyStatus
CANCELLED	0x00000000
TENTATIVE	0x00000001
CONFIRMED	0x00000002

#### Exporting from Calendar objects

This property SHOULD NOT be exported.

### 2.1.3.1.1.20.24 Property: SUMMARY

RFC Reference: [\[RFC2445\]](#) section 4.8.1.12

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Specifies the subject of an appointment.

### Importing to Calendar objects

This property SHOULD [<194>](#) be stripped of all carriage returns (U+000D) and line feeds (U+000A), and SHOULD [<195>](#) be truncated to a length of 255 WCHARs if its length exceeds 255 WCHARs. The truncation SHOULD NOT [<196>](#) split surrogate pairs. This property MUST be stored in **PidTagSubject**. If this property could not be imported, **PidTagSubject** SHOULD [<197>](#) be set to the zero-length string.

### Exporting from Calendar objects

**PidTagSubject** MUST be exported as a SUMMARY property. If **PidTagSubject** is not set, then the zero-length string SHOULD [<198>](#) be exported as a SUMMARY property.

## 2.1.3.1.1.20.24.1 Parameter: LANGUAGE

RFC Reference: [\[RFC2445\]](#) section 4.2.10

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Specifies the language of the property.

### Importing to Calendar objects

This parameter SHOULD [<199>](#) be parsed as a language tag (as specified in [\[RFC1766\]](#)) and stored in **PidTagMessageLocaleId** as the corresponding [\[MS-LCID\]](#) language code identifier.

### Exporting from Calendar objects

**PidTagMessageLocaleId** SHOULD [<200>](#) be converted from an [MS-LCID] language code identifier to an [\[RFC1766\]](#) language tag and exported as a LANGUAGE parameter.

## 2.1.3.1.1.20.25 Property: TRANSP

RFC Reference: [\[RFC2445\]](#) section 4.8.2.7

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Specifies whether or not this appointment is intended to be visible in availability searches.

### Importing to Calendar objects

If **PidLidBusyStatus** cannot be imported from X-MICROSOFT-CDO-BUSYSTATUS (section [2.1.3.1.1.20.31](#)) or X-MICROSOFT-MSNCALENDAR-BUSYSTATUS (section [2.1.3.1.1.20.42](#)), this property SHOULD [<201>](#) be imported into **PidLidBusyStatus** as specified in the following table.

STATUS	PidLidBusyStatus
TRANSPARENT	0x00000000
OPAQUE	0x00000002

## Exporting from Calendar objects

This property SHOULD [<202>](#) be exported from **PidLidBusyStatus** as specified in the following table.

PidLidBusyStatus	STATUS
0x00000000	TRANSPARENT
0x00000001	OPAQUE
0x00000002	OPAQUE
0x00000003	OPAQUE
0x00000004 <a href="#">&lt;203&gt;</a>	TRANSPARENT

### 2.1.3.1.1.20.26 Property: UID

RFC Reference: [\[RFC2445\]](#) section 4.8.4.7

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Provides a globally unique identifier for the appointment.

### Importing to Calendar objects

There are two supported forms of textual representation of the UID property. The **Augmented Backus-Naur Form (ABNF)** syntax, as specified in [\[RFC5234\]](#), for this value is shown in the following example.

```
UID = EncodedGlobalId / ThirdPartyGlobalId

EncodedGlobalId      = Header GlobalIdData
ThirdPartyGlobalId   = 1*UTF8-octets      ; Assuming UTF-8 is the encoding

Header = ByteArrayID InstanceDate CreationDateTime Padding DataSize

ByteArrayID          = "040000008200E00074C5B7101A82E008"
InstanceDate         = InstanceYear InstanceMonth InstanceDay
InstanceYear         = 4*4HEXDIG          ; UInt16
InstanceMonth        = 2*2HEXDIG          ; UInt8
InstanceDay          = 2*2HEXDIG          ; UInt8
CreationDateTime     = FileTime
FileTime             = 16*16HEXDIG        ; UInt64
Padding              = 16*16HEXDIG        ; "0000000000000000" recommended
DataSize             = 8*8HEXDIG          ; UInt32 little-endian
GlobalIdData         = 2*HEXDIG

UTF8-octets = *( UTF8-char )
UTF8-char   = UTF8-1 / UTF8-2 / UTF8-3 / UTF8-4
UTF8-1      = %x00-7F
UTF8-2      = %xC2-DF UTF8-tail
UTF8-3      = %xE0 %xA0-BF UTF8-tail / %xE1-EC 2( UTF8-tail ) /
              %xED %x80-9F UTF8-tail / %xEE-EF 2( UTF8-tail )
UTF8-4      = %xF0 %x90-BF 2( UTF8-tail ) / %xF1-F3 3( UTF8-tail ) /
```

```
UTF8-tail = %x80-BF
           %xF4 %x80-8F 2( UTF8-tail )
```

To be of type **EncodedGlobalId**, the value of the UID property MUST satisfy the following constraints:

- Every character MUST be a HEXDIG.
- The length of the string MUST be eighty-two (82) characters or more.
- The length of the string MUST be evenly divisible by 2.
- The first thirty-two characters MUST match (case insensitive) [<204>](#) "040000008200E00074C5B7101A82E008".

Otherwise, the UID property is of type **ThirdPartyGlobalId**.

If the UID is of type **EncodedGlobalId**, then the data MUST be decoded to its binary representation (every two HEXDIGs compose one byte).

A temporary variable *EffectiveInstanceDate* is defined as follows:

- If the UID is of type **EncodedGlobalId** and if the **InstanceDate** portion of the UID is a valid date in the range of January 1st, 1601 to December 31st, 4500 (inclusive), then the *EffectiveInstanceDate* is the **ThirdPartyGlobalId** portion of the UID.
- If the UID is of type **EncodedGlobalId** but the **ThirdPartyGlobalId** portion of the UID is not a valid date in the range of January 1st, 1601 to December 31st, 4500 (inclusive), then the *EffectiveInstanceDate* is the date from the RECURRENCE-ID property (in its local time zone). In the case where RECURRENCE-ID property is not present, the *EffectiveInstanceDate* is zero (Year = Month = Day = 0).
- If the UID is of type **ThirdPartyGlobalId**, then the *EffectiveInstanceDate* is the date from the RECURRENCE-ID property (in its local time zone). In the case where RECURRENCE-ID property is not present, the *EffectiveInstanceDate* is zero (Year = Month = Day = 0).

If the UID is of type **EncodedGlobalId**, it MUST be imported into **PidLidGlobalObjectId** as specified below. The **PidLidGlobalObjectId** structure is specified in [\[MS-OXOCAL\]](#) section 2.2.1.27.

- The **Byte Array ID** field MUST be set to: 0x04, 0x00, 0x00, 0x00, 0x82, 0x00, 0xE0, 0x00, 0x74, 0xC5, 0xB7, 0x10, 0x1A, 0x82, 0xE0, 0x08.
- The **YH** field MUST be set to the high byte of the *EffectiveInstanceDate*'s year.
- The **YL** field MUST be set to the low byte of the *EffectiveInstanceDate*'s year.
- The **M** field MUST be set to the value of the *EffectiveInstanceDate*'s month.
- The **D** field MUST be set to the value of the *EffectiveInstanceDate*'s day.
- The **Creation Time** field MUST be set to the CreationDateTime value.
- The **X** field MUST be set to the Padding value.
- The **Size** field MUST be set to the DataSize value.

- The **Data** field MUST be set to the binary value of GlobalIdData.

If the UID is of type **EncodedGlobalId**, it MUST also be imported into **PidLidCleanGlobalObjectId** ([MS-OXPROPS] section 2.57) as specified below. The **PidLidCleanGlobalObjectId** structure is specified in [MS-OXOCAL] section 2.2.1.28.

- The **Byte Array ID** field MUST be set to: 0x04, 0x00, 0x00, 0x00, 0x82, 0x00, 0xE0, 0x00, 0x74, 0xC5, 0xB7, 0x10, 0x1A, 0x82, 0xE0, 0x08.
- The **YH** field MUST be set to 0x00.
- The **YL** field MUST be set to 0x00.
- The **M** field MUST be set to 0x00.
- The **D** field MUST be set to 0x00.
- The **Creation Time** field MUST be set to the CreationDateTime value.
- The **X** field MUST be set to the Padding value.
- The **Size** field MUST be set to the DataSize value.
- The **Data** field MUST be set to the binary value of GlobalIdData.

If the UID is of type **ThirdPartyGlobalId**, it MUST be imported into **PidLidGlobalObjectId** as specified below.

- The **Byte Array ID** field MUST be set to: 0x04, 0x00, 0x00, 0x00, 0x82, 0x00, 0xE0, 0x00, 0x74, 0xC5, 0xB7, 0x10, 0x1A, 0x82, 0xE0, 0x08.
- The **YH** field MUST be set to the high byte of the *EffectiveInstanceDate*'s year.
- The **YL** field MUST be set to the low byte of the *EffectiveInstanceDate*'s year.
- The **M** field MUST be set to the value of the *EffectiveInstanceDate*'s month.
- The **D** field MUST be set to the value of the *EffectiveInstanceDate*'s day.
- The **Creation Time** field MUST be set to 0x0000000000000000.
- The **X** field MUST be set to 0x0000000000000000.
- The **Size** field MUST be set to the number of OCTETS in **ThirdPartyGlobalId** (UTF-8 encoded length) + 0x0000000C.
- The **Data** field MUST be set to the following bytes: 0x76, 0x43, 0x61, 0x6C, 0x2D, 0x55, 0x69, 0x64, 0x01, 0x00, 0x00, 0x00, followed by the value of **ThirdPartyGlobalId** (encoded in UTF-8).

If the UID is of type **ThirdPartyGlobalId**, it MUST also be imported into **PidLidCleanGlobalObjectId** as specified below.

- The **Byte Array ID** field MUST be set to: 0x04, 0x00, 0x00, 0x00, 0x82, 0x00, 0xE0, 0x00, 0x74, 0xC5, 0xB7, 0x10, 0x1A, 0x82, 0xE0, 0x08.
- The **YH** field MUST be set to 0x00.
- The **YL** field MUST be set to 0x00.

- The **M** field MUST be set to 0x00.
- The **D** field MUST be set to 0x00.
- The **Creation Time** field MUST be set to 0x0000000000000000.
- The **X** field MUST be set to 0x0000000000000000.
- The **Size** field MUST be set to the number of OCTETS in **ThirdPartyGlobalId** (UTF-8 encoded length) + 0x0000000C.
- The **Data** field MUST be set to the following bytes: 0x76, 0x43, 0x61, 0x6C, 0x2D, 0x55, 0x69, 0x64, 0x01, 0x00, 0x00, 0x00, followed by the value of **ThirdPartyGlobalId** (encoded in UTF-8).

#### Exporting from Calendar objects

If the **Data** field of **PidLidGlobalObjectId** begins with the following 12 bytes: 0x76, 0x43, 0x61, 0x6C, 0x2D, 0x55, 0x69, 0x64, 0x01, 0x00, 0x00, 0x00, the remainder of the **Data** field (starting at the 13th byte) MUST be treated as a UTF-8 encoded string and exported directly as the UID property.

Otherwise, a modified copy of **PidLidGlobalObjectId**, with the **YH**, **YL**, **M**, and **D** fields set to 0x00, MUST be encoded as a hexadecimal string, and exported as the UID property.

### 2.1.3.1.1.20.27 Property: X-ALT-DESC

RFC Reference: N/A

Number of Instances Allowed: 0+

Format: Text ([RFC2445] section 4.3.11)

Brief Description: Provides an alternate format for the DESCRIPTION property (an **HTML** body).

#### Importing To Calendar objects

If the FMTTYPE parameter is 'text/HTML', then the HTML SHOULD [<205>](#) be converted to encapsulated **RTF** as specified in [\[MS-OXRTFEX\]](#) and stored in **PidTagRtfCompressed**, as specified in [\[MS-OXRTFCP\]](#).

If the FMTTYPE parameter is absent or undocumented, then the X-ALT-DESC property SHOULD be ignored.

#### Exporting from Calendar objects

**PidTagRtfCompressed** SHOULD [<206>](#) be converted to HTML and exported as an X-ALT-DESC property with a FMTTYPE parameter of 'text/HTML'.

### 2.1.3.1.1.20.27.1 Parameter: FMTTYPE

RFC Reference: [\[RFC2445\]](#) section 4.2.8

Number of Instances Allowed: 0, 1

Format: Text ([RFC2445] section 4.3.11)

Brief Description: Specifies the text format of the X-ALT-DESC property.

## Importing to and Exporting from Calendar objects

See section [2.1.3.1.1.20.27](#).

### 2.1.3.1.1.20.28 Property: X-MICROSOFT-CDO-ALLDAYEVENT

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Boolean ([\[RFC2445\]](#) section 4.3.2)

Brief Description: Specifies whether an appointment is intended to be treated as all-day.

#### Importing to Calendar objects

If this property is set to TRUE and if DTSTART and DTEND are both specified as local times falling at midnight in their respective [<207>](#) time zones, then this appointment SHOULD [<208>](#) be imported as an all-day appointment. Specifically, **PidLidAppointmentSubType** SHOULD [<209>](#) be set to 0x00000001 and **PidLidAppointmentStartWhole** and **PidLidAppointmentEndWhole** SHOULD [<210>](#) be set to fall on midnight of the current system time zone (in UTC).

#### Exporting from Calendar objects

This property SHOULD NOT [<211>](#) be exported. Section [2.1.3.1.1.20.10](#) specifies how to correctly export all-day events.

### 2.1.3.1.1.20.29 Property: X-MICROSOFT-CDO-APPT-SEQUENCE

RFC Reference: N/A

Number of Instances Allowed: 0,1

Format: Integer ([\[RFC2445\]](#) section 4.3.8)

Brief Description: Specifies the sequence number of the meeting request.

#### Importing to Calendar objects

This property SHOULD [<212>](#) be imported into **PidLidAppointmentSequence**.

#### Exporting from Calendar objects

This property SHOULD NOT [<213>](#) be exported. Section [2.1.3.1.1.20.22](#) specifies how to correctly export **PidLidAppointmentSequence** using the SEQUENCE property.

### 2.1.3.1.1.20.30 Property: X-MICROSOFT-CDO-ATTENDEE-CRITICAL-CHANGE

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Date-Time ([\[RFC2445\]](#) section 4.3.5)

Brief Description: Specifies the time at which the attendee accepted, tentatively accepted, or declined the meeting request.

#### Importing to Calendar objects



This property MAY [<214>](#) be imported as **PidLidAttendeeCriticalChange**.

#### Exporting from Calendar objects

**PidLidAttendeeCriticalChange** MAY [<215>](#) be exported as X-MICROSOFT-CDO-ATTENDEE-CRITICAL-CHANGE.

### 2.1.3.1.1.20.31 Property: X-MICROSOFT-CDO-BUSYSTATUS

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Specifies the BUSY status of an appointment.

#### Importing to and Exporting from Calendar objects

This property SHOULD [<216>](#) be mapped into **PidLidBusyStatus** as specified by the following table.

X-MICROSOFT-CDO-BUSYSTATUS	PidLidBusyStatus
FREE	0x00000000
TENTATIVE	0x00000001
BUSY	0x00000002
OOF	0x00000003

### 2.1.3.1.1.20.32 Property: X-MICROSOFT-CDO-IMPORTANCE

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Integer ([\[RFC2445\]](#) section 4.3.8)

Brief Description: Specifies the importance of an appointment.

#### Importing to Calendar objects

This property SHOULD be imported into **PidTagImportance** as specified by the following table.

X-MICROSOFT-CDO-IMPORTANCE	PidTagImportance
0	0x00000000
1	0x00000001
2	0x00000002

#### Exporting from Calendar objects

This property SHOULD be exported as specified in the preceding table.

### 2.1.3.1.1.20.33 Property: X-MICROSOFT-CDO-INSTTYPE

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Integer ([\[RFC2445\]](#) section 4.3.8)

Brief Description: Indicates whether the VEVENT represents a non-recurring appointment, a recurring appointment, or an exception to a recurring appointment.

#### Importing to Calendar objects

This property SHOULD be ignored.

#### Exporting from Calendar objects

This property SHOULD NOT [<217>](#) be exported. The instance type of a VEVENT can be correctly determined based on the existence of the RRULE and RECURRENCE-ID properties.

### 2.1.3.1.1.20.34 Property: X-MICROSOFT-CDO-INTENDEDSTATUS

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Specifies the busy status that the meeting organizer intends the attendee's copy of the meeting to have.

#### Importing to Calendar objects

This property SHOULD [<218>](#) be imported into **PidLidIntendedBusyStatus** ([\[MS-OXPROPS\]](#) section 2.151) using the same import mapping as X-MICROSOFT-CDO-BUSYSTATUS as specified in section [2.1.3.1.1.20.31](#).

If the METHOD property is REQUEST and an X-MICROSOFT-CDO-INTENDEDSTATUS property is present, the value of the **PidLidBusyStatus** property ([\[MS-OXOCAL\]](#) section 2.2.1.2) MAY [<219>](#) be set to 0x00000001.

If the METHOD property is REQUEST and an X-MICROSOFT-CDO-INTENDEDSTATUS property is absent, then **PidLidIntendedBusyStatus** SHOULD [<220>](#) copy the value of **PidLidBusyStatus**, defaulting to 0x00000002 if **PidLidBusyStatus** was not set, and **PidLidBusyStatus** SHOULD [<221>](#) be set to 0x00000001.

#### Exporting from Calendar objects

If the METHOD property is REQUEST, **PidLidIntendedBusyStatus** SHOULD [<222>](#) be exported as X-MICROSOFT-CDO-INTENDEDSTATUS using the mapping specified in section [2.1.3.1.1.20.31](#).

### 2.1.3.1.1.20.35 Property: X-MICROSOFT-CDO-OWNERAPPTID

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Integer ([\[RFC2445\]](#) section 4.3.8)

Brief Description: Provides an identifier for the appointment which is unique in the scope of the organizer's primary calendar.

#### **Importing to and Exporting from Calendar objects**

This property SHOULD [<223>](#) be directly imported to and exported from **PidTagOwnerAppointmentId** ([\[MS-OXPROPS\]](#) section 2.922).

### **2.1.3.1.1.20.36 Property: X-MICROSOFT-CDO-OWNER-CRITICAL-CHANGE**

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Date-Time ([\[RFC2445\]](#) section 4.3.5)

Brief Description: Specifies the time at which the organizer requested, updated, or cancelled the meeting.

#### **Importing to Calendar objects**

When present, this property MAY [<224>](#) be imported as **PidLidOwnerCriticalChange**.

#### **Exporting from Calendar objects**

**PidLidOwnerCriticalChange** MAY [<225>](#) be exported as X-MICROSOFT-CDO-OWNER-CRITICAL-CHANGE.

### **2.1.3.1.1.20.37 Property: X-MICROSOFT-CDO-REPLYTIME**

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Date-Time ([\[RFC2445\]](#) section 4.3.5)

Brief Description: Specifies the time in which the attendee responded to a meeting request.

#### **Importing to Calendar objects**

This property MAY [<226>](#) be imported as **PidLidAppointmentReplyTime**.

#### **Exporting from Calendar objects**

**PidLidAppointmentReplyTime** MAY [<227>](#) be exported as X-MICROSOFT-CDO-REPLYTIME.

### **2.1.3.1.1.20.38 Property: X-MICROSOFT-DISALLOW-COUNTER**

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Boolean ([\[RFC2445\]](#) section 4.3.2)

Brief Description: Specifies whether or not the organizer is willing to receive counter-proposals.

#### **Importing to and Exporting from Calendar objects**

This property SHOULD<228> be directly imported to and exported from **PidLidAppointmentNotAllowPropose** ([MS-OXPROPS] section 2.17).

### 2.1.3.1.1.20.39 Property: X-MICROSOFT-EXDATE

RFC Reference: N/A

Number of Instances Allowed: 0+

Format: Date-Time ([RFC2445] section 4.3.5), Date ([RFC2445] section 4.3.4)

Brief Description: Specifies the original start time of instances of the recurring appointment which have been deleted.

#### Importing to Calendar objects

If this property is specified, an X-MICROSOFT-RRULE MUST also be specified in the same VEVENT.

This property SHOULD<229> be imported in the same way that the EXDATE property is imported. See section 2.1.3.1.1.20.13.

#### Exporting from Calendar objects

The X-MICROSOFT-EXDATE property MUST NOT be exported for non-recurring appointments or exceptions of recurring appointments.

If the **CalendarType** field of the **RecurrencePattern** field of the **AppointmentRecurrencePattern** structure ([MS-OXOCAL] section 2.2.1.44.5) in the **PidLidAppointmentRecur** property ([MS-OXOCAL] section 2.2.1.44) is non-zero or if the **PatternType** field is 0x000A or 0x000B, this property SHOULD<230> be exported in place of the EXDATE property. If exported, the value of this property MUST be exactly what the value of the EXDATE property would have been (see section 2.1.3.1.1.20.13).

### 2.1.3.1.1.20.39.1 Parameter: VALUE

RFC Reference: [RFC2445] section 4.2.20

Number of Instances Allowed: 0, 1

Format: Text ([RFC2445] section 4.3.11)

Brief Description: Specifies the format of this property.

#### Importing to Calendar objects

This parameter SHOULD be ignored.

#### Exporting from Calendar objects

This parameter MUST be exported as 'DATE-TIME'.

### 2.1.3.1.1.20.40 Property: X-MICROSOFT-ISDRAFT

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Boolean ([RFC2445] section 4.3.2)

Brief Description: Specifies whether an appointment is intended to be treated as all-day.

#### **Importing to Calendar objects**

For iCalendar files with a method of REQUEST, REPLY, CANCEL, or COUNTER, **PidLidFInvited** ([\[MS-OXPROPS\]](#) section 2.135) MUST be set to TRUE regardless of the value of X-MICROSOFT-ISDRAFT.

For iCalendar files with a method of publish, **PidLidFInvited** SHOULD<231> be set to TRUE if the VEVENT is a meeting and X-MICROSOFT-ISDRAFT is not set to TRUE. Otherwise, **PidLidFInvited** SHOULD be set to FALSE.

#### **Exporting from Calendar objects**

For iCalendar files with a method of PUBLISH, if the organizer of the meeting is the user and if **PidLidFInvited** is not TRUE, then X-MICROSOFT-ISDRAFT SHOULD<232> be exported as TRUE.

For all other cases, X-MICROSOFT-ISDRAFT MUST NOT be exported.

### **2.1.3.1.1.20.41 Property: X-MICROSOFT-MSNCALENDAR-ALLDAYEVENT**

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Boolean ([\[RFC2445\]](#) section 4.3.2)

Brief Description: Specifies whether an appointment is intended to be treated as all day.

#### **Importing to and Exporting from Calendar objects**

This property is synonymous with X-MICROSOFT-CDO-ALLDAYEVENT.<233> See section [2.1.3.1.1.20.28](#) for usage.

### **2.1.3.1.1.20.42 Property: X-MICROSOFT-MSNCALENDAR-BUSYSTATUS**

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Specifies the busy status of an appointment.

#### **Importing to Calendar objects**

This property is synonymous with X-MICROSOFT-CDO-BUSYSTATUS (see section [2.1.3.1.1.20.31](#)) and SHOULD<234> be imported into **PidLidBusyStatus** as specified in section [2.1.3.1.1.20.31](#).

#### **Exporting from Calendar objects**

This property SHOULD NOT be exported.

### **2.1.3.1.1.20.43 Property: X-MICROSOFT-MSNCALENDAR-IMPORTANCE**

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Integer ([\[RFC2445\]](#) section 4.3.8)

Brief Description: Specifies the importance of an appointment.

#### **Importing to and Exporting from Calendar objects**

This property is synonymous [<235>](#) with X-MICROSOFT-CDO-IMPORTANCE. See section [2.1.3.1.1.20.32](#) for usage.

### **2.1.3.1.1.20.44 Property: X-MICROSOFT-MSNCALENDAR-INTENDEDSTATUS**

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Specifies the busy status that the meeting organizer intends the attendee's copy of the meeting to have.

#### **Importing to Calendar objects**

This property is synonymous with X-MICROSOFT-CDO-INTENDEDSTATUS (see section [2.1.3.1.1.20.34](#)) and SHOULD [<236>](#) be imported into **PidLidIntendedBusyStatus** as specified in section [2.1.3.1.1.20.31](#).

#### **Exporting from Calendar objects**

This property SHOULD NOT be exported.

### **2.1.3.1.1.20.45 Property: X-MICROSOFT-RRULE**

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Recurrence rule ([\[RFC2445\]](#) section 4.3.10)

Brief Description: Specifies the recurrence pattern of a recurring appointment.

#### **Importing to and Exporting from Calendar objects**

Section [2.1.3.2.2](#) specifies how the X-MICROSOFT-RRULE property is imported and exported.

If this property is specified, an X-MICROSOFT-CALSCALE MUST also be specified in the same VEVENT.

#### **2.1.3.1.1.20.45.1 Parameter: VALUE**

RFC Reference: [\[RFC2445\]](#) section 4.2.20

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Specifies the format of this property.

#### **Importing to Calendar objects**

This parameter SHOULD be ignored.

#### **Exporting from Calendar objects**

This parameter MUST be exported as 'RECUR'.

### **2.1.3.1.1.20.45.2 Parameter: X-MICROSOFT-ISLEAPMONTH**

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Boolean ([\[RFC2445\]](#) section 4.3.2)

Brief Description: Specifies whether the month specified in a yearly non-Gregorian recurrence is a leap month of that calendar.

#### **Importing to Calendar objects**

This parameter SHOULD be ignored. The month of a yearly recurrence is determined from DTSTART.

#### **Exporting from Calendar objects**

If the recurrence is a Yearly (section [2.1.3.2.2.5](#)) or Yearly Nth (section [2.1.3.2.2.6](#)), this property SHOULD<237> be exported as a Boolean ([\[RFC2445\]](#) section 4.3.2) indicating whether or not the month of the recurrence is a leap month.

### **2.1.3.1.1.20.46 Property: X-MS-OLK-ALLOWEXTERNCHECK**

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Boolean ([\[RFC2445\]](#) section 4.3.2)

Brief Description: Specifies whether attendees not directly invited by the organizer can connect to the conferencing instance.

#### **Importing to and Exporting from Calendar objects**

This property SHOULD<238> be directly imported to and exported from **PidLidAllowExternalCheck** ([\[MS-OXPROPS\]](#) section 2.6).

### **2.1.3.1.1.20.47 Property: X-MS-OLK-APPTLASTSEQUENCE**

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Integer ([\[RFC2445\]](#) section 4.3.8)

Brief Description: Specifies the last-known maximum sequence number of a meeting.

#### **Importing to and Exporting from Calendar objects**

This property SHOULD<239> be directly imported to and exported from **PidLidAppointmentLastSequence** ([\[MS-OXPROPS\]](#) section 2.15).

### 2.1.3.1.1.20.48 Property: X-MS-OLK-APPTSEQTIME

RFC Reference: N/A

Number of Instances Allowed: 1

Format: Date-Time ([\[RFC2445\]](#) section 4.3.5), Date ([\[RFC2445\]](#) section 4.3.4)

Brief Description: The creation time of the iCalendar.

#### Importing to Calendar objects

This property SHOULD [<240>](#) be imported (in UTC) to **PidLidAppointmentSequenceTime** ([\[MS-OXPROPS\]](#) section 2.26).

#### Exporting from Calendar objects

**PidLidAppointmentSequenceTime** SHOULD [<241>](#) be exported as this property (in UTC).

### 2.1.3.1.1.20.48.1 Parameter: TZID

RFC Reference: [\[RFC2445\]](#) section 4.2.19

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: In conjunction with a matching VTIMEZONE, specifies the time zone of a Date-Time property provided in local time.

Refer to [\[RFC2445\]](#) section 4.2.19 for additional details on the TZID parameter.

### 2.1.3.1.1.20.49 Property: X-MS-OLK-AUTOFILLLOCATION

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Boolean ([\[RFC2445\]](#) section 4.3.2)

Brief Description: Specifies whether the location is being automatically populated with recipients (1) of type RESOURCE.

#### Importing to and Exporting from Calendar objects

This property SHOULD [<242>](#) be directly imported to and exported from **PidLidAutoFillLocation** ([\[MS-OXPROPS\]](#) section 2.38).

### 2.1.3.1.1.20.50 Property: X-MS-OLK-AUTOSTARTCHECK

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Boolean ([\[RFC2445\]](#) section 4.3.2)

Brief Description: Specifies whether or not to automatically start the conferencing application when a **reminder** for the meeting fires.



### **Importing to and Exporting from Calendar objects**

This property SHOULD [<243>](#) be directly imported to and exported from **PidLidAutoStartCheck** ([\[MS-OXPROPS\]](#) section 2.41).

#### **2.1.3.1.1.20.51 Property: X-MS-OLK-COLLABORATEDOC**

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Specifies the path to the conferencing collaboration document.

### **Importing to and Exporting from Calendar objects**

This property SHOULD [<244>](#) be directly imported to and exported from **PidLidCollaborateDoc** ([\[MS-OXPROPS\]](#) section 2.61).

#### **2.1.3.1.1.20.52 Property: X-MS-OLK-CONFHECK**

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Boolean ([\[RFC2445\]](#) section 4.3.2)

Brief Description: Specifies whether or not conferencing is enabled on this appointment.

### **Importing to and Exporting from Calendar objects**

This property SHOULD [<245>](#) be directly imported to and exported from **PidLidConferencingCheck** ([\[MS-OXPROPS\]](#) section 2.65).

#### **2.1.3.1.1.20.53 Property: X-MS-OLK-CONFTYPE**

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Integer ([\[RFC2445\]](#) section 4.3.8)

Brief Description: Specifies the type of conferencing that is enabled on the appointment.

### **Importing to and Exporting from Calendar objects**

This property SHOULD [<246>](#) be directly imported to and exported from **PidLidConferencingType** ([\[MS-OXPROPS\]](#) section 2.66).

#### **2.1.3.1.1.20.54 Property: X-MS-OLK-DIRECTORY**

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Specifies the path to the conferencing server.

#### **Importing to and Exporting from Calendar objects**

This property SHOULD [<247>](#) be directly imported to and exported from **PidLidDirectory** ([\[MS-OXPROPS\]](#) section 2.94).

#### **2.1.3.1.1.20.55 Property: X-MS-OLK-MWSURL**

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Specifies the **URL** of the **Meeting Workspace**.

#### **Importing to and Exporting from Calendar objects**

This property SHOULD [<248>](#) be directly imported to and exported from **PidLidMeetingWorkspaceUrl** ([\[MS-OXPROPS\]](#) section 2.171).

#### **2.1.3.1.1.20.56 Property: X-MS-OLK-NETSHOWURL**

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Specifies the URL of the NetShow conference.

#### **Importing to and Exporting from Calendar objects**

This property SHOULD [<249>](#) be directly imported to and exported from **PidLidNetShowUrl** ([\[MS-OXPROPS\]](#) section 2.175).

#### **2.1.3.1.1.20.57 Property: X-MS-OLK-ONLINEPASSWORD**

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Specifies the password to the conferencing instance.

#### **Importing to and Exporting from Calendar objects**

This property SHOULD [<250>](#) be directly imported to and exported from **PidLidOnlinePassword** ([\[MS-OXPROPS\]](#) section 2.193).

#### **2.1.3.1.1.20.58 Property: X-MS-OLK-ORGALIAS**

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Specifies the e-mail address of the conferencing instance's organizer.

#### **Importing to and Exporting from Calendar objects**

This property SHOULD<251> be directly imported to and exported from **PidLidOrganizerAlias** ([\[MS-OXPROPS\]](#) section 2.195).

### **2.1.3.1.1.20.59 Property: X-MS-OLK-ORIGINALEND**

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Date-Time ([\[RFC2445\]](#) section 4.3.5), Date ([\[RFC2445\]](#) section 4.3.4)

Brief Description: Specifies the original end time of a meeting on a counter proposal.

#### **Importing to and Exporting from Calendar objects**

If the METHOD property of the VCALENDAR component is set to 'COUNTER', this property SHOULD<252> be directly mapped to **PidLidAppointmentEndWhole**, and **PidLidAppointmentDuration** SHOULD<253> be set to the number of minutes between X-MS-OLK-ORIGINALSTART and X-MS-OLK-ORIGINALEND.

For other values of METHOD, X-MS-OLK-ORIGINALEND MUST be ignored and MUST NOT be exported.

### **2.1.3.1.1.20.60 Property: X-MS-OLK-ORIGINALSTART**

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: Date-Time ([\[RFC2445\]](#) section 4.3.5), Date ([\[RFC2445\]](#) section 4.3.4)

Brief Description: Specifies the original start time of a meeting on a counter proposal.

#### **Importing to and Exporting from Calendar objects**

If the METHOD property of the VCALENDAR component is set to 'COUNTER', this property SHOULD<254> be directly mapped to **PidLidAppointmentStartWhole**, and **PidLidAppointmentDuration** SHOULD<255> be set to the number of minutes between X-MS-OLK-ORIGINALSTART and X-MS-OLK-ORIGINALEND.

For other values of METHOD, X-MS-OLK-ORIGINALSTART MUST be ignored and MUST NOT be exported.

### **2.1.3.1.1.20.61 Property: X-MS-OLK-SENDER**

RFC Reference: N/A

Number of Instances Allowed: 0, 1

Format: URI ([\[RFC2445\]](#) section 4.3.13)

Brief Description: The **delegate** sending the meeting on behalf of the organizer.

## Importing to Calendar objects

This property SHOULD<256> be parsed as a valid mailto URI, as specified in [\[RFC2368\]](#). The resulting SMTP address SHOULD<257> be resolved against the address book, as specified in [\[MS-OXOABK\]](#). If no match was found, a one-off EntryID ([\[MS-OXCDATA\]](#) section 2.2.5.1) SHOULD<258> be created using the SMTP address and the CN parameter. If resolved successfully, the Address Book object SHOULD<259> be imported into **PidTagSenderAddressType** ([\[MS-OXPROPS\]](#) section 2.1064), **PidTagSenderEmailAddress** ([\[MS-OXPROPS\]](#) section 2.1065), **PidTagSenderEntryId** ([\[MS-OXPROPS\]](#) section 2.1066), and **PidTagSenderName** ([\[MS-OXPROPS\]](#) section 2.1068).

## Exporting from Calendar objects

If the 0x00000001 flag of **PidLidAppointmentStateFlags** is 0, then an X-MS-OLK-SENDER property MUST NOT be exported. Also, if **PidTagSenderEntryId** refers to the same Address Book object as the organizer, then the X-MS-OLK-SENDER property SHOULD NOT be exported.

The value of this property SHOULD<260> be a mailto URI, as specified in [\[RFC2368\]](#), with the SMTP address of the Address Book object, as specified in [\[MS-OXOABK\]](#), referenced by **PidTagSenderEntryId**. If the Address Book object does not have an SMTP address, then the value of the property SHOULD<261> be set to 'invalid:nomail'.

### 2.1.3.1.1.20.61.1 Parameter: CN

RFC Reference: [\[RFC2445\]](#) section 4.2.2

Number of Instances Allowed: 0,1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: The display name of the delegate sending the meeting on behalf of the organizer.

## Importing to Calendar objects

See section [2.1.3.1.1.20.61](#).

## Exporting from Calendar objects

This parameter SHOULD<262> be exported from the **PidTagDisplayName** from the Address Book object (falling back on the **PidTagSenderName** from the Calendar object, if necessary).

### 2.1.3.1.1.20.62 Component: VALARM

RFC Reference: [\[RFC2445\]](#) section 4.6.6

Number of Instances Allowed: 0, 1

Brief Description: Specifies a reminder for an appointment.

## Importing to Calendar objects

If there is a VALARM component with a TRIGGER property specified as a Duration ([\[RFC2445\]](#) section 4.3.6) or a Date-Time ([\[RFC2445\]](#) section 4.3.5), then it MUST be parsed according to the following table.

Named Property	Value
<b>PidLidReminderDelta</b>	If TRIGGER is specified as a Duration, <b>PidLidReminderDelta</b> MUST be set to the absolute value of the number of minutes specified by the TRIGGER property. If TRIGGER is specified as a Date-Time, <b>PidLidReminderDelta</b> SHOULD<263> be set to the difference in minutes between DTSTART and the value of TRIGGER. If no such TRIGGER property could be parsed, <b>PidLidReminderDelta</b> SHOULD<264> be set to 0x0000000F for non-all day appointments and 0x00000438 for all day appointments.
<b>PidLidReminderTime</b> ([MS-OXPROPS] section 2.225)	MUST be set to the next instance of the appointment, in UTC. If all instances of the appointment are in the past, then this property SHOULD NOT be set.
<b>PidLidReminderSignalTime</b> ([MS-OXPROPS] section 2.224)	If TRIGGER is specified as a Duration, <b>PidLidReminderSignalTime</b> SHOULD<265> be set to <b>PidLidReminderDelta</b> minutes earlier than <b>PidLidReminderTime</b> . If TRIGGER is specified as a Date-Time, <b>PidLidReminderSignalTime</b> SHOULD<266> be set to the value of TRIGGER in UTC. If <b>PidLidReminderTime</b> is not set, then this property SHOULD NOT be set.
<b>PidLidReminderSet</b> ([MS-OXPROPS] section 2.223)	MUST be set to TRUE if and only if <b>PidLidReminderDelta</b> was successfully parsed from a TRIGGER property and <b>PidLidReminderTime</b> was set.

### Exporting from Calendar objects

If **PidLidReminderSet** is TRUE, then a VALARM component MUST be exported with the properties specified in the following table.

VALARM Property	Value
TRIGGER	MUST be set to a Duration ([RFC2445] section 4.3.6) representing the number of minutes specified by <b>PidLidReminderDelta</b> . If <b>PidLidReminderDelta</b> is set to 0x5AE980E1, TRIGGER MUST be exported as 15 minutes.
ACTION	MUST be set to 'DISPLAY'
DESCRIPTION	MUST be set to 'Reminder'

#### 2.1.3.1.1.20.62.1 Property: TRIGGER

RFC Reference: [RFC2445] section 4.8.6.3

Number of Instances Allowed: 1

Format: Duration ([RFC2445] section 4.3.6), Date-Time ([RFC2445] section 4.3.5)

Brief Description: Specifies the **signal time** of the reminder as an interval, in minutes, before the beginning of an instance of the appointment.

#### Importing to and Exporting from Calendar objects

See [2.1.3.1.1.20.62](#).

### **2.1.3.1.1.20.62.2 Property: ACTION**

RFC Reference: [\[RFC2445\]](#) section 4.8.6.1

Number of Instances Allowed: 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Specifies the action to take when the reminder is signaled.

#### **Importing to Calendar objects**

This property SHOULD be ignored on import.

#### **Exporting from Calendar objects**

See [2.1.3.1.1.20.62](#).

### **2.1.3.1.1.20.62.3 Property: DESCRIPTION**

RFC Reference: [\[RFC2445\]](#) section 4.8.1.5

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Provides a plain-text description for the reminder.

#### **Importing to Calendar objects**

This property SHOULD be ignored on import.

#### **Exporting from Calendar objects**

See [2.1.3.1.1.20.62](#).

## **2.1.3.2 Additional Information on Recurrences**

Additional information that is necessary to specify a mapping from iCalendar RRULEs to **PidLidAppointmentRecur** can be found below.

### **2.1.3.2.1 iCalendar Recurrence Syntax**

An iCalendar recurrence data type is a semicolon-delimited list of recurrence parts. The ordering of these recurrence parts does not matter, but a single iCalendar recurrence MUST NOT contain more than one instance of the same recurrence part.

#### **2.1.3.2.1.1 Recurrence Part: FREQ**

RFC Reference: [\[RFC2445\]](#) section 4.3.10

Number of Instances Allowed: 1

Format: Text ([\[RFC2445\]](#) section 4.3.11)

Brief Description: Specifies the frequency of the recurrence.

The FREQ recurrence part MUST be set to one of the values defined in the following table.

<b>FREQ Value</b>	<b>Meaning</b>
DAILY	The appointment occurs every <interval> days. Supported configurations of DAILY recurrences are specified in section <a href="#">2.1.3.2.2.1</a> .
WEEKLY	The appointment occurs every <interval> weeks. Supported configurations of WEEKLY recurrences are specified in section <a href="#">2.1.3.2.2.2</a> .
MONTHLY	The appointment occurs every <interval> months. Supported configurations of MONTHLY recurrences are specified in section <a href="#">2.1.3.2.2.3</a> and section <a href="#">2.1.3.2.2.4</a> .
YEARLY	The appointment occurs every <interval> years. Supported configurations of YEARLY recurrences are specified in section <a href="#">2.1.3.2.2.5</a> and section <a href="#">2.1.3.2.2.6</a> .

### 2.1.3.2.1.2 Recurrence Part: INTERVAL

RFC Reference: [\[RFC2445\]](#) section 4.3.10

Number of Instances Allowed: 0, 1

Format: Integer ([\[RFC2445\]](#) section 4.3.8)

Brief Description: Specifies a multiplier for the period of a recurrence.

The INTERVAL recurrence part MUST be within the bounds defined in the following table. If an INTERVAL is omitted, the recurrence MUST be parsed as though the INTERVAL were 1.

<b>FREQ Value</b>	<b>Minimum INTERVAL</b>	<b>Maximum INTERVAL</b>
DAILY	1	999
WEEKLY	1	99
MONTHLY	1	99
YEARLY	1	8< <a href="#">267</a> >

### 2.1.3.2.1.3 Recurrence Part: BYMINUTE

RFC Reference: [\[RFC2445\]](#) section 4.3.10

Number of Instances Allowed: 0, 1

Format: Integer ([\[RFC2445\]](#) section 4.3.8)

Brief Description: Specifies the minute(s) on which a recurrence occurs.

The BYMINUTE recurrence part MUST be an integer between 0 and 59 (inclusive). Furthermore, the BYMINUTE recurrence part MUST NOT specify more than one value. If no BYMINUTE is specified, the minute from the DTSTART property MUST be used.

### 2.1.3.2.1.4 Recurrence Part: BYHOUR

RFC Reference: [\[RFC2445\]](#) section 4.3.10

Number of Instances Allowed: 0, 1

Format: Integer ([\[RFC2445\]](#) section 4.3.8)

Brief Description: Specifies the hour(s) on which a recurrence occurs.

The BYHOUR recurrence part MUST be an integer between 0 and 23 (inclusive). Furthermore, the BYHOUR recurrence part MUST NOT specify more than one value. If no BYHOUR is specified, the hour from the DTSTART property MUST be used.

### 2.1.3.2.1.5 Recurrence Part: BYMONTHDAY

RFC Reference: [\[RFC2445\]](#) section 4.3.10

Number of Instances Allowed: Dependent on the recurrence template (section [2.1.3.2.2](#))

Format: Integer ([\[RFC2445\]](#) section 4.3.8)

Brief Description: Specifies the day(s) of the month on which a recurrence occurs.

The BYMONTHDAY recurrence part MUST be -1, or an integer between 1 and 31 (inclusive). Furthermore, the BYMONTHDAY recurrence part MUST NOT specify more than one value. If no BYMONTHDAY is specified, the day of month from the DTSTART property MUST be used.

### 2.1.3.2.1.6 Recurrence Part: BYDAY

RFC Reference: [\[RFC2445\]](#) section 4.3.10

Number of Instances Allowed: Dependent on the recurrence template (section [2.1.3.2.2](#))

Format: Text ([\[RFC2445\]](#) section 4.3.8)

Brief Description: Specifies the day(s) of the week on which a recurrence occurs.

The BYDAY recurrence part MUST be a comma-delimited list of elements consisting of an optional week number followed by a mandatory 2-character code for the day of week. A BYDAY recurrence part with no week number will be termed week independent.

The following table specifies the possible values for the mandatory character code for the day of the week.

Day of Week Character Code	Meaning
SU	Sunday
MO	Monday
TU	Tuesday
WE	Wednesday
TH	Thursday
FR	Friday
SA	Saturday

The following table specifies the possible values for the optional week number.



Week Number	Meaning
-1	Last instance
1	First instance
2	Second instance
3	Third instance
4	Fourth instance

### 2.1.3.2.1.7 Recurrence Part: BYMONTH

RFC Reference: [\[RFC2445\]](#) section 4.3.10

Number of Instances Allowed: Dependent on the recurrence template (section [2.1.3.2.2](#))

Format: Integer ([\[RFC2445\]](#) section 4.3.8)

Brief Description: Specifies the month(s) on which a recurrence occurs.

The BYMONTH recurrence part MUST be an integer between 1 and 12 (inclusive). Furthermore, the BYMONTH recurrence part MUST NOT specify more than one value. If no BYMONTH is specified, the month from the DTSTART property MUST be used.

### 2.1.3.2.1.8 Recurrence Part: BYSETPOS

RFC Reference: [\[RFC2445\]](#) section 4.3.10

Number of Instances Allowed: Dependent on the recurrence template (section [2.1.3.2.2](#))

Format: Integer ([\[RFC2445\]](#) section 4.3.8)

Brief Description: Specifies the instances of a multi-BYDAY appointment to use each INTERVAL (see section [2.1.3.2.2.4](#) and [2.1.3.2.2.6](#)).

The BYSETPOS recurrence part MUST be -1 or an integer between 1 and 4 (inclusive), as specified in the following table. Furthermore, the BYSETPOS recurrence part MUST NOT specify more than one value.

BYSETPOS Value	Meaning
-1	Last instance
1	First instance
2	Second instance
3	Third instance
4	Fourth instance

### 2.1.3.2.1.9 Recurrence Part: WKST

RFC Reference: [\[RFC2445\]](#) section 4.3.10

Number of Instances Allowed: 0, 1

Format: Text ([\[RFC2445\]](#) section 4.3.8)

Brief Description: Specifies the day of week on which a week is considered to start.

The WKST recurrence part MUST one of the day of week character codes specified in section [2.1.3.2.1.6](#). If no WKST recurrence part is specified, 'SU' MUST be used.

#### **2.1.3.2.1.10 Recurrence Part: UNTIL**

RFC Reference: [\[RFC2445\]](#) section 4.3.10

Number of Instances Allowed: 0, 1

Format: Date-Time ([\[RFC2445\]](#) section 4.3.5)

Brief Description: Specifies the time of the last instance of a recurring appointment (inclusive).

The UNTIL recurrence part MUST be a Date-Time occurring after the DTSTART property. The UNTIL recurrence part MUST NOT be specified in conjunction with the COUNT recurrence part. If neither an UNTIL nor a COUNT is specified, the recurrence MUST be treated as infinitely recurring. If the last instance of a recurring appointment would occur on or after January 1, 4501 in the time zone specified by **PidLidTimeZoneStruct**, the recurrence SHOULD [<268>](#) be treated as infinitely recurring.

#### **2.1.3.2.1.11 Recurrence Part: COUNT**

RFC Reference: [\[RFC2445\]](#) section 4.3.10

Number of Instances Allowed: 0, 1

Format: Integer ([\[RFC2445\]](#) section 4.3.8)

Brief Description: Specifies the number of instances in a recurring appointment.

The COUNT recurrence part MUST be an Integer between 1 and 999 (inclusive). The COUNT recurrence part MUST NOT be specified in conjunction with the UNTIL recurrence part. If neither an UNTIL nor a COUNT is specified, the recurrence MUST be treated as infinitely recurring. If the last instance of a recurring appointment would occur on or after January 1, 4501, the recurrence SHOULD [<269>](#) be treated as infinitely recurring.

#### **2.1.3.2.2 Recurrence Templates**

The RRULE and X-MICROSOFT-RRULE properties MUST NOT be exported for non-recurring appointments or exceptions of recurring appointments.

Although the syntax permits a wide variety of recurrences, only RRULE properties and X-MICROSOFT-RRULE properties fitting the templates enumerated in this section SHOULD [<270>](#) be mapped into the **AppointmentRecurrencePattern** structure ([\[MS-OXOCAL\]](#) section 2.2.1.44.5) in the **PidLidAppointmentRecur** property ([\[MS-OXOCAL\]](#) section 2.2.1.44).

Implementations SHOULD gracefully fail to map any recurrences that do not fit the templates enumerated in this section.

Once a recurrence has been successfully mapped into the **AppointmentRecurrencePattern** structure, implementations SHOULD [<271>](#) also set the **PidLidClipStart** property ([\[MS-OXOCAL\]](#)

section 2.2.1.14) to the value of the **StartDate** field of the **AppointmentRecurrencePattern** structure and set the **PidLidClipEnd** property ([\[MS-OXOCAL\]](#) section 2.2.1.15) to the value of the **EndDate** field of the **AppointmentRecurrencePattern** structure.

The following sections express the templates in ABNF notation, as specified in [\[RFC5234\]](#). The following code shows common rules used in the templates.

```

common-parts      = [interval-part] [byhour-part] [byminute-part]
                   [(until-part / count-part)] [wkst-part]

interval-part     = ";"INTERVAL=" 1*DIGIT           ; See 2.3.1.2
byminute-part    = ";"BYMINUTE=" 1*2DIGIT         ; See 2.3.1.3
byhour-part      = ";"BYHOUR=" 1*2DIGIT           ; See 2.3.1.4
bymonthday-part  = ";"BYMONTHDAY=" ["-"]1*2DIGIT   ; See 2.3.1.5
byday-part       = ";"BYDAY=" byday-list          ; See 2.3.1.6
byday-nth-part   = ";"BYDAY=" byday-nth-list      ; See 2.3.1.6
bymonth-part     = ";"BYMONTH=" 1*2DIGIT         ; See 2.3.1.7
bysetpos-part    = ";"BYSETPOS=" weeknum         ; See 2.3.1.8
wkst-part        = ";"WKST=" dayofweek           ; See 2.3.1.9
until-part       = ";"UNTIL=" datetime           ; See 2.3.1.10
count-part       = ";"COUNT=" 1*3DIGIT         ; See 2.3.1.11

byday-list       = byday-elm *("," byday-elm)
byday-elm        = [weeknum] dayofweek
dayofweek        = "SU" / "MO" / "TU" / "WE" / "TH" / "FR" / "SA"

weeknum          = "-1" / "1" / "2" / "3" / "4"
byday-nth-list   = dayofweek
byday-nth-list   =/ "SA,SU"                       ; Any ordering
byday-nth-list   =/ "MO,TU,WE,TH,FR"             ; Any ordering
byday-nth-list   =/ "SU,MO,TU,WE,TH,FR,SA"       ; Any ordering
datetime         = year month day "T" hour minute second ["Z"]
year             = 4DIGIT
month            = 2DIGIT
day              = 2DIGIT
hour             = 2DIGIT
minute           = 2DIGIT
second          = "00"

```

### 2.1.3.2.2.1 Template: Daily Recurrences

#### ABNF Description

```
daily-template= "FREQ=DAILY" [common-parts]
```

#### Template Examples

Every day:

```
FREQ=DAILY
```

Every day at 3:30 P.M.:

FREQ=DAILY;BYMINUTE=30;BYHOUR=15

Every 3 days:

FREQ=DAILY;INTERVAL=3

Every 3 days at 3:30 P.M.:

FREQ=DAILY;INTERVAL=3;BYMINUTE=30;BYHOUR=15

Every 3 days at 3:30 P.M. for 30 instances:

FREQ=DAILY;INTERVAL=3;BYMINUTE=30;BYHOUR=15;COUNT=30

### Importing to Calendar objects

An RRULE or X-MICROSOFT-RRULE matching this template SHOULD [<272>](#) be imported into **PidLidAppointmentRecur** as specified in the following table. A VEVENT MUST NOT specify both an RRULE and an X-MICROSOFT-RRULE.

AppointmentRecurrencePattern Field	Value
<b>ReaderVersion</b>	Set to 0x3004
<b>WriterVersion</b>	Set to 0x3004
<b>RecurFrequency</b>	Set to 0x200A
<b>PatternType</b>	Set to 0x0000. Can be overridden by X-MICROSOFT-CALSCALE, see section <a href="#">2.1.3.1.1.8</a> .
<b>CalendarType</b>	Imported from X-MICROSOFT-CALSCALE (see section <a href="#">2.1.3.1.1.8</a> ).
<b>FirstDateTime</b>	Set as specified in <a href="#">[MS-OXOCAL]</a> section 2.2.1.44.1.
<b>Period</b>	Set to (1440 * INTERVAL)
<b>SlidingFlag</b>	Set to 0x00000000
<b>PatternTypeSpecific.Week.Sa-Su</b>	(unset)
<b>PatternTypeSpecific.Month.Day</b>	(unset)
<b>PatternTypeSpecific.MonthNth.Sa-Su</b>	(unset)
<b>PatternTypeSpecific.MonthNth.N</b>	(unset)
<b>EndType</b>	If the recurrence is infinite, set <b>EndType</b> to 0x00002023. If the recurrence is specified with a COUNT, set <b>EndType</b> to 0x00002022. Otherwise, set <b>EndType</b> to 0x00002021.
<b>OccurrenceCount</b>	Set to the number of occurrences of the recurrence based on

AppointmentRecurrencePattern Field	Value
	UNTIL or COUNT. If the recurrence is infinite, set OccurrenceCount to 0x0000000A.
<b>FirstDOW</b>	Set to the correct value based on WKST (see the following table for how to map WKST values to <b>FirstDOW</b> values)
<b>DeletedInstanceCount / DeletedInstanceDates</b>	See section <a href="#">2.1.3.1.1.20.13</a>
<b>ModifiedInstanceCount / ModifiedInstanceDates</b>	See section <a href="#">2.1.3.1.1.20.18</a>
<b>StartDate</b>	Set to the date portion of DTSTART, in the time zone specified by <b>PidLidTimeZoneStruct</b> . This date is stored in minutes after midnight January 1, 1601. Note that this value <b>MUST</b> always be evenly divisible by 1440.
<b>EndDate</b>	Set to the start date of the last instance of a recurrence, in the time zone specified by <b>PidLidTimeZoneStruct</b> . This date is stored in minutes after midnight January 1, 1601. If the recurrence is infinite, set <b>EndDate</b> to 0x5AE980DF. Note that this value <b>MUST</b> always be evenly divisible by 1440, except for the special value 0x5AE980DF.
<b>ReaderVersion2</b>	Set to 0x00003006
<b>WriterVersion2</b>	Set to 0x00003009
<b>StartTimeOffset</b>	Set to (60*BYHOUR + BYMINUTE)
<b>EndTimeOffset</b>	Set to ( <b>StartTimeOffset</b> + <b>PidLidAppointmentDuration</b> )
<b>ExceptionCount / ExceptionInfo</b>	See section <a href="#">2.1.3.1.1.20.18</a>
<b>(ReservedBlocks and ExtendedExceptions)</b>	Refer to [MS-OXOCAL]

The following table specifies how to map WKST values to **FirstDOW** values.

WKST Value	FirstDOW Value
SU	0x00000000
MO	0x00000001
TU	0x00000002
WE	0x00000003
TH	0x00000004
FR	0x00000005
SA	0x00000006

## Exporting From Calendar objects

The **AppointmentRecurrencePattern** structure ([MS-OXOCAL] section 2.2.1.44.5) in the **PidLidAppointmentRecur** property ([MS-OXOCAL] section 2.2.1.44) SHOULD<273> be exported as the property specified in the following table. If a case matches more than one row, the first matching row applies.

CalendarType field	PatternType field	Recurrence property
0x0000	0x0000	RRULE
0x0000	0x0001	RRULE
0x0000	0x0002	RRULE
0x0000	0x0003	RRULE
0x0000	0x000A	X-MICROSOFT-RRULE
0x0000	0x000B	X-MICROSOFT-RRULE
(any)	0x0000	RRULE<274>
(any)	0x0001	RRULE<275>
0x0001	(any)	RRULE
0x0002	(any)	RRULE
0x0003	(any)	RRULE
0x0004	(any)	RRULE
0x0005	(any)	RRULE
0x0006	(any)	X-MICROSOFT-RRULE
0x0007	(any)	RRULE
0x0008	(any)	X-MICROSOFT-RRULE
0x0009	(any)	RRULE
0x000A	(any)	RRULE
0x000B	(any)	RRULE
0x000C	(any)	RRULE
0x000E	(any)	X-MICROSOFT-RRULE
0x000F	(any)	X-MICROSOFT-RRULE
0x0010	(any)	X-MICROSOFT-RRULE
0x0011	(any)	X-MICROSOFT-RRULE
0x0012	(any)	X-MICROSOFT-RRULE
0x0013	(any)	X-MICROSOFT-RRULE
0x0014	(any)	X-MICROSOFT-RRULE

CalendarType field	PatternType field	Recurrence property
0x0017	(any)	X-MICROSOFT-RRULE

The exported property MUST be assigned the value generated by the recurrence template specified in the following table.

PatternType field	Period field	Recurrence template
0x0000	(any)	Daily Recurrence (section <a href="#">2.1.3.2.2.1</a> )
0x0001	(any)	Weekly Recurrence (section <a href="#">2.1.3.2.2.2</a> )
0x0002	(not evenly divisible by 12)	Monthly Recurrence (section <a href="#">2.1.3.2.2.3</a> )
0x0002	(evenly divisible by 12)	Yearly Recurrence (section <a href="#">2.1.3.2.2.5</a> )
0x0003	(not evenly divisible by 12)	Monthly Nth Recurrence (section <a href="#">2.1.3.2.2.4</a> )
0x0003	(evenly divisible by 12)	Yearly Nth Recurrence (section <a href="#">2.1.3.2.2.6</a> )
0x000A	(not evenly divisible by 12)	Monthly Recurrence (section <a href="#">2.1.3.2.2.3</a> )
0x000A	(evenly divisible by 12)	Yearly Recurrence (section <a href="#">2.1.3.2.2.5</a> )
0x000B	(not evenly divisible by 12)	Monthly Nth Recurrence (section <a href="#">2.1.3.2.2.4</a> )
0x000B	(evenly divisible by 12)	Yearly Nth Recurrence (section <a href="#">2.1.3.2.2.6</a> )

If **PidLidAppointmentRecur** is being exported with the Daily Recurrence template, it MUST contain the recurrence parts specified in the following table.

Recurrence Part	Value
FREQ	Set to 'DAILY'
INTERVAL	Set to (Period / 1440). If the value is 1, omit this recurrence part.
COUNT	If EndType is 0x00002022, set to <b>OccurrenceCount</b> . Otherwise, omit this recurrence part.
UNTIL	If <b>EndType</b> is 0x00002021, SHOULD <a href="#">&lt;276&gt;</a> be set to ( <b>EndDate</b> + <b>StartTimeOffset</b> ), converted from the time zone specified by <b>PidLidTimeZoneStruct</b> to the UTC time zone. Alternatively, MAY <a href="#">&lt;277&gt;</a> be set to midnight on the date specified by <b>EndDate</b> . If <b>EndType</b> is not 0x00002021, omit this recurrence part.
WKST	The WKST recurrence part SHOULD <a href="#">&lt;278&gt;</a> be omitted.

## 2.1.3.2.2.2 Template: Weekly Recurrences

### ABNF Description

```
weekly-template= "FREQ=WEEKLY" [byday-part] [common-parts]
```

### Template Examples

Every Monday and Tuesday:

```
FREQ=WEEKLY;BYDAY=MO,TU
```

Every Monday and Tuesday at 3:30 P.M:

```
FREQ=WEEKLY;BYDAY=MO,TU;BYMINUTE=30;BYHOUR=15
```

The Monday and Tuesday of every two weeks, for 7 occurrences:

```
FREQ=WEEKLY;BYDAY=MO,TU;INTERVAL=2;COUNT=7
```

The Sunday and Monday of every two weeks, as interpreted by someone who considers a week to start on Monday (common in Europe). This is different in that, after a Sunday instance, there will be a seven-day gap before the next instance on a Monday:

```
FREQ=WEEKLY;BYDAY=SU,MO;INTERVAL=2;WKST=MO
```

### Importing to Calendar objects

An RRULE or X-MICROSOFT-RRULE matching this template SHOULD [<279>](#) be imported into **PidLidAppointmentRecur** as specified in the following table. A VEVENT MUST NOT specify both an RRULE and an X-MICROSOFT-RRULE. The BYDAY recurrence part MUST be week independent.

AppointmentRecurrencePattern field	Value
ReaderVersion	Set to 0x3004
WriterVersion	Set to 0x3004
RecurFrequency	Set to 0x200B
PatternType	Set to 0x0001. Can be overridden by X-MICROSOFT-CALSCALE, see section <a href="#">2.1.3.1.1.8</a> .
CalendarType	Imported from X-MICROSOFT-CALSCALE (see section <a href="#">2.1.3.1.1.8</a> ).
FirstDateTime	Set as specified in <a href="#">[MS-OXOCAL]</a> section 2.2.1.44.1.
Period	Set to the value of INTERVAL
SlidingFlag	Set to 0x00000000
PatternTypeSpecific.Week.Sa-Su	Set to a bitmask representation of BYDAY as specified in the table that follows this table. If no BYDAY is specified, the day of week for DTSTART (in the time zone specified by <b>PidLidTimeZoneStruct</b> ) MUST be used.
PatternTypeSpecific.Month.Day	(unset)
PatternTypeSpecific.MonthNth.Sa-Su	(unset)



<b>AppointmentRecurrencePattern field</b>	<b>Value</b>
<b>PatternTypeSpecific.MonthNth.N</b>	(unset)
<b>EndType</b>	If the recurrence is infinite, set <b>EndType</b> to 0x00002023. If the recurrence is specified with a COUNT, set <b>EndType</b> to 0x00002022. Otherwise, set <b>EndType</b> to 0x00002021.
<b>OccurrenceCount</b>	Set to the number of occurrences of the recurrence based on UNTIL or COUNT. If the recurrence is infinite, set <b>OccurrenceCount</b> to 0x0000000A.
<b>FirstDOW</b>	Set to the correct value based on WKST as specified in section <a href="#">2.1.3.2.2.1</a> .
<b>DeletedInstanceCount / DeletedInstanceDates</b>	See section <a href="#">2.1.3.1.1.20.13</a>
<b>ModifiedInstanceCount / ModifiedInstanceDates</b>	See section <a href="#">2.1.3.1.1.20.18</a>
<b>StartDate</b>	Set to the date portion of DTSTART, in the time zone specified by <b>PidLidTimeZoneStruct</b> . This date is stored in minutes after midnight Jan 1, 1601. Note that this value MUST always be evenly divisible by 1440.
<b>EndDate</b>	Set to the start date of the last instance of a recurrence, in the time zone specified by <b>PidLidTimeZoneStruct</b> . This date is stored in minutes after midnight January 1, 1601. If the recurrence is infinite, set <b>EndDate</b> to 0x5AE980DF. Note that this value MUST always be evenly divisible by 1440, except for the special value 0x5AE980DF.
<b>ReaderVersion2</b>	Set to 0x00003006
<b>WriterVersion2</b>	Set to 0x00003009
<b>StartTimeOffset</b>	Set to (60*BYHOUR + BYMINUTE)
<b>EndTimeOffset</b>	Set to ( <b>StartTimeOffset</b> + <b>PidLidAppointmentDuration</b> )
<b>ExceptionCount / ExceptionInfo</b>	See section <a href="#">2.1.3.1.1.20.18</a>
<b>(ReservedBlocks and ExtendedExceptions)</b>	Refer to [MS-OXOCAL]

The following table specifies how to map BYDAY values to a **PatternTypeSpecific.Week.Sa-Su** bitmask.

<b>BYDAY value</b>	<b>PatternTypeSpecific.Week.Sa-Su bit</b>
SU	0x00000001
MO	0x00000002
TU	0x00000004
WE	0x00000008

BYDAY value	PatternTypeSpecific.Week.Sa-Su bit
TH	0x00000010
FR	0x00000020
SA	0x00000040

### Exporting from Calendar objects

The **AppointmentRecurrencePattern** structure ([MS-OXOCAL] section 2.2.1.44.5) in the **PidLidAppointmentRecur** property ([MS-OXOCAL] section 2.2.1.44) SHOULD<280> be exported as the property specified by the table of recurrence properties in section 2.1.3.2.2.1. The exported property MUST be assigned the value generated by the Recurrence template specified by the table of recurrence templates specified in section 2.1.3.2.2.1.

If **PidLidAppointmentRecur** is being exported with the Weekly Recurrence template, then it MUST contain the recurrence parts specified in the following table.

Recurrence part	Value
FREQ	Set to 'WEEKLY'
INTERVAL	Set to Period. If the value is 1, omit this recurrence part.
BYDAY	Set to the BYDAY representation of the <b>PatternTypeSpecific.Week.Sa-Su</b> bitmask.
COUNT	If <b>EndType</b> is 0x00002022, set to <b>OccurrenceCount</b> . Otherwise, omit this recurrence part.
UNTIL	If <b>EndType</b> is 0x00002021, SHOULD<281> be set to ( <b>EndDate</b> + <b>StartTimeOffset</b> ), converted from the time zone specified by <b>PidLidTimeZoneStruct</b> to the UTC time zone. Alternatively, MAY<282> be set to midnight on the date specified by <b>EndDate</b> . If <b>EndType</b> is not 0x00002021, omit this recurrence part.
WKST	If <b>Period</b> is greater than 1, <b>FirstDOW</b> MUST be exported as the WKST recurrence part as specified in section 2.1.3.2.2.1. Otherwise, the WKST recurrence part SHOULD<283> be omitted.

### 2.1.3.2.2.3 Template: Monthly Recurrences

#### ABNF Description

```
monthly-template= "FREQ=MONTHLY" [bymonthday-part] [common-parts]
```

#### Template Examples

The last day of every month:

```
FREQ=MONTHLY;BYMONTHDAY=-1
```

The 10th day of every month at 3:30 P.M.:

FREQ=MONTHLY;BYMONTHDAY=10;BYMINUTE=30;BYHOUR=15

The 15th day of every 3 months, for 7 occurrences:

FREQ=MONTHLY;BYMONTHDAY=15;INTERVAL=3;COUNT=7

### Importing to Calendar objects

An RRULE or X-MICROSOFT-RRULE matching this template SHOULD [<284>](#) be imported into **PidLidAppointmentRecur** as specified in the following table. A VEVENT MUST NOT specify both an RRULE and an X-MICROSOFT-RRULE.

AppointmentRecurrencePattern field	Value
<b>ReaderVersion</b>	Set to 0x3004
<b>WriterVersion</b>	Set to 0x3004
<b>RecurFrequency</b>	Set to 0x200C. If the INTERVAL is evenly divisible by 12, <b>RecurFrequency</b> MAY <a href="#">&lt;285&gt;</a> be set to 0x200D.
<b>PatternType</b>	Set to 0x0002. Can be overridden by X-MICROSOFT-CALSCALE, see section <a href="#">2.1.3.1.1.8</a> .
<b>CalendarType</b>	Imported from X-MICROSOFT-CALSCALE (see section <a href="#">2.1.3.1.1.8</a> ).
<b>FirstDateTime</b>	Set as specified in <a href="#">[MS-OXOCAL]</a> section 2.2.1.44.1.
<b>Period</b>	Set to the value of INTERVAL
<b>SlidingFlag</b>	Set to 0x00000000
<b>PatternTypeSpecific.Week.Sa-Su</b>	(unset)
<b>PatternTypeSpecific.Month.Day</b>	Set to the value of BYMONTHDAY. If the value of BYMONTHDAY is -1, <b>PatternTypeSpecific.Month.Day</b> SHOULD <a href="#">&lt;286&gt;</a> be set to 0x0000001F.
<b>PatternTypeSpecific.MonthNth.Sa-Su</b>	(unset)
<b>PatternTypeSpecific.MonthNth.N</b>	(unset)
<b>EndType</b>	If the recurrence is infinite, set <b>EndType</b> to 0x00002023. If the recurrence is specified with a COUNT, set <b>EndType</b> to 0x00002022. Otherwise, set <b>EndType</b> to 0x00002021.
<b>OccurrenceCount</b>	Set to the number of occurrences of the recurrence based on UNTIL or COUNT. If the recurrence is infinite, set <b>OccurrenceCount</b> to 0x0000000A.
<b>FirstDOW</b>	Set to the correct value based on WKST as specified in section <a href="#">2.1.3.2.2.1</a> .
<b>DeletedInstanceCount / DeletedInstanceDates</b>	See section <a href="#">2.1.3.1.1.20.13</a> .

AppointmentRecurrencePattern field	Value
<b>ModifiedInstanceCount / ModifiedInstanceDates</b>	See section <a href="#">2.1.3.1.1.20.18</a> .
<b>StartDate</b>	Set to the date portion of DTSTART, in the time zone specified by <b>PidLidTimeZoneStruct</b> . This date is stored in minutes after midnight Jan 1, 1601. Note that this value MUST always be evenly divisible by 1440. If the BYMONTHDAY is specified, it MUST override the day portion of DTSTART.
<b>EndDate</b>	Set to the start date of the last instance of a recurrence, in the time zone specified by <b>PidLidTimeZoneStruct</b> . This date is stored in minutes after midnight Jan 1, 1601. If the recurrence is infinite, set <b>EndDate</b> to 0x5AE980DF. Note that this value MUST always be evenly divisible by 1440, except for the special value 0x5AE980DF.
<b>ReaderVersion2</b>	Set to 0x00003006
<b>WriterVersion2</b>	Set to 0x00003009
<b>StartTimeOffset</b>	Set to (60*BYHOUR + BYMINUTE)
<b>EndTimeOffset</b>	Set to ( <b>StartTimeOffset</b> + <b>PidLidAppointmentDuration</b> )
<b>ExceptionCount / ExceptionInfo</b>	See section <a href="#">2.1.3.1.1.20.18</a>
<b>(ReservedBlocks and ExtendedExceptions)</b>	Refer to [MS-OXOCAL]

### Exporting from Calendar objects

The **AppointmentRecurrencePattern** structure ([\[MS-OXOCAL\]](#) section 2.2.1.44.5) in the **PidLidAppointmentRecur** property ([\[MS-OXOCAL\]](#) section 2.2.1.44) SHOULD<287> be exported as the property specified by the table of recurrence properties in section [2.1.3.2.2.1](#). The exported property MUST be assigned the value generated by the Recurrence template specified by the table of Recurrence templates specified in section [2.1.3.2.2.1](#).

If **PidLidAppointmentRecur** is being exported with the Monthly Recurrence Template, it MUST contain the recurrence parts specified in the following table.

Recurrence part	Value
FREQ	Set to 'MONTHLY'
INTERVAL	Set to <b>Period</b> . If the value is 1, omit this recurrence part.
BYMONTHDAY	Set to <b>PatternTypeSpecific.Month.Day</b> . If <b>PatternTypeSpecific.Month.Day</b> is 0x0000001F, BYMONTHDAY SHOULD<288> be set to -1.
COUNT	If <b>EndType</b> is 0x00002022, set to <b>OccurrenceCount</b> . Otherwise, omit this recurrence part.
UNTIL	If <b>EndType</b> is 0x00002021, SHOULD<289> be set to ( <b>EndDate</b> + <b>StartTimeOffset</b> ), converted from the time zone specified by <b>PidLidTimeZoneStruct</b> to the UTC time zone. Alternatively, MAY<290> be set to midnight on the date specified by <b>EndDate</b> . If

Recurrence part	Value
	<b>EndType</b> is not 0x00002021, omit this recurrence part.
WKST	The WKST recurrence part SHOULD <a href="#">&lt;291&gt;</a> be omitted.

## 2.1.3.2.2.4 Template: Monthly Nth Recurrences

### ABNF Description

```
monthlynth-template= "FREQ=MONTHLY" monthlynth-args
monthlynth-args= byday-nth-part bysetpos-part [common-parts]
```

### Template Examples

The 3rd Sunday of every month:

```
FREQ=MONTHLY;BYDAY=SU;BYSETPOS=3
```

The last weekday of every month at 3:30 P.M.:

```
FREQ=MONTHLY;BYDAY=MO, TU, WE, TH, FR;BYSETPOS=-1;BYMINUTE=30;BYHOUR=15
```

The first Monday of every month, for 7 occurrences:

```
FREQ=MONTHLY;BYDAY=MO;BYSETPOS=1;COUNT=7
```

### Importing to Calendar objects

An RRULE or X-MICROSOFT-RRULE matching this template SHOULD [<292>](#) be imported into **PidLidAppointmentRecur** as specified in the following table. A VEVENT MUST NOT specify both an RRULE and an X-MICROSOFT-RRULE.

AppointmentRecurrencePattern field	Value
<b>ReaderVersion</b>	Set to 0x3004
<b>WriterVersion</b>	Set to 0x3004
<b>RecurFrequency</b>	Set to 0x200C. If the INTERVAL is evenly divisible by 12, <b>RecurFrequency</b> MAY <a href="#">&lt;293&gt;</a> be set to 0x200D.
<b>PatternType</b>	Set to 0x0003. Can be overridden by X-MICROSOFT-CALSCALE, see section <a href="#">2.1.3.1.1.8</a> .
<b>CalendarType</b>	Imported from X-MICROSOFT-CALSCALE (see section <a href="#">2.1.3.1.1.8</a> ).
<b>FirstDateTime</b>	Set as specified in <a href="#">[MS-OXOCAL]</a> section 2.2.1.44.1.
<b>Period</b>	Set to the value of INTERVAL

<b>AppointmentRecurrencePattern field</b>	<b>Value</b>
<b>SlidingFlag</b>	Set to 0x00000000
<b>PatternTypeSpecific.Week.Sa-Su</b>	(unset)
<b>PatternTypeSpecific.Month.Day</b>	(unset)
<b>PatternTypeSpecific.MonthNth.Sa-Su</b>	Set to a bitmask representation of BYDAY as specified in section <a href="#">2.1.3.2.2.2</a> .
<b>PatternTypeSpecific.MonthNth.N</b>	Set to the value of BYSETPOS. If the value of BYSETPOS is -1, <b>PatternTypeSpecific.MonthNth.N</b> MUST be set to 0x00000005.
<b>EndType</b>	If the recurrence is infinite, set <b>EndType</b> to 0x00002023. If the recurrence is specified with a COUNT, set <b>EndType</b> to 0x00002022. Otherwise, set <b>EndType</b> to 0x00002021.
<b>OccurrenceCount</b>	Set to the number of occurrences of the recurrence based on UNTIL or COUNT. If the recurrence is infinite, set <b>OccurrenceCount</b> to 0x0000000A.
<b>FirstDOW</b>	Set to the correct value based on WKST as specified in section <a href="#">2.1.3.2.2.1</a> .
<b>DeletedInstanceCount / DeletedInstanceDates</b>	See section <a href="#">2.1.3.1.1.20.13</a>
<b>ModifiedInstanceCount / ModifiedInstanceDates</b>	See section <a href="#">2.1.3.1.1.20.18</a>
<b>StartDate</b>	Set to the date portion of DTSTART, in the time zone specified by <b>PidLidTimeZoneStruct</b> . This date is stored in minutes after midnight January 1, 1601. Note that this value MUST always be evenly divisible by 1440.
<b>EndDate</b>	Set to the start date of the last instance of a recurrence, in the time zone specified by <b>PidLidTimeZoneStruct</b> . This date is stored in minutes after midnight January 1, 1601. If the recurrence is infinite, set <b>EndDate</b> to 0x5AE980DF. Note that this value MUST always be evenly divisible by 1440, except for the special value 0x5AE980DF.
<b>ReaderVersion2</b>	Set to 0x00003006
<b>WriterVersion2</b>	Set to 0x00003009
<b>StartTimeOffset</b>	Set to (60*BYHOUR + BYMINUTE)
<b>EndTimeOffset</b>	Set to ( <b>StartTimeOffset</b> + <b>PidLidAppointmentDuration</b> )
<b>ExceptionCount / ExceptionInfo</b>	See section <a href="#">2.1.3.1.1.20.18</a>
<b>(ReservedBlocks and ExtendedExceptions)</b>	Refer to [MS-OXOCAL]

## Exporting from Calendar objects

The **AppointmentRecurrencePattern** structure ([MS-OXOCAL] section 2.2.1.44.5) in the **PidLidAppointmentRecur** property ([MS-OXOCAL] section 2.2.1.44) SHOULD<294> be exported as the property specified by the table of recurrence properties in section 2.1.3.2.2.1. The exported property MUST be assigned the value generated by the Recurrence template specified by the table of recurrence templates specified in section 2.1.3.2.2.1.

If **PidLidAppointmentRecur** is being exported with the Monthly Nth Recurrence template, then it MUST contain the recurrence parts specified in the following table.

Recurrence part	Value
FREQ	Set to 'MONTHLY'
INTERVAL	Set to <b>Period</b> . If the value is 1, omit this recurrence part.
BYDAY	Set to the BYDAY representation of the <b>PatternTypeSpecific.MonthNth.Sa-Su</b> bitmask as specified in section 2.1.3.2.2.2.
BYSETPOS	Set to <b>PatternTypeSpecific.MonthNth.N</b> . If <b>PatternTypeSpecific.MonthNth.N</b> is 0x00000005, set BYSETPOS to -1.
COUNT	If <b>EndType</b> is 0x00002022, set to <b>OccurrenceCount</b> . Otherwise, omit this recurrence part.
UNTIL	If <b>EndType</b> is 0x00002021, SHOULD<295> be set to ( <b>EndDate</b> + <b>StartTimeOffset</b> ), converted from the time zone specified by <b>PidLidTimeZoneStruct</b> to the UTC time zone. Alternatively, MAY<296> be set to midnight on the date specified by <b>EndDate</b> . If <b>EndType</b> is not 0x00002021, omit this recurrence part.
WKST	The WKST recurrence part SHOULD<297> be omitted.

### 2.1.3.2.2.5 Template: Yearly Recurrences

#### ABNF Description

```
yearly-template= "FREQ=YEARLY" yearly-args
yearly-args= [bymonthday-part] [bymonth-part] [common-parts]
```

#### Template Examples

The last day of every September:

```
FREQ=YEARLY;BYMONTHDAY=-1;BYMONTH=9
```

The 10th day of every January at 3:30 P.M.:

```
FREQ=YEARLY;BYMONTHDAY=10;BYMONTH=1;BYMINUTE=30;BYHOUR=15
```

The 15th day of March, every 3 years, for 7 occurrences:

```
FREQ=YEARLY;BYMONTHDAY=15;BYMONTH=3;INTERVAL=3;COUNT=7
```

## Importing to Calendar objects

An RRULE or X-MICROSOFT-RRULE matching this template SHOULD [<298>](#) be imported into **PidLidAppointmentRecur** as specified in the following table. A VEVENT MUST NOT specify both an RRULE and an X-MICROSOFT-RRULE.

AppointmentRecurrencePattern field	Value
<b>ReaderVersion</b>	Set to 0x3004
<b>WriterVersion</b>	Set to 0x3004
<b>RecurFrequency</b>	Set to 0x200D. If the INTERVAL is not 1, <b>RecurFrequency</b> SHOULD <a href="#">&lt;299&gt;</a> be set to 0x200C.
<b>PatternType</b>	Set to 0x0002. Can be overridden by X-MICROSOFT-CALSCALE, see section <a href="#">2.1.3.1.1.8</a> .
<b>CalendarType</b>	Imported from X-MICROSOFT-CALSCALE (see section <a href="#">2.1.3.1.1.8</a> ).
<b>FirstDateTime</b>	Set as specified in <a href="#">[MS-OXOCAL]</a> section 2.2.1.44.1.
<b>Period</b>	Set to (12 * INTERVAL)
<b>SlidingFlag</b>	Set to 0x00000000
<b>PatternTypeSpecific.Week.Sa-Su</b>	(unset)
<b>PatternTypeSpecific.Month.Day</b>	Set to the value of BYMONTHDAY. If the value of BYMONTHDAY is -1, <b>PatternTypeSpecific.Month.Day</b> SHOULD <a href="#">&lt;300&gt;</a> be set to 0x0000001F.
<b>PatternTypeSpecific.MonthNth.Sa-Su</b>	(unset)
<b>PatternTypeSpecific.MonthNth.N</b>	(unset)
<b>EndType</b>	If the recurrence is infinite, set <b>EndType</b> to 0x00002023. If the recurrence is specified with a COUNT, set <b>EndType</b> to 0x00002022. Otherwise, set <b>EndType</b> to 0x00002021.
<b>OccurrenceCount</b>	Set to the number of occurrences of the recurrence based on UNTIL or COUNT. If the recurrence is infinite, set <b>OccurrenceCount</b> to 0x0000000A.
<b>FirstDOW</b>	Set to the correct value based on WKST as specified in section <a href="#">2.1.3.2.2.1</a> .
<b>DeletedInstanceCount / DeletedInstanceDates</b>	See section <a href="#">2.1.3.1.1.20.13</a>
<b>ModifiedInstanceCount / ModifiedInstanceDates</b>	See section <a href="#">2.1.3.1.1.20.18</a>
<b>StartDate</b>	Set to the date portion of DTSTART, in the time zone specified by <b>PidLidTimeZoneStruct</b> . This date is stored in minutes after midnight Jan 1, 1601. Note that this value MUST always be evenly divisible by 1440. If BYMONTH is specified, it MUST override the month portion of DTSTART. If the BYMONTHDAY is



AppointmentRecurrencePattern field	Value
	specified, it MUST override the day portion of DTSTART.
<b>EndDate</b>	Set to the start date of the last instance of a recurrence, in the time zone specified by <b>PidLidTimeZoneStruct</b> . This date is stored in minutes after midnight Jan 1, 1601. If the recurrence is infinite, set <b>EndDate</b> to 0x5AE980DF. Note that this value MUST always be evenly divisible by 1440, except for the special value 0x5AE980DF.
<b>ReaderVersion2</b>	Set to 0x00003006
<b>WriterVersion2</b>	Set to 0x00003009
<b>StartTimeOffset</b>	Set to (60*BYHOUR + BYMINUTE)
<b>EndTimeOffset</b>	Set to ( <b>StartTimeOffset</b> + <b>PidLidAppointmentDuration</b> )
<b>ExceptionCount / ExceptionInfo</b>	See section <a href="#">2.1.3.1.1.20.18</a>
<b>(ReservedBlocks and ExtendedExceptions)</b>	Refer to [MS-OXOCAL]

### Exporting from Calendar objects

The **AppointmentRecurrencePattern** structure ([\[MS-OXOCAL\]](#) section 2.2.1.44.5) in the **PidLidAppointmentRecur** property ([\[MS-OXOCAL\]](#) section 2.2.1.44) SHOULD<301> be exported as the property specified by the table of recurrence properties in section [2.1.3.2.2.1](#). The exported property MUST be assigned the value generated by the Recurrence template specified by the table of Recurrence templates specified in section [2.1.3.2.2.1](#).

If **PidLidAppointmentRecur** is being exported with the Yearly Recurrence Template, then it MUST contain the recurrence parts specified in the following table.

Recurrence part	Value
FREQ	Set to 'YEARLY'
INTERVAL	Set to ( <b>Period</b> / 12). If the value is 1, omit this recurrence part.
BYMONTHDAY	Set to <b>PatternTypeSpecific.Month.Day</b> . If <b>PatternTypeSpecific.Month.Day</b> is 0x0000001F, BYMONTHDAY SHOULD<302> be set to -1.
BYMONTH	Set to the month from <b>FirstDateTime</b> .
COUNT	If <b>EndType</b> is 0x00002022, set to <b>OccurrenceCount</b> . Otherwise, omit this recurrence part.
UNTIL	If <b>EndType</b> is 0x00002021, SHOULD<303> be set to ( <b>EndDate</b> + <b>StartTimeOffset</b> ), converted from the time zone specified by <b>PidLidTimeZoneStruct</b> to the UTC time zone. Alternatively, MAY<304> be set to midnight on the date specified by <b>EndDate</b> . If <b>EndType</b> is not 0x00002021, omit this recurrence part.
WKST	The WKST recurrence part SHOULD<305> be omitted.

## 2.1.3.2.2.6 Template: Yearly Nth Recurrences

### ABNF Description

```
yearlynth-template= "FREQ=YEARLY" yearlynth-args [common-parts]  
yearlynth-args= byday-nth-part bysetpos-part bymonth-part
```

### Template Examples

The 3rd Sunday of every June:

```
FREQ=YEARLY;BYDAY=SU;BYSETPOS=3;BYMONTH=6
```

The last weekday of every April at 3:30 P.M.:

```
FREQ=YEARLY;BYDAY=MO,TU,WE,TH,FR;BYSETPOS=-1;BYMONTH=4;BYMINUTE=30;BYHOUR=15
```

The first Monday of every October, every 3 years, for 7 occurrences:

```
FREQ=YEARLY;BYDAY=MO;BYSETPOS=1;BYMONTH=10;COUNT=7
```

### Importing to Calendar objects

An RRULE or X-MICROSOFT-RRULE matching this template SHOULD [<306>](#) be imported into **PidLidAppointmentRecur** as specified in the following table. A VEVENT MUST NOT specify both an RRULE and an X-MICROSOFT-RRULE.

AppointmentRecurrencePattern field	Value
<b>ReaderVersion</b>	Set to 0x3004
<b>WriterVersion</b>	Set to 0x3004
<b>RecurFrequency</b>	Set to 0x200D. If the INTERVAL is not 1, <b>RecurFrequency</b> SHOULD <a href="#">&lt;307&gt;</a> be set to 0x200C.
<b>PatternType</b>	Set to 0x0003. Can be overridden by X-MICROSOFT-CALSCALE, see section <a href="#">2.1.3.1.1.8</a> .
<b>CalendarType</b>	Imported from X-MICROSOFT-CALSCALE (see section <a href="#">2.1.3.1.1.8</a> ).
<b>FirstDateTime</b>	Set as specified in <a href="#">[MS-OXOCAL]</a> section 2.2.1.44.1.
<b>Period</b>	Set to (12 * INTERVAL)
<b>SlidingFlag</b>	Set to 0x00000000
<b>PatternTypeSpecific.Week.Sa-Su</b>	(unset)
<b>PatternTypeSpecific.Month.Day</b>	(unset)
<b>PatternTypeSpecific.MonthNth.Sa-</b>	Set to a bitmask representation of BYDAY as specified in section

AppointmentRecurrencePattern field	Value
<b>Su</b>	<a href="#">2.1.3.2.2.2.</a>
<b>PatternTypeSpecific.MonthNth.N</b>	Set to the value of BYSETPOS. If the value of BYSETPOS is -1, <b>PatternTypeSpecific.MonthNth.N</b> MUST be set to 0x00000005.
<b>EndType</b>	If the recurrence is infinite, set <b>EndType</b> to 0x00002023. If the recurrence is specified with a COUNT, set <b>EndType</b> to 0x00002022. Otherwise, set <b>EndType</b> to 0x00002021.
<b>OccurrenceCount</b>	Set to the number of occurrences of the recurrence based on UNTIL or COUNT. If the recurrence is infinite, set <b>OccurrenceCount</b> to 0x0000000A.
<b>FirstDOW</b>	Set to the correct value based on WKST as specified in section <a href="#">2.1.3.2.2.1.</a>
<b>DeletedInstanceCount / DeletedInstanceDates</b>	See section <a href="#">2.1.3.1.1.20.13</a>
<b>ModifiedInstanceCount / ModifiedInstanceDates</b>	See section <a href="#">2.1.3.1.1.20.18</a>
<b>StartDate</b>	Set to the date portion of DTSTART, in the time zone specified by <b>PidLidTimeZoneStruct</b> . This date is stored in minutes after midnight Jan 1, 1601. Note that this value MUST always be evenly divisible by 1440. If BYMONTH is specified, it MUST override the month portion of DTSTART.
<b>EndDate</b>	Set to the start date of the last instance of a recurrence, in the time zone specified by <b>PidLidTimeZoneStruct</b> . This date is stored in minutes after midnight Jan 1, 1601. If the recurrence is infinite, set <b>EndDate</b> to 0x5AE980DF. Note that this value MUST always be evenly divisible by 1440, except for the special value 0x5AE980DF.
<b>ReaderVersion2</b>	Set to 0x00003006
<b>WriterVersion2</b>	Set to 0x00003009
<b>StartTimeOffset</b>	Set to (60*BYHOUR + BYMINUTE)
<b>EndTimeOffset</b>	Set to ( <b>StartTimeOffset</b> + <b>PidLidAppointmentDuration</b> )
<b>ExceptionCount / ExceptionInfo</b>	See section <a href="#">2.1.3.1.1.20.18</a>
<b>(ReservedBlocks and ExtendedExceptions)</b>	Refer to [MS-OXOCAL]

### Exporting from Calendar objects

The **AppointmentRecurrencePattern** structure ([\[MS-OXOCAL\]](#) section 2.2.1.44.5) in the **PidLidAppointmentRecur** property ([\[MS-OXOCAL\]](#) section 2.2.1.44) SHOULD<308> be exported as the property specified by the table of recurrence properties in section [2.1.3.2.2.1](#). The exported property MUST be assigned the value generated by the Recurrence template specified by the table of Recurrence templates specified in section [2.1.3.2.2.1](#).

If **PidLidAppointmentRecur** is being exported with the Yearly Nth Recurrence Template, it MUST contain the recurrence parts specified in the following table.

Recurrence part	Value
FREQ	Set to 'YEARLY'
INTERVAL	Set to <b>(Period / 12)</b> . If the value is 1, omit this recurrence part.
BYDAY	Set to the BYDAY representation of the <b>PatternTypeSpecific.MonthNth.Sa-Su</b> bitmask as specified in section <a href="#">2.1.3.2.2.2</a> .
BYSETPOS	Set to <b>PatternTypeSpecific.MonthNth.N</b> . If <b>PatternTypeSpecific.MonthNth.N</b> is 0x00000005, set BYSETPOS to -1.
BYMONTH	Set to the month from <b>FirstDateTime</b> .
COUNT	If <b>EndType</b> is 0x00002022, set to <b>OccurrenceCount</b> . Otherwise, omit this recurrence part.
UNTIL	If <b>EndType</b> is 0x00002021, SHOULD< <a href="#">309</a> > be set to <b>(EndDate + StartTimeOffset)</b> , converted from the time zone specified by <b>PidLidTimeZoneStruct</b> to the UTC time zone. Alternatively, MAY< <a href="#">310</a> > be set to midnight on the date specified by <b>EndDate..</b> If <b>EndType</b> is not 0x00002021, omit this recurrence part.
WKST	The WKST recurrence part SHOULD< <a href="#">311</a> > be omitted.

### 2.1.3.2.3 End-of-Month Concerns

[\[RFC2445\]](#) specifies that Monthly Recurrences (section [2.1.3.2.2.3](#)) in which the BYMONTHDAY recurrence part is 29, 30, or 31 MUST skip over months that do not have a sufficient number of days. Conversely, [\[MS-OXOCAL\]](#) specifies that Monthly Recurrences with a **PatternTypeSpecific.Month.Day** of 0x0000001D, 0x0000001E, or 0x0000001F MUST occur on the last day of months that do not have a sufficient number of days.

### 2.1.3.2.4 Legacy UNTIL Concerns

If the PROPID property (see section [2.1.3.1.1.2](#)) indicates that a version of the MIMEDIR between 1 and 11 (inclusive) generated the iCalendar file and if the UNTIL recurrence part is specified with a trailing 'Z', it SHOULD NOT<[312](#)> be treated as a UTC Date-time. Instead, only the year, month, and day of the Date-time SHOULD<[313](#)> be retained, and the UNTIL recurrence part SHOULD<[314](#)> be interpreted as 11:59 P.M. of that day (in the time zone specified by **PidLidTimeZoneStruct**).

### 2.1.3.3 Additional Rules for MIME Messages

For import scenarios where the original iCalendar data is contained in a **MIME message**, implementations MAY<[315](#)> set additional properties on the Calendar object, as specified in the following table.

Property	Value
<b>PidLidInboundICalStream</b> (section <a href="#">2.2.1</a> )	The value of this property is set to the contents of the <b>MIME part</b> of the original MIME message that has a Content-Type header value of "text/calendar".

Property	Value
<b>PidLidSingleBodyICal</b> (section <a href="#">2.2.2</a> )	The value of this property is set to TRUE if the original MIME message contained only one MIME part, and the Content-Type header value for that MIME part was "text/calendar".

## 2.2 Calendar Object Properties

This algorithm specifies the following additional properties for Calendar objects.

- **PidLidInboundICalStream** (section [2.2.1](#))
- **PidLidSingleBodyICal** (section [2.2.2](#))
- **PidNameLocationUrl** (section [2.2.3](#))

### 2.2.1 PidLidInboundICalStream

Type: **PtypBinary** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidLidInboundICalStream** property ([\[MS-OXPROPS\]](#) section 2.148) is an optional property on Calendar objects that were converted from MIME messages. It contains the contents of the iCalendar MIME part of the original MIME message.

### 2.2.2 PidLidSingleBodyICal

Type: **PtypBoolean** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidLidSingleBodyICal** property ([\[MS-OXPROPS\]](#) section 2.301) is an optional property on Calendar objects that were converted from MIME messages. A value of TRUE indicates that the original MIME message contained a single MIME part.

### 2.2.3 PidNameLocationUrl

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidNameLocationUrl** property ([\[MS-OXPROPS\]](#) section 2.502) is an optional property on Calendar objects. It contains a URL where attendees can access location information in HTML format.

### 3 Algorithm Examples

The following subsections contain annotated iCalendar files representing several example scenarios.

#### 3.1 Birthday Calendar for 2008

In this example, Elizabeth has a non-primary calendar containing the birthdays of herself (October 12, 1975) and her closest friends: Shu (February 27, 1978) and Anne (July 7, 1982). Elizabeth sets 7-day reminders on all the birthdays so she has enough time to prepare. The following tables represent the contents of the Birthday calendar's Folder object and its three Calendar objects.

The following table shows the property on the Folder object.

Property name	Value
PidTagDisplayName	Birthdays

The following table lists the properties on the Calendar object for Elizabeth's Birthday.

Property name	Value
PidLidAllowExternalCheck	TRUE
PidLidAppointmentCounterProposal	FALSE
PidLidAppointmentDuration	1440
PidLidAppointmentEndWhole	07:00:00.000 AM 10/13/1975
PidLidAppointmentNotAllowPropose	FALSE
PidLidAppointmentRecur	cb: 80 lpb: 043004300D2002000000A0FF05000C00000000000000C000000232000000A000000000000000 00000000000000080B4BF0BDF80E95A063000000930000000000000A00500000000000000000 000000
PidLidAppointmentSequence	0

Property name	Value
PidLidAppointmentStartWhole	07:00:00.000 AM 10/12/1975
PidLidAppointmentStateFlags	0
PidLidAppointmentSubType	TRUE
PidLidBusyStatus	0
PidLidGlobalObjectId	cb: 56 lpb: 040000008200E00074C5B7101A82E0080000000020C397BAB068C80100000000000000001000 0000D4429044CA28924C8FD122A133685E4A
PidLidCollaborateDoc	
PidLidConferencingType	0
PidLidDirectory	
PidLidInvited	FALSE
PidLidGlobalObjectId	cb: 56 lpb: 040000008200E00074C5B7101A82E0080000000020C397BAB068C80100000000000000001000 0000D4429044CA28924C8FD122A133685E4A
PidLidIntendedBusyStatus	4294967295
PidLidLocation	
PidLidNetShowUrl	
PidLidOnlinePassword	
PidLidOr	

Property name	Value
<b>ganizerAlias</b>	
<b>PidLidReminderDelta</b>	10080
<b>PidLidReminderSet</b>	TRUE
<b>PidLidReminderSignalTime</b>	07:00:00.000 AM 10/5/2008
<b>PidLidReminderTime</b>	07:00:00.000 AM 10/12/1975
<b>PidLidResponseStatus</b>	0
<b>PidLidTimeZoneDescription</b>	(GMT-08:00) Pacific Time (US & Canada)
<b>PidLidTimeZoneStruct</b>	cb: 48 lpb: E001000000000000C4FFFFFF00000000B000000010002000000000000000000000030000000 20002000000000000000
<b>PidTagBody</b>	Happy Birthday to me!
<b>PidTagCreationTime</b>	07:08:02.739 PM 2/6/2008
<b>PidTagImportance</b>	1
<b>PidTagLastModificationTime</b>	07:08:02.739 PM 2/6/2008
<b>PidTagMessageClass</b>	IPM.Appointment
<b>PidTagMessageLocalId</b>	1033
<b>PidTagReplyReq</b>	TRUE



Property name	Value
Requested	
PidTagResponseRequested	TRUE
PidTagRtfCompressed	cb: 5487 lpb: 6B150000125A00004C5A4675A0C61C7507000601010B606E6731303266350064007263700DD0 0E0032050C60630D446633313530423700F5737473680570627463680FD23610840900110B683 30EB0111A62690FD70DA43333891426666514A374686507809F146715D71560014015D763730 1E8F302A413B064690336020011000AC00873657402D170727132A500002A0AA16E6F1A50200 DF0D51BA13614B0300FF0341C2101D0991C10347D076D02833334191F1F1A2400501AAF20EF2 1107D4361F706D0072105D06115D01DE410101E66FF03E319FF1B0B01301C721BB21C501C10F 326A122216C6922611DE40FE1190FFF246F1B2F1C3F1D4E0FE11FC1287F298FFF2A9F2BAF2CBE 0F202DDF2EEF2FF73102FF30C430A22704225327B714D0334F345FFF2FFF310F321F1E4F392F3A 3F3B4F3C5FFF0FF00E103DAF3EBF3FCF40DF41EF1160FF237F442F259F26AF27B72358439F4A1F 3745BF46CF1DE4394D6F4E7432338A384EE420076D20434502833F50A052AF53B53D72546F55 737972B755D4332F1F56361FC5584F4709D17E6B55D4381F5AF759E15BBF038254EF087055D43 D8F1F563723515F8F0382D8284865226007D02955D442FFF6277543F6416071001A00EB064F5 48685D1EED384861673F0382420740747F0EB055D44D5F5AF75DB16B3F644356590890746E22 4007906564F530FF5298490C5418274555A70DE071AF575E7F73B759660EF074DF5B0E73B65D0 931FF5DB878AE5F5673B660D75B607B7F6A8EFF73B66C890FD267016D7F53DF54EF27D5DF529 F75DF845F59650FD1312DBF791FFF5C0F5D1789A259EF7C7F5FDF60E589A2FF5DBF627F6F6F64 9A89A2616F667F93EFFF689A89A2656F7FBF6B8F815B7E996DEF7F9BDF700F9558823F834F882F 856731EF860F871FA4CF89383289EF8AFF8C0FFD8D1A328DEF8EFF900F9118A420AE6FF792EF9 3FF950C3295FF970FB45F992DDF0E01B68F9B5F9C6F8179329E3F9F4F7FB88FA16FAA21A2AFA3 BF2236855832FFA67FA78FC53789380FD0C67F792F2245BD8D0B33AE5FAF6F2236910933BA9FF FBBAF2236814CA432D0DFA3EFA4FFC955FFC66FC77FD65F893874A0D81FAB7FAC8FFF8D2959D FCE4FDDFF91095DAFB33FE1FFFF94EE615FB76FE5DF991E655FD1AFEAOFFF814C695FBFAFEE3F C1CFDBA2D43FD54FFBDA2F856734D80FD91FF6CF893889C0FFF88FDD0FDE1F8D290F11FC7FE1 1FE22FFFBC7E3CFE4DFF25F94FDDBC0044FE91F7FEA2F993CFC30087FED4FEE5F816A35FFF03F F14F0A8FF36FFC21F4AFF5BFFA9FFD856735F87FF98F173F8938FDE2191FFFFD9FFFAF8D4701E2 1CF019F02AF1C46EF043F054F12CF94FD36086F097F26CFBD992D360C9F0DAF0EBF815B3610A FFF11BF2AFF13DF1C911518723F734F1C37EF719F19FF76EE4D11371CC878AF79BFFD8D293778 0F21DF7D8E3BF22D087F4FFF805F816A2A62314F165F176F3BC518EFF739EF48CF8938381CCF3 D4F1EEF8D1ADE3820CF40CF22EF91183824AF25BF7B333F94FD3828DF29EF585F992D38FF2D0F 442F2F2F815B60225ECF325F336F0370A881B1636F6C6F727450626C3B5C8D106474C0678D8D 116E74C06730756530675FFA65BA8035688A69A1695F6A6968747F6A9268FF6CCF6C8D6C0F6A3 F688F65FD8DD038725A7371732F743968747462BF72CF769F765D75DF740F77D4395250FF7B24 7C8174A37C80725F6B0776BF7500A181B12A5C64654F517063112B85C244B173AE4020808670 61F98121716C6310455067A0CFA067A0A13CE06463746C82907283902599307080D161759D60 5C611E73829083F03D5084F26E756D2589806184B0746F84F0646AC8757374CFA0676884E0CFA 0A7680145506801697482A0308200305C6E6F7144D15D306F744C65208D7086B0796C5CB068F D8D20748D7082EF83FF850F861F872F4F7DC08AF04F604F4173316310615F815357D0901081D1 8C006C4F2067FC3130BA808A118DD08F848F218159DB8A20911333563091026674D09372CE63 786062E093136E7093699504416310736E6578748F2173B7887067005D4074963144E0696700F 587D07988104E9702674080838FC1EF8F218D8062F09D707688F08920A1E0786D696862E080D 05D608920757A6E9A31658DB0678097598FE044698BA420503D6061786082A068A020466F6E7 48074748FD0B74E509DF04EF07794A08DD0669DF0E25762E074684256308DD082905D99506C9 1405C009F84729FF866AE6C9F669ED0A16762A167729F62FC636282903DA0A3528281A3C2673 04F87406791A484894070659F6173F063656C6C8AB19F309ED1A4E1FE7399A06710BDC19DE1B 580A080A7463A6CA75562A7558B30A7646467DFA846A9C0A9468F90A7647682CF8AEFFF8BFF8 D0F8E1F8F2F903F914F925F936FFF947F958F3DA0B1A199EF9AF896E69824FF64B0EB408960988 7B3319948B11CB0E1B7B36AAD9066C06657B0963162ADDOFF67809D609902B8AF9AF889403D 7062E0C7DBB15BF05620392048A571A830778740CCA398C336BC3FBD4FBE5B38FFBF3FC04FC1 5FC2639D50A6009E706780FFC2BFBF12C40BF18F4510B35FB466A410BF96A2C71FC8269788976 1A6F0739D60C7BB11892066D06D706FF3E0C94FC420455D40696C53894257B0B7668380B0DF1

Property name	Value
	0766721890055C320F98850776ED5B6C1F1D652D773C226E5DB616D97216850ACF0D9039D52 CA335A606DE7106B428742DA4528537562DAB17398516C467DEB3063DAB162F0ADE09C314E5 06DD46C4D3D6067DA9372DD1780D1EC4A63DCD1AD1249A4C067F03DA0E7E7E0DAB18740744 C5C90DAB16610547279DFF131808378DCF06E1FAF80D662E114B1A0AFD074703A9C2F2FA5D08 9905D40732EC7F0AE634EF0D2E09ED02ED3612FE3902266EB60652F776700642FDF3A50B530E 473DCF066905C8291A6F0DA7774E032DF81E5B3685A32DAB1FFDD219FE0DF73DD21A090E796 DF55DD21DA62DF6367AF0088E0728761AF90FFF3E0ACA06310AC719E70ACA0A8319ED0386E62 6AADC067F099506F63FB9EA1DC106B88C099A0CD50EC3496F47FEF70B2E180C09D6088D1DA4 06780739C797396F0DF417DC16C799D609E76DCF067A0EE188781676497307A6167A266EC01D 630DF31A691767F4541F0D19670DCF04E5089809E7070F7B2C0A5E0F2F06C9F20967287C0B6B 0FB6700C7E178678066D09D70DF3167A0FC736199A08740F213E121F531F2F1BFE121A6F04EF0 3D704E50885078B2C0A9E2506F7967F05C96707089807F67104F308850AD91A830ADE0EC2064 E79D706730E1506264A8C08850ADE13FA5E096F1BEC196F28980AF40655CF9F2F0727AEC02A9 C0E7328740FBD1CE68FA136010EFD16776FCA9FB61FFAFB087408171FD22FE24FDD3F2E2EDF1 BBFD41FFB36AF8014F20B660763450FC776BA4B15E900112A5D04540B5C1F7E651E940AAD265 AF40027596F088D0FB9761EF6074D6F08740FB40EB610407FFAFD05D40AF00ADE08841E140AF D0AF41FF6721BEB014500FD0D060E140B2A1F952FFA4B1ABE004100201ACA067309E810401FF 67216710AA71E140DA51FA81FB408850FBD451AD10700672965082A0AF10B632FF8740A5E2B2 A1CA91E430A5F0C841EEA073A5F0AD0170709AC0ACA0ADC169FF4F20099728106721C1B2AD9 03D108850FF78609E70AEF2E430ADB09B21F431DB90BF894096F14550AF808841A4B16EDA417 F9DF014B0A5F00981A5F0D630884163FE78ADE087E0BB6187C0A4C0F8E1CAB0EF1261F7D1885 0B1D063E1510672B1D0EF1253AF008740A8406813C303D2E260F667ACD2EE3163F21005B3672 0DA601F14826330085216D2F210747862FC785C09B0B6C03D709660ADB00200FBE2C1F4B16C0 7016310F8912C40D3712F9732B5B09690809277F131666DF71800D520E9E120E63081808832B5 B0FF973023F03D90F84088D0ACB074D087C0BE6C96F05D4002000810E140758800FFCE72ACD1 9631EA719B51EA3587729670FF67A0EBD19AD0A6F0FB401FD3AD641EE03F8920EB63890180B0 AE80EA616C76FFF2B1AE81E350AEB0235187E0671023D2FFA4B1DF313FA0E6519AD0B2D18901 AE80F318D087E0202ED5C42356525023F2FFCE81245F256F267F23B05630AE8080D0EFEC20284 F295F2A6F6C5A60AE80CCF0F7280F2CDF2DE52926CC5E902BAF309FFD2DC5625D70385131CF2 38344B02F6FFF343F354F365F23A157D037B2243F391FFF3A2F323D5C0037BF3D4F3E5F3F6F23A 1FF4A703C4F41EF42FF4405E5A1A790E5A0FFB2C08740CE63ACD2ABBFACCFADDFAEFFFAFFFE4 8F25381C209CCCFB21FB32FB43FFFB54FB65F95A859F050AF51B052DCD0014F13519E50C1FB82 A0707961A0695D671068F0D05B404D902064E0217F5E1157BF58CF59DF453063B2D42B0D7E0A 48F28204F771F1B289434A6073C7EEA0EDB065807832363C206271FF66F0EC70678080D187616 281C7E780D1FF1E3062719AC864F6BA5563D6978680D1FC3939D8E063479670A5E00A804A51F F643AC582655A6A54BA5513167596A54FF63749807697F6A8F6B9F97A450716D39F302E2EDC 120316E43709F71AF72B7EF7DA1737F748F728A33766F777F726CEE34797F7A8F726C357C8F7D 9F726CFE367F9F80AF726CD5A082BF83CF727BEE3885BF86CF726C396E4397865062FB6D394D 906373358C2F8D3876548E3FFF8D387964904F8D387C74925F8D387F84F946F8D388294967F8 D3885A4988F8D38FF88B49A9F8D388BC4891F9CE352C26D48FF02000A806CA0D7006E5F6F6F9 E9F6CA4FBD0D26D39544F20BB71A44B6D1BDCA1B94C0220504F91F130B0C068CA51FFDFD0A1 6FA27FA38FA496A71CDB41EDB0FFA616A9AFAABFABCDF400CE43AD494E10FDF4D067AE6FAF7 FB08FB1966D0CD4F0BB4CA1C1F073B35FB46F6759358A6CF2541312204755D1B863B4AE6D66F 650F3361C9154F3C1B86FBCDFB57FFFA6AF6DA4ADD0FA21EDC1BF9FC0AF6759FE366D0CDF0F4 E41ADD0FB11C48FC59FFFC6ADA71CC874DFF04E00C94FCA5FC6DAFFB21CC874BC87CDFFCF0F C72557706D2AFA4D1A00694D20C8C67335D25FD36FFDC72534D4FFD6097654D71FD82FC725B FA01CD5C5CD62D6AFDC7FC6BC36DE7FFDF86DB7FE11FC6CB5DA2E33FD1C2DFFFFB59FC6BC 38E79FE8A6E49FEA3FC6CBBFB4CE86A91F4EE1FEF2F6CA4376D0C7A444FB06BCD5FF31FF42FA 71C43FB05F0FEF0664C10C8CFF73FF84FF501FFD08CFA67F66FFC3FF43ED4ECFA67D1CF8F00CF C69FD09FC8B7204163BEC0FF61E0E91F057FCB4F079DFB3092F0A3FFF0B4FD05FD1680E0F0F1 F102FD4AFD5BFFF12FF140F151FD96FDA7F184F195F1A6F1FDE2FDF3C1D9CBD1FA785526576FF FFC0A13F1F0FC18F9C891BBCDFB3A8771F259F26AF27BFB196BB4C51756FBF61C02B0F2C1F2D 2F9CB66D0C4961E0FF64D037302F8F309F1FEFE2EFE3F91D9FFF35CF36DFE74FE85C39DF3AEF3 BFFEBDFFFEC3EFF400F411FF06FF17C441F452FFF463FF4FFF608493F4A4F4B5FF94FFA5FFF4E 1F4F2F503FFE0FFF1C536F547F558FFF029F03AC588F599F5AAF072F083F5DD3FFEDBF5F3F0BBF 0CCF5859634F645F10AFF11BF5D79683F694F159F47CF17BF6D2FFF6E3F1AEF705F1D0F727F73 8F203F75AFFF225C77CF78DF375F7AFF397C7CE7DFFFF3C7F801F3E9C820F831F419F853F43BC FF872F883F46BF8A5F48DC8C4F8D5F4BDFFF4CEF679F91DF92EF512F523F62AF96BFFF97CF567F

Property name	Value
	<p>578F9B2F9C3F9D4F5BCF5CDFFFA07FA18F8E2F611F622FF23FA6DF655FFFA8FF584AAAFAC0F6A5F6B6F5D79AFEFFFB0FF6F4F8F7F716FB4DFB5EF749FB80FFF76BFBA2FBB3F79EFBD5F225CBF7FC08FFF7F0FC2AF397CC49FC5AF842FC7CF3E9CFCC9BFCACF894FCCEFA43BCCEDFCFEF8E6FFFD20F48DCD3FFD50F938F949FAF4FD98FFFDA9F98DF99EFAA5FDE6DF7F9E2F9F3FFFE2DFE3EFE4FFA37FA48FE82FE93FD5DFF3A8CFA9DF2034ED9FEEAFAD2FAE3FFF5868F2AFF3BFB20FB31F5D79F79FF8AFFFB6FFD72FB91FFC8FFD9FBC4FFFBFB6FFF01DF02EFC19F050F225C072F083FC6BFFF0A5F397C0C4F0D5FCBDF0F7F3E9C116FFF127FD0FF149F43BC168F179FD61F19BFFF48DC1BAF1CBFDB3FDC4FF6FF213F224FFFE08FE19FF20F261F272FE5DFE6EF2A8FFF2B9F2CAFEB2FEC3F2FDF30EF1D8FF07FF9F18F2035354F365FF4DFF5EF5868FF3A5F3B6FF9BFFACF5D793F4F405FFFAFFF1EDF00CF443F454F03FF476F061F498FFF4A9F094F4CBF7C0C4EDF4FEF0E6F520FFF812C53FF550F138F572F864C591F5A2FFF18AF5C4F8B6C5E3F5F4F1DCF616F908CFF635F646F22EF23FF3EAF68EF69FF283FFF294F39BF6DCF6EDF2D8F2E9F723F734FFF745F32DF33EF778F789F653F382F393FFC20367CFF7E0F3C8F3D9FA018820FFF831F416F427FA52986FF880F465F668FFF487F8BEF8CFF4BAF8F1F4DCF913F924FFF50FF946FC3BC968F979F561F99BFC8DCFF9BAF9CBF5B3F9EDFCDFCA0CFA1DF605FFFA3FFD31CA5EFA6FF657FA91FD83CAB0FFAC1F6A9F6BAF865FB09FB1AF6FEF70FFF816FB57FB68F753F764FB9EFBAFFBC0F9F7A8F7B9FBF3FC04FACE67166C370586D6174B7F47F4631ADFC53007562746C6520456DFA7000D0730B70C4AFC5BFC6CF7F55FA32B7FC49ED50ED40C140C99FCAAF1BCBBFC74E33B7FCC935526566FC6572ED40ED30CFBFD0CFD1DFD2E67F89ECCEB6D4BFD5CFD6DFD7EF8EDC42F46F6F24C0547F90C970DAE3D2D721A3BC4269626C7F6067727A61CF5079DAE3DD3FD313ADFC54204F4320486500E33B7DC07D7B5C2A5C64C740CF700674C370CF1030313035302DE72232E723E6E038E784346481C250373836643663D8E0003265353334313538C3E980E86034633532996084E0EF94109960BD30E92033EA00EAD0E7840FEB8E7FC0E7218A9063663131206530613162ED206165F7E6F0EDEFEEEDC33ED40EFC1E720DA70F066663039EC66F13FE7C1F20DFFF1EDF062F482F166F46EF4E7F6EFF7FFFF90FFA1FFB2FFC3FFD4FFE5FF6F6007FFF018F029F03AF04BF05CF06DF07EF08FFF0A0F0B1F0C2F0D3F0E4F0F5F106F117FFF128F139F14AF15BF16CF17DF18EF19FFF1B0F1C1F1D2F1E3F1F4F205F216F227FFF238F249F25AF26BF27CF28DF29EF2AFFFD2BEC642BE5F4752DDF2EEF2FFF310FFF321F332F343F354F365F376F387F398FFF3A9F3BAF3CBF3DCF3EDF3FEF40FF420FFF431F442F453F464F475F486F497F4A8FFF4B9F4CAF4DBF4ECF4FDF50EF51FF530FFF541F552F563F574F585F596F5A7F5B8FFF5C9F5DAF5EBF5FCF60DF61EF62FF640FFF651F662F673F684F695F6A6F6B7FF6834FEA00EC71F4D16D223734E75434FDE71136EFF16DA2BD306D81F0B26F6FFF707F718F729F73AFE7C1EC92E7116BDF452D0663ADE0643938774062AD776033E9D1E99039E57066E8E07A64E97162ED40F5DF7956E77039E632777077D06633A8C077D0E6E0FFF56F7C6F7D7F7E8F7F9F80AF81BF82CFFF83DFF67F85DC845F87EF88FF8A0F8B1FFF8C2F8D3F8E4F8F5F906F917F928F939FFF84BF95BF86DF97DF98EF99FF9B0F9C1FFF9D2F9E3F9F4FA05FA16FA27FA38F94AFFFA5AF96CFA7CFA8DFA9EFAAFF32EE7140BA BE5E5E000AE10</p>
<b>PidTagSenderAddressType</b>	SMTP
<b>PidTagSenderEmailAddress</b>	eandersen@contoso.com
<b>PidTagSenderEntryId</b>	cb: 70 lpb: 00000000812B1FA4BEA310199D6E00DD010F540200000000456C697A616265746820416E64657273656E00534D54500065616E64657273656E40636F6E746F736F2E636F6D00
<b>PidTagSenderName</b>	Elizabeth Andersen
<b>PidTagSensitivity</b>	0

Property name	Value
<b>PidTagSubject</b>	Elizabeth's Birthday

The following table lists the properties on the Calendar object for Shu's Birthday.

Property name	Value
<b>PidLidAllowExternalCheck</b>	TRUE
<b>PidLidAppointmentCounterProposal</b>	FALSE
<b>PidLidAppointmentDuration</b>	1440
<b>PidLidAppointmentEndWhole</b>	08:00:00.000 AM 2/28/1978
<b>PidLidAppointmentNotAllowPropose</b>	FALSE
<b>PidLidAppointmentRecur</b>	cb: 80 lpb: 043004300D200200000060AE0000C00000000000001B000000232000000A00000000000000 0000000000000000A0CCD20BDF80E95A06300000093000000000000A005000000000000000 00000000
<b>PidLidAppointmentSequence</b>	0
<b>PidLidAppointmentStartWhole</b>	08:00:00.000 AM 2/27/1978
<b>PidLidAppointmentStateFlags</b>	0
<b>PidLidAppointmentSubTy</b>	TRUE

Property name	Value
<b>pe</b>	
<b>PidLidBusyStatus</b>	0
<b>PidLidCleanGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E00800000000E0243DD0B068C80100000000000000001000000EE6CCE82EE4BC14BB01478A948D182FB
<b>PidLidCollaborateDoc</b>	
<b>PidLidConferenceType</b>	0
<b>PidLidDirectory</b>	
<b>PidLidInvited</b>	FALSE
<b>PidLidGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E00800000000E0243DD0B068C80100000000000000001000000EE6CCE82EE4BC14BB01478A948D182FB
<b>PidLidIntendedBusyStatus</b>	4294967295
<b>PidLidLocation</b>	
<b>PidLidNetShowUrl</b>	
<b>PidLidOnlinePassword</b>	
<b>PidLidOrganizerAlias</b>	
<b>PidLidReminderDelta</b>	10080
<b>PidLidReminderSet</b>	TRUE
<b>PidLidReminderSignalTime</b>	08:00:00.000 AM 2/20/2008

Property name	Value
e	
PidLidReminderTime	08:00:00.000 AM 2/27/1978
PidLidResponseStatus	0
PidLidTimeZoneDescription	(GMT-08:00) Pacific Time (US & Canada)
PidLidTimeZoneStruct	cb: 48 lpb: E001000000000000C4FFFFFF00000000B000000010002000000000000000000000030000000 20002000000000000000
PidTagBody	Gift ideas: Baseball tickets
PidTagCreationTime	07:09:26.913 PM 2/6/2008
PidTagImportance	1
PidTagLastModificationTime	07:09:26.913 PM 2/6/2008
PidTagMessageClass	IPM.Appointment
PidTagMessageLocaleId	1033
PidTagReplyRequested	TRUE
PidTagResponseRequested	TRUE
PidTagRtfCompressed	cb: 5488 lpb: 6C150000195A00004C5A46755A0567E507000601010B606E6731303266350064007263700DD0 0E0032050C60630D446633313530423700F5737473680570627463680FD23610840900110B683 30EB0111A62690FD70DA43333891426666514A374686507809F146715D71560014015D763730 1E8F302A413B064690336020011000AC00873657402D170727132A500002A0AA16E6F1A50200 DF0D51BA13614B0300FF0341C2101D0991C10347D076D02833334191F1F1A2400501AAF20EF2

Property name	Value
	1107D4361F706D0072105D06115D01DE410101E66FF03E319FF1B0B01301C721BB21C501C10F 326A122216C6922611DE40FE1190FFF246F1B2F1C3F1D4E0FE11FC1287F298FFF2A9F2BAF2CBE 0F202DDF2EEF2FF73102FF30C430A22704225327B714D0334F345FFF2FFF310F321F1E4F392F3A 3F3B4F3C5FFF0FF00E103DAF3EBF3FCF40DF41EF1160FF237F442F259F26AF27B72358439F4A1F 3745BF46CF1DE4394D6F4E7432338A384EE420076D20434502833F50A052AF53B53D72546F55 737972B755D4332F1F56361FC5584F4709D17E6B55D4381F5AF759E15BBF038254EF087055D43 D8F1F563723515F8F0382D8284865226007D02955D442FFFF6277543F6416071001A00EB064F5 48685D1EED384861673F0382420740747F0EB055D44D5F5AF75DB16B3F644356590890746E22 4007906564F530FF5298490C5418274555A70DE071AF575E7F73B759660EF074DF5B0E73B65D0 931FF5DB878AE5F5673B660D75B607B7F6A8EFF73B66C890FD267016D7F53DF54EF27D5DF529 F75DF845F59650FD1312DBF791FFF5C0F5D1789A259EF7C7F5FDF60E589A2FF5DBF627F6F6F64 9A89A2616F667F93EFFF689A89A2656F7FBFB68F815B7E996DEF7F9BDF700F9558823F834F882F 856731EF860F871FA4CF89383289EF8AFF8C0FFD8D1A328DEF8EFF900F9118A420AE6FF792EF9 3FF950C3295FF970FB45F992DDF0E01B68F9B5F9C6F8179329E3F9F4F7FB88FA16FAA21A2AFA3 BF2236855832FFA67FA78FC53789380FD0C67F792F2245BD8D0B33AE5FAF6F2236910933BA9FF FBBAF2236814CA432D0DFA3EFA4FFC955FFC66FC77FD65F893874A0D81FAB7FAC8FFF8D2959D FCE4FDDFF91095DAFB33FE1FFFF94EE615FB76FE5DF991E655FD1AFEA0FFF814C695FBFAFEE3F C1CFDBA2D43FD54FFBDA2F856734D80FD91FF6CF893889C0FFF88FDD0FDE1F8D290F11FC7FE1 1FE22FFFBC7E3CFE4DFF25F94FDDBC0044FE91F7FEA2F993CFC30087FED4FEE5F816A35FFF03F F14F0A8FF36FFC21F4AFF5BFFA9FFD856735F87FF98F173F8938FDE2191FFFDF9FEAF8D4701E2 1CFF019F02AF1C46EF043F054F12CF94FD36086F097F26CFBD992D360C9F0DAF0EBF815B3610A FFF11BF2AFF13DF1C911518723F734F1C37EF719F19FF76EE4D11371CC878AF79BFFD8D293778 0F21DF7D8E3BF22D087F4FFF805F816A2A62314F165F176F3BC518EFF739EF48CF8938381CCF3 D4F1EEF8D1ADE3820CF40CF22EF91183824AF25BF7B333F94FD3828DF29EF585F992D38FF2D0F 442F2F815B60225ECF325F336F0370A881B1636F6C6F727450626C3B5C8D106474C0678D8D 116E74C06730756530675FFA65BA8035688A69A1695F6A6968747F6A9268FF6CCFC6C8D6C0F6A3 F688F65FD8DD038725A7371732F743968747462BF72CF769F765D75DF740F77D4395250FF7B24 7C8174A37C80725F6B0776BF7500A181B12A5C64654F517063112B85C244B173AE4020808670 61F98121716C6310455067A0CFA067A0A13CE06463746C82907283902599307080D161759D60 5C611E73829083F03D5084F26E756D2589806184B0746F84F0646AC8757374CFA0676884E0CFA 0A7680145506801697482A0308200305C6E6F7144D15D306F744C65208D7086B0796C5CB068F D8D20748D7082EF83FF850F861F872F4F7DC08AF04F604F4173316310615F815357D0901081D1 8C006C4F2067FC3130BA808A118DD08F848F218159DB8A20911333563091026674D09372CE63 786062E093136E7093699504416310736E6578748F2173B7887067005D4074963144E0696700F 587D07988104E9702674080838FC1EF8F218D8062F09D707688F08920A1E0786D696862E080D 05D608920757A6E9A31658DB0678097598FE044698BA420503D6061786082A068A020466F6E7 48074748FD0B74E509DF04EF07794A08DD0669DF0E25762E074684256308DD082905D99506C9 1405C009F84729FF866AE6C9F669ED0A16762A167729F62FC636282903DA0A3528281A3C2673 04F87406791A484894070659F6173F063656C6C8AB19F309ED1A4E1FE7399A06710BDC19DE1B 580A080A7463A6CA75562A7558B30A7646467DFA846A9C0A9468F90A7647682CF8AEFFF8BFF8 D0F8E1F8F2F903F914F925F936FFF947F958F3DA0B1A199EF9AF896E69824FF64B0E408960988 7B3319948B11CB0E1B7B36AAD9066C06657B0963162ADD0FF67809D609902B8AF9AF889403D 7062E0C7DBB14300B310382048A571A830F78740CCA398C336BC3FBD4FBE5BC290FFBF4FC05F C16FC2729D50A6009E706780FFC2BFBF12C40FB18F4510B35FB466A410BF96A2C71FC82697889 761A6F0739D60C7BB11892066D06D706FF3E0C94FC420455D40696C53894257B0B7668380B0D F10766721890055C320F98850776ED5B6C1F1D652D773C226E5DB616D97216850ACF0D9039D 52CA335A606DE7106B428742DA4528537562DAB17398516C467DEB3063DAB162F0ADE09C314 E506DD46C4D3D6067DA9372DD1780D1EC4A63DCD1AD1249A4C067F03DA0E7E7E0DAB187407 44C5C90DAB16610547279DFF131808378DCF06E1FAF80D662E114B1A0AFD074703A9C2F2FA5D 089905D40732EC7F0AE634EF0D2E09ED02ED3612FE3902266EB60652F776700642FDF3A50B53 0E473DCF066905C8291A6F0DA7774E032DF81E5B3685A32DAB1FFDD219FE0DF73DD21A090E7 96DF55DD21DA62DF6367AF0088E0728761AF90FFF3E0ACA06310AC719E70ACA0A8319ED0386E 626AADC067F099506F63FB9EA1DC106B88C099A0CD50EC3496F47FEF70B2E180C09D6088D1D A406780739C797396F0DF417DC16C799D609E76DCF067A0EE188781676497307A6167A266EC0 1D630DF31A691767F4541F0D19670DCF04E5089809E7070F7B2C0A5E0F2F06C9F20967287C0B 6B0FB6700C7E178678066D09D70DF3167A0FC736199A08740F213E121F531F2F1BFE121A6F04E F03D704E50885078B2C0A9E2506F7967F05C96707089807F67104F308850AD91A830ADE0EC20 64E79D706730E1506264A8C08850ADE13FA5E096F1BEC196F28980AF40655CF9F2F0727AEC02

Property name	Value
	A9C0E7328740FBD1CE68FA136010EFD16776FCA9FB61FFAFB087408171FD22FE24FDD3F2E2ED F1BBFD41FFB36AF8014F20B660763450FC776BA4B15E900112A5D04540B5C1F7E651E940AAD2 65AF40027596F088D0FB9761EF6074D6F08740FB40EB610407FFAFD05D40AF00ADE08841E140 AFD0AF41FF6721BEB014500FD0D060E140B2A1F952FFA4B1ABE004100201ACA067309E810401 FF67216710AA71E140DA51FA81FB408850FBDA51AD10700672965082A0AF10B632FF8740A5E2 B2A1CA91E430A5F0C841EEA073A5F0AD0170709AC0ACA0ADC169FF4F20099728106721C1B2A D903D108850FF78609E70AEF2E430ADB09B21F431DB90BF894096F14550AF808841A4B16EDA4 17F9DF014B0A5F00981A5F0D630884163FE78ADE087E0BB6187C0A4C0F8E1CAB0EF1261F7D18 850B1D063E1510672B1D0EF1253AF008740A8406813C303D2E260F667ACD2EE3163F21005B36 720DA601F14826330085216D2F210747862FC785C09B0B6C03D709660ADB00200FBE2C1F4B16 C07016310F8912C40D3712F9732B5B09690809277F131666DF71800D520E9E120E6308180883 2B5B0FF973023F03D90F84088D0ACB074D087C0BE6C96F05D4002000810E140758800FFCE72A CD19631EA719B51EA3587729670FF67A0EBD19AD0A6F0FB401FD3AD641EE03F8920EB6389018 0B0AE80EA616C76FFF2B1AE81E350AEB0235187E0671023D2FFA4B1DF313FA0E6519AD0B2D18 901AE80F318D087E0202ED5C42356525023F2FFCE81245F256F267F23B05630AE808D0EFEC20 284F295F2A6F6C5A60AE80CCF0F7280F2CDF2DE52926CC5E902BAF309FFD2DC5625D70385131 CF238344B02F6FFF343F354F365F23A157D037B2243F391FFF3A2F323D5C0037BF3D4F3E5F3F6F 23A1FF4A703C4F41EF42FF4405E5A1A790E5A0FFB2C08740CE63ACD2ABBFAACCFADDDFAEEFFFAF FE48F25381C209CCCFB21FB32FB43FFFB54FB65F95A859F050AF51B052DCD001A713519E50C1F A4769E3A0209AF17D4C503A61A1665007014A4061E16BFD6400735E1157BF58CF59DF784063B 2F9D42B0D0A48F28204F771F1B289431D4A6073EEA05C506580783236FF3C2062E166F05C71C 8315F1162E2C7E7FF80D11E3062E19AC86566BA5564469786F980D13939D8E063B79670A5E00 A80FF4A5164AAC58265CA6AC4BA55513167C97F6AC463E4980769EF6AFF6C0F97A439E76D8B0 2E2EDC120316EB3710F721FDF73277DA173EF74FF72FA3376DF77EFD72DC3479EF7AFF72DC3 57CFF7E0FFD72DC36800F811F72DCD5A0832F843FDD72EB38862F873F72DC396EB39786F6338 ADC4D906373A58C9F8DA876C4FF8EAF8DA879D490BF8DA87CE492CF8DA8FF7FF494DF8DA883 0496EF8DA8861498FFF8DA889249B0F8DA88C34898F9D5352C2FF6DB802000A806D10D7006E CF6DF9F0FF76D14D0D26DA9544F20BB71A4BB6D8B73DCA14C0220504F91F130B0C068FFCA5 1DFD0A1DFA2EFA3FFA506A78CDB41FF5C50A686AA1FAB2FAC3FD400CE43ADB9FB4E10F4D067 AEDFAFEFB0FFB2066D7C77D4F04CA1C1F073B3CFB4DF67C935FD8ADC5413125AF055D1B8D3B 51E6DD6F650F3361C9154F3C1B8DFBD4FB5EFFF71F6E14AE40FA21EDC1C00FC11F67C9FE366 D7CDFF04E41AE40FB11C4FFC60FFFC71DA78CC8E4DFF04E00C9BFCACFC74AFFB28CC8E4BCF7C E6FCF7FC79557706D9AFA4D1A00694D20C93673A5D2CFD3DFFDC79534D56FD67976C4D78FD8 9FC795BFA08CD635CDD2D71FDCEFC72C36DEEFFDFF6DBEF18FC73B5E12E3AFBCF2E06FFFE6 0FC72C5071E82FE934E50FEAAFC73BBF8ADCE8DA79D4EE8FEF9F6D14376D7C7A444FB06BCDC FF38FF49FA78C43FB05F0FEF0664C10C93FF7AFF8BFF571FFD0FCFAD7F6DFFCAFF4ED55CFAD7 D23F8F013FC70FD10FC927204163BF30FF6250E98F05EFCBBF080FE023099F0AAFF0B5BFD0CFD 1D80E7F0F8F109FD51FD62FFF136F147F158FD9DFDAEF18BF19CF1ADF1FDE9DFAC1E0CBD8FA 7F5526576FF0030A1AF1F7FC1FF9CF91C2CE023A8E71F260F271F282FB2068ADC51756FBF6230 2B7F2C8F2D9F9D266D7C496250FF65405BE02FFF310F205FE35FE4691E0FFF363F374FE7BFE8C C3A4F3B5F3C6FEC4FFFED5C3F6F407F418FF0DF1EC448F459FFF46AFF56FF67849AF4ABF4BCFF 9BFFACFFF4E8F4F9F50AFFE7FFF8C53DF54EF55FFF030F041C58FF5A0F5B1F079F08AF5E43FFEE 2F5FAF0C2F0D3F58C963BF64CF111FFF122F5DE968AF69BF160F483F182F6D9FFF6EAF1B5F70CF 1D7F72EF73FF20AF761FFF22CC783F794F37CF7B6F39EC7D5F7E6FFF3CEF808F3F0C827F838F42 0F85AF442CFF879F88AF472F8ACF494C8CBF8DCF4C4FFF4D5F680F924F935F519F52AF631F972F FF983F56EF57FF9B9F9CAF9DBF5C3F5D4FFFA0EFA1FF8E9F618F629FF2AFA74F65CFFFA96F58BA AB6FAC7F6ACF6BDF5DE9B05FFF16F6FB8FEF71DFB54FB65F750FB87FFF772FBA9FBBAF7A5FB DCF22CCBFEC0FFFF7F7FC31F39ECC50FC61F849FC83F3F0CFFCA2FCB3F89BFC5D442CCF4FD0 5F8EDFFD27F494CD46FD57F93FF950FAFBFD9FFFFDB0F994F9A5FAACFDEDFDEF9E9F9FAFFFE 34FE45FE56FA3EFA4FFE89FE9AFD64FF3A93FAA4F2034EE0FEF1FAD9FAEAF58D8F31FF42FB27 FB38F5DE9F80FF91FFF76FD79FB98FFCFFFE0FBCBF002FBEDFFF024F035FC20F057F22CC079F0 8AFC72FFF0ACF39EC0CBF0DCFC4F0FEF3F0C11DFFF12EFD16F150F442C16FF180FD68F1A2FFF 494C1C1F1D2FDBAFDCBFF76F21AF22BFFFE0FFE20FF27F268F279FE64FE75F2AFFFF2C0F2D1FEB 9FEC4F304F315F1DFFF0EFF9F1FF203535BF36CFF54FF65F58D8FF3ACF3BDFFA2FFB3F5DE93FBF 40CFFF1FFF1F4F013F44AF45BF046F47DF068F49FFFF4B0F09BF4D2F7C7C4F4F505F0EDF527FFF8 19C546F557F13FF579F86BC598F5A9FFF191F5CBF8BDC5EAF5FBF1E3F61DF90FCFF63CF64DF23 5F246F3F1F695F6A6F28AFF29BF3A2F6E3F6F4F2DFF2F0F72AF73BFFF74CF334F345F77FF790F6 5AF389F39AFFC20367D6F7E7F3CFF3E0FA088827FFF838F41DF42EFA599876F887F46CF66FFFF4



Property name	Value
	8EF8C5F8D6F4C1F8F8F4E3F91AF92BFFF516F94DFC42C96FF980F568F9A2FC94CFF9C1F9D2F5BAF9F4FCE6CA13FA24F60CFFFA46FD38CA65FA76F65EFA98FD8ACAB7FFFAC8F6B0F6C1F86CFB10FB21F705F716FFF81DFB5EFB6FF75AF76BFBA5FBB6FBC7F9F7AFF7C0FBFAFC0BFAD567166C3E0586D6174B8647FB631AE6C53007562746C6520456DFA700140730BE0C51FC62FC73F7FC5FA32B86C49EDC0EDB0C1B0CA0FCB1F1BCC2FC7BE33B86CC9A5526566FC6572EDB0EDA0D02FD13FD24FD3567F8A5CCF26D52FD63FD74FD85F8F4C42F46F6F2530548000C9E0DB53D34721A42C4269626C7FD067727A61CFC079DB53DDAFD383AE6C54204F4320486501533B7DC07D7B5C2A5C64C7B0CFE00674C3E0CF8030313035302DE79232E793E75038E7F4346481C2C0373836643663D95000326535334313538C3E9F0E8D03463353299D08550EF948099D0BDA0E99033EA70EB40E7F40FEBFE8030E7918B0063663131206530613162ED906165F7E760EE5FEF4C33EDB0F031E790DAE0F066663039ECD6F1AFE831F27DFFF25DF0D2F4F2F1D6F4DEF557F75FF86FFFF97FFA8FFB9FFCAFFDBFFECFFDF00EFFF01FF030F041F052F063F074F085F096FFF0A7F0B8F0C9F0DAF0EBF0FCF10DF11EFFF12FF140F151F162F173F184F195F1A6FFF1B7F1C8F1D9F1EAF1FBF20CF21DF22EFFF23FF250F261F272F283F294F2A5F2B6FFD2C5C642C55F4E52E4F2F5F306F317FFF328F339F34AF35BF36CF37DF38EF39FFF3B0F3C1F3D2F3E3F3F4F405F416F427FFF438F449F45AF46BF47CF48DF49EF4AFF4C0F4D1F4E2F4F3F504F515F526F537FFF548F559F56AF57BF58CF59DF5AEF5BFFF5D0F5E1F5F2F603F614F625F636F647FFF658F669F67AF68BF69CF6ADF6BEFF4F34FEA70ECE1F5416D923734E7C434FDE78136F0616E12BDA06DF1F1226FDFFF70EF71FF730F741FE831ED0E7816C4F452D7663AE5064393877B062AD77D033EA41EA0039E5E066E950FA64E9E162EDB0F64F79C6EDB0EAD1FBED40DAD033A9307840E750F5DF7CDFFF7DEF7EFF800F811F822F833F844FF6EFFF864C84CF885F896F8A7F8B8F8C9F8DAFFF8EBF8FCF90DF91EF92FF940F852F962FFF874F984F995F9A6F9B7F9C8F9D9F9EAF9FF9FBFA0CFA1DFA2EFA3FF951FA61F973FFFA83FA94FAA5FAB6FF39EE784AC55E6500200AE80
<b>PidTagSenderAddressType</b>	SMTP
<b>PidTagSenderEmailAddress</b>	eandersen@contoso.com
<b>PidTagSenderEntryId</b>	cb: 70 lpb: 00000000812B1FA4BEA310199D6E00DD010F540200000000456C697A616265746820416E64657273656E00534D54500065616E64657273656E40636F6E746F736F2E6636F6D00
<b>PidTagSenderName</b>	Elizabeth Andersen
<b>PidTagSensitivity</b>	0
<b>PidTagSubject</b>	Shu's Birthday

The following table lists the properties on the Calendar object for Anne's Birthday.

Property name	Value
<b>PidLidAllowExternalCheck</b>	TRUE

Property name	Value
<b>PidLidAppointmentCounterProposal</b>	FALSE
<b>PidLidAppointmentDuration</b>	1440
<b>PidLidAppointmentEndWhole</b>	07:00:00.000 AM 7/8/1982
<b>PidLidAppointmentNotAllowPropose</b>	FALSE
<b>PidLidAppointmentRecur</b>	cb: 80 lpb: 043004300D200200000020FA03000C000000000000007000000232000000A000000000000000 00000000000000000000C2F50BDF80E95A063000000930000000000000A005000000000000000 000000
<b>PidLidAppointmentSequence</b>	0
<b>PidLidAppointmentStartWhole</b>	07:00:00.000 AM 7/7/1982
<b>PidLidAppointmentStateFlags</b>	0
<b>PidLidAppointmentSubType</b>	TRUE
<b>PidLidBusyStatus</b>	0
<b>PidLidCleanGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E00800000000307DD3F5B068C80100000000000000001000 0000FC39CE77217D824FB608D84F4FDfE22B
<b>PidLidCollaborateDoc</b>	

Property name	Value
<b>PidLidConferencingType</b>	0
<b>PidLidDirectory</b>	
<b>PidLidFInvited</b>	FALSE
<b>PidLidGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E00800000000307DD3F5B068C80100000000000000001000000FC39CE77217D824FB608D84F4DFE22B
<b>PidLidIntendedBusyStatus</b>	4294967295
<b>PidLidLocation</b>	
<b>PidLidNetShowUrl</b>	
<b>PidLidOnlinePassword</b>	
<b>PidLidOrganizerAlias</b>	
<b>PidLidReminderDelta</b>	10080
<b>PidLidReminderSet</b>	TRUE
<b>PidLidReminderSignalTime</b>	07:00:00.000 AM 6/30/2008
<b>PidLidReminderTime</b>	07:00:00.000 AM 7/7/1982
<b>PidLidResponseStatus</b>	0
<b>PidLidTimeZoneDescriptor</b>	(GMT-08:00) Pacific Time (US & Canada)

Property name	Value
<b>on</b>	
<b>PidLidTimeZoneStruct</b>	cb: 48 lpb: E001000000000000C4FFFFFF00000000B000000010002000000000000000000000030000000 20002000000000000000
<b>PidTagBody</b>	Gift ideas: New camera phone
<b>PidTagCreationTime</b>	07:10:03.026 PM 2/6/2008
<b>PidTagImportance</b>	1
<b>PidTagLastModificationTime</b>	07:10:03.026 PM 2/6/2008
<b>PidTagMessageClass</b>	IPM.Appointment
<b>PidTagMessageLocaleId</b>	1033
<b>PidTagReplyRequested</b>	TRUE
<b>PidTagResponseRequested</b>	TRUE
<b>PidTagRtfCompressed</b>	cb: 5487 lpb: 6B150000115A00004C5A4675219AA95B07000601010B606E6731303266350064007263700DD0 0E0032050C60630D446633313530423700F5737473680570627463680FD23610840900110B683 30EB0111A62690FD70DA43333891426666514A374686507809F146715D71560014015D763730 1E8F302A413B064690336020011000AC00873657402D170727132A500002A0AA16E6F1A50200 DF0D51BA13614B0300FF0341C2101D0991C10347D076D02833334191F1F1A2400501AAF20EF2 1107D4361F706D0072105D06115D01DE410101E66FF03E319FF1B0B01301C721BB21C501C10F 326A122216C6922611DE40FE1190FFF246F1B2F1C3F1D4E0FE11FC1287F298FFF2A9F2BAF2CBE 0F202DDF2EEF2FF73102FF30C430A22704225327B714D0334F345FFF2FFF310F321F1E4F392F3A 3F3B4F3C5FFF0FF00E103DAF3EBF3FCF40DF41EF1160FF237F442F259F26AF27B72358439F4A1F 3745BF46CF1DE4394D6F4E7432338A384EE420076D20434502833F50A052AF53B53D72546F55 737972B755D4332F1F56361FC5584F4709D17E6B55D4381F5AF759E15BBF038254EF087055D43 D8F1F563723515F8F0382D8284865226007D02955D442FFFF6277543F6416071001A00EB064F5 48685D1EED384861673F0382420740747F0EB055D44D5F5AF75DB16B3F644356590890746E22 4007906564F530FF5298490C5418274555A70DE071AF575E7F73B759660EF074DF5B0E73B65D0 931FF5DB878AE5F5673B660D75B607B7F6A8EFF73B66C890FD267016D7F53DF54EF27D5DF529 F75DF845F59650FD1312DBF791FFF5C0F5D1789A259EF7C7F5DF60E589A2FF5DBF627F6F6F64 9A89A2616F667F93EFF689A89A2656F7FBF6B8F815B7E996DEF7F9BDF700F9558823F834F882F 856731EF860F871FA4CF89383289EF8AFF8C0FFD8D1A328DEF8EFF900F9118A420AE6FF792EF9

Property name	Value
	<p>3FF950C3295FF970FB45F992DDF0E01B68F9B5F9C6F8179329E3F9F4F7FB88FA16FAA21A2AFA3  BF2236855832FFA67FA78FC53789380FD0C67F792F2245BD8D0B33AE5FAF6F2236910933BA9FF  FBBAF2236814CA432D0DFA3EFA4FFC955FFC66FC77FD65F893874A0D81FAB7FAC8FFF8D2959D  FCE4FDDFF91095DAFB33FE1FFFF94EE615FB76FE5DF991E655FD1AFEAOFFF814C695FBFAFEE3F  C1CFDBA2D43FD54FFBDA2F856734D80FD91FF6CF893889C0FFF88FDD0FDE1F8D290F11FC7FE1  1FE22FFFBC7E3CFE4DFF25F94FDDBC0044FE91F7FEA2F993CFC30087FED4FEE5F816A35FFF03F  F14F0A8FF36FFC21F4AFF5BFFA9FFD856735F87FF98F173F8938FDE2191FFFFD9FFFAF8D4701E2  1CFF019F02AF1C46EF043F054F12CF94FD36086F097F26CFBD992D360C9F0DAF0EBF815B3610A  FFF11BF2AFF13DF1C911518723F734F1C37EF719F19FF76EE4D11371CC878AF79BFFD8D293778  0F21DF7D8E3BF22D087F4FFF805F816A2A62314F165F176F3BC518EFF739EF48CF8938381CCF3  D4F1EEF8D1ADE3820CF40CF22EF91183824AF25BF7B333F94FD3828DF29EF585F992D38FF2D0F  442F2F2F815B60225ECF325F336F0370A881B1636F6C6F727450626C3B5C8D106474C0678D8D  116E74C06730756530675FFA65BA8035688A69A1695F6A6968747F6A9268FF6CCF6C8D6C0F6A3  F688F65FD8DD038725A7371732F743968747462BF72CF769F765D75DF740F77D4395250FF7B24  7C8174A37C80725F6B0776BF7500A181B12A5C64654F517063112B85C244B173AE4020808670  61F98121716C6310455067A0CFA067A0A13CE06463746C82907283902599307080D161759D60  5C611E73829083F03D5084F26E756D2589806184B0746F84F0646AC8757374CFA0676884E0CFA  0A7680145506801697482A0308200305C6E6F7144D15D306F744C65208D7086B0796C5CB068F  D8D20748D7082EF83FF850F861F872F4F7DC08AF04F604F4173316310615F815357D0901081D1  8C006C4F2067FC3130BA808A118DD08F848F218159DB8A20911333563091026674D09372CE63  786062E093136E7093699504416310736E6578748F2173B7887067005D4074963144E0696700F  587D07988104E9702674080838FC1EF8F218D8062F09D707688F08920A1E0786D696862E080D  05D608920757A6E9A31658DB0678097598FE044698BA420503D6061786082A068A0204666F6E7  48074748FD0B74E509DF04EF0779A08DD0669DF0E25762E074684256308DD082905D99506C9  1405C009F84729FF866AE6C9F669ED0A16762A167729F62FC636282903DA0A3528281A3C2673  04F87406791A484894070659F6173F063656C6C8AB19F309ED1A4E1FE7399A06710BDC19DE1B  580A080A7463A6CA75562A7558B30A7646467DFA846A9C0A9468F90A7647682CF8AEFF8BFF8  D0F8E1F8F2F903F914F925F936FFF947F958F3DA0B1A199EF9AF896E69824FF64B0EB408960988  7B3319948B11CB0E1B7B36AAD90666C06657B0963162ADD0FF67809D609902B8AF9AF889403D  7062E0ED003132F860881048A571A8308740BBCCA398C336BC3FBD4FBE5B38BF3FFFC04FC15F  C2629D50A6009E706780C2AFFFBF12C3FFB18F4510B35FB466A41096A2DFC70FC81697889761  A6F0739D60BB1163892066D06D706FF3E0C93F45F15D40696C53894257B0668380B06DDF1076  6721890055C3108850777E6ED586C1F1D622D743C225DB616DB997216850ACF0D8C39D52335  A60326DE7106B428742DA0553754A62DA717398516C46EB30631FDA7162F0ADE09C314E506D  6C4D353D6067DA5372DCD780D14A63FBDC91AD1249A4C067F03DA0E7E0DA71398740744C5C  90DA7166107279D5DFB131808378DCB0EAF80D63207E0D4B1A0AFD074703A2F2FA7A5D0899  05D40732EC7E0634EFOABD2C09ED02ED3412FE35066EB60C8652F776700642F3A50B530B7E43  3DCB066905C8291A6F07774E0F7C25067A0E573685A32DA71DCE19FE0BFDF33DCE1A090E756  DF15DCE162DF23F667AF0088E0728761AF90F3E0ACA03F6310AC719E70ACA0A8319ED06E62CE  6AADC067F099506F639EA1DBD0FE6B88C099A0CD30EBF496F4EF70B2E11F80C09D6088D1DA0  06780737973A796F0DF017DC16C799D6076DCB0A767A0EDD88781676497306167A2DE66EBC1  D600DEF1A691764541F091DF9670DCB04E5089809E7070B2C0A5E0FDF2B06C9F20967287C0B6  B06700C7D13E78678066D09D70DEF167A07361FF99A08740F1D3E0E1F4F1F2B1E0E1A6F06F4EF  03D704E50885078B2C0E2106FEA7967F05C967070898067104F30DF8850AD91A830ADE0EBE06  49D706730F9E1106264A8C08850ADE1A5E096F14FBEC196F28980AF40655CF2B072BE7AEBEC2A  9C0E6F28740FB9168F9D3F36010EF916776FC69FB21AFB08740FF8171FCE2FDE4FD93F2A2EDB1  FD01FF732E6AF7C14F20B660763450776BFFA4B15E9000D2A5D04540B5C1E611E900FDAAD265  AF40023596F088D09761EF20FE74D6C08740FB00EB2103C7AFD05D40FFAF00ADE08841E100AF  D0AF416721BEB0FF14500FD0D040E100B2A1F912A4B1ABE0FF03D001C1ACA067309E8103C167  216710FFAA71E100DA11FA41FB008850DA11AD10FE700632965082A0AF10B6328740A5E2FFB2  A1CA71E3F0A5F0C831EE60A5F0AD01DC70709AC0ACA0ADC1694F200957FF28106721C1B2AD9  03D10885078609E70FFAEF2E3F0ADB09B21F3F1DB50894096F1EF4550AF808841A4B16EDA019  DF014B09FA5F00941A5F0D60088416378ADE0FF87E0BB6187C0A4C0F8A1CA901221F791FB885  0B1D063E1110632B1D01213AF00BB8740A8406813830392E22067ACD2FDEDF163F1D00573672  0DA20144263300708121692F1D0747862785CFF0970B6C03D709660ADB001C0E281F471FE6C0  6C16310F8512C40D3519732B5B0CB9690809277F0F1666D17C0D4F0FDE9A120C25081808832B  5B0973023F0BF3D90F80088D0ACB074D087C06C96F0EF5D4001C007D0E100758800CE52ACD1  FF9631EA319B51E9F58772967067A0EB91FF9AD0A6F0FB001F93AD641EA08920EB23CF890180B</p>

Property name	Value
	0AE80EA216C76F271AE81FFE310AEB0231187E067102392A4B1DEF1FF3FA0E6119AD0B2D1890 1AE80189087E0FC202ED5942316525023B2CE61241FFF252F263F23705630AE8080D0EBE0280F FB291F2A2F6C5A60AE80CCD027CF2C9F7D2DA529268C5E902B6F305F2D8562FF5D703851318F 234344B02F2F33FF350FFF361F236157D0377223FF38DF39EF31FDF5C00377F3D0F3E1F3F2F23 614A703C0FFF41AF42BF43C5E561A790E560B2C08740FFCE43ACD2ABBFACCFADDFAEFFA4E8 B2FF5381C208CCAFB21FB32FB43FB54FB65FFF95A859F0505F5160528CCFE113119E5069C1F94 769E360209AF14C103A6F5CD301C064E05DA0204C609D60657F5E11576F587F598F66C063C1D 40A0D7E0A48B28204F731F17289434A2073C7EE60ED7065807832363BE06261FF66F0EC306780 80D187616271C7D780D1FF1DF062619AC864E6BA5563C6978680D1FC3939D8A063379670A5E 00A404A11FF642AC572654A6A44BA5550E167496A44BF63649807696F6A7F6B8F97A4396D0BF 302A2ED8120316E33708F719F72A7EF7DA1736F747F727A33765F776F725CEE34796F7A7F725C 357C7F7D8F725CFE367F8F809F725CD57082AF83BF726B6E3885AF86BF725C396E33978633FB8 A5C4D506373258C1F8D2876448E2FFF8D287954903F8D287C64924F8D287F74FF945F8D28828 4966F8D288594987F8D28FF88A49A8F8D288BB4890F9CD352726D38FF01C00A406C90D6D06E4 F6F5F9E8F6C94FBD0B26D29544EE0BB71A43B6D0BDC61B94BC220504F1F0F0B0C068CA31FFD F90A15FA26FA37FA486A70CDB01ED70FFA606A99FAAAFABBF3E0CE23AD394DD0FDF49067AE 5FAF6FB07FB1866CFCD4C0BB4C61C1F073B34FB45F6749358A5C7E5412D25A905581B853B49E 6D5650FBF2F61C5154F381B85FBCCFB56FA69F7F6D94ADC0F9E1ED81BF8FC09F674936FF6CFC DFB04E01ADC0FAD1C47FC58FC69DFFA70CC864DFB04DC0C93FCA4FC6CAB20C7FC864BC77CD EFCE5F71557206D1A4DFD19C0694CE0C8B67325D24FD35FC715FE34D4EFD5F7644D70FD81F C715A00CDFD5B5CD52D69FDC6FC6AC36DE6DF76FFDB6FE10FC6BB5DB2E32FBC72DFE5E58FF DC6AC38E78FE896E48FEA2FC6BB8A5C5FE85A7954EE0FEF1F6C94376CFC44BD4F706BCD4FF30 FF41FA70C4305B0FDFEB0664BD0C8BFF72FF83FF4F1D07CFFFA57F65FFC2FF42ED4DCF457D1BF 00BFC7C68FD08FC8A7204163BEB061D0FFE90F056FCB3F078FDFA3091F0A2F0B3FFFD04FD1580 DFF0F0F101FD49FD5AF12EFFF13FF150FD95FDA6F183F194F1A5FDE1F8FDF2C1D8CDB0FA77552 6576FFB0FFA12F1EFFC17F9C791BACDFA3A867258F8F269F27AFB1868A5C51756F61B0DF2AFF2 C0F2D1F9CA66CFC4961D064C0FF36F02F7F308F1FDFFE2DFE3E91D8F35BFFF36CFE73FE84C39CF 3ADF3BEFEBFCFCDF3EEF3FFF410FF05FF16C440F451F462FFFF4EFF5F8492F4A3F4B4FF93FFA4 F4E0FFF4F1F502FFDFFF0C535F546F557F028FFF039C587F598F5A9F071F082F5DC3EDAFFF5F2F 0BAF0CBF5849633F644F109F11AFF5D69682F693F158F47BF17AF6D1F6E2FFF1ADF704F1CFF72 6F737F202F759F224CFF77BF78CF374F7AEF396C7CDF7DEF3C6FFF800F3E8C81FF830F418F852F 43AC871FFF882F46AF8A4F48CC8C3F8D4F4BCF4CDFFF678F91CF92DF511F522F629F96AF97BFF F566F577F9B1F9C2F9D3F5BBF5CCFA06FFFA17F8E1F610F621FF22FA6CF654FA8EFFF583AAAEFA BFF6A4F6B5F5D69AFDFB0EFFF6F3F8F6F715FB4CFB5DF748FB7FF76AFFFB1FBB2F79DFBD4F22 4CBF6FC07F7EFFFCC29F396CC48FC59F841FC7BF3E8CC9AFFFCABF893FCCDF43ACCECFDF8E5 FD1FFFF48CCD3EFD4FF937F948FAF3FD97F8A8FF98CF99DFAA4FDE5FDF6F9E1F9F2FE2CFFFE3 DFE4EFA36FA47FE81FE92FD5CFA8BFF9A9CF2034ED8FEE9FAD1FAE2F5858FF29FF2AFB1FFB30F 5D69F78FF89FB6EFFF71FB90FFC7FFD8FBC3FFFAFBE5F01CFFF02DFC18F04FF224C071F082FC6 AF0A4FFF396C0C3F0D4FCBCF0F6F3E8C115F126FFF0EF148F43AC167F178FD60F19AF48CCFF1 B9F1CAFDB2FDC3FF6EF212F223FE07FFFE18FF1FF260F271FE5CFE6DF2A7F2B8FFF2C9FEB1FEC2 F2FCF30DF1D7FF06FF17FFC2035353F364FF4CFF5DF58583A4FFF3B5FF9AFFABF5D693F3F404FF E9F1ECFFF00BF442F453F03EF475F060F497F4A8FFF093F4CAF7BFC4ECF4FDF0E5F51FF811CFF53 EF54FF137F571F863C590F5A1F189FFF5C3F8B5C5E2F5F3F1DBF615F907C634FFF645F22DF23EF 3E9F68DF69EF282F293FFF39AF6DBF6ECC2D7F2E8F722F733F744F7F32CF33DF777F788F652F38 1F392F20FE367CEFD7FF3C7F3D8FA00881FF830FFF415F426FA51986EF87FF464F667F486FFF8B DF8CE4B9F8F0F4DBF912F923F50EFFF945FC3AC967F978F560F99AFC8CC9B9FFF9CAF5B2F9EC FCDECA0BFA1CF604FA3EFFF30CA5DFA6EF656FA90FD82CAAFFAC0FFF6A8F6B9F864FB08FB19F 6FDF70EF815FFF56FB67F752F763FB9DFBAEFBFF7A7F4F7B8FBF2FC03FACD67166C3606D2C6 174B7E47F3631ADE53750062746C6520456D707D00C0730B60C49FC5AFC6BF7F4532FDB7EC4 9ED40ED30C130C98FCA9FCBAF0DC73E33B7ECC92552656665FE72ED30ED20CFAFD0BFD1CFD2 D689DC3FCEA6D4AFD5BFD6CFD7DF8ECC426FFA6F24B0547F80C960DAD3D2C7A3AC10426962 6C7F506772613DCF4079DAD3DD2FD303ADEC544F104320486500D33B7D7D607B5C2A5C64C7 30CF607483C360CF003031303530E7129632E713E6D038E7743464C24040373836643663D8D0 328065353334313538E970E1E85034633532995084D09400F79950BD20E91033E9F0EAC0E774E B7E077FB0E7118A8063663131659030613162ED106165E6E07BEDDFEECC33ED30EFB1E710DA6 066F8663039EC56F12FE7B1F1FDF1DDFFF052F472F156F45EF4D7F6DFF7EFF8FFFFA0FFB1FFC2 FFD3FFE4FFF5F006F017FFF028F039F04AF05BF06CF07DF08EF09FFF0B0F0C1F0D2F0E3F0F4F10 5F116F127FFF138F149F15AF16BF17CF18DF19EF1AFFFF1C0F1D1F1E2F1F3F204F215F226F237FF

Property name	Value
	F248F259F26AF27BF28CF29DF2AEF2BDCFE642BD5F4652DCF2EDF2FEF30FF320FFF331F342F353F364F375F386F397F3A8FFF3B9F3CAF3DBF3ECF3FDF40EF41FF430FFF441F452F463F474F485F496F4A7F4B8FFF4C9F4DAF4EBF4FCF50DF51EF52FF540FFF551F562F573F584F595F5A6F5B7F5C8FFF5D9F5EAF5FBF60CF61DF62EF63FF650FFF661F672F683F694F6A5F6B6FF473E9F0A7EC61F4C16D123734E74434E701FE36EFE16D92BD206D71F0A26F5F706FFF717F728F739FE7B1EC82E7016BCF2CF6A263ADD064393877306277505633E9C1E98039E56066E8D0649DE96162ED30F5CFEF5730622CE0E97FB03366EA603877C0E6D0F55FFF7C5F7D6F7E7F7F8F809F81AF82BF83CFFFF66F85CC844F87DF88EF89FF8B0F8C1FFF8D2F8E3F8F4F905F916F927F938F84AFF95AF86CF97CF98DF99EF9AFF9C0F9D1FFF9E2F9F3FA04FA15FA26FA37F949FA59FFF96BFA7BFA8CFA9DFAAEFF31EE704ABD505E5D000AE00
<b>PidTagSenderAddressType</b>	SMTP
<b>PidTagSenderEmailAddress</b>	eandersen@contoso.com
<b>PidTagSenderEntryId</b>	cb: 70 lpb: 00000000812B1FA4BEA310199D6E00DD010F540200000000456C697A616265746820416E64657273656E00534D54500065616E64657273656E40636F6E746F736F2E636F6D00
<b>PidTagSenderName</b>	Elizabeth Andersen
<b>PidTagSensitivity</b>	0
<b>PidTagSubject</b>	Anne's Birthday

Elizabeth saves her calendar to share with Shu. The following shows the resulting iCalendar file.

```
BEGIN:VCALENDAR
PRODID:-//Microsoft Corporation//Outlook 12.0 MIMEDIR//EN
VERSION:2.0
METHOD:PUBLISH
X-CALSTART:19751012T000000
X-WR-RELCALID:{00000018-0E80-EBB5-82FB-58F695E239B2}
X-WR-CALNAME:Birthdays
BEGIN:VEVENT
CLASS:PUBLIC
CREATED:20080206T190802Z
DESCRIPTION:Happy Birthday to me!\n
DTEND;VALUE=DATE:19751013
DTSTAMP:20080206T191251Z
DTSTART;VALUE=DATE:19751012
LAST-MODIFIED:20080206T190802Z
PRIORITY:5
RRULE:FREQ=YEARLY;BYMONTHDAY=12;BYMONTH=10
SEQUENCE:0
SUMMARY;LANGUAGE=en-us:Elizabeth's Birthday
```

TRANSP:TRANSPARENT  
 UID:040000008200E00074C5B7101A82E008000000020C397BAB068C80100000000000000  
 010000000D4429044CA28924C8FD122A133685E4A  
 X-ALT-DESC;FMTTYPE=text/html:<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 3.2//EN">\n<HTML>\n<HEAD>\n<META NAME="Generator" CONTENT="MS Exchange Server version 08.00.0681.000">\n<TITLE></TITLE>\n</HEAD>\n<BODY>\n<!-- Converted from text/rtf format -->\n\n<P DIR=LTR><SPAN LANG="en-us"><FONT FACE="Calibri">Happy Birthday to me!</FONT></SPAN><SPAN LANG="en-us"></SPAN></P>\n\n</BODY>\n</HTML>  
 X-MICROSOFT-CDO-BUSYSTATUS:FREE  
 X-MICROSOFT-CDO-IMPORTANCE:1  
 X-MICROSOFT-DISALLOW-COUNTER:FALSE  
 X-MS-OLK-ALLOWEXTERNCHECK:TRUE  
 X-MS-OLK-CONFTYPE:0  
 BEGIN:VALARM  
 TRIGGER:-PT10080M  
 ACTION:DISPLAY  
 DESCRIPTION:Reminder  
 END:VALARM  
 END:VEVENT  
 BEGIN:VEVENT  
 CLASS:PUBLIC  
 CREATED:20080206T190926Z  
 DESCRIPTION:Gift ideas: Baseball tickets\n  
 DTEND;VALUE=DATE:19780228  
 DTSTAMP:20080206T191251Z  
 DTSTART;VALUE=DATE:19780227  
 LAST-MODIFIED:20080206T190926Z  
 PRIORITY:5  
 RRULE:FREQ=YEARLY;BYMONTHDAY=27;BYMONTH=2  
 SEQUENCE:0  
 SUMMARY;LANGUAGE=en-us:Shu's Birthday  
 TRANSP:TRANSPARENT  
 UID:040000008200E00074C5B7101A82E0080000000E0243DD0B068C80100000000000000  
 010000000EE6CCE82EE4BC14BB01478A948D182FB  
 X-ALT-DESC;FMTTYPE=text/html:<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 3.2//EN">\n<HTML>\n<HEAD>\n<META NAME="Generator" CONTENT="MS Exchange Server version 08.00.0681.000">\n<TITLE></TITLE>\n</HEAD>\n<BODY>\n<!-- Converted from text/rtf format -->\n\n<P DIR=LTR><SPAN LANG="en-us"><FONT FACE="Calibri">Gift ideas: Baseball tickets</FONT></SPAN><SPAN LANG="en-us"></SPAN></P>\n\n</BODY>\n</HTML>  
 X-MICROSOFT-CDO-BUSYSTATUS:FREE  
 X-MICROSOFT-CDO-IMPORTANCE:1  
 X-MICROSOFT-DISALLOW-COUNTER:FALSE  
 X-MS-OLK-ALLOWEXTERNCHECK:TRUE  
 X-MS-OLK-CONFTYPE:0  
 BEGIN:VALARM  
 TRIGGER:-PT10080M  
 ACTION:DISPLAY  
 DESCRIPTION:Reminder  
 END:VALARM  
 END:VEVENT  
 BEGIN:VEVENT  
 CLASS:PUBLIC  
 CREATED:20080206T191003Z  
 DESCRIPTION:Gift ideas: New camera phone\n  
 DTEND;VALUE=DATE:19820708  
 DTSTAMP:20080206T191251Z  
 DTSTART;VALUE=DATE:19820707



```

LAST-MODIFIED:20080206T191003Z
PRIORITY:5
RRULE:FREQ=YEARLY;BYMONTHDAY=7;BYMONTH=7
SEQUENCE:0
SUMMARY;LANGUAGE=en-us:Anne's Birthday
TRANSP:TRANSPARENT
UID:040000008200E00074C5B7101A82E0080000000307DD3F5B068C80100000000000000
01000000FC39CE77217D824FB608D84F4FD22B
X-ALT-DESC;FMTTYPE=text/html:<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 3.2//EN">\n<HTML>\n<HEAD>\n<META NAME="Generator" CONTENT="MS Exchange Server version 08.00.0681.000">\n<TITLE></TITLE>\n</HEAD>\n<BODY>\n<!-- Converted from text/rtf format -->\n\n<P DIR=LTR><SPAN LANG="en-us"><FONT FACE="Calibri">Gift ideas: New camera phone</FONT></SPAN><SPAN LANG="en-us"></SPAN></P>\n\n</BODY>\n</HTML>
X-MICROSOFT-CDO-BUSYSTATUS:FREE
X-MICROSOFT-CDO-IMPORTANCE:1
X-MICROSOFT-DISALLOW-COUNTER:FALSE
X-MS-OLK-ALLOWEXTERNCHECK:TRUE
X-MS-OLK-CONFTYPE:0
BEGIN:VALARM
TRIGGER:-PT10080M
ACTION:DISPLAY
DESCRIPTION:Reminder
END:VALARM
END:VEVENT
END:VCALENDAR

```

Shu opens the iCalendar file. The following tables represent the contents of the Birthday calendar's Folder object and its three Calendar objects in Shu's **store**.

The following table shows the property on the Folder object.

Property name	Value
<b>PidTagDisplayName</b>	Birthdays

The following table lists the properties on the Calendar object for Elizabeth's Birthday.

Property name	Value
<b>PidLidAllowExternalCheck</b>	TRUE
<b>PidLidAppointmentDuration</b>	1440
<b>PidLidAppointmentEndWhole</b>	07:00:00.000 AM 10/13/1975
<b>PidLidAp</b>	FALSE

Property name	Value
<b>pointmentNotAllowPropose</b>	
<b>PidLidAppointmentRecur</b>	cb: 80 lpb: 043004300D200200000A0FF05000C00000000000000C000000232000000A00000000000000000000000000080B4BF0BDF80E95A0630000009300000000000000A00500000000000000000000000000000000000
<b>PidLidAppointmentSequence</b>	0
<b>PidLidAppointmentStartWhole</b>	07:00:00.000 AM 10/12/1975
<b>PidLidAppointmentStateFlags</b>	0
<b>PidLidAppointmentSubType</b>	TRUE
<b>PidLidBusyStatus</b>	0
<b>PidLidCalendarGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E0080000000020C397BAB068C80100000000000000001000000D4429044CA28924C8FD122A133685E4A
<b>PidLidConflictingType</b>	0
<b>PidLidInvited</b>	FALSE
<b>PidLidGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E0080000000020C397BAB068C80100000000000000001000000D4429044CA28924C8FD122A133685E4A
<b>PidLidLocation</b>	
<b>PidLidOwnerCriticalChange</b>	07:12:51.000 PM 2/6/2008
<b>PidLidRe</b>	10080

Property name	Value
minderDelta	
PidLidReminderSet	FALSE
PidLidReminderSignalTime	07:00:00.000 AM 10/5/2008
PidLidReminderTime	07:00:00.000 AM 10/12/2008
PidLidResponseStatus	0
PidLidTimeZoneDescription	(GMT-08:00) Pacific Time (US & Canada)
PidLidTimeZoneStruct	cb: 48 lpb: E001000000000000C4FFFFFF00000000B0000000100020000000000000000000000000030000000 20002000000000000000
PidTagBody	Happy Birthday to me!
PidTagCreationTime	07:14:57.374 PM 2/6/2008
PidTagImportance	1
PidTagLastModificationTime	07:14:57.374 PM 2/6/2008
PidTagMessageClass	IPM.Appointment
PidTagMessageLocalId	1033
PidTagReplyRequested	FALSE
PidTagResponse	FALSE

Property name	Value
<b>Requested</b>	
<b>PidTagRtfCompressed</b>	cb: 652 lpb: 88020000AB0500004C5A46750D2BFF6703000A00726370673132358232034368746D6C310331F862696404000330010301F70A80FF02A403E40713028010830050045608559F07B211B50E510301020063680AC07073657432060006C311B5335B044614473012BF02003403C643F9074069620510028011C308EF09F7B63B1A1F0E303511B20C60630050330B090164333616E00BA534205910822A5C0EB20190671EC03300203C21444F4354590050452048544D4C20005055424C49432022402D2F5733432180444454442094332E32218045F84E223E11C31F371FE00AA3231CFC31391FF020A2230D14D0241F23D1E31ED02570454144230D0EF126EF050E10360EF03C4D455441C507B0412B103D224709F0049014617405B02216F04F4E544D22D0542BA005E1457814616EF4676506527613112DF100900220402030382E30302ED0367438312ED13022FE297F25033782371FF05449544C4525CEA6340EF0246D38351FF02F323F7F306F1F55338134D0284F269F1F6435C116E03C424F4459230D1E4147393F1FB13A61212D2D16F16E552DF1740980200352203E0078FC742F00213E3005B000C005403D702F3ADF3BEF408F1F643628115020804449523D4C54522300BF1F433EE2000044451E4144465C1F80CE720AB1460214605C71032144E7051EFB3828115350414E201A4C48E0472BA009F02D75734722F1443F478E3134381FF046E12C81204641432B9118B549CC0318104709486170707920C4426900206864614F602C20CA20078021247C353634C14C52F749D949E7479D3914D034D048C251EFFF52FF487F498F556F53BF54CF45490AA2FF55580A8145870AB15DA855ED01C034C1BE503FBF421F615F39F54C212F3A9F5F38EF1F65320137C025937D67A0
<b>PidTagSensitivity</b>	0
<b>PidTagSubject</b>	Elizabeth's Birthday

The following table lists the properties on the Calendar object for Shu's Birthday.

Property name	Value
<b>PidLidAllowExternalCheck</b>	TRUE
<b>PidLidAppointmentDuration</b>	1440
<b>PidLidAppointmentEndWhole</b>	08:00:00.000 AM 2/28/1978
<b>PidLidAppointmentNotAllowPropose</b>	FALSE
<b>PidLidAppointment</b>	cb: 80 lpb: 043004300D200200000060AE0000C00000000000001B000000232000000A00000000000000

Property name	Value
<b>ntRecur</b>	0000000000000000A0CCD20BDF80E95A06300000093000000000000A005000000000000000000000000000000
<b>PidLidAppointmentSequence</b>	0
<b>PidLidAppointmentStartWhole</b>	08:00:00.000 AM 2/27/1978
<b>PidLidAppointmentStateFlags</b>	0
<b>PidLidAppointmentSubType</b>	TRUE
<b>PidLidBusyStatus</b>	0
<b>PidLidCalendarGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E00800000000E0243DD0B068C80100000000000000001000000EE6CCE82EE4BC14BB01478A948D182FB
<b>PidLidConferenceType</b>	0
<b>PidLidInvited</b>	FALSE
<b>PidLidGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E00800000000E0243DD0B068C80100000000000000001000000EE6CCE82EE4BC14BB01478A948D182FB
<b>PidLidLocation</b>	
<b>PidLidOwnerCriticalChange</b>	07:12:51.000 PM 2/6/2008
<b>PidLidReminderDelta</b>	10080
<b>PidLidReminderSet</b>	FALSE

Property name	Value
<b>PidLidReminderSignalTime</b>	08:00:00.000 AM 2/20/2008
<b>PidLidReminderTime</b>	08:00:00.000 AM 2/27/2008
<b>PidLidResponseStatus</b>	0
<b>PidLidTimeZoneDescription</b>	(GMT-08:00) Pacific Time (US & Canada)
<b>PidLidTimeZoneStruct</b>	cb: 48 lpb: E001000000000000C4FFFFFF000000000B0000000100020000000000000000000000000030000000 20002000000000000000
<b>PidTagBody</b>	Gift ideas: Baseball tickets
<b>PidTagCreationTime</b>	07:14:57.405 PM 2/6/2008
<b>PidTagImportance</b>	1
<b>PidTagLastModificationTime</b>	07:14:57.405 PM 2/6/2008
<b>PidTagMessageClass</b>	IPM.Appointment
<b>PidTagMessageLocalId</b>	1033
<b>PidTagReplyRequested</b>	FALSE
<b>PidTagResponseRequested</b>	FALSE
<b>PidTagRtfCompressed</b>	cb: 660 lpb: 90020000B20500004C5A46752E94CCFE03000A00726370673132358232034368746D6C310331 F862696404000330010301F70A80FF02A403E40713028010830050045608559F07B211B50E510



Property name	Value
nce	
PidLidAppointmentStartWhole	07:00:00.000 AM 7/7/1982
PidLidAppointmentStateFlags	0
PidLidAppointmentSubType	TRUE
PidLidBusyStatus	0
PidLidGlobalObjectId	cb: 56 lpb: 040000008200E00074C5B7101A82E0080000000307DD3F5B068C80100000000000000001000000FC39CE77217D824FB608D84F4DFDE22B
PidLid ConferencingType	0
PidLidInvited	FALSE
PidLidGlobalObjectId	cb: 56 lpb: 040000008200E00074C5B7101A82E0080000000307DD3F5B068C80100000000000000001000000FC39CE77217D824FB608D84F4DFDE22B
PidLidLocation	
PidLidOwnerCriticalChange	07:12:51.000 PM 2/6/2008
PidLidReminderDelta	10080
PidLidReminderSet	FALSE
PidLidReminderSignalTime	07:00:00.000 AM 6/30/2008
PidLidReminderTime	07:00:00.000 AM 7/7/2008



Property name	Value
me	
PidLidResponseStatus	0
PidLidTimeZoneDescription	(GMT-08:00) Pacific Time (US & Canada)
PidLidTimeZoneStruct	cb: 48 lpb: E001000000000000C4FFFFFF00000000B000000010002000000000000000000000030000000 20002000000000000000
PidTagBody	Gift ideas: New camera phone
PidTagCreationTime	07:14:57.421 PM 2/6/2008
PidTagImportance	1
PidTagLastModificationTime	07:14:57.421 PM 2/6/2008
PidTagMessageClass	IPM.Appointment
PidTagMessageLocaleId	1033
PidTagReplyRequested	FALSE
PidTagResponseRequested	FALSE
PidTagRTFCompressed	cb: 656 lpb: 8C020000B20500004C5A46752EC3261E03000A00726370673132358232034368746D6C310331 F862696404000330010301F70A80FF02A403E40713028010830050045608559F07B211B50E510 301020063680AC07073657432060006C311B5335B044614473012BF02003403C643F907406962 0510028011C308EF09F7B63B1A1F0E303511B20C60630050330B090164333616E00BA53420591 0822A5C0EB20190671EC03300203C21444F4354590050452048544D4C20005055424C4943202 2402D2F2F5733432180444454442094332E32218045F84E223E11C31F371FE00AA3231CFC3139 1FF020A2230D14D0241F23D1E31ED02570454144230D0EF126EF050E10360EF03C4D455441C5 07B0412B103D224709F0049014617405B02216F04F4E544D22D0542BA005E1457814616EF467 6506527613112DF100900220402030382E30302ED0367438312ED13022FE297F25033782371FF

Property name	Value
	05449544C4525CEA6340EF0246D38351FF02F323F7F306F1F55338134D0284F269F1F6435C116E03C424F4459230D1E4147393F1FB13A61212D2D16F16E552DF1740980200352203E0078FC742F00213E3005B000C005403D702F3ADF3BEF408F1F643628115020804449523D4C54522300BF1F433EE200044451E4144465C1F80CE720AB1460214605C71032144E7051EFB3828115350414E201A4C48E0472BA009F02D75734722F1443F478E3134381FF046E12C81204641432B9118B549C3B1810470947069005400F40656164733A07B3636107802C0020947068022065247C353634C1EF4C5249D949E7479D3914D034D048C2FF525F536F487F498F55DF542F553F4549FF0AA255C80A8145870AB15E18565D01C07D34C1503FBF421F61CF39F54C212FBF3A9F38EF1F65320137C025937D6810
<b>PidTagSensitivity</b>	0
<b>PidTagSubject</b>	Anne's Birthday

### 3.2 Schedule for the Week of June 16, 2008

In this example, Elizabeth's primary calendar contains her schedule for the work-week of June 16, 2008.

The following table lists the properties on the Calendar object for Elizabeth's lunch break.

Property name	Value
<b>PidLidAllowExternalCheck</b>	TRUE
<b>PidLidAppointmentCounterProposal</b>	FALSE
<b>PidLidAppointmentDuration</b>	30
<b>PidLidAppointmentEndWhole</b>	07:00:00.000 PM 6/16/2008
<b>PidLidAppointmentNotAllowPropose</b>	FALSE
<b>PidLidAppointmentRecur</b>	cb: 80 lpb: 043004300B2001000000C02100000100000000000003E00000022200000050000000000000000000000000000080F8C50C000FC60C0630000009300000B2020000D00200000000000000000

Property name	Value
	000000
PidLidAppointmentSequence	0
PidLidAppointmentStartWhole	06:30:00.000 PM 6/16/2008
PidLidAppointmentStateFlags	0
PidLidAppointmentSubType	FALSE
PidLidAutoStartCheck	FALSE
PidLidBusyStatus	1
PidLidCleanGlobalObjectId	cb: 56 lpb: 040000008200E00074C5B7101A82E00800000000C0FE0C40B268C801000000000000000010000 000DD26B2AEDF5D2145BCE907145185EA4D
PidLidCollaborateDoc	
PidLidConflictingType	0
PidLidDirectory	
PidLidInvited	FALSE
PidLidGlobalObjectId	cb: 56 lpb: 040000008200E00074C5B7101A82E00800000000C0FE0C40B268C801000000000000000010000 000DD26B2AEDF5D2145BCE907145185EA4D
PidLidIntendedBusyStatus	4294967295
PidLidLo	

Property name	Value
<b>cation</b>	
<b>PidLidNetShowUrl</b>	
<b>PidLidOnlinePassword</b>	
<b>PidLidOrganizerAlias</b>	
<b>PidLidReminderDelta</b>	15
<b>PidLidReminderSet</b>	FALSE
<b>PidLidReminderSignalTime</b>	06:15:00.000 PM 6/16/2008
<b>PidLidReminderTime</b>	06:30:00.000 PM 6/16/2008
<b>PidLidResponseStatus</b>	0
<b>PidLidTimeZoneDescription</b>	(GMT-08:00) Pacific Time (US & Canada)
<b>PidLidTimeZoneStruct</b>	cb: 48 lpb: E001000000000000C4FFFFFF00000000B0000000100020000000000000000000000000030000000 20002000000000000000
<b>PidTagBody</b>	
<b>PidTagCreationTime</b>	07:19:19.224 PM 2/6/2008
<b>PidTagImportance</b>	1
<b>PidTagLastModificationTime</b>	07:30:58.552 PM 2/6/2008

Property name	Value
me	
PidTagMessageClass	IPM.Appointment
PidTagMessageLocalId	1033
PidTagReplyRequested	TRUE
PidTagResponseRequested	TRUE
PidTagRtfCompressed	cb: 5468 lpb: 58150000DC5900004C5A4675BA50E15507000601010B606E6731303266350064007263700DD0 0E0032050C60630D446633313530423700F5737473680570627463680FD23610840900110B683 30EB0111A62690FD70DA43333891426666514A374686507809F146715D71560014015D763730 1E8F302A413B064690336020011000AC00873657402D170727132A500002A0AA16E6F1A50200 DF0D51BA13614B0300FF0341C2101D0991C10347D076D02833334191F1F1A2400501AAF20EF2 1107D4361F706D0072105D06115D01DE410101E66FF03E319FF1B0B01301C721BB21C501C10F 326A122216C6922611DE40FE1190FFF246F1B2F1C3F1D4E0FE11FC1287F298FFF2A9F2BAF2CBE 0F202DD2EEF2FF73102FF30C430A22704225327B714D0334F345FFF2FFF310F321F1E4F392F3A 3F3B4F3C5FFF0FF00E103DAF3EBF3FCF40DF41EF1160FF237F442F259F26AF27B72358439F4A1F 3745BF46CF1DE4394D6F4E7432338A384EE420076D20434502833F50A052AF53B53D72546F55 737972B755D4332F1F56361FC5584F4709D17E6B55D4381F5AF759E15BBF038254EF087055D43 D8F1F563723515F8F0382D8284865226007D02955D442FFFF6277543F6416071001A00EB064F5 48685D1EED384861673F0382420740747F0EB055D44D5F5AF75DB16B3F644356590890746E22 4007906564F530FF5298490C5418274555A70DE071AF575E7F73B759660EF074DF5B0E73B65D0 931FF5DB878AE5F5673B660D75B607B7F6A8EFF73B66C890FD267016D7F53DF54EF27D5DF529 F75DF845F59650FD1312DBF791FFF5C0F5D1789A259EF7C7F5DF60E589A2FF5DBF627F6F6F64 9A89A2616F667F93EFF689A89A2656F7FBF6B8F815B7E996DEF7F9BDF700F9558823F834F882F 856731EF860F871FA4CF89383289EF8AFF8C0FFD8D1A328DEF8EFF900F9118A420AE6FF792EF9 3FF950C3295FF970FB45F992DDF0E01B68F9B5F9C6F8179329E3F9F4F7FB88FA16FAA21A2AFA3 BF2236855832FFA67FA78FC53789380FD0C67F792F2245BD8D0B33AE5FAF6F2236910933BA9FF FBBAF2236814CA432D0DFA3EFA4FFC955FFC66FC77FD65F893874A0D81FAB7FAC8FFF8D2959D FCE4FDDFF91095DAFB33FE1FFFF94EE615FB76FE5DF991E655FD1AFEAF0FFF814C695FBFAFEE3F C1CFDBA2D43FD54FFBDA2F856734D80FD91FF6CF893889C0FFF88FDD0FDE1F8D290F11FC7FE1 1FE22FFFBC7E3CFE4DFF25F94FDDBC0044FE91F7FEA2F993CFC30087FED4FEE5F816A35FFF03F F14F0A8FF36FFC21F4AFF5BFFA9FFD856735F87FF98F173F8938FDE2191FFFFD9FFFAF8D4701E2 1CFF019F02AF1C46EF043F054F12CF94FD36086F097F26CFBD992D360C9F0DAF0EBF815B3610A FFF11BF2AFF13DF1C9111518723F734F1C37EF719F19FF76EE4D11371CC878AF79BFFD8D293778 0F21DF7D8E3BF22D087F4FFF805F816A2A62314F165F176F3BC518EFF739EF48CF8938381CCF3 D4F1EEF8D1ADE3820CF40CF22EF91183824AF25BF7B333F94FD3828DF29EF585F992D38FF2D0F 442F2F2F815B60225ECF325F336F0370A881B1636F6C6F727450626C3B5C8D106474C0678D8D 116E74C06730756530675FFA65BA8035688A69A1695F6A6968747F6A9268FF6CCF6C8D6C0F6A3 F688F65FD8DD038725A7371732F743968747462BF72CF769F765D75DF740F77D4395250FF7B24 7C8174A37C80725F6B0776BF7500A181B12A5C64654F517063112B85C244B173AE4020808670 61F98121716C6310455067A0CFA067A0A13CE06463746C82907283902599307080D161759D60 5C611E73829083F03D5084F26E756D2589806184B0746F84F0646AC8757374CFA0676884E0CFA 0A7680145506801697482A0308200305C6E6F7144D15D306F744C65208D7086B0796C5CB068F D8D20748D7082EF83FF850F861F872F4F7DC08AF04F604F4173316310615F815357D0901081D1 8C006C4F2067FC3130BA808A118DD08F848F218159DB8A20911333563091026674D09372CE63

Property name	Value
	786062E093136E7093699504416310736E6578748F2173B7887067005D4074963144E0696700F D87D07996A289403D7062E091409140FF6020DBD05CD09702674080838FC18F21778D8062F09 D707688F08920A1E06D3C696862E080D05D608920756EBD9B41658DB0678097598FE0448BA4 3420503D6061786082A06820D0466F6E748074748FD04E505B9F004EF07794A08DD0669F0057 F162E074684256308DD082909A60966C98C1A08572A108666CA0762B9FE0A27762A27772A072 6362FF82903DA0A4628281A4D267308740679113A59489407065A071736365BC6C6C8AB1A040 9FE1A5F1739AB0BF6710BDC19EF1B580A190A8566CA865CE62A8658B30A8746467A956AAD0F7 AA568F90A8747682CF8AEF8BFF8D0FFF8E1F8F2F903F914F925F936F947F958FFF3DA0B2B19AFF 9C0896E6993464B0EB40FF89609997B4419A58B22CB1F1B47AAEA0ED66C06657B0963162AEE0 67809E70EF9A12B9BF9C08984432E7E0C65060107C2048A681A9408740CCA399D336FFBD4FBE 5FBF6BC390C05FC16FC27FC381FF9E60A7109F806780C3BFC022C50FB29FFF4510B46FB576A52 096A2C81FC926978A3DC3D1739E70BC21892066D06D70166FF3E0CA4F455D40696C53DF8942 57B0668380B0DF107667218900E655C4208850776ED6969871D7325FD853C335D85398A6DF61 6D972168AE50AE00DAA39E62335A606DE7108C6B428742DBE5537562DC51D27399616C46EB3 063DC5162F047AEF09D414E506D6C4D3D6067CDDC3372DEB780D14A63DE71AE227E49A5D06 7F03DA0E7E0DC51874074CE4C5C90DC5166107279E191DA62F580B078DE906E090D742E2B4 B2B0C1B0E074703A2F2FA6E08990E95D40732EC8F0634EF0D3D09FE02A2ED4512FE53066EB60 652FF2776700642F3A50B640E613DE90ED66905C8291A8007774E0C33067A0FDE753685A32DC 51DEC1A0F0E113DEC1AFA1A0E936E0F5DEC162E10367B010FD88E0728761B0A0F3E0ADB06310 AD818F9F80ADB0A9419FE06E626AAED0B367F09A4066F639FB1DDB06B88C0FF9ABOCE40EDD49 6F40FE0B3F180C09E70C788D1DBE0678073797396F0E0E1E97DC16C799E07076E9067A0EF88A 98781676497306167A266EDA1F7D710E0D1A7A1764541F2719670DE90774E5089809F8070B3D 0A6F0F4906CBFA030967287C0B7C06700C8E1786780CF66D09E80E0D167A073619AB08740FFF 3B3E2C1F6D1F491E2C1A8004EF03D709B4E50885078B3D0E3F06F7967F0FA5C9670708980671 04F308850AEA177A940AEF0EDC0649E806730E2F062FE64A9D08850AEF1A6F096F1BFD196F293 8980B050655CF490727AEDA2EFAAD0E8D28740FD7168FBB36010F171FC6776FE49FD01B0C087 408171FEC2BFFFC4FF73F482EF91FEE101536AF9A1CB4F20B770763450776BA5C15E907F02B2A 6E04540B6D1E7F1EAE0ABE265BFB050041596F088D09761F10074D7D0FF8740FCE0ED0105A7B 0E05D40B010AEF0FF8841E2E0B0E0B0516721BFC014500FD0FFD150E2E0B3B1FAF2A5C1ACF00 5B003A1FFADB067309F9105A167216710AB81E2E0BFBDF1FC21FCE08850DBF1AE20700812FF9 65082A0B020B7428740A6F2B3B1CB813FE5D0A700C941F040A700AE117070F79BD0ADB0AED1 694F200B3728106721FF9832AEA03D10885078609F80B002E5D0FFAEC09C31F5D1DD30894096 F14550B090FB8841A5C16EDBE19F0014B0A7000B21E7A700D71088416378AEF087E0BC71FF87 C0A5D0FA81CBA01401F9718850B2E0FE63E2F10812B2E013F3B0108740A9506E6815630572E40 067ADE2EFD163FFF3B007536720DC001622633009F21872C1F3B0747862785C0B50B7D0BF3D7 09660AEC003A0E461F6516C08A1FF6310FA312C40D4619732B6C0969080927277F2D1666D19A 0D600EB8120FFC33081808832B6C0973023F03D90F9E0EF88D0ADC074D087C06C96F05D4003A 0FB09B0E2E0758800CF62ADE19631EC11FF9C61EBD58772967067A0ED719BE0A800FFFCE0217 3AE7420808920ED03890180B0F3AF90EC016C76F451AF91E4F0AFC0FF24F187E067102572A5C1 E0D13FA0E7F13F9BE0B3E18901AF901A7087E020EFFF6A424F652502592CF7125FF270F281FF F25505630AF9080D0EDC029EF2AFF2C0F7E6C5A60AF90CDE029AF2E7F2F8529DF286C5E902D4 F323F2F65625D703BB1FF336F252344B0310F35DF36EF37FF2541FF57D0395225DF3ABF3BCF33 DD5C00395FFF3EEF3FFF410F25414A703DEF438F449FFF45A5E741A8A0E740B3D08740CF53ADE 2FFACCFADDAEEFAFFFB10E4A925381C318FFCDBFB32FB43FB54FB65FB76F95A85E20FF523F53 40546CD0F114F19F60D90963B2F9C2FA0D0A4A928204F911F35289431D4C0073F04061E06580 783236FF3DC05F1166F0EE10678080D187615F21FFC8E780D11FD05F119BD8619696E56076F39 78680D13939DA805FE79670A6F0FF0C204BF160DAC68261FA66F4BB6552C1FF63F966F4601488 109935661F672F683F9D97A43969BB0482EF6120316AE37F6D3F6E4F6F577DA1701F712F6F2A3 3F7730F741F6F0C34761F772F6F0C7EF1F7794F7A5F6F2A367C3F7D4F6F0CD680777F5F806F6F1 B38825F836F6F0C39DB6AE3978633870C4F30636FD588CFFF89D872F48ADF89D876048CEFF89D 87914FF8EFF89D87C24910F89D87F34931F89D8FF8244952F89D88554973F89D8886485BFFF99 83545269E803A00C209960D7E06AFFDF6C0F9B3F9964D1C269D95450C0BC81CFA0EB69BBDE4 14DA220505131F2D0FDB1D068CB41E1709E0F9F1FA02FA136FFA3BCDCE15F50A2B6A64FA75FA 86FD4F0EFCF33A9E94FB0F67067AB0FAC1FAD2FDFAE3669ACD5D04E41D9C073AFFFB10FCD63F 935870CBC5320475761B503DBB14E6A0650F4D61E3154F561B50FFF9B97FB21FA34F6A44AA70F BC1EF61BC3FFBBD4F63F93669ACE1904FE1AA70FCB1FFC12FC23FC34DA3BCC514E1904FA0C5E FFFC6FFC37AAEBCC514B927CA9FCBAFC3C5EB590069CA4D1BA0694EC0C5666FD5F7CEFFD00FC 3C534D19FD2A972F4D3BFFFD4CFC3C59CBBCD265CA02D34FD91FC35CFE36DB1FDC26D81FDD8

Property name	Value
	<p>FC36B5A62DFDFFFC62DC9FE23FC35C5201E45FE564E13FFFE6DFC36B870CE50A7604EABFEBC  F9964EA3769AC4451506BC9FFEFBFFOCFEDA3BC430790FC10664DB0C56FF3DFF4EFF1A1CD2  CF707F30FF8DFF0DED18C3FF707CE6FFD6FC33CD3FC5572041FE63BB600910E5BF021FC7EF04  3FDC53FF05CF06DF07EFCFFCE080AAF0BBF0CCFFFD14FD25F0F9F10AF11BFD60FD71F14EF7F1  5FF170FDACFDBDC1A3CB9BFA42552FC6576DC609DDF1BAFBE2F9929185C7FDC53A517223F23  4F245FAE36870C51FC756F5E6027AF28BF29CF995669ACFE495E80617034602C2F2D3F1C8FDF8  FFFE0991A3F326F337FE3EFE4FC367F378FFF389FE87FE98C3B9F3CAF3DBFED0FEE1CFF40BF41C  F42DFF19FF2A845DF46EF47FFFF5EFF6FF4ABF4BCF4CDFFAAFFBBC500FFF511F522FFF3F004C5  52F563F574F03CFFF04DF5A73EA5F5BDF085F096F54F95FEFFF60FF0D4F0E5F5A1964DF65EF123  F446FFF145F69CF6ADF178F6CFF19AF6F1F702FFF1CDF724F1EFC746F757F33FF779F361CFF798F  7A9F391F7CBF3B3C7EAF7FBF3E3FFF81DF405C83CF84DF435F86FF457C88EFFF89FF487F498F64  3F8E7F8F8F4DCF4EDFFF5F4F935F946F531F542F97CF98DF99EFFF586F597F9D1F9E2F8ACF5DBF  5ECFEEDFFFA37F61FFA59F54EAA79FA8AF66FF680FFF5A19AC8FAD9F6BEF8C1F6E0FB17FB28FFF  713FB4AF735FB6CFB7DF768FB9FF1EFCFFBC1FBD2F7BAFBF4F361CC13FC24F80CFFFC46F3B3CC  65FC76F85EFC98F405CCB7FFCC8F8B0FCEAF457CD09FD1AF902F913FFFABEFD62FD73F957F96  8FA6FFDB0FDC1FFF9ACF9BDFDF7FE08FE19FA01FA12FE4CFCFE5DFD27FA56FA67F2034EA3FEB4  FFFA9CFAADF5508EF4FF05FAEAFABF5A19FFF43FF54FB39FD3CFB5BFF92FFA3FB8EFFFFC5FBB0  FFE7FFF8FBE3F01AF1EFC03CFFF04DFC35F06FF361C08EF09FFC87F0C1FFF3B3C0E0F0F1FCD9F1  13F405C132F143FFFD2BF165F457C184F195FD7DFD8EFFF39FFF1DDF1EEFDD2FDE3FEEAF22BF23  CFE27FFFE38F272F283F294FE7CFE8DF2C7F2D8FE71A2FED1FEE2F203531EF32FFF17FFF28F55  0836FF380FF65FF76F5A193BEFFF3CFFB4F1B7FFD6F40DF41EF009F440FF02BF462F473F05EF4  95F78AC4B7F4C8FFF0B0F4EAF7DCC509F51AF102F53CF82ECFF55BF56CF154F58EF880C5ADF5B  EF1A6FFF5E0F8D2C5FFF610F1F8F209F3B4F658FFF669F24DF25EF365F6A6F6B7F2A2F2B3FFF6E  DF6FEF70FF2F7F308F742F753F61DFF334CF35DF2036799F7AAF392F3A3FFF9CB87EAF7FBF3E0F  3F1FA1C9839F84AFF42FF632F451F888F899F484F8BBF4A6FFF8DDF8EEF4D9F910FC05C932F94  3F52BFFF965FC57C984F995F57DF9B7FCA9C9D6FFF9E7F5CFFA09FCFBCA28FA39F621FA5BFFFD  4DCA7AFA8BF673F684F82FFAD3FAE4FFF6C8F6D9F7E0FB21FB32F71DF72EFB68F7FB79FB8AF77  2F783FBBDFBCEFA986716266C0106D6174B4947BE63101AA9C537562746C6520E8456D70FD70  730D30C14FC25FEBC36F7BF532B49C49E9F0E9E0BDE06FC63FC74FC85FC3EE33B49CC5D552F0  65666572E9E0E9D0CC5FCD6FFFCE7FCF86868CCB56D15FD26FD37FD48FD18B7C426F6F216054  7C30C61087D783CF77A05C4269626C7C00E8677261CBF079D783D9DFCFB381AA9C544F43204  865FD83003B7D7D7B5C2A5C641BC3E0CC1074C010CBB0303130B43530E3C232E3C3E38038E4  24043464BEF037383664360263D5803265353334310C3538E620E50034633532BF9600818090B  09600B9D0E5C033E6A03FE770E424E82E7C60E3C1873063668031316530613162E9C0DC6165E  390EA8FEB7C33E9E0EC61C3E3C0D71066663039E906EDDFFFE461EEADEE8DED02F122EE06F10  EF187FFF38FF49FF5AFF6BFF7CFF8DFF9EFAFFFFC0FFD1FFE2FFF3F004F015F026F037FFF048F0  59F06AF07BF08CF09DF0AEF0BFFFF0D0F0E1F0F2F103F114F125F136F147FFF158F169F17AF18BF  19CF1ADF1BEF1CFFFF1E0F1F1F202F213F224F235F246F257FF268F279F288C642885F1152A7F  2B8FFF2C9F2DAF2EBF2FCF30DF31EF32FF340FFF351F362F373F384F395F3A6F3B7F3C8FFF3D9F  3EAF3FBF40CF41DF42EF43FF450FFF461F472F483F494F4A5F4B6F4C7F4D8FFF4E9F4FAF50BF51  CF52DF53EF54FF560FFF571F582F593F5A4F5B5F5C6F5D7F5E8FFF5F9F60AF61BF62CF63DF64EF  65FF670F3F681FF123E6A0E911F17169C23734F5E3F434E3B136EC916A42B9D06A21FFED526C0  F6D1F6E2F6F3F704FE461E93217E3B1687F29A663AA80643938B573E062740033E671E63039E2  10EA66E58064E61162E9E0F27F75F6B663EC71E7C034D700E6D0387470FFE380F20F790F7A1F7  B2F7C3F7D4F7E5FFF7F6F807FF31F827C80FF848F859F86AFF87BF88CF89DF8AEF8BFF8D0F8E1  F8F2FFF903F815F925F837F947F958F969F97AFF98BF99CF9ADF9BEF9CFF9E0F9F1FA02FFF914F  A24F936FA46FA57FA68FA79FEFCE17E3B4A885E28000AAB0</p>
<b>PidTagS enderAd dressTyp e</b>	SMTP
<b>PidTagS enderEm ailAddre ss</b>	eandersen@contoso.com

Property name	Value
<b>PidTagSenderEntryId</b>	cb: 70 lpb: 00000000812B1FA4BEA310199D6E00DD010F54020000000456C697A616265746820416E64657273656E00534D54500065616E64657273656E40636F6E746F736F2E636F6D00
<b>PidTagSenderName</b>	Elizabeth Andersen
<b>PidTagSensitivity</b>	0
<b>PidTagSubject</b>	Lunch

The following table lists the properties on the Calendar object for Elizabeth's doctor appointment.

Property name	Value
<b>PidLidAllowExternalCheck</b>	TRUE
<b>PidLidAppointmentCounterProposal</b>	FALSE
<b>PidLidAppointmentDuration</b>	60
<b>PidLidAppointmentEndWhole</b>	04:00:00.000 PM 6/16/2008
<b>PidLidAppointmentNotAllowPropose</b>	FALSE
<b>PidLidAppointmentSequence</b>	0
<b>PidLidAppointmentStartWhole</b>	03:00:00.000 PM 6/16/2008
<b>PidLidAp</b>	0



Property name	Value
<b>pointmentStateFlags</b>	
<b>PidLidAppointmentSubType</b>	FALSE
<b>PidLidAutoFillLocation</b>	FALSE
<b>PidLidBusyStatus</b>	3
<b>PidLidCalendarGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E00800000000E0E7F7AAB268C801000000000000000010000000D3BDD3F67FDD814E823B9EE04A816204
<b>PidLidCollaborateDoc</b>	
<b>PidLidConferencingType</b>	0
<b>PidLidDirectory</b>	
<b>PidLidInvited</b>	FALSE
<b>PidLidGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E00800000000E0E7F7AAB268C801000000000000000010000000D3BDD3F67FDD814E823B9EE04A816204
<b>PidLidIntendedBusyStatus</b>	4294967295
<b>PidLidLocation</b>	4567 Main St., Buffalo, NY 98052
<b>PidLidNetShowUrl</b>	
<b>PidLidOnlinePassword</b>	
<b>PidLidOrganizerAlias</b>	

Property name	Value
<b>PidLidReminderDelta</b>	720
<b>PidLidReminderSet</b>	TRUE
<b>PidLidReminderSignalTime</b>	03:00:00.000 AM 6/16/2008
<b>PidLidReminderTime</b>	03:00:00.000 PM 6/16/2008
<b>PidLidResponseStatus</b>	0
<b>PidLidTimeZoneDescription</b>	(GMT-08:00) Pacific Time (US & Canada)
<b>PidTagBody</b>	
<b>PidTagCreationTime</b>	07:20:46.387 PM 2/6/2008
<b>PidTagImportance</b>	2
<b>PidTagLastModificationTime</b>	09:40:42.099 PM 2/6/2008
<b>PidTagMessageClass</b>	IPM.Appointment
<b>PidTagMessageLocalId</b>	1033
<b>PidTagReplyRequested</b>	TRUE
<b>PidTagResponseRequested</b>	TRUE

Property name	Value
<b>PidTagRt fCompressed</b>	cb: 5515 lpb: 87150000F65A00004C5A4675A691184207000601010B606E6731303266350064007263700DD0 0E0032050C60630D446633313530423700F5737473680570627463680FD23610840900110B683 30EB0111A62690FD70DA43333891426666514A374686507809F146715D71560014015D763730 1E8F302A413B064690336020011000AC00873657402D170727132A500002A0AA16E6F1A50200 DF0D51BA13614B0300FF0341C2101D0991C10347D076D02833334191F8F1A2F1B3620EF21107 D436106D0FB072105D06115D01DE410101E6603E3FF1F3F1B0B01301C721BB21C501C1026A1F 922216C6922611DE40FE1190F246FFF1B2F1C3F1D4E0FE10050286F297F2A8FFF2B9F2CAF0F202 DDF2EEF2FF7310230C4FF30A22704225327B714D0334F345F2FFFFF310F321F1E4F392F3A3F3B4 F3C5F0FF0FF0E103DAF3EBF3FCF40DF41EF1160237FFF442F259F26AF27B72358439F4A1F45BF1 B46CF1DE4394D6F4E74323338C54EE420076D204345028350A09F52AF53B53D72546F5573797 255D473332F4E6531362DB1580F038247FD09D16B55D4381F5AF759E15BBF0382DE54087055D 43D8F5AF63723515F8FB10382284865226007D02955D4FF42FF6277543F6416071001A00EB064 F5BB48685A8D384861673F0382420740FE740EB055D44D5F5AF75DB16B3F6443B2560890746E 224007906564F4FF2340529F53AF223A55A65420563F574FFF73BC5965542059EF5AFF73BB5D0 85420FF5DBF5ECF73BB60D65420696F6A7F73BBFD6C8A307198490C731A276355A70DE0FF83B F763F85D659660EF086EF79CF85D5FD5D09317C588ABE7DF885E460D75B60FF8D8F810F85D56 C890FD26701801F53DF7F54EF27D5719F87EF966F78160FE031FF2DBF8B2F5C0F7BA89BC178AF 8E8F5DFDFF7F569BC17C5F627F6F649A9BB2616FFF667FA5FF689A9BB2656F91CF6B8F936BFF 90A96DEFADEF700FA768944F955F9A3FB9D977731981F992FB6DF9B48329BFFF79D0F9E1F9F2A3 29FFFA10FA21FA328DFB630C07FA4FFA60FA71C32A80FA91F7FC66FAB3D0E01C89FAD6FAE7F93 8932FFB04FB15FCA9FB37FBC31B4BFB5CF2236FD976832B88FB99FD7479B480FD088F78B3F 22459F1B33C06FC17F2236A319FE33CCAFCDDBF2236935CB642E2EFB5FFFFB70FDB65D87FD98F E86F9B4886B0EA2FFFBD8FBE9F9F3959DFE05FF00FA3195DAFFFC54FF40FA6FE615FC97FF7EFAB 2E655FFFE3BFFC1F935C695FD1BF004FD3DFEDB2EFE64FE75FEC3F977734EA1FEB2F08DFFF9B4 89BD00A9FEF1FF02F9F39BC400E7FFF31FF42F0DC8F5DFF6EF046FA70DEDD0FF165FFB2FFC3F AB4C0E401A8FFF5F006FFD937A35024F035F1C9F057F0E3106BFF707CF0CAF9777350A8F0B9F2 94F9B48FF0FF22B2F0FAF10BF9F5713F22F0F13AFBF14BF2E56164F175F24DFA70D361A7FF71B8 F38DFAB3D361EAF1FBF20CF936BFE3622BF23CF3D0F25EF2EA12728844FBF855F2E4783AF2C0F 88FE9401372ED8F78ABF8BCF9F39378A1F33EF8F9E4E02FF3F18915F926F937A3C72435F286F29 7FDF4DD52AFF4BFF5ADF9B48382EDF4F5FFF30FF9F2A789F52CF627FA3197C4F37BF7B667FA6F E383AEF3BFF6A6FAB3D38FF3F1F563F413F936B7FDF442F2BF464C0193C1636F6C6F727462A8 6C3B5C9F206486D0679F21466E86D07940756530796F65FDCC90357A9A7BB17B6F7C797A847C A2BF7B0F7EDF7E9D7E1F7C4F7A9F659FE0FE38846A8581853F86497A84867284DFDF88AF886D8 7EF861F89E43964608D34FF8E9186B38E90846F7D1788CF871093C1D02A5C6465616170752197 D29556C173C05020929670619331FC716C7520576079B0E1B079B04EF0D06463746C94A07295 A0AB40127092E16175AF705C61738F94A096004F6097026E756D9B90126196C0746F9700646A7 5E47374E1B0676896F0E1B07A115357607A11697494B03094105C186E6F7156E16F406F7465A6 209F8098C0796C6EC0689F30FE749F8094FF960F971F982F993F8FD0A79D00617061517331752 06193632F69E0A22093E19E106C61306731FE30CC909C219FE0A194A13193699C306DA323336 840A3126686E0A58263E78A7074F0A5236E70A579A7147520A0736E657874A131739A80DB791 06F5074A84156F069791099E0FE79A8B29B504F8074F0A350A3507230FFEDE06EE0A912795092 93A1D1A1319F903B7500AF80769B009B30B3F06D699E6874F092E06F709B30756EAD515E659F C07990A969A1F0449DB4201A504F70618A7094B0682046E86F6E74928474A1E06060B110AD61 0077A6B09FE066B1105774F07874684268409FE09A0AC706CCBAAD1B29572B318666CB286B1 F095B48762B48772B282636294A0FF4FB0B6729491B6E27940995079A1B7A4099B507065B2817 363656CDE6C9CC1B250B1F1B80173ACC079205FCFD1B101C790B3A0BA666CBA7562E7BA759D 40BA846467BB66BCE0BC66FBA1A0BA847694DF9CFF9E0F9F1FA02FFFA13FA24FA35FA46FA57FA 68FA79F4FB0FFC4C1AD0FAE18A8F6AB4476C0FD509B70FFABA7C651AC68C43CC401C68AC0B07 8D0F66669C0A84162C0F07990B080AC226FCBCFAE18AA544C60384C709A2048DFB891BB50995 0DEB3ABE336CF5FD06FFDD17B38D25FD36FD47FD581B070B920FFB1907990D5BFD232D70FC4 AF76B0C67F7FC786B730A8B2DA1FDB26A99AD5D1738FB080CE319B3078E06D706F05F0C5D4B E456F50696C539B5269C0B7789392C0F1207679319B1055D620F99A60776EE8766AA81E912EA3 3D54497EA33AAB6ED716DA9316850C0102BEC738072336C706DF9206B42A39952EDB5537562 EE2173AB71F46C46FD4063EE217500C100AF515160606D6C4D4F7067EE0372B3F08792E14A63 F041C03249B7E09F7A004FB0F9F0EE219950744C6EA073EE2105B07279F361EC3292C0787DF06 06EC2A0E922F484C4C0C2F07470703A2F2FB8F09BA06F5073BA2EDAF0636100E5C0B1F02EE64 18A2FF70066FD70652F7779107C642F4C60C850F7E3F06078A05C6B94A1BA107786F032EB51F9

Property name	Value
	<p>2368FF6C42EE21F091B300F2E3F091B3B0FB066BF2C5F09162F2D367C2209AF072FF9971C2B005F0BFC07520BF91B190BFC0E3BB51B1F06E626AC0E07A00AC70EC6F63B1C1EF806B9AD0ACC0E030FFFA4A90421F0C60192D0B0809AE1EDB0717990737973A900F2B18FD16C7A79B08076F06079B00188999167EA64A9406179B266FF71E8F0F2A1FDB9B17657510441A880F06060609B90DB19070C5E0B90006606CB240A882EF99D0C9D07910DAE178799078E0B090F3F2A179B07361ACC099500583F491FF08A10661F491BA1061004F8060609A60A678C5E0F5C06F797A005CA880FE709B90792061409A60C0B1BB50C1009DFF9064B0907940F4C06264BBE0FF9A60C101B900A901D1E1A9029B90C260E4655C0660727AFF72BCE0FAA23B99500F41680D83722003416776FF10190ED1C2D099509381109211941143EF0652016110B113236A0B716130C980F2764660776BB7D170A01482B8F0DF5750C8E1F9C1FCB0BDF265C26015E5EFA9009AE0A97102D074E9B099500EB0FFFED11777C2F06F50C220C1009A51F4B0FFC2F0C2617931D1D0266021E0E340F4B0FFC5C10CC2B7D1BF0017801571BFC07940FFB1A1177179317920BD91F4B0EDC10DF1EF0EB09A60EDC1C0307019E2A86094B0FFC230C9529950B902C5C1DD71F7A0B910CFDB410210B910C0217070ADE0BFC0FDC0E16961301D073A207931AA42C0B0FF4F209A608A70B190C212F7A0C0D0AE41FF07A1EF009B50A9015760C2A09A51B7D1FE6EEDB1B11026C0B9101CF1B910E8F0F99A516378C10099F0CE8199D0B7E0BF0C51DD9025D10B419A60C4F063F4C1BF19E2C4F025C3C2209950BB60682733DB1742F5D067BFF201A163058019237F7930EDD027F275401BC22A42058074F07862785C1D20C9E04F80A870EFCDD01570F63108216C1A7175200C01BF3E50E651A942C8D0A8A092A27704A1DC666D2B70E7E0FD5120F9A09390FF9A42C8D0A94036004FA00BB09AE0BFD0FB86E099D06CA9006F5015701B80F4B0FE759A10E152BFF1A841FDE1AE71FDA5FF9982A88079B0FF41ADF0BA100EB03343FFC08432509B30FED39B1192C0C1A0FDD1FC6C760621C1A1F6C0C1D036C199F0FF79203742B7D1F2A151B0F9C1ADF0C5F1CF9B11C1A02C4099F0202EE88436C6FF64603762E16137CF38DF39EF37206840BFC1A092E0FF903BBF3CCF3DDDF6C6C70DFC1A0DFD03B7F404F4155293A3C70A0F73F1F440F4135626F804DC1453F36F3FF56C042DF47AF48BF49CF371169E04B22FF37AF4C8F4D9F45AD6E104B2F50BF51CFFF52DF37115C804FBF555F566F5775F911FFBAB0F910C5E09950E143BFF2BEDFBFEFFFC0FFC20FC31E5C626591D527DFAF53FFFC64FC75FC86FC97FA7B86C0063FF65007F662CE2E126C1B170EAE875C2D5090D7E0A5C6294140AE105229B535DD073C7021073F077907832364F9070B1FF7900FFE0799092E1997170C1DAE792E1FF31A070B1ADE87336A8F57216A99692E1FC3939EC507187A880B9001DF05DC1FF727AD882739A7894CD756481759978947F71B49A20AB4577BF78CF79DFA9B439E77B5B1652013120317C837EDF7FEFDF80F78FB181BF82CF80CA3384AF85BFFD80AC3487BF88CF80AC91018AEF8BFFFD80CA368DDF8EEF80ACE86090FF920FDD80BB3893FF950F80AC397C83A996F63398AC61006381759A6F9B788494FF9C7F9B7887A49E8F9B788AB4A09F9B78FF8DC4A2AF9B7890D4A4BF9B7893E4A6CFFF9B7896F4A8DF9B789A04975FAB236612FF7B8815701DF0AB00E9C07C9F7DAFACDF7AB04E3B27B79546290CE91B28B7B5B73F0115F722050630104A0C3E068FFDD31F340AFAB0BFB1CFB2D6B55CEEB1FF70FB456B7EFB8FFBA0FE6E0E123BB89FB618008406D7BCAFBDBFBECFBFD67B4C77E7B06011EB9073C19FC2AF759935F398ACCE6320476921C6A3C2EE7BA6F65006A63001540731C6AFCB1FC3BFFF4EF7BE4BC100D910131CDDFCCEF7599FE367B4CF36061B1BC100E81D2CFD3DFFFD4EDB55CD6B4F3606170D78FD89FD51AFFC05CD6B4CAC7DC3FDD4FD5656AC07B6AFA4D2D70696090D7068175E09FE1AFFDD56534E33FE4498494E55FE66FD565BFAE5CE405DBA2E4EFEABFD4FC36ECBFFFEDC6E9BFEF5FD50B6C22F17FE002EE3FFBF3DFD4FC38F5DFF6E6F2DFF87FD50BBF98ACF6AA87A4FC5FFD6FAB04377B4C7A4463206BDB9F015F026FB55C43FB19600DE0665F80D70F057F068F0341FFDECC08A704AF0A7F027EE32C08A7E00F8F0F0FD4DFDEDFD6F7204163CD00FF1AE0F75F13BFD98F15DFEDF3176F187FFF198FDE9FDFA81C4F1D5F1E6FE2EFE3FFF213F224F235FE7AFE8BF268F279F28AF1FEC6FED7C2BDCCB5FB5C5526576FFEE00AF7F2D4FCFCFAAC929FCEDF3B6B71F33DF34EF35FFBFD698AC51756FBF7000394F3A5F3B6FAAF67B4C497020FF731046303DCF3EDF2E2FF12FF2392BDDFF440F451FF58FF69C481F492F4A3FFA1FFFFB2C4D3F4E4F4F5FFEAFFBFC525F536FFF547F033F0448577F588F599F078F089FFF5C5F5D6F5E7F0C4F0D5C61AF62BF63CFFF10DF11EC66CF67DF68EF156F167F6C13FFFBF6D7F19FF1B0F6699718F729F1EEFFF1FFF6BB9767F778F23DF560F25FF7B6FFF7C7F292F7E9F2B4F80BF81CF2E7F83EFFF309C860F871F459F893F47BC8B2F8C3FFF4ABF8E5F4CDC904F915F4FDF937F51FCFF956F967F54FF989F571C9A8F9B9F5A1FFF5B2F75DFA01FA12F5F6F07F70EFA4FFFA60F64BF65CFA96FAA7FAB8F6A0F6B1FFFAEBFAFCF9C6F6F5F706F007FB51F739FFB73F668AB93FBA4F789F79AF6BB9BE2FFBFB3F7D8F9DBF7FAFC31FC42F82DFC64FFF84FFC86FC97F882FCB9F309CCBFCCECFF8D4FD0EF47BCD2DFD3EF926FD60F4CDCFFD7FFD90F978FDB2F51FCDD1FDE2F9CAFFFE04F571CE23FE34FA1CFA2DFBD8FE7CFFF8DFA71FA82FB89FECAFEDBFAC6FAD7FFFF11FF22FF33FB1BF82CFF66FF77FE41FF3B70FB81F2034FBDFCEFBFB6FBC7FFF66A800EF01FFC04FC15F6BB905DF06EFFFF53FE56FC75F0ACF0BDFCA8F0DFFFCAFFF101F112FCDFD134F309C156F167FD4FFFF189F47BC1A8F1B9FDA1F1DFB4CD</p>

Property name	Value
	C1FAFFF20BFDF3F22DF51FC24CF25DFE45F27FFFF571C29EF2AFFE97FEA8F053F2F7F308FFFECCFEFDF004F345F356FF41FF52F38CFFF39DF3AEFF96FFA7F3E1F3F2F2BCFFEBFF9FFCF2035438F449F031F042F66A8FF489F49AF07FF090F6BB94D8F4E9F0CEFFF2D1F0F0F527F538F123F55AF145F57CFFF58DF178F5AFF8A4C5D1F5E2F1CAF604FFF8F6C623F634F21CF656F948C675F686FFF26EF6A8F99AC6C7F6D8F2C0F6FAF9ECCFF719F72AF312F323F4CEF772F783F367FFF378F47FF7C0F7D1F3BCF3CDF807F818FFF829F411F422F85CF86DF737F466F477FFC20368B3F8C4F4ACF4BDFAE58904FFF915F4FAF50BFB369953F964F549F74CFFF56BF9A2F9B3F59EF9D5F5C0F9F7FA08FFF5F3FA2AFD1FCA4CFA5DF645FA7FFD71CFFA9EFAAFF697FAD1FDC3CAF0FB01F6E9FFFB23FE15CB42FB53F73BFB75FE67CB94FFFBA5F78DF79EF949FBEDFBFEF7E2F7F3FFF8FAFC3BFC4CF837F848FC82FC93FCA4F9F88CF89DFCD7FCE8FBB267166D1B0586D6174C6348D8631BC3C53007562746C6520456DFA700F10731ED0D2EFD3FFD50F8D95FA32C63C49FB90FB80CF80D7DFD8EF1BD9FFD58E33C63CD775526566FC6572FB80FB70DDFFDF0FE01FE1267F982CDCF6E2FFE40FE51FE62F9D1C42F46F6F3300548DD0D7B0E923E11721B1FC4269626C8DA067727A61DD9079E923EB7FE153BC3C54204F432048650F233B7DC07D7B5C2A5C64D580DDB00674D1B0DD5030313035302DF56232F563F52038F5C4346481D090373836643663E720003265353334313538C3F7C0F6A034633532A7A09320EFA250A7A0CB70F76033F840F910F5C40FF9CE8E00F56198D063663131206530613162FB606165F7F530FC2FFD1C33FB80FE01F560E8B0F066663039FAA6FF7FF601004DFF002DFEA202C2FFA602AE0327052F063FFF074F085F096F0A7F0B8F0C9F0DAF0EBFFF0FCF10DF11EF12FF140F151F162F173FFF184F195F1A6F1B7F1C8F1D9F1EAF1FBFFF20CF21DF22EF23FF250F261F272F283FFF294F2A5F2B6F2C7F2D8F2E9F2FAF30BFFF31CF32DF33EF34FF360F371F382F393FFD3A2C643A2502B53C1F3D2F3E3F3F4FFF405F416F427F438F449F45AF46BF47CFFF48DF49EF4AFF4C0F4D1F4E2F4F3F504FFF515F526F537F548F559F56AF57BF58CFFF59DF5AEF5BFF5D0F5E1F5F2F603F614FFF625F636F647F658F669F67AF68BF69CFFF6ADF6BEF6CFF6E0F6F1F702F713F724FFF735F746F757F768F779F78AF79BF02C34FF840FAB103117B623734F59434FDF55136FE317BE2CB707BC1FEF27DAFFF7EBF7FCF80DF81EFF601FAD2F5517A1F453B4663BC20643938858062AD85A033F811F7D039F3B066F7207A64F7B162FB80041F8796FB8032F1C6206262397B10B7008610F520FF03AF8AAF8BBF8CCF8DDF8EEF8FFF910FFF921F04BF941C929F962F973F984F995FFF9A6F9B7F9C8F9D9F9EAF9FBFA0CFA1DFFF92FFA3FF951FA61FA72FA83FA94FAA5FFFAB6FAC7FAD8FAE9FAFAFB0BFB1CFA2EFFF3EFA50FB60FB71FB82FB93F016EF5540BBA25F42000BC50
<b>PidTagSenderAddressType</b>	SMTP
<b>PidTagSenderEmailAddress</b>	eandersen@contoso.com
<b>PidTagSenderEntryId</b>	cb: 70 lpb: 00000000812B1FA4BEA310199D6E00DD010F54020000000456C697A616265746820416E64657273656E00534D54500065616E64657273656E40636F6E746F736F2E636F6D00
<b>PidTagSenderName</b>	Elizabeth Andersen
<b>PidTagSensitivity</b>	2
<b>PidTagSubject</b>	Doctor's Appointment

The following table lists the properties on the Calendar object for the Fabrikam Project pre-meeting.

Property name	Value
<b>PidLidAllowExternalCheck</b>	TRUE
<b>PidLidAppointmentCounterProposal</b>	FALSE
<b>PidLidAppointmentDuration</b>	30
<b>PidLidAppointmentEndWhole</b>	05:00:00.000 PM 6/18/2008
<b>PidLidAppointmentNotAllowPropose</b>	FALSE
<b>PidLidAppointmentSequence</b>	0
<b>PidLidAppointmentStartWhole</b>	04:30:00.000 PM 6/18/2008
<b>PidLidAppointmentStateFlags</b>	1
<b>PidLidAppointmentSubType</b>	FALSE
<b>PidLidAppointmentSequenceTime</b>	07:30:17.980 PM 2/6/2008
<b>PidLidAttendeeCriticalChange</b>	12:00:00.000 AM 1/1/4501
<b>PidLidAutoFillLoc</b>	FALSE

Property name	Value
<b>ation</b>	
<b>PidLidBusystatus</b>	2
<b>PidLidCleanGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E008000000005019899AB368C801000000000000000010000 0005D7DB73EA4A89A4894F5C022C6CAA58F
<b>PidLidCollaborateDoc</b>	
<b>PidLidConferencingType</b>	0
<b>PidLidDirectory</b>	
<b>PidLidInvited</b>	TRUE
<b>PidLidGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E008000000005019899AB368C801000000000000000010000 0005D7DB73EA4A89A4894F5C022C6CAA58F
<b>PidLidIntendedBusyStatus</b>	4294967295
<b>PidLidLocation</b>	Patrick's Office
<b>PidLidNetShowUrl</b>	
<b>PidLidOnlinePassword</b>	
<b>PidLidOrganizerAlias</b>	
<b>PidLidOwnerCriticalChange</b>	07:30:17.980 PM 2/6/2008
<b>PidLidReminderDelta</b>	15
<b>PidLidReminders</b>	TRUE

Property name	Value
<b>et</b>	
<b>PidLidReminderSignalTime</b>	04:15:00.000 PM 6/18/2008
<b>PidLidReminderTime</b>	04:30:00.000 PM 6/18/2008
<b>PidLidResponseStatus</b>	1
<b>PidLidTimeZoneDescription</b>	(GMT-08:00) Pacific Time (US & Canada)
<b>PidTagBody</b>	Hey Patrick\,\n\nCan we sync up before the upcoming Fabrikam status meeting?\n\nThanks\,\nElizabeth\n
<b>PidTagCreationTime</b>	07:27:11.156 PM 2/6/2008
<b>PidTagImportance</b>	1
<b>PidTagLastModificationTime</b>	07:30:18.762 PM 2/6/2008
<b>PidTagMessageClass</b>	IPM.Appointment
<b>PidTagMessageLocaleId</b>	1033
<b>PidTagOwnerAppointmentId</b>	1246111704
<b>PidTagReplyRequested</b>	TRUE
<b>PidTagResponseRequested</b>	TRUE
<b>PidTagRt</b>	cb: 5666 lpb:



Property name	Value
<b>fCompressed</b>	1E1600004E5D00004C5A46755B24DBD807000601010B606E6731303266350064007263700DD0 0E0032050C60630D446633313530423700F5737473680570627463680FD23610840900110B683 30EB0111A62690FD70DA43333891426666514A374686507809F146715D71560014015D763730 1E8F302A413B064690336020011000AC00873657402D170727132A500002A0AA16E6F1A50200 DF0D51BA13614B0300FF0341C2101D0991C10347D076D02833334191F8F1A2F1B3620EF21107 D436106D0FB072105D06115D01DE410101E6603E3FF1F3F1B0B01301C721BB21C501C1026A1F 922216C6922611DE40FE1190F246FFF1B2F1C3F1D4E0FE10050286F297F2A8FFF2B9F2CAF0F202 DDF2EEF2FF7310230C4FF30A22704225327B714D0334F345F2FFFFF310F321F1E4F392F3A3F3B4 F3C5F0FF0FF0E103DAF3EBF3FCF40DF41EF1160237FFF442F259F26AF27B72358439F4A1F45BF1 F46CF028350A04D6F4E74323338C54EE420076D20434552342DBFCF53A63D72546F557379725 234381FB94E6531365631580F03824709D17E6B52343D8F5AF733215BBF038254EF0870523442 FF5AF63723515F8F0382D8284865226007D02952344868FF620E543F6416071001A00EB064F54 D5F5D5AF6384861673F038242074074FF0EB052346701699F5B2459E16B3F6443B2560890746E 224007906564F4FF5420529F53AF223A55A65420563F574FFF73BC5965542059EF5AFF73BB5D0 85420FF5DBF5ECF73BB60D65420696F6A7F73BBFF6C8A0DE0487F72BF275455A87518844DF77 6A985E559663178A8490C7A2A85E4FD5D09317C588ABE7DF885E460D762E0FF8D8F810F85D56 C890FD26D4F84BF585FFB74950FE139945F575F586F78250FE0FF86C9794F99CF5CAE9BB2332F 8E8F5DFDFF7F569BC178AF627F6F6F649A9BB27C5FFF667FA5FF689A9BB2616F91CF6B8F936BFF 9D70AC4F6E6F6F7F708E9BC1944F955F7B9A3F977731981F992FB6DF9B4832EF9BFF9D0F9E1F9 F2A329FFFA10FA21FBFA328B630C07FA4FFA60FA71C32A80FFFA91FC66FAB3D0E01C89FAD6FAE 7F9389FE32B04FB15FCA9FB37FBC31B4BFB5CFFB2236976832B88FB99FD7479B480FD0EFD88F8 B3F22459F1B33C06FC17F2236FDA31933CAFCDBF2236935CB642E2EFFB5FFB70FDB65D87FD 98FE86F9B48562FF7DCDFEC2F9F1B34DF5FE06FC28FA328FF59DFC54FF40FA6FE5DAFC97FF7EF AB2EFF615FE3BFFC1F935C655FD1BF004FD3DFDFEDB2E64FE75FEC3F977734EA1FEB2FFF08DF9 B489BD00A9FEF1FF02F9F39BC40FF0E7FF31FF42F0DC8F5DFF6EF046FA70DFEDD0165FFB2FFC 3FAB4C0E401A8FFF5FFB006F937A35024F035F1C9F057F0E31EF06BF07CF0CAF9777350A8F0B9F 294FFF9B480FF22B2F0FAF10BF9F5713F22F0F7F13AF14BF2E56164F175F24DFA70D36EF1A7F1B 8F38DFAB3D361EAF1FBF20CFD936B3622BF23CF3D0F25EF2EA127287F844F855F2E472AF8877 F888F9B5737FF86DF2FEF8C3F4DF332D88E1F8F2F4DA8FF3F18915F926F937A3C72435F286F297 FFF4DD52AFF4BFF5ADF9B48750F4F4F5E9FFD9F1B3832DF52DF34FFA328789F37BFBF667FA6FE 7C4F3BEF6A5FAB2E383F1FFF563F413F936B723270DF446F457FB3A80193C1636F6C6F727462A 86C3B5C9F206483A0679F21466E83A07940756530796F65FDCC90357A9A7BB17B6F7C797A847 CA2BF7B0F7EDF7E9D7E1F7C4F7A9F659FE0FE38846A8581853F86497A84867284DFD88AF886 D87EF861F89E43964608D34FF8E9186B38E90846F7D1788CF871093C1D02A5C6465616170752 197D29556C173C05020929670619331FC716C7520576079B0E1B079B04EF0D06463746C9A07 295A0AB40127092E16175AF705C61738F9A096004F6097026E756D9B90126196C0746F970064 6A75E47374E1B0676896F0E1B07A115357607A11697494B03094105C186E6F7156E16F406F746 5A6209F8098C0796C6EC0689F30FE749F8094FF960F971F982F993F8FD0A79D00617061517331 75206193632F69E0A22093E19E106C61306731FE30CC909C219FE0A194A13193699C306DA323 336840A3126686E0A58263E78A7074F0A5236E70A579A7147520A0736E657874A131739A80DB 79106F5074A84156F069791099E0FE79A8B29B504F8074F0A350A3507230FFEDE06EE0A912795 09293A1D1A1319F903B7500AF80769B009B30B3F06D699E6874F092E06F709B30756EAD515E6 59FC07990A969A1F0449DB4201A504F70618A7094B0682046E86F6E74928474A1E06060B110A D610077A6B09FE066B1105774F07874684268409FE094A0AC706CCBAAD1B29572B318666CB28 6B1F0F5B48762B48772B2817940995079A113B6849B507065B281736365BC6C6C9CC1B250B1F 1B6E173ACC0BF7920CFD1B101C790B3A0B9466CB955CE62B9559D40B9646467BA46BBC0F7BB 46A1A0B9647694DF9CF9E0F9F1FFFA02FA13FA24FA35FA46FA57FA68FA79FFF4FB0C3A1AD0FA E18A8F6AB4476C0FD50FF9B70ABA7C531AC68C31CC2E1C56ABF90ED78D06669C0A84162BFD0 7990B0809FAC22CAFAE18AA5693F03430D8507C2048B771BA309950DEB3ABE336F7CE3FCF4F D05B38D13FD24FD35FD463FFB070B800B1907990D4BFD112D60FC38FFF76B0C55FC666D0FOA 8B2D91FDA26A99A3DD4D173B080CD119B3078E06D70266F05F0DB4F20456F50696CBE539B52 69C0789392C0F120767931CD9B1055D5209A60776EE7B6AA81BF852E973AAB6EA05D444ED7 16DA9315C6850BEF0EBD3B072336C706D19F9206B429952ED15537562A5ED8173AB716C46FD 4063ED818F7500BFE0AF5160606D6C4D4F709A67ED6372EFE792E14A63EFA1FDBF1249B6C07A 004FB0F9F0ED8199509C744C6EA0ED8105B07279F2C1EA31929378EFC06EC180E862F3E483C3 A0C1D074703A2F2FB7D0D39BA06F50732ED9F0636100E4E055B1F02EE5612FF66066FD7065E4 2F777910642F4C60C730F743DBEFC078A05C94A1B8F07786F0D451FDF874686C42ED81EFF1B3 00F243EFF1AFB3B0FA66F225EFF162F23367C100FD9AF0729971C19005F0BEA07520BE718FB19

Property name	Value
	0BEA0BA31B1F06E626ABFC0B37A00AC706F63B1C1EEE06B9AD0FFACCD0DF50FF04A90421F0C4E 192D0B080C79AE1ED107990737973A900F211E98FD16C79B08076EFC079B000E8A999916764A 9406179B266FED1F7E830F201B89176575103A1A880EFC07760609B90B19070C4C0B7E005C06 CBFB240A88299D0C8B07910D9E1787990CF78E0B090F20179B07361ACC09950FF04E3F31080 105C1F3F1B8F061004F809B60609A6078C4C0F5206F797A00FA5CA880709B90792061409A60BF 9177BA30BFE0FEF064B0907940F42062FE64BAC09A60BFE1B7E0A901D0C1A902939B90C14065 5C05C0727AFED2EFBBC0FA0299500EA1680CE3722002A1FC67760F790E31C1B0995093810FF2 BF10F410A305B200C1101112836A0AD1CB6130C860764660776BB6B170A07F13E2B7D05750C7 C1F921FC10BCD265BFC1401545A9009AE0A971023074E8F0FF99500E10FE3116D7C1D06F50C1 00BFE0FF9A51F410C1D0C1417931D0B0266021E0FFE260F410C4A10C22B6B1BDE016E014D1FF BEA07940B1A116D179317920BC71F410BFED210D510E109A60ED21BF10701942FFA86094B0C1 10C8329950B7E2C4A1DC913FF700B7F0DA410170B7F0BF017070F7ADE0BEA0BFC16961301C67 3A207931FFAA42BF904F209A608A70B190C0F2F700FFBFB0AE410701EE609B50A9015760C180F B9A51B6B16EED11B11026C0B7F01C51E7B7F0E8309A516378BFE099F0CD61FF99D0B6C00BB1D CB025310AA19A60C3D0FE63F4211942C3D02523C1009950BA406E68269316A2F53067BED2010 163FF04E018837930ED30275275401B2229A2C104E0747862785C1C80C8C0BF4F80A870BFB01 4D0F59107816C19D1FF75200B613E50E571A942C7B0A8A092A272770401666D2AD0E720FCB12 0FFD45093909A42C7B0A94036004FA00B10EF9AE0EBE086E099D06CA9006F5014D0FB1AE0F41 0759A10E072BED1A841FD41FFAE71FD059982A88079B0FEA1ADF0B8F0FF0E1032A3BF6431B09 B30FE339B1192C0F3C080FD316C760581C081F620C0B0FF362199F0792036A2B6B1F20151B0F9 213FADF0C4D19B11C0802BA099F0202EFFE7C43626646036C2E081372F383F394FFF36806840C 08092E0FEF03B1F3C2F3D3F7E6C6C70C080DEF03ADF3FAF40B529DF399C70A03E7F436F409562 6F804A61FF449F365356C0423F470F481F492F3671FF69E04A82370F4BEF4CFF450D6E104A8FFF 501F512F523F36715C804F1F54BF55CFFF56D5F871B990F870C4C09950E063BED2FFBDBFBECFB FDFC0EFC1FE5BC26591D409FFDEFC41FC52FC63FC74FC85FA7B86C007F637F648065ACE2012 621B170D3FB65FE7994126A8F6B9F6CAFE1E175D1D3EB7FAFD060E1FF406E1F6F2F703FD4632C 540D0A5BC22076A543208020ADDCB02001801E502031E0200150FFA9019B00B250731F742F75 3FD4639B00FF31E0F6A10091790F7A1F7B2FD4636E0F3F7E2F7F3F713FDC05CD5068A06B617E6 D80BF81CF82DF805458B1304073AC206D9BB100913F76AC544041FC6B73769685CF86DF87EFE 6A40500FE7ACD5030718C0F8D1F8E2F83EFD463BF8B9836000A4104829B535D30730170E3008 0FBE07832364EF09631DC90FF000DCC05EA199719641D9E75EA131007F9631ADE898B6CC559 796A9965EA139FE39EBB09707A880B7E01D505D2197FAFFD782991A9E14CC5564019B199E149 734BFC2E0AB459D3F9E4F9F5FA9B439A0DBF315B200912031A203A45FA56FA677EE32A71FA82 FA62C33AA2FAB3FA62CEE34AD3FAE4FA62C35B04FB15FA62CFE36B35FB46FA62CE7A0B67FB78 FA63B6E38B97FBA8FA62C39A203BDA633FFBE2C60607820A704BFEEFC0F8AA14C1FFFFC0F8AD2 4C40FC0F8B034C61FC0F8B344FFC82FC0F8B654CA3FC0F8B964CC4FC0F8FFBC74CE5FC0F8BF84 BCDFD0A36592A108FF14D01D50BDC0E900A21FA32FD25FBDC4FBE2D2A0F95461F02530D01B9 FE4A126BFEF715ED27291EED004006210688530FF07A1D52FD63FD74FD856DADCEE110080FFD 9D6DD6FDE7FDF8F219088D0E0DC60E07D07A067E22FE33FE44FE556A0CC45772DD05F8093E0 73E71FE82F9B1935E5BE2C5425E2204768A1EC23E86EEDA1265006062F61540691EC2FF09FFF 93FDA6FA164E1900CF10091F35FF46FF59B1936A0CC4C6102E1900DE1F84FFFF95FFA6DDADCFC 34FC3023D0FD0FFE1FFFFA9AE5DCFC34F04701BF02CFFAE56A40F5A0EA4D2CD0695FF0FC86A6F 5061FFB072FFAE53408BF09C9AA140ADF0BEF7FFAE5D3DC098501220A6F103FFA7C36FF123F13 460F3F14DFFA8B916216FFF042F713BF195FFA7C381B5F1C66185F1DFF7FFA8BBE2C1C2AAD242 1DF22EFBDC437F5A0CC4462806B011F26DF27EFDADCF643F2B078A066DBF0FC8F2AFF2C0FFF2 8C1E5DC2E272A2F2FF27FE08AC2E271F058F348FFA5F045FFC77204163FF9CE095A01CDF393F FF0F3B5F13733CEFFF3DFF3F0F041F052841CF42DF43EF086FFF097F46BF47CF48DF0D2F0E3F4C 0F4D1F3F4E2F11EF12FC515CF0DFDB455265FE76EC00D4FF52CFF54FD0494F7C13733FDC37595 F5A6F5B7FE556246C51757E6F95805ECF5FDF60EFD07628FC49FF95A0989057C0634F645F53AF 16AF17B9FF515F698F6A9F1B0F1C1C6D9F6EAF6FBFFF1F9F20AC72BF73CF74DF242F253C77DFF F78EF79FF28BF29C87CFF7E0F7F1F2D0FFF2E1F81DF82EF83FF31CF32DC872F883FFF894F365F3 76C8C4F8D5F8E6F3AEF3BFFFF9193217F92FF3F7F408F8C19970F981FFF446F457F91399BFF9D0 F495F7B8F4B7FFFA0EFA1FF4EAF41F50CFA63FA74F53FFFA96F561CAB8FAC9F6B1FAEBF6D3C B0AFFB1BF703FB3DF725CB5CFB6DF755FB8FFFF777CBAEFBFF7A7FBE1F7C9CC00FC11FFF7F9 F80AF9B5FC59FC6AF84EF85FF966FFFC7FCB8F8A3F8B4FCEEFCFFFD10F8F8FFF909FD43FD54FC 1EF94DF95EF25FFDA9FFF991FDCBF8C0ADEBDFCF9E1F9F2F9139FFE3AFE4BFA30FC33FA52FE8 9FE9AFA85FFFEBFAA7FEDEFEEFFADAFF11F561CF33FFFF44FB2CFF66F6D3CF85FF96FB7EFFB8F FF725CFD7FFE8FBD0F00AF777C029F03AFFC22F05CF7C9C07BF08CFC74FC85FE30FFF0D4F0E5

Property name	Value
	FCC9FCDAFDE1F122F133FD1EFFFFD2FF169F17AF18BFD73FD84F1BEF1CFFE7099FDC8FDD9F2034215F226FE0EFFFFE1FF8C28266F277FE5CFE6DF91392B5FFF2C6FEABF0AEFECDF304F315FF00F337FFFF22F359F36AFF55F38CF561C3AEF3BFFFFFA7F3E1F6D3C400F411FFF9F433F725CFF452F463F04BF485F777C4A4F4B5F09DFFF4D7F7C9C4F6F507F0EFF100F2ABF54FFFF560F144F155F25CF59DF5AEF199F1AAFF5E4F5F5F606F1EEF1FFF639F64AF514FF3243F254F2035690F6A1F289F29AFF8C286E1F6F2F2D7F2E8F9139730F741FFF326F529F348F77FF790F37BF7B2F39DFFF7D4F7E5F3D0F807FAFCC829F83AF422FFF85CFB4EC87BF88CF474F8AEFBA0C8CDFFF8DEF4C6F900FBF2C91FF930F518F952FFFC44C971F982F56AF57BF726F9CAF9DBFFF5BFF5D0F6D7FA18FA29F614F625FA5FFFFA70FA81F669F67AFAB4FAC5F98FF6BEFF96CFF2036B0BFB1CF704F715FD3D8FFB5CFB6DF752F763FD8E9BABFBBCF7A1FFF9A4F7C3FBFAFC0BF7F6FC2DF818FC4FFFFC60F84BFC82FF77CCA4FCB5F89DFCD7FFFFC9CCF6FD07F8EFFD29F01BCD48FD59FFF941FD7BF06DCD9AFDABF993FDCDF0BFCFFDECDFDF9E5F9F6FBA1FE45FE56FA3AFFFA4BFB52FE93FEA4FA8FFAA0FEDAFEEBF3FEFCFAE4FAF5FF2FFF40FE0A67166B1F7306D6174EBB4B30631E1BC00537562746C652045F46D703490733F30F86FF97FFA8FF5B31532EBBC4921102100F500FD5F37FE6FFF7FFB0E33EBBCFCF55265F8666572210020F0037F048F059FFF06A6F10C0276087F098F0A9F0BAFC29CE8426F6F588054B350FD300EA3430697D77C4269626CB32067F472610310790EA310FF06D3E1BC40544F4320486534A33B807D7D7B5C2A5C64FB000D033074F73002D0303130355A301AE2321AE31AA0381B44340264F610373836643663010CA03265353334313586381D401C2034633532CD20DFB8A0C7D0CD20F0F01CE0331DC01E901F1B441F4EB3801AE1BE506366314031653061316220E061EE651AB021AF229C33210023811AE0E10E3066663039202624FF1B81FF25CD25AD24228422526282E28A72AAFF2BBF2CCF2DDF2EEF2FFF310F321F332FFF343F354F365F376F387F398F3A9F3BAFF3CBF3DCF3EDF3FEF40FF420F431F442FFF453F464F475F486F497F4A8F4B9F4CAFFF4DBF4ECF4FDF50EF51FF530F541F552FFF563F574F585F596F5A7F5B8F5C9F5DAFFB5EBF5FAC645FA52835619F62AF63BFFF64CF65DF66EF67FF690F6A1F6B2F6C3FFF6D4F6E5F6F6F70F718F729F73AF74BFFF75CF76DF77EF78FF7A0F7B1F7C2F7D3FFF7E4F7F5F806F817F828F839F84AF85BFFF86CF87DF88EF89FF8B0F8C1F8D2F8E3FFF8F4F905F916F927F938F949F95AF96BFFF97CF98DF99EF9AFF9C0F9D1F9E2F9F3F9F28431DC020312891A0E237341B14FA341AD13623B1A162F0F0A1412472FA32FA43FA54FA65FA76F1B8120521AD18B9F9F60C663E1A0643938AB005A62AB20331D911D5039193066F51CA0641D31622100299FAD16BE50E265AAF0306234ABF0DC80AB90FF1AA0292FB02FB13FB24FB35FB46FB57FFF68FB79F2A3FB99CB81FBBAFBBCBFBDCFFFBEDFBFEFC0FFC20FC31FC42FC53FC64FFFC75FB87FC97FBA9FCB9FCCAFCCBFCCEFFCFDF0EFD1FFD30FD41FD52FD63FD74FFFC86FD96FCA8FDB8FDC9FDDAFDEBF26EE171AD4DFA519A000E1D0
<b>PidTagSenderAddressType</b>	SMTP
<b>PidTagSenderEmailAddresses</b>	eandersen@contoso.com
<b>PidTagSenderEntryId</b>	cb: 70 lpb: 00000000812B1FA4BEA310199D6E00DD010F540200000000456C697A616265746820416E64657273656E00534D54500065616E64657273656E40636F6E746F736F2E636F6D00
<b>PidTagSenderName</b>	Elizabeth Andersen
<b>PidTagSensitivity</b>	0
<b>PidTagSubject</b>	Pre-status meeting sync-up

The following table lists the properties on the Calendar object for the Fabrikam Project meeting.

Property name	Value
<b>PidLidAllowExternalCheck</b>	TRUE
<b>PidLidAppointmentCounterProposed</b>	FALSE
<b>PidLidAppointmentDuration</b>	60
<b>PidLidAppointmentEndWhole</b>	06:00:00.000 PM 6/18/2008
<b>PidLidAppointmentNotAllowPropose</b>	FALSE
<b>PidLidAppointmentSequence</b>	0
<b>PidLidAppointmentStartWhole</b>	05:00:00.000 PM 6/18/2008
<b>PidLidAppointmentStateFlags</b>	1
<b>PidLidAppointmentSubType</b>	FALSE
<b>PidLidAppointmentSequenceTime</b>	07:33:34.236 PM 2/6/2008
<b>PidLidAttendeeCriticalChange</b>	12:00:00.000 AM 1/1/4501

Property name	Value
<b>PidLidAutoFillLocation</b>	FALSE
<b>PidLidBusystatus</b>	2
<b>PidLidCleanGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E00800000000B0CF8013B468C80100000000000000001000000FB83BE9C4AADB5439C06943C06CF7548
<b>PidLidCollaborateDoc</b>	
<b>PidLidConferencingType</b>	0
<b>PidLidDirectory</b>	
<b>PidLidFInvited</b>	TRUE
<b>PidLidGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E00800000000B0CF8013B468C80100000000000000001000000FB83BE9C4AADB5439C06943C06CF7548
<b>PidLidIntendedBusyStatus</b>	4294967295
<b>PidLidLocation</b>	Conference Room 234
<b>PidLidNetShowUrl</b>	
<b>PidLidOnlinePassword</b>	
<b>PidLidOrganizerAlias</b>	
<b>PidLidOwnerCriticalChange</b>	07:33:34.236 PM 2/6/2008
<b>PidLidReminderDelta</b>	15

Property name	Value
<b>PidLidReminderSet</b>	TRUE
<b>PidLidReminderSignalTime</b>	04:45:00.000 PM 6/18/2008
<b>PidLidReminderTime</b>	05:00:00.000 PM 6/18/2008
<b>PidLidResponseStatus</b>	1
<b>PidLidTimeZoneDescription</b>	(GMT-08:00) Pacific Time (US & Canada)
<b>PidTagBody</b>	Hey team\\,\n\nLet's meet up to discuss the status of the Fabrikam Project.\n\nThanks\\,\n\nElizabeth\n
<b>PidTagCreationTime</b>	07:31:09.578 PM 2/6/2008
<b>PidTagImportance</b>	2
<b>PidTagLastModificationTime</b>	07:33:34.361 PM 2/6/2008
<b>PidTagMessageClass</b>	IPM.Appointment
<b>PidTagMessageLocalId</b>	1033
<b>PidTagOwnerAppointmentId</b>	1252403160
<b>PidTagReplyRequested</b>	TRUE
<b>PidTagResponseRequest</b>	TRUE

Property name	Value
ed	
PidTagRtfCompressed	cb: 5635 lpb: FF150000515C00004C5A4675EDCA2E4F07000601010B606E6731303266350064007263700DD0 0E0032050C60630D446633313530423700F5737473680570627463680FD23610840900110B683 30EB0111A62690FD70DA43333891426666514A374686507809F146715D71560014015D763730 1E8F302A413B064690336020011000AC00873657402D170727132A500002A0AA16E6F1A50200 DF0D51BA13614B0300FF0341C2101D0991C10347D076D02833334191F8F1A2F1B3620EF21107 D436106D0FB072105D06115D01DE410101E6603E3FF1F3F1B0B01301C721BB21C501C1026A1F 922216C6922611DE40FE1190F246FFF1B2F1C3F1D4E0FE10050286F297F2A8FFF2B9F2CAF0F202 DDF2EEF2FF7310230C4FF30A22704225327B714D0334F345F2FFFFF310F321F1E4F392F3A3F3B4 F3C5F0FF0FF0E103DAF3EBF3FCF40DF41EF1160237FFF442F259F26AF27B72358439F4A1F45BF1 F46CF028350A04D6F4E74323338C54EE420076D20434552342DBFCF53A63D72546F557379725 234381FB94E6531365631580F03824709D17E6B52343D8F5AF733215BBF038254EF0870523442 FF5AF63723515F8F0382D8284865226007D02952344868FF620E543F6416071001A00EB064F54 D5F5D5AF6384861673F03824074074FF0EB052346701699F5B2459E16B3F6443B2560890746E 224007906564F4FF5420529F53AF223A55A65420563F574FFF73BC5965542059EF5AFF73BB5D0 85420FF5DBF5ECF73BB60D65420696F6A7F73BBFF6C8A0DE0487F72BF275455A87518844DF7 6A985E559663178A8490C7A2A85E4FD5D09317C588ABE7DF885E460D762E0FF8D8F810F85D56 C890FD26D4F84BF585FFB74950FE139945F575F586F78250FE0FF86C9794F99CF5CAE9BB2332F 8E85F5DFFF7F569BC178AF627F6F6F649A9BB27C5FFF667FA5FF689A9BB2616F91CF6B8F936BFF 9D70AC4F6E6F6F7F708E9BC1944F955F7B9A3F977731981F992FB6DF9B4832EF9BFF9D0F9E1F9 F2A329FFFA10FA21FBFA328B630C07FA4FFA60FA71C32A80FFFA91FC66FAB3D0E01C89FAD6FAE 7F9389FE32B04FB15FCA9FB37FBC31B4BFB5CFFB2236976832B88FB99FD7479B480FD0EFD88F8 B3F22459F1B33C06FC17F2236FDA31933CAFCDBF2236935CB642E2EFFF5FFB70FDB65D87FD 98FE86F9B48562FF7DCDFEC2F9F1B34DF5FE06FC28FA328FF59DFC54FF40FA6FE5DAFC97FF7EF AB2EFF615FE3BFFC1F935C655FD1BF004FD3DFDFEDB2E64FE75FEC3F977734EA1FEB2FFF08DF9 B489BD00A9FEF1FF02F9F39BC40FF0E7FF31FF42F0DC8F5DFF6EF046FA70DFFEDD0165FFB2FFC 3FAB4C0E401A8FFF5FFB006F937A35024F035F1C9F057F0E31EF06BF07C0CAF9777350A8F0B9F 294FFF9B480FF22B2F0FAF10BF9F5713F22F0F7F13AF14BF2E56164F175F24DFA70D36EF1A7F1B 8F38DFAB3D361EAF1FBF20CFFD936B3622BF23CF3D0F25EF2EA127287F844F855F2E472AF8877 F888F9B5737FF86DF2FEF8C3F4DF332D88E1F8F2F4DA8FF3F18915F926F937A3C72435F286F297 FFF4DD52AFF4BFF5ADF9B48750F4F4F5E9FFD9F1B3832DF52DF34FFA328789F37BFBF667FA6FE 7C4F3BEF6A5FAB2E383F1FFF563F413F936B723270DF446F457FB3A80193C1636F6C6F727462A 86C3B5C9F206483A0679F21466E83A07940756530796F65FDCC90357A9A7BB17B6F7C797A847 CA2BF7B0F7EDF7E9D7E1F7C4F7A9F659FE0FE38846A8581853F86497A84867284DFD88AF886 D87EF861F89E43964608D34FF8E9186B38E90846F7D1788CF871093C1D02A5C6465616170752 197D29556C173C05020929670619331FC716C7520576079B0E1B079B04EF0D06463746C94A07 295A0AB40127092E16175AF705C61738F9A096004F6097026E756D9B90126196C0746F970064 6A75E47374E1B0676896F0E1B07A115357607A11697494B03094105C186E6F7156E16F406F746 5A6209F8098C0796C6EC0689F30FE749F8094FF960F971F982F993F8FD0A79D00617061517331 75206193632F69E0A22093E19E106C61306731FE30CC909C219FE0A194A13193699C306DA323 336840A3126686E0A58263E78A7074F0A5236E70A579A7147520A0736E657874A131739A80DB 79106F5074A84156F069791099E0FE79A8B29B504F8074F0A350A3507230FFFE06EE0A912795 09293A1D1A1319F903B7500AF80769B009B30B3F06D699E6874F092E06F709B30756EAD515E6 59FC07990A969A1F0449DB4201A504F70618A7094B0682046E86F6E74928474A1E06060B110A D610077A6B09FE066B1105774F07874684268409FE094A0AC706CCBAAD1B29572B318666CB28 6B1F0F5B48762B48772B2817940995079A113B6849B507065B281736365BC6C6C9CC1B250B1F 1B6E173ACC0BF7920CFD1B101C790B3A0B9466CB955CE62B9559D40B9646467BA46BBC0F7BB 46A1A0B9647694DF9CFF9E0F9F1FFFA02FA13FA24FA35FA46FA57FA68FA79FFF4FB0C3A1AD0FA E18A8F6AB4476C0FD50FF9B70ABA7C531AC68C31CC2E1C56ABF90ED78D06669C0A84162BFD0 7990B080DFAC22CAAFAE18AA56764032C5009A20BE48B771BA309950DEB3ABE336CE3FFBFC4F D05B38D13FD24FD35FD463B070FFB800B1907990D4BFD112D60FC38F76B0FFC55FC666D0F0A 8B2D91FDA26A99AD4D11E73B080CD119B3078E06D706F1305F0DB4F20456F50696C53DF9B52 69C0789392C0F1207679319B10E655D5209A60776EE7B6AA81E8525FE973AAB6EA05D444ED71 6DA93168AE50BEF0EBD3B072336C706DF9208C6B429952ED15537562ED81D273AB716C46FD4 063ED81750047BFE0AF5160606D6C4D4F7067CDED6372EFE792E14A63EFA1BF127E49B6C07A0 04FB0F9F0ED819950744E4C6EA0ED8105B07279F2C131F5929378EFC06EC180E862F3E4C3A0C

Property name	Value
	1C1D074703A2F2FB7D09BA0E96F50732ED9F0636100E4E0B1F02A2EE5612FF66066FD70652FF2 777910642F4C60C730F743EFC0AD78A05C94A1B8F07786F032F251FDF883686C42ED81EFF1B30 0F243EFF1AFB3B0FA66F225EFF162F23367C100FD9AF0729971C19005F0BEA07520BE718FB190 BEA0BA31B1F06E626ABFC0B37A00AC706F63B1C1EEE06B9AD0FFACC0DF50FF04A90421F0C4E1 92D0B080C79AE1ED107990737973A900F211E98FD16C79B08076EFC079B000E8A999916764A9 406179B266FED1F7E830F201B89176575103A1A880EFC07760609B90B19070C4C0B7E005C06C BFB240A88299D0C8B07910D9E1787990CF78E0B090F20179B07361ACC09950FF04E3F3F10801 05C1F3F1B8F061004F809B60609A6078C4C0F5206F797A00FA5CA880709B90792061409A60BF9 177BA30BFE0FEF064B0907940F42062FE64BAC09A60BFE1B7E0A901D0C1A902939B90C140655 C05C0727AFED2EFBBC0FA0299500EA1680CE3722002A1FC67760F790E31C1B0995093810FF2B F10F410A305B200C1101112836A0AD1CB6130C860764660776BB6B170A07F13E2B7D05750C7C 1F921FC10BCD265BFC1401545A9009AE0A971023074E8F0FF99500E10FE3116D7C1D06F50C10 0BF0E0FF9A51F410C1D0C1417931D0B0266021E0FFE260F410C4A10C22B6B1BDE016E014D1FFB EA07940B1A116D179317920BC71F410BFED210D510E109A60ED21BF10701942FFA86094B0C11 0C8329950B7E2C4A1DC913FF700B7F0DA410170B7F0BF017070F7ADE0BEA0BFC16961301C673 A207931FFAA42BF904F209A608A70B190C0F2F700FFBFB0AE410701EE609B50A9015760C180FB 9A51B6B16EED11B11026C0B7F01C51E7B7F0E8309A516378BFE099F0CD61FF99D0B6C00BB1D CB025310AA19A60C3D0FE63F4211942C3D02523C1009950BA406E68269316A2F53067BED2010 163FF04E018837930ED30275275401B2229A2C104E0747862785C1C80C8C0BF4F80A870BFB01 4D0F59107816C19D1FF75200B613E50E571A942C7B0A8A092A272770401666D2AD0E720FCB12 0FF90093909A42C7B0A94036004FA00B10EF9AE0BEB086E099D06CA9006F5014D0FB1AE0F41 0759A10E072BED1A841FD41FFAE71FD059982A88079B0FEA1ADF0B8F0FF0E1032A3BF6431B09 B30FE339B1192C0F3C080FD316C760581C081F620C0B0FF362199F0792036A2B6B1F20151B0F9 213FADF0C4D19B11C0802BA099F0202EF7C43626646036C2E081372F383F394FFF36806840C 08092E0FEF03B1F3C2F3D3F7E6C6C70C080DEF03ADF3FAF40B529DF399C70A03E7F436F409562 6F804A61FF449F365356C0423F470F481F492F3671FF69E04A82370F4BEF4CFF450D6E104A8FFF 501F512F523F36715C804F1F54BF55CFFF56D5F871B990F870C4C09950E063BED2FFBDBFBECFB FDFOEFC1FE5BC26591D409FFDECF41FC52FC63FC74FC85FA7B86C007F637F648065ACE2012 621B170D3FB658C79209AF078302C0D0A5BC2FA206E654C761074316A8F6B9F6CAFF96342717 59AE26F7F08F719FD4636C732078402C602031E06E006FFA20EF316360C076F0B2509B0058B1 6F304076F0660783346CD5068A06BFF6E30AFC09AB013605DF0737F748F759F95D4632E6E6C5 440416B736E56FA4505007ACD5030717A6F7B7F7C8FFFD462ABF05F80BB30D3FA6E6592930A4 17704829B535D307301700080FB0E78FC32364EF08661DC90FF408FF092E1FF99718671D9E792 E131008661ADE888E6CFC5587C6A99692E13939EBB08737FFA880B7E01D505D21882AD78289 4A8E44FFCC5564018B498E4487649A20AB458D6F778E7F8F8FA9B439910B15B2009120DE3192 33948F959F96A732974F985FDD965C339A5F9B6F965C349D6F9E7FDD965C35A07FA18F965C36 A38FA49FDF965CE7A0A6AFA7BF966B38A9AFAABF6D965C399233ADD633AE5C606063FF9725B0 1FB1289A44B22FB1289D54B43FFFB128A064B64FB128A374B85FB128A684FFBA6FB128A994BC 7FB128ACA4BE8FB128FFAFB4AD0FC0D36592913814D01D50ADF07FE900924F935FC28FADF4E2 D2912954FF61F0CD71C83B910BEF715ED279E06261FB0400621068DC51F2A0C55FC66FC77FFF C886CB0CEE110080CA06CD9FCEAFCFBDFE600E043D13960E007A067D25FD36FBFD47FD5869 0FCE6F05F71EA2073D74F2BD85F8B4935AE5C5425E220476F68A1DC53D89E91565006062F615 4FF0691DC5FE0CFD96FCA9F9194D1C00CF1EF0091E38FE49F8B493690FCF2C06111FFD1C00DE 1E87FE98FEA9DCB0CEC64F2C0FF23D0ED3FEE4FEACAD60CEC64E077F1EFAFF2FFEB156A40911 A4D2CD0695FF0DFECB69725F64FF75FEB1534F8EFF9F9FF9A44FB0FFC1FEB15C40CF9B5F152FA 9FFB00FEAAC36026F0376FF6F05FEABBBF8192072FE07203EF098FEAAC380B8FFFC096088F0E 2FEABAE5C0C5A9D54120FAB131FADF43790FC4462806BF14FB7170F181FCB0C432D0090A066 5EE0FFECBF1B2F1C3F18F1D60C1E571A5F202FFF182EF8DC1E57F5BF24BFEA8FF48FECA7F8204 1638D1085D00D0F296FEF3FFF2B8F03A32D1F2E2F2F3FF44FF55831FFFF330F341FF89FF9AF36E F37FF390FFD5FFFE6F3C3F3D4F3E5F021F032C418CE10FF1CB7552657677D0C52F42FFE57FFFC 0793FAC03A3CC67498F4A9F4BAFD586FD149C5173224EFF500F511FC0A690FCFE4985D088C04 7F0537F548F43DF06DFFF07E9418F59BF5ACF0B3F0C4C5DC5EDFFF5FEF0FCF10DC62EF63FF65 0F145F156CFF680F691F6A2F18EF19F86D2F6E3F6F4FFF1D3F1E4F720F731F742F21FF230C775FF F786F797F268F279C7C7F7D8F7E9F2B1FFF2C2F81C311AF832F2FAF30BF7C49873FFF884F349F3 5AF81698C2F8D3F398F6BBFFF3BAF911F922F3EDF944F40FF966F977FFF442F999F464C9BBF9CC F5B4F9EEF5D6CFFA0DFA1EF606FA40F628CA5FFA70F658FFFA92F67ACAB1FAC2F6AAFAE4F6CCC B03FFFB14F6FCF70DF8B8FB5CFB6DF751F762FFF869FBAAFBBBF7A6F7B7FBF1FC02FC13FFF7FBF 80CFC46FC57FB21F850F861F162FFFCACF894FCCEF7C3ACEEFCFF8E4F8F5FFF8169D3DFD4EF9



Property name	Value
	33FB36F955FD8CFD9DFFF988FDBFF9AAFDE1FDF2F9DDFE14F464CFFE36FE47FA2FFE69F5D6CE88FE99FA81FFFE8BF628CEDAFE8FAD3FF0DF67ACF2CFFFF3DFB25FF5FF6CCCF7EFF8FFB77FB88FFD33FFD7FFE8FBCCFBDDFCE4F025F036FFFC21FC32F06CF07DF08EFC76FC87F0C1FCF0D2FF9CCBCFDCDF2034118F129FFFD11FD22F7C58169F17AFD5FFD70F8169FF1B8F1C9FDAE8FFB1FDD0F207F218FE03FFF23AFE25F25CF26DFE58F28FF464C2B1FFF2C2FEAAF2E4F5D6C303F314FEFCF336FFF628C355F366FF4EF388F67AC3A7F3B8FFFFA0F3DAF6CCC3F9F40AFF2F003F1AEFFF452F463F047F058F15FF4A0F4B1F09CFFF0ADF4E7F4F8F509F0F1F102F53CF54DFE7417F146F157F2035593F5A4F18CFFF19DF7C585E4F5F5F1DAF1EBF8169633FFF644F229F42CF24BF682F693F27EF6B5FFF2A0F6D7F6E8F2D3F70AF9FFC72CF73DFFF325F75FFA51C77EF78FF377F7B1FAA3CFF7D0F7E1F3C9F803FAF5C822F833F41BFFF855FB47C874F885F46DF47EF629F8CDFFF8DEF4C2F4D3F5DAF91BF92CF517F528FFF962F973F984F56CF57DF9B7F9C8F892FF35C1F5D2F2036A0EFA1FF607F618FFFC408A5FFA70F655F666FC919AAEFABFFFF6A4F8A7F6C6FAFD0EF6F9FB30F71BFFF52FB63F74EFB85FE7ACBA7FBB8F7A0FFFBDADFECBCBF9C0AF7F2FC2CFF1ECC4BFFFC5CF844FC7EFF70CC9DFCAEF896FCD0FFFFC2CCEFFD00F8E8F8F9FAA4FD48FD59FFF93DF94EFA55FD96FDA7F992F9A3FDDDF7FDEEFDFFF9E7F9F8FE32FE43FD0D6716266E7606D6174DBE4A3363101D1EC537562746C6520E8456D7024C0732F60E89FE9AFEBEABFA34532DBEC4911401130E5306FED8FE9FE9FAFEB3E33DBECED2552F06566657211301120F3AFF4BFFFF5CFF6D6ADDC2A6F8AFF9BFFACFFBDFD1E65C426F6F48B054A380ED6087FED3F6C7C7AC4269626CA350E8677261F34079FED3012F70381D1EC544F4320486524D3003B7D7D7B5C2A5C641BEB30F36074E760F300303130B435300B12320B130AD0380B74043464E64037383664360263FCD03265353334310C35380D700C5034633532BFB50A8D0B800BD50E1200D10330DF03F0EC00B740F7EA3B00B11AE80636680313165306131621110DC61650AE011DF12CC33113013B1C30B10FE60666630391056152FFF0BB115FD15DD145218721556185E18D77F1ADF1BEF1CFF1E0F1F1F202F213F224FFF235F246F257F268F279F28AF29BF2ACFFF2BDF2CEF2DFF2F0F301F312F323F334FFF345F356F367F378F389F39AF3ABF3BCFFF3CDF3DEF3EFF400F411F422F433F444FFF455F466F477F488F499F4AAF4BBF4CCFF4DDF4EEF4FDC644FD5186551CF52DFFF53EF54FF560F571F582F593F5A4F5B5FFF5C6F5D7F5E8F5F9F60AF61BF62CF63DFFF64EF65FF670F681F692F6A3F6B4F6C5FFF6D6F6E7F6F8F709F71AF72BF73CF74DFFF75EF76FF780F791F7A2F7B3F7C4F7D5FFF7E6F7F7F808F819F82AF83BF84CF85DFFF86EF87FF890F8A1F8B2F8C3F8D4F8E5F3F8F6F18730DF0106118C191123734F50B44340B013613E19192E1209171FF14A2935F946F957F968F979F0BB11082170B018FCF50F663D1D0643938B59B30629B50330DC10D80390960EA660CD0640D6162113019CF9D46926214316134F1B06637CCB0F99BC00AD0195FA05FA16FA27FA38FA49FFFA5AFA6BFA7CF1A6FA9CCA84FABDFACEFFADFFAF0FB01FB12FB23FB34FB45FB56FFF67FB78FA8AFB9AFAACFBBCFBDFBDEFFFBEFFC00FC11FC22FC33FC44FC55FC66FFFC77FB89FC99FBAFBFCBFFCCCFDFFCEEF2F171E0B04CFD509D000D200
<b>PidTagSenderAddressType</b>	SMTP
<b>PidTagSenderEmailAddress</b>	eandersen@contoso.com
<b>PidTagSenderEntryId</b>	cb: 70 lpb: 00000000812B1FA4BEA310199D6E00DD010F540200000000456C697A616265746820416E64657273656E00534D54500065616E64657273656E40636F6E746F736F2E636F6D00
<b>PidTagSenderName</b>	Elizabeth Andersen
<b>PidTagSensitivity</b>	0
<b>PidTagS</b>	Fabrikam status meeting

Property name	Value
subject	

Elizabeth saves her calendar to share with Shu. The following shows the resulting iCalendar file.

```

BEGIN:VCALENDAR
PRODID:-//Microsoft Corporation//Outlook 12.0 MIMEDIR//EN
VERSION:2.0
METHOD:PUBLISH
X-CALSTART:20080616T150000Z
X-CALEND:20080620T190000Z
X-CLIPSTART:20080616T070000Z
X-CLIPEND:20080621T070000Z
X-WR-RELCALID:{00000018-47DA-D2D5-82FB-58F6F5E139B2}
X-WR-CALNAME:Elizabeth Andersen
X-PRIMARY-CALENDAR:TRUE
X-OWNER;CN="Elizabeth Andersen":mailto:eandersen@contoso.com
X-MS-OLK-WKHRSTART;TZID="Pacific Time (US & Canada)":080000
X-MS-OLK-WKHREND;TZID="Pacific Time (US & Canada)":170000
X-MS-OLK-WKHRDAYS:MO,TU,WE,TH,FR
BEGIN:VTIMEZONE
TZID:Pacific Time (US & Canada)
BEGIN:STANDARD
DTSTART:16011104T020000
RRULE:FREQ=YEARLY;BYDAY=1SU;BYMONTH=11
TZOFFSETFROM:-0700
TZOFFSETTO:-0800
END:STANDARD
BEGIN:DAYLIGHT
DTSTART:16010311T020000
RRULE:FREQ=YEARLY;BYDAY=2SU;BYMONTH=3
TZOFFSETFROM:-0800
TZOFFSETTO:-0700
END:DAYLIGHT
END:VTIMEZONE
BEGIN:VEVENT
CLASS:PUBLIC
CREATED:20080206T191919Z
DESCRIPTION:\n
DTEND;TZID="Pacific Time (US & Canada)":20080616T120000
DTSTAMP:20080206T215757Z
DTSTART;TZID="Pacific Time (US & Canada)":20080616T113000
LAST-MODIFIED:20080206T193058Z
PRIORITY:5
RRULE:FREQ=WEEKLY;COUNT=5;BYDAY=MO,TU,WE,TH,FR
SEQUENCE:0
SUMMARY;LANGUAGE=en-us:Lunch
TRANSP:OPAQUE
UID:040000008200E00074C5B7101A82E00800000000C0FE0C40B268C8010000000000000000
01000000DD26B2AEDF5D2145BCE907145185EA4D
X-ALT-DESC;FMTTYPE=text/html:<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 3.2//EN
">\n<HTML>\n<HEAD>\n<META NAME="Generator" CONTENT="MS Exchange Server ve
rsion 08.00.0681.000">\n<TITLE></TITLE>\n</HEAD>\n<BODY>\n<!-- Converted f
rom text/rtf format -->\n\n<P DIR=LTR><SPAN LANG="en-us"></SPAN></P>\n\n</
BODY>\n</HTML>
X-MICROSOFT-CDO-BUSYSSTATUS:TENTATIVE

```

X-MICROSOFT-CDO-IMPORTANCE:1  
X-MICROSOFT-DISALLOW-COUNTER:FALSE  
X-MS-OLK-ALLOWEXTERNCHECK:TRUE  
X-MS-OLK-AUTOSTARTCHECK:FALSE  
X-MS-OLK-CONFTYPE:0  
END:VEVENT  
BEGIN:VEVENT  
CLASS:PRIVATE  
CREATED:20080206T192046Z  
DESCRIPTION:\n  
DTEND:20080616T160000Z  
DTSTAMP:20080206T215757Z  
DTSTART:20080616T150000Z  
LAST-MODIFIED:20080206T214042Z  
LOCATION:4567 Main St.\, Buffalo\, NY 98052  
PRIORITY:1  
SEQUENCE:0  
SUMMARY;LANGUAGE=en-us:Doctor's Appointment  
TRANSP:OPAQUE  
UID:040000008200E00074C5B7101A82E0080000000E0E7F7AAB268C8010000000000000000  
010000000D3BDD3F67FDD814E823B9EE04A816204  
X-ALT-DESC;FMTTYPE=text/html:<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 3.2//EN">\n<HTML>\n<HEAD>\n<META NAME="Generator" CONTENT="MS Exchange Server version 08.00.0681.000">\n<TITLE></TITLE>\n</HEAD>\n<BODY>\n<!-- Converted from text/rtf format -->\n\n<P DIR=LTR><SPAN LANG="en-us"></SPAN></P>\n\n</BODY>\n</HTML>

X-MICROSOFT-CDO-BUSYSTATUS:OOF  
X-MICROSOFT-CDO-IMPORTANCE:2  
X-MICROSOFT-DISALLOW-COUNTER:FALSE  
X-MS-OLK-ALLOWEXTERNCHECK:TRUE  
X-MS-OLK-AUTOFILLLOCATION:FALSE  
X-MS-OLK-CONFTYPE:0  
BEGIN:VALARM  
TRIGGER:-PT720M  
ACTION:DISPLAY  
DESCRIPTION:Reminder  
END:VALARM  
END:VEVENT  
BEGIN:VEVENT  
ATTENDEE;CN=pcook@contoso.com;RSVP=TRUE;mailto:pcook@contoso.com  
CLASS:PUBLIC  
CREATED:20080206T192711Z  
DESCRIPTION:Hey Patrick\,\n\nCan we sync up before the upcoming Fabrikam status meeting?\n\nThanks\,\nElizabeth\n  
DTEND:20080618T170000Z  
DTSTAMP:20080206T193017Z  
DTSTART:20080618T163000Z  
LAST-MODIFIED:20080206T193018Z  
LOCATION:Patrick's Office  
ORGANIZER;CN="Elizabeth Andersen";mailto:eandersen@contoso.com  
PRIORITY:5  
SEQUENCE:0  
SUMMARY;LANGUAGE=en-us:Pre-status meeting sync-up  
TRANSP:OPAQUE  
UID:040000008200E00074C5B7101A82E00800000005019899AB368C8010000000000000000  
0100000005D7DB73EA4A89A4894F5C022C6CAA58F  
X-ALT-DESC;FMTTYPE=text/html:<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 3.2//EN">\n<HTML>\n<HEAD>\n<META NAME="Generator" CONTENT="MS Exchange Server version 08.00.0681.000">\n<TITLE></TITLE>\n</HEAD>\n<BODY>\n<!-- Converted f

```

rom text/rtf format -->\n\n<P DIR=LTR><SPAN LANG="en-us"><FONT FACE="Calibri">Hey</FONT></SPAN><SPAN LANG="en-us"> <FONT FACE="Calibri">Patrick</FONT></SPAN><SPAN LANG="en-us"><FONT FACE="Calibri">\,</FONT></SPAN></P>\n\n<P DIR=LTR><SPAN LANG="en-us"><FONT FACE="Calibri">Can we sync up before the upcoming</FONT></SPAN><SPAN LANG="en-us"><FONT FACE="Calibri"></FONT></SPAN><SPAN LANG="en-us"><FONT FACE="Calibri">Fabrikam</FONT></SPAN><SPAN LANG="en-us"><FONT FACE="Calibri"> status meeting?</FONT></SPAN></P>\n\n<P DIR=LTR><SPAN LANG="en-us"><FONT FACE="Calibri">Thanks\,</FONT></SPAN></P>\n\n<P DIR=LTR><SPAN LANG="en-us"><FONT FACE="Calibri">Elizabeth</FONT></SPAN><SPAN LANG="en-us"></SPAN></P>\n\n</BODY>\n</HTML>
X-MICROSOFT-CDO-BUSYSTATUS:BUSY
X-MICROSOFT-CDO-IMPORTANCE:1
X-MICROSOFT-DISALLOW-COUNTER:FALSE
X-MS-OLK-ALLOWEXTERNCHECK:TRUE
X-MS-OLK-APPTSEQTIME:20080206T193017Z
X-MS-OLK-AUTOFILLLOCATION:FALSE
X-MS-OLK-CONFTYPE:0
BEGIN:VALARM
TRIGGER:-PT15M
ACTION:DISPLAY
DESCRIPTION:Reminder
END:VALARM
END:VEVENT
BEGIN:VEVENT
ATTENDEE;CN=sito@contoso.com;RSVP=TRUE:mailto:sito@contoso.com
ATTENDEE;CN=pcook@contoso.com;RSVP=TRUE:mailto:pcook@contoso.com
ATTENDEE;CN=aweiler@contoso.com;RSVP=TRUE:mailto:aweiler@contoso.com
CLASS:PUBLIC
CREATED:20080206T193109Z
DESCRIPTION:Hey team\,\n\nLet's meet up to discuss the status of the Fabrikam Project.\n\nThanks\,\nElizabeth\n
DTEND:20080618T180000Z
DTSTAMP:20080206T193334Z
DTSTART:20080618T170000Z
LAST-MODIFIED:20080206T193334Z
LOCATION:Conference Room 234
ORGANIZER;CN="Elizabeth Andersen":mailto:eandersen@contoso.com
PRIORITY:1
SEQUENCE:0
SUMMARY;LANGUAGE=en-us:Fabrikam status meeting
TRANSP:OPAQUE
UID:040000008200E00074C5B7101A82E00800000000B0CF8013B468C801000000000000000010000000FB83BE9C4AADB5439C06943C06CF7548
X-ALT-DESC;FMTTYPE=text/html:<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 3.2//EN">\n<HTML>\n<HEAD>\n<META NAME="Generator" CONTENT="MS Exchange Server version 08.00.0681.000">\n<TITLE></TITLE>\n</HEAD>\n<BODY>\n<!-- Converted from text/rtf format -->\n\n<P DIR=LTR><SPAN LANG="en-us"><FONT FACE="Calibri">Hey team\,</FONT></SPAN></P>\n\n<P DIR=LTR><SPAN LANG="en-us"><FONT FACE="Calibri">Let</FONT></SPAN><SPAN LANG="en-us"><FONT FACE="Calibri">'</FONT></SPAN><SPAN LANG="en-us"><FONT FACE="Calibri">s meet up to discuss the status of the Fabrikam Project</FONT></SPAN><SPAN LANG="en-us"><FONT FACE="Calibri">.</FONT></SPAN></P>\n\n<P DIR=LTR><SPAN LANG="en-us"><FONT FACE="Calibri">Thanks\,</FONT></SPAN></P>\n\n<P DIR=LTR><SPAN LANG="en-us"><FONT FACE="Calibri">Elizabeth</FONT></SPAN><SPAN LANG="en-us"></SPAN></P>\n\n</BODY>\n</HTML>
X-MICROSOFT-CDO-BUSYSTATUS:BUSY
X-MICROSOFT-CDO-IMPORTANCE:2
X-MICROSOFT-DISALLOW-COUNTER:FALSE

```

```

X-MS-OLK-ALLOWEXTERNALCHECK:TRUE
X-MS-OLK-APPTSEQTIME:20080206T193334Z
X-MS-OLK-AUTOFILLLOCATION:FALSE
X-MS-OLK-CONFTYPE:0
BEGIN:VALARM
TRIGGER:-PT15M
ACTION:DISPLAY
DESCRIPTION:Reminder
END:VALARM
END:VEVENT
END:VCALENDAR

```

Shu opens the iCalendar file. The following tables represent the contents of Shu's copy of Elizabeth's Schedule.

The following table lists the properties on the Calendar object for Elizabeth's lunch break.

Property name	Value
<b>PidLidAllowExternalCheck</b>	TRUE
<b>PidLidAppointmentDuration</b>	30
<b>PidLidAppointmentEndWhole</b>	07:00:00.000 PM 6/16/2008
<b>PidLidAppointmentNotAllowPropose</b>	FALSE
<b>PidLidAppointmentRecur</b>	cb: 80 lpb: 043004300B2001000000C021000001000000000000003E00000022200000050000000000000000000000000000080F8C50C000FC60C06300000093000000B2020000D002000000000000000000000000000
<b>PidLidAppointmentSequence</b>	0
<b>PidLidAppointmentStartWhole</b>	06:30:00.000 PM 6/16/2008
<b>PidLidAppointmentStateFlags</b>	0

Property name	Value
<b>PidLidAppointmentSubType</b>	FALSE
<b>PidLidAutoStartCheck</b>	FALSE
<b>PidLidBusyStatus</b>	1
<b>PidLidCleanGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E0080000000C0FE0C40B268C801000000000000000010000 000DD26B2AEDF5D2145BCE907145185EA4D
<b>PidLid ConferencingType</b>	0
<b>PidLidFInvited</b>	FALSE
<b>PidLidGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E0080000000C0FE0C40B268C801000000000000000010000 000DD26B2AEDF5D2145BCE907145185EA4D
<b>PidLidLocation</b>	
<b>PidLidOwnerCriticalChange</b>	09:57:57.000 PM 2/6/2008
<b>PidLidReminderDelta</b>	1080
<b>PidLidReminderSet</b>	FALSE
<b>PidLidReminderSignalTime</b>	12:30:00.000 AM 6/16/2008
<b>PidLidReminderTime</b>	06:30:00.000 PM 6/16/2008
<b>PidLidResponseStatus</b>	0
<b>PidLidTi</b>	(GMT-08:00) Pacific Time (US & Canada)

Property name	Value
<b>meZone Description</b>	
<b>PidLidTimeZone Struct</b>	cb: 48 lpb: E001000000000000C4FFFFFF00000000B0000000100020000000000000000000000000000000030000000 20002000000000000000
<b>PidTagBody</b>	
<b>PidTagCreationTime</b>	10:35:40.383 PM 2/6/2008
<b>PidTagImportance</b>	1
<b>PidTagLastModificationTime</b>	10:35:40.383 PM 2/6/2008
<b>PidTagMessageClass</b>	IPM.Appointment
<b>PidTagMessageLocalId</b>	1033
<b>PidTagReplyRequested</b>	FALSE
<b>PidTagResponseRequested</b>	FALSE
<b>PidTagRtfCompressed</b>	cb: 556 lpb: 28020000920400004C5A467517CE658C03000A00726370673132358232034368746D6C310331 F862696404000330010301F70A80FF02A403E40713028010830050045608559F07B211B50E510 301020063680AC07073657432060006C311B5337B044614473012BC11C308EF09F73BDB18AF0 E303511B20C606300500B09990164333616E00BA5342010822C2A5C0EB20190671D503320003 C21444F4354595000452048544D4C20500055424C494320222D202F2F5733432010445422441F 24332E322010454E7C223E11C31DC71E700AA321AC31FE391E801F32219D14D022AF22611D60 F12400454144219D0EF1257F0E1082360EF03C4D45544107B0624129A03D224709F00490618A7 405B02212B04F4E54216026542A3005E1457814616E677A6506527613112C8100900220202030 382E30302D6036383A312D6130218E280F23933737411E805449544C45245E34D30EF022FD38 351E802F30CF2EFFBF1DE53211336026DF252F1DF43516E0E03C424F4459219D1CD137CFA31E 4138F1212D2D12B16E2C812A740980200352203C907874FE2F00213CC005B000C005403C0039 6F173A7F3F1F1DF43626A1502044C049523D4C545221901DD35F3D72000042D51CD142D65C1 E1072E70AB1449214605C71032143771D8B023826A15350414E204C8D4770472A3009F02D757 32181FB42CF461E3914D03360475248694877BF43E84BD80A801D8B01C03351503E4FF740AF4 FCF3885383351392F377F1DF5173091365024237D5610

Property name	Value
PidTagSensitivity	0
PidTagSubject	Lunch

The following table lists the properties on the Calendar object for Elizabeth's doctor appointment.

Property name	Value
PidLidAllowExternalCheck	TRUE
PidLidAppointmentDuration	60
PidLidAppointmentEndWhole	04:00:00.000 PM 6/16/2008
PidLidAppointmentNotAllowPropose	FALSE
PidLidAppointmentSequence	0
PidLidAppointmentStartWhole	03:00:00.000 PM 6/16/2008
PidLidAppointmentStateFlags	0
PidLidAppointmentSubType	FALSE
PidLidAutoFillLocation	FALSE
PidLidBusy	3



Property name	Value
<b>syStatus</b>	
<b>PidLidGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E00800000000E0E7F7AAB268C801000000000000000010000 000D3BDD3F67FDD814E823B9EE04A816204
<b>PidLidConferenceType</b>	0
<b>PidLidFInvited</b>	FALSE
<b>PidLidGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E00800000000E0E7F7AAB268C801000000000000000010000 000D3BDD3F67FDD814E823B9EE04A816204
<b>PidLidLocation</b>	4567 Main St., Buffalo, NY 98052
<b>PidLidOwnerCriticalChange</b>	09:57:57.000 PM 2/6/2008
<b>PidLidReminderDelta</b>	720
<b>PidLidReminderSet</b>	FALSE
<b>PidLidReminderSignalTime</b>	03:00:00.000 AM 6/16/2008
<b>PidLidReminderTime</b>	03:00:00.000 PM 6/16/2008
<b>PidLidResponseStatus</b>	0
<b>PidTagBody</b>	
<b>PidTagCreationTime</b>	10:35:40.398 PM 2/6/2008
<b>PidTagImportance</b>	2

Property name	Value
<b>PidTagLastModificationTime</b>	10:35:40.398 PM 2/6/2008
<b>PidTagMessageClass</b>	IPM.Appointment
<b>PidTagMessageLocalId</b>	1033
<b>PidTagReplyRequested</b>	FALSE
<b>PidTagResponseRequested</b>	FALSE
<b>PidTagRtfCompressed</b>	cb: 556 lpb: 28020000920400004C5A467517CE658C03000A00726370673132358232034368746D6C310331F862696404000330010301F70A80FF02A403E40713028010830050045608559F07B211B50E510301020063680AC07073657432060006C311B5337B044614473012BC11C308EF09F73BDB18AF0E303511B20C606300500B09990164333616E00BA5342010822C2A5C0EB20190671D503320003C21444F4354595000452048544D4C20500055424C494320222D202F2F5733432010445422441F24332E322010454E7C223E11C31DC71E700AA321AC31FE391E801F32219D14D022AF22611D60F12400454144219D0EF1257F0E1082360EF03C4D45544107B0624129A03D224709F00490618A7405B02212B04F4E54216026542A3005E1457814616E677A6506527613112C8100900220202030382E30302D6036383A312D6130218E280F23933737411E805449544C45245E34D30EF022FD38351E802F30CF2EFFBF1DE53211336026DF252F1DF43516E0E03C424F4459219D1CD137CFA31E4138F1212D2D12B16E2C812A740980200352203C907874FE2F00213CC005B000C005403C00396F173A7F3F1F1DF43626A1502044C049523D4C545221901DD35F3D72000042D51CD142D65C1E1072E70AB1449214605C71032143771D8B023826A15350414E204C8D4770472A3009F02D75732181FB42CF461E3914D03360475248694877BF43E84BD80A801D8B01C03351503E4FF740AF4FCF3885383351392F377F1DF5173091365024237D5610
<b>PidTagSensitivity</b>	2
<b>PidTagSubject</b>	Doctor's Appointment

The following table lists the properties on the Calendar object for the Fabrikam Project pre-meeting.

Property name	Value
<b>PidLidAllowExternalCheck</b>	TRUE
<b>PidLidAppointment</b>	30

Property name	Value
<b>ntDuration</b>	
<b>PidLidAppointmentEndWhole</b>	05:00:00.000 PM 6/18/2008
<b>PidLidAppointmentNotAllowPropose</b>	FALSE
<b>PidLidAppointmentSequence</b>	0
<b>PidLidAppointmentStartWhole</b>	04:30:00.000 PM 6/18/2008
<b>PidLidAppointmentStateFlags</b>	3
<b>PidLidAppointmentSubType</b>	FALSE
<b>PidLidAppointmentSequenceTime</b>	07:30:17.000 PM 2/6/2008
<b>PidLidAutoFillLocation</b>	FALSE
<b>PidLidBusyStatus</b>	2
<b>PidLidCalendarGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E008000000005019899AB368C801000000000000000010000 0005D7DB73EA4A89A4894F5C022C6CAA58F
<b>PidLidConferenceType</b>	0
<b>PidLidInvited</b>	TRUE

Property name	Value
<b>PidLidGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E008000000005019899AB368C801000000000000000010000 0005D7DB73EA4A89A4894F5C022C6CAA58F
<b>PidLidLocation</b>	Patrick's Office
<b>PidLidOwnerCriticalChange</b>	07:30:17.000 PM 2/6/2008
<b>PidLidReminderDelta</b>	15
<b>PidLidReminderSet</b>	FALSE
<b>PidLidReminderSignalTime</b>	04:15:00.000 PM 6/18/2008
<b>PidLidReminderTime</b>	04:30:00.000 PM 6/18/2008
<b>PidLidResponseStatus</b>	5
<b>PidTagBody</b>	Hey Patrick,\n\nCan we sync up before the upcoming Fabrikam status meeting?\n\nThanks,\nElizabeth\n
<b>PidTagCreationTime</b>	10:35:40.414 PM 2/6/2008
<b>PidTagImportance</b>	1
<b>PidTagLastModificationTime</b>	10:35:40.414 PM 2/6/2008
<b>PidTagMessageClass</b>	IPM.Appointment
<b>PidTagMessageLocalId</b>	1033
<b>PidTagO</b>	4294967295

Property name	Value
<b>wnerAppointmentId</b>	
<b>PidTagReplyRequested</b>	TRUE
<b>PidTagResponseRequested</b>	TRUE
<b>PidTagRtfCompressed</b>	cb: 1033 lpb: 05040000890F00004C5A46753162233603000A00726370673132358232034368746D6C310331F862696404000330010301F70A80FF02A403E40713028010830050045608559F07B211B50E510301020063680AC07073657432060006C311B5335B044614473012BF02003403C643F9074069620510028011C308EF09F7B63B1A1F0E303511B20C60630050330B090164333616E00BA534205910822A5C0EB20190671EC03300203C21444F4354590050452048544D4C20005055424C49432022402D2F2F5733432180444454442094332E32218045F84E223E11C31F371FE00AA3231CFC31391FF020A2230D14D0241F23D1E31ED02570454144230D0EF126EF050E10360EF03C4D455441C507B0412B103D224709F0049014617405B02216F04F4E544D22D0542BA005E1457814616EF4676506527613112DF100900220402030382E30302ED0367438312ED13022FE297F25033782371FF05449544C4525CEA6340EF0246D38351FF02F323F7F306F1F55338134D0284F269F1F6435C116E03C424F4459230D1E4147393F1FB13A61212D2D16F16E552DF1740980200352203E0078FC742F00213E3005B000C005403D702F3ADF3BEF408F1F643628115020804449523D4C54522300BF1F433EE2000044451E4144465C1F80CE720AB1460214605C71032144E7051EFB3828115350414E201A4C48E0472BA009F02D75734722F1443F478E3134381FF046E12C81204641432B9118B549CC2318104709486579247C3536DF34C14C5249D949E7479D3914D034D0FF48C250CF51DF487F498F44D84B2F4C3F9B4D4F4E5B502C100510636B4F5FFF506F543F528F5E5F5F6F55BF56CF61DFEF58FF5A0F5B1F45322C5CDF5DEF61BFFF600F6B6F453A0AA26C080A8145870AB1EF70D8624D01C034C1503FBF421F748FFF42EF43FF450F461F71FF62EF63FF650FBF661F672F683F78E718B003A0772DA00073796E6320757020CE62011005B02DA0746869EF6AFFF6C0F6D1F862F873F7C8F7D9F89AF7FBFBF80CF81DF79322DA083E005A06D0B80FE6784AF85BF898F87DF93CF94DF8B0FFF8C1F974F8E3F8F4F905F9B1F931F96EFFF953F964FA19F986F997F579F9B8F9C9F1B9DAF78E74601A005106B616DFF9F4FA05FA42FA27FAE5FAF6FA5FA6BF5FB1DFA8EFA9FFAB0FA81373019074DB45020078014B092113FACDFADEFFFB1BFB00FBC5F6F3F704F715F726F737FFF75DFC53F76AF77BF78CF79DF7AEFB2AFBFB3BFC94FB5DFB6EFB7FF4E5B542D61FC6B7369DFBBDFFBCEFBDFD5FFC01FFFC12FC23FC34FC45FC6BFDEDFC78FC89FFFC9AFCABFCBCFCDFCDEFE2EFD00FD11FEBD22F4E4C4518D07A01A014B0849FFFD58FD69FD7AFEF0DFE71FE82FF34FFFF19FF2AFD9EFD AFFDC0FDD1FDE2FE08FF7FF0F39C8EAC12F3A9F38EF1F6532010B37C025937D0580
<b>PidTagSenderAddressType</b>	SMTTP
<b>PidTagSenderEmailAddress</b>	eandersen@contoso.com
<b>PidTagSenderEntryId</b>	cb: 116 lpb: 00000000812B1FA4BEA310199D6E00DD010F5402000008045006C0069007A0061006200650074006800200041006E00640065007200730065006E00000053004D00540050000000650061006E00640065007200730065006E00400063006F006E0074006F0073006F002E0063006F006D000000

Property name	Value
<b>PidTagSenderName</b>	Elizabeth Andersen
<b>PidTagSensitivity</b>	0
<b>PidTagSubject</b>	Pre-status meeting sync-up

The following table lists the properties on the Calendar object for the Fabrikam Project meeting.

Property name	Value
<b>PidLidAllowExternalCheck</b>	TRUE
<b>PidLidAppointmentDuration</b>	60
<b>PidLidAppointmentEndWhole</b>	06:00:00.000 PM 6/18/2008
<b>PidLidAppointmentNotAllowPropose</b>	FALSE
<b>PidLidAppointmentSequence</b>	0
<b>PidLidAppointmentStartWhole</b>	05:00:00.000 PM 6/18/2008
<b>PidLidAppointmentStateFlags</b>	3
<b>PidLidAppointmentSubType</b>	FALSE
<b>PidLidAp</b>	07:33:34.000 PM 2/6/2008

Property name	Value
<b>pointmentSequenceTime</b>	
<b>PidLidAutoFillLocation</b>	FALSE
<b>PidLidBusSystemStatus</b>	2
<b>PidLidCleanGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E00800000000B0CF8013B468C801000000000000000010000 000FB83BE9C4AADB5439C06943C06CF7548
<b>PidLidConferenceType</b>	0
<b>PidLidFInvited</b>	TRUE
<b>PidLidGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E00800000000B0CF8013B468C801000000000000000010000 000FB83BE9C4AADB5439C06943C06CF7548
<b>PidLidLocation</b>	Conference Room 234
<b>PidLidOwnerCriticalChange</b>	07:33:34.000 PM 2/6/2008
<b>PidLidReminderDelta</b>	15
<b>PidLidReminderSet</b>	FALSE
<b>PidLidReminderSignalTime</b>	04:45:00.000 PM 6/18/2008
<b>PidLidReminderTime</b>	05:00:00.000 PM 6/18/2008
<b>PidLidResponseStatus</b>	5
<b>PidTagBody</b>	Hey team\,\n\nLet's meet up to discuss the status of the Fabrikam Project.\n\nThanks\,\n\nElizabeth\n

Property name	Value
<b>PidTagCreationTime</b>	10:35:40.429 PM 2/6/2008
<b>PidTagImportance</b>	2
<b>PidTagLastModificationTime</b>	10:35:40.429 PM 2/6/2008
<b>PidTagMessageClass</b>	IPM.Appointment
<b>PidTagMessageLocalId</b>	1033
<b>PidTagOwnerAppointmentId</b>	4294967295
<b>PidTagReplyRequested</b>	TRUE
<b>PidTagResponseRequested</b>	TRUE
<b>PidTagRtfCompressed</b>	cb: 953 lpb: B5030000240D00004C5A46754D27F7AF03000A00726370673132358232034368746D6C310331 F862696404000330010301F70A80FF02A403E40713028010830050045608559F07B211B50E510 301020063680AC07073657432060006C311B533DB044614473012BF02003403C5165AF907406 9620510028011C308EF09F7B63B1ABF0E303511B20C60630050330B090164333616E00BA53420 5910822A5C0EB20190671F603300203C21444F4354590050452048544D4C20005055424C49432 022402D2F2F5733432220444454442134332E32222045F84E223E11C31FD720800AA323BCFC31 392090214223AD14D024BF2471E31F70261045414423AD0EF1278F050E10360EF03C4D455441 C507B0412BB03D224709F0049014617405B02216F04F4E544D2370542C4005E1457814616EF46 76506527613112E9100900220402030382E30302F70367438312F7130239E2A1F25A337823720 905449544C45266EA6340EF0250D383520902F32DF7F310F1FF53421357028EF273F200435C11 6E03C424F445923AD1EE14739DF20513B01212D2D16F16E552E91740980200352203EA078FC7 42F00213ED005B000C005403E102F3B7F3C8F412F20043628B15020804449523D4C545223A0BF 1FE33F82000044E51EE144E65C2020CE720AB146A214605C7103214587051F9B3828B15350414 E201A4C4980472C4009F02D757347239144DF482E313438209046E12D21204641432C3119554 A6C23181047A94865793F21616DF22C251C353635614CF24A794A87FD483D3914D0357049625 1CF45CB0AA2FF52780A8146270AB15748483D01C03561FE50405F42BF5AFF438F449F45AF46BF FF586F48DF49EF4AFF4C0F4D1F4E2F5F57FE4C14B0505F516F527F538F6B4F6C5F7F62FF640F6E CF662F673F684F5FA327FF6D6069CF6ADF6EAF6CFF788F799F702FFF713F7C0F735F746F757F5F A2042007809114B02075703F206F200F51A6637E80042074682E40730190B2747E80206F3FA08 5524601A0DD05106B5020218003606A059069BFFF780F7BDF7A2F88EF89FF7D5F7E6F8C6FEF80 8F819F82AF5F932E877F888F8C5FFF8AAF960F55AF56BF57CF58DF59EF5C4FFF9EEF5D1F5E2F5F 3F604F615F8D4F8E5F5FA2FF907F918F929F4EFB542E016BFE73504F958F969F97AFAF99CF9A



Property name	Value
	DFFF9BEF9CFF9E0FA06FB88FA13FA24FA35FFFA46FA57FA68FA79FBC9FA9BFAACFABDFB54EEC4519707A01A014B068AE3FFFAF4FB05FB16FC98FCA9FC0DFC1EFCDOFFFCB5FCC6FB3AFB4BFB5CFB6DFB7EFBA4FF7D8CF3A77C4712F3B3F398F200532A10B386026337DDF30
<b>PidTagSenderAddressType</b>	SMTP
<b>PidTagSenderEmailAddress</b>	eandersen@contoso.com
<b>PidTagSenderEntryId</b>	cb: 116 lpb: 00000000812B1FA4BEA310199D6E00DD010F5402000008045006C0069007A0061006200650074006800200041006E00640065007200730065006E00000053004D00540050000000650061006E00640065007200730065006E00400063006F006E0074006F0073006F002E0063006F006D000000
<b>PidTagSenderName</b>	Elizabeth Andersen
<b>PidTagSensitivity</b>	0
<b>PidTagSubject</b>	Fabrikam status meeting

### 3.3 Single Meeting Scenario

This subsection describes a multi-step scenario in which an organizer, Elizabeth, sets up a meeting with an attendee, Shu, but later decides to cancel it.

#### 3.3.1 Organizer's Meeting Request

Elizabeth invites Shu to lunch at Fourth Coffee from noon to 12:30 P.M. (Pacific Time) on February 8, 2008.

The following table lists the properties on the Calendar object that Elizabeth sends.

Property name	Value
<b>PidLidAllowExternalCheck</b>	TRUE
<b>PidLidAppointmentCounterProposal</b>	FALSE

Property name	Value
<b>PidLidAppointmentDuration</b>	30
<b>PidLidAppointmentEndWhole</b>	08:30:00.000 PM 2/8/2008
<b>PidLidAppointmentNotAllowPropose</b>	FALSE
<b>PidLidAppointmentSequence</b>	0
<b>PidLidAppointmentStartWhole</b>	08:00:00.000 PM 2/8/2008
<b>PidLidAppointmentStateFlags</b>	3
<b>PidLidAppointmentSubType</b>	FALSE
<b>PidLidAttendeeCriticalChange</b>	05:39:55.801 PM 2/8/2008
<b>PidLidAutoStartCheck</b>	FALSE
<b>PidLidBusyStatus</b>	1
<b>PidLidCleanGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E0080000000010C4F838346AC801000000000000000010000 0002009EB53F098B249AD66CBE6BB3B8B99
<b>PidLidCollaborateDoc</b>	
<b>PidLidCo</b>	0

Property name	Value
referencingType	
PidLidDirectory	
PidLidInvited	TRUE
PidLidGlobalObjectId	cb: 56 lpb: 040000008200E00074C5B7101A82E008000000010C4F838346AC801000000000000000010000 0002009EB53F098B249AD66CBE6BB3B8B99
PidLidIntendedBusyStatus	2
PidLidLocation	Fourth Coffee
PidLidNetShowUrl	
PidLidOnlinePassword	
PidLidOrganizerAlias	
PidLidOwnerCriticalChange	05:39:55.801 PM 2/8/2008
PidLidReminderDelta	1525252321
PidLidReminderSet	TRUE
PidLidReminderSignalTime	08:00:00.000 PM 2/8/2008
PidLidReminderTime	08:00:00.000 PM 2/8/2008
PidLidResponseStatus	5

Property name	Value
<b>PidLidTimeZoneDescription</b>	(GMT-08:00) Pacific Time (US & Canada)
<b>PidTagBody</b>	When: Friday\, February 08\, 2008 12:00 PM-12:30 PM (GMT-08:00) Pacific Time (US & Canada).\nWhere: Fourth Coffee\n\n*~*~*~*~*~*~*~*~*~*\n\nI haven't had a raspberry scone in forever! Want to head down to Fourth Coffee for lunch?\n
<b>PidTagCreationTime</b>	05:39:55.801 PM 2/8/2008
<b>PidTagImportance</b>	1
<b>PidTagLastModificationTime</b>	05:39:55.910 PM 2/8/2008
<b>PidTagMessageClass</b>	IPM.Schedule.Meeting.Request
<b>PidTagMessageLocalId</b>	1033
<b>PidTagOwnerAppointmentId</b>	2758289368
<b>PidTagResponseRequested</b>	TRUE
<b>PidTagRtfCompressed</b>	cb: 5750 lpb: 72160000AB5C00004C5A467577E57A7507000601010B606E6731303266350064007263700DD0 0E00321D0C60630D4401340131737473E26805706263681035090010C03433371044680EB011 8762699311910D773333131666651393F87468650780135714C7145001403914C7637301E802A 412D064698F0336020010C00AC073657402D1507072713200002A0AA16E5A6F1940200DF01A9 13613A030383530341B1101D01B00347DF3076D02833334180F191F1A281B42C71B041AE21FE 17D436106D00721FD05D06114C01CD411A01D5603E31E2F3F19FB01301B621AA21B4020C66C 69FB21511CD4311B2017FF235F1A1F1B2FFF1C3E27010050275F286F297F2A8F2B9FFF0F202CCF 2DDF1F7F208F26A713C0323FFF334F2EEF2FFF310F1D3F381F392F3A3FFF3B4F3FA00E103C9F3D AF3EBF3FCF40DFFE36225F430F247F258F26982248428F6F490F44AF45BF1CD4394C5F4D64321 433384DD420076D2043457F02834F90519F52A53C62535F546379CE7254C4321F4D5531362CA 156FFF503824709D16B54C4370F59E758D17B5AAF038254087054C43C7F59E637C722415E7F03 82284865215007D0FE2954C441EF6167532F6306071001A0EF0EB063E54758597D384751662F0 382FA420740740EB054C44C4F59E75CA1CB6A2F6333560890746E21300790FE6563E41190518F 529F212A54965310FF552F563F72AC5855531058DF59EF72ABFF5BF853105CAF5DBF72AB5FC65 310685FF7696F72AB6B7A30708847FC720A2653FF54970DE082AF752F84C658560EF085DFF778 BF84C55BF9317B4889AE7CE884D4FF5FC75A508C7F7FFF84C56B7926F265F1FF7F0F52CF53DF2 6C5708F86DF955F7706FD2700312CAF8A1F5AFF7A989AB1779FFF8D7F5ECF7E469AB17B4F616F

Property name	Value
	6E5F638AFF9AA2605F656FA4EF678A9AA2645F90BFFF6A7F925B8F996CDFACDF6EFAA658933FF 7944F992F966731970F981FB5CF9A38DE329AEF9BFF9D0F9E1A329EEF9FFF7FA10FA218B520BF 6FA3EFA4FFA60C32FFA6FFA80FC55FAA2D0E01C78FAC5FAD6FFD927932AF3FB04FC98FB26FBB2 1B3AFF7B4BF2126965832B77FB88FD6379A38DF26F0D77F8A2F21359E0B33BF5FC06FFB2126A2 0933CB9FCCAF2126924CB532FFE1DFB4EFB5FFDA55D76FD87FE75F9A38FF85A0E91FBC7FBD8F 9E2958CFDF4FEFFFAA2095C9FC43FF2FFA5EE604FC86FF6DFFFAA1E644FE2AFFB0F924C684FD0 AFFF3FBFD2CFECA2E53FE64FEB2F966734E90FFFEA1F07CF9A389AC0098FEE0FEF1F9E29FFBB30 0D6FF20FF31F0CB8F4CFF5DF035FFFA5FDECC0154FFA1FFB2FAA3C0D30197FF7FE4FFF5F926A35 013F024F1B8F046FD0D2105AF06BF0B9F966735097F0A8FFF283F9A380EE22A1F0E9F0FAF9E47 12E2FF2DFF129F13AF2D46153F164F23CFA5FDDDE36196F1A7F37CFAA2D361D9F1EAFB1FBF925 B3621AF22BF3BFF24DF2D91FF2618833F844F2D37829F2AFF87EE92F1DE372DC889AF8ABF9E29 37890F32DFFF8E8E4CF23E08904F915F926A3B62424F7F275F286F4CC529EF4AEF59CF9A3838FF 2DCF4E4F2FEF9E1A778F51BF616FA209EF7B3F36AF656FA5EE3839DF3AEF695FFDAA2D383E0F5 52F402F925B7ECF431F0771AF453C92B1636F6C6F72A074626C3B5C9E106485C01A679E116E85 C07830756530F5785F65CB8035798A7AA17A5F7B69FF79747B9279FF7DCFF7D8D7D0F7B3F98F FA659ED038835A8471842F853979747F856283CF879F875D86DF850F88D4393F63508C248D81 85A38D8092A22A5C54646560517074113368D17325BF40208EC670618F61716C3F7410565078 A0E0A078A04DE06463B4746C90A07291A0AA30708F11C46175AE605C617390A09200A34E5093 026E756D96A06192C004746F9300646A757374F9E0A0676892F0E0A079015650790114697490B 03090105C6E6F867155D16E306F7465209A70A994C0796C6DB0689E20749A70FF90FF920F931F 942F953F836099006060C9604173317410616678A09E208B8FE19A106C6020673130CB807F982 19BE09D949D318F9698309EE333DB67309ED26685D0A11263896073E039A0B36E70A109A2A47 410736EE86578749D3173968078006E40B674A3D155E069780095E079A4427F97504E7073E0B B40D75054009DF04EFAA4A278408EC39DD19D319B9073F0AE708E7697009730B2E06D696873E 0A78F106E609730756EA8D1659BC0977880A4F99DF04499B420504E600661896090B06820466F 6E7A748EB4749DE05F50AC905FF0772BA2409BE066AC905773E07468DE4267309BE09A0A7F0 6C9F106D00E5AE2472AE98666CAE06AD70B007CA62B00772AE02636290A04EA0FFB1F29091B2 62783095507891B3249750047065AE017363656C6CEF98C1ADD0AD71B38173A8407810CEC1AF AC81C680AF20B5E66CB5F562B5F5F39940B6046467B6E6B860B7E69DA0FDB6047690DF98FF9A 0F9B1F9C2F9D3FFF8FA19E6F9F7FA08FA19FA2AFA3B7ACB0FFA86FA97AA486A6C475B0CAB0977 0A727BFC1A1A7E89D6DC1BCBC3077C06675A0FD973062BC707880AC00A7A2C6EFA9987DA5EC 48B411B6D09550DDA3A76336FFCA7FCB8FCC9A85E0CD6FCE7FCF8FA682FFABF0B4A0AD10788 0D0DF68B0D20F9DBEFFC1BFC2C4B2B0A442D53FD646A52AD0F11E73AC00C951973077D06D70 6F8B04E0D76F456E40696C5397526F68B077838EF0F010767821971055F3D1409660776EE346A 611E3E2E5035C363046705F41A60231E8C139FE385B70A609E503F4B0ECD0A6406D0057E5A36 8B0FD0134EC616DA4C1687E50BB90E973ABF2E820E960F8106B46429552EAB5537562EB2173E 9A6F16C46FC3063EB2173F0BC80A3AAD15F506D6C4D4E6067EB036672ED878F114A63ED41BB B2493FB36078F04EA0F8E0EB219550744CA76D90EB2104A07279F061318EC3FA78ED606EBE20 E3F2F1849DF0BE70E074703A2F2FB47097A06E4074732ED610635FF0E080AD702E15E1012FF40 066FC60652F77F97800642F4B50C370F4E3ED607790D65C90A1B5907785E032EFF1F623FE686B 32EB21ED91AE80EFE3ED91AF30D7F806EFC5ED9162EFD367BDA096F0FE729571BE3004E0BB40 7410BB11AD10C7BB40B6D1AD706E626ABC6078F0D9A7F06F63AD41EC806B96D0A840FF9DE0F CA4A4940070C1518F00AC0096E1E3EAB07880737973A490EFB18361F46C79AC0076ED6078A0F E889591D46764A4D06178A266FC71E3C0FBFA1B5317656410141A410ED605F50BB9790AD107 0C130B48003606CADC0DFA41295D0C4F07800D60178788077D0E7AC10EFA178A07361A84095 500283FFF19105A10361F191B5905FF04E705F504D966078C130F2C06F7978F05CFDA41070979 0781060309660BC31B6D03BBC80FC9064AC107830F1C06264FFB7609660BC81B480A491CD01A 4929790C9BDE0655C0360727AFC72B86077F7A295500C41680A837110004167FE760D190BD1B E50955011200D830E94DF0E430352FE610DB110236A08716020E5C4A0764550776BB3516B601 182BFB4705640C401F6C1F9B0B97265BDE0DF12E5A49096E0A501FFD074E4809550FF0BB0FBD 11477BE706E40BDA0BC809651FFF1B0BE70BDE17821CCF0255020D0DE00FFF1B0C11109C2B35 1BA8014801271BB40FF7830AD21147178217810B911F1B0EAC1DF0AF10BB09660EAC1BBB0701 6E2A3F0FF90B0BDB0C4729550B482C111D8A1F4A09FB490D661FF10B490BBA17070A960FB4 0BC616960201A06A6025FF096E0FBE696A400777821A5D2BC304E109660FF8960AD10BD92F4A 0BC50A9C104A1EC00BF9750A4915650BE209651B3516EEAB17FAC9025B0B49019F1B490E3C09 65163FE78BC8095F0C9A195D0B3600951D8C0EF23D1084196609E2063F1C116E29E20EF23C3B DA09550B6E06825331442F2D0F667BB72FEA163028016237820EAD01F25F2743018C22842028 0747862FC785C1A20C5004E70A400BC501270FBF33105216C1771741009013D40E1112FA4D2C

Property name	Value
	3F0A4308ED27701A1666DF72970E2B0FA5120F6A00F009642C3F0FFA4D034F04E9008B096E0BB 5085D095D0BE6CA4906E4012701880F1B0759610FFDC42BB71A3D1FAE1A9F1FAA59582A410FF 78A0FC41A970B5900BB03143BC043050FF3133E8999730FBD397118EF0BD20FAD1FC6C760321 BD21F3C0BD5035C195F0FF78103642B351EFA150A0F6C1A970C141CF9711BD202A4095F0202E E35435C6FF63503662DC5136CF37DF38EF36206730BFBD208F10FC903ABF3BCF3CDF6C6B60DF BD20DB003A7F3F4F405529393C6F90F73E1F430F4035626E704CB1443F35F3FF55B041DF46AF4 7BF48CF361168D04A22FF36AF4B8F4C9F44AD6D004A2F4FBF50CFFF51DF36115B704EBF545F55 6F5675F611FFB630F610C1309550DC33BB72BA5FBFB6FFFBC7FBD8FBE9FDADFC0CFDC5FC2EFC3 FFFFC50FA3B16AF0D2CF641ADDA124C1ACF0C9E7E8205713506E3AABE066C1A861792CABE065 EAC075F0D1BE20AEA06C60F5416B8085E03AF55069AB404D2D6DA1336DE276B047584D542DA EA06DC129AB41630E69F4A175B376B0555320260C20437470603061292E0DFE0A5B626B9278D 06BE109107810ABD09E43F48178E0713571352A7E73CFFF72EC5B545C1F5D2F5E3F5F4F605F95 B6BF5B625870A619688F699F6AAE49F2A0E305D1259072717596E2A4E00B81FE2040A0EC7078F 0FEF0B7D06CF0E0F11DA400205BF1A4910201722120BF6B9070C0A4E07A20F2A0136120FB516F 5C0083C1721B82C2208B501BF068FE3FE9417D3F7E4F6ACBA7707940B7D07FA61975668ED207 E10222975376F073C7FF10FE20F9807832368FB08C01FFD8A0FCE0D8D08F1195718C11D607907 1FF2FA08C01A9688E86C8958D66A5267861FC3939E9508CD7A410B4801AF076E1FF8DCAD3A28 EEA93E4C895629190E993E47F8D0461D0A6C5930F941F952FA54439FF96AB1352FE316D9097D 39A2F9B3F9C47EE329CEF9DF9BFC339FFFA10F9BFCEE34A30FA41F9BFC35A61FA72F9BFCFE36 A92FAA3F9BFCE330AC4FAD5F9C0B6E38AF4FB05F9BFC3997D3B37633FFB3FC7A206FE09CD4B5 BFB6C89FE4B7CFFF6C8A2F4B9DFB6C8A604BBEFB6C8A914FFBDFB6C8AC24C00FB6C8AF34C2 1FB6C8FFB244C42FB6C8B554B2AFC67363E296D8FF12701AF0B390E49097EF98FFC82FB394FFD E7296C970002F71C5EB95B496F6ED11FF78926F71EC7001A061B07260EA42CAFFFFCC0FCD1FCE 26D0ACEBB1FE20CFA6D33F7FD44FD55FE1A0F690D6AC7AA0054067FFD7FFD90FDA1FDB26969 CE28079317C607E73DCEFDFF90E91F70CEBC248220DE4766C1E1F3DE3E96F65003A62E01FE5 40431E1FFE66DF0FD03F9734D7605F0A91FE31E92FEA3F90E936969C4CFF7AC2D7600B81EE1F EF2FF03DD0ACF204FFF2002270F2DFF3EFF06ADBACF204E6175FF78FF89FF0B5686096BA4D2B7 069BF79B0F2569CC5FBEFFCFFF0B534FE8FFFF999FE400AF01BFF0B5C9ACFF55F6F2F7003F060 FF04C36080F0916050F0AAFFDF05B370C9FFF91E612098F0F2FF04CFF6B80113F12450E2F13CFF 05BB3FC11FAAFA2F417AF18BFB39437969C445870FE6BF6EF1CAF1DBFD0AC72808D002D70FF7 8A0F25F20CF21DF1E91DBAC23F71FFFF25CF1DCEFE7C23F7FB5F2A5FF02FFA2FF1F247204163E 850839112BF2F1FFFF4EFF5FF095232BF33CF34DFF9EFFAF8FF379F38AF39BFFE3FFF4F3C8F3D9F 3EAFF02FF040F41DF42EF43FF07BF08CC472CFBE6AFD115528300E1D0CACF489FEB1FFFC6194 54C0943D2074F2F503F514FDB26FD1A3C5180D2549F55AF56BFC646969CFE498B706BC04D905 91F5A2F497F0C7FFF0D89472F5F5F606F10DF11EC636F647FFF658F156F167C688F699F6AAFF19F F1B0CFF6DAF6EBF6FCF1E8F1F9872CF73DF74EFFF22DF23EF77AF78BF79CF279F28AC7CFFF7E0 F7F1F2C2F2D3C821F832F843F30BFFF31CF8763174F88CF354F365F81E98CDF8DEF3A3F3B4F8 70991CF92DF3F2F715FFF414F96BF97CF447F99EF469F9C0F9D1FFF49CF9F3F4BECA15FA26F60E FA48F630CFFA67FA78F660FA9AF682CAB9FACAF6B2FFFAECF6D4CB0BFB1CF704FB3FEF726CB5DF FFB6EF756F767F912FBB6FBC7F7ABF7BCFFF8C3FC04FC15F800F811FC4BFC5CFC6DFFF855F866F CA0FCB1FB7BF8AAAF8BBF1BCFFFD06F8EEFD28F81DAD48FD59F93EF94FFF8709D97F7DA8F98DF B90F9AFFDE6FDF7FFF9E2FE19FA04FE3BFE4CFA37FE6EF4BECFFE90FEA1FA89FEC3F630CEE2FEF 3FADBFFFF15F682CF34FF45FB2DFF67F6D4CF86FFFF97FB7FFB9F726CFD8FFE9FBD1FBE2FFFD8 DF031F042FC26FC37FD3EF07FF090FFFC7BFC8CF0C6F0D7F0E8FCD0FCE1F11BFCF12CFFF6FD25 FD36F2034172F183FFD6BFD7CF81F81C3F1D4FDB9FDCAF8709FF212F223FE08F00BFE2AF261F 272FE5DFFF294FE7FF2B6F2C7FEB2F2E9F4BEC30BFFF31CFF04F33EF630C35DF36EFF56F390FFF 682C3AFF3C0FFA8F3E2F6D4C01F412FFFFFAF434F726C453F464F04CF05DF208FFF4ACF4BDF0A 1F0B2F1B9F4FAF50BF0F6FFF107F541F552F563F14BF15CF596F5A7FE7471F1A0F1B1F20355EDF 5FEF1E6FFF1F7F81F863EF64FF234F245F870968DFFF69EF283F486F2A5F6DC6FEDF2D8F70FFF2 FAF731F742F32DF764FA59C786F797FFF37FF7B9FAABC7D8F7E9F3D1F80BFAFDCCF82AF83BF42 3F85DFB4FC87CF88DF475FFF8AFFBA1C8CEF8DFF4C7F4D8F683F927FFF938F51CF52DF634F975 F986F571F582FFF9BCF9CDF9DEF5C6F5D7FA11FA22F8ECFF361BF62CF2036A68FA79F661F672FF FC9A8AB9FACAF6AFF6C0FCEB9B08FB19FFF6FEF901F720FB57FB68F753FB8AF775FFFACFBBD 7A8FBDFFED4CC01FC12F7AFFFC34FF26CC53FC64F84CFC86FF78CCA5FFFCB6F89EFCDF8FFCACC F7FD08F8F0FD2AFF01CCD49FD5AF942F953FAFEFDA2FDB3FFF997F9A8FAAFFDF0FE01F9ECF9F DFE37F7FE48FE59FA41FA52FE8CFE9DFD676716266ED006D6174E184A8D63101D78C53756274 6C6520E8456D702A60733500EE3FEF4FEBF05FA8E532E18C4916E016D0EAD06FF32FF43FF54FF 0DE33E18CF2C552F06566657216D016C0F94FFA5FFFFB6FFC76B37CF846FE4FFF5F006F017FD1E

Property name	Value
	BFC426F6F4E5054A920F300870473FC67CD4C4269626CA8F0E8677261F8E079047306CFFCA381D78C544F432048652A73003B7D7D7B5C2A5C641BF0D0F90074ED00F8A0303130B4353010B23210B31070381114043464EBE0373836643602630270326535334310C3538131011F034633532BFC2F0AE70BDA0C2F0E6C012B03313903F14601114151EA95010B1E7806366803131653061316216B0DC61651080177F186C3316D01951C310B004006666303915F61ACFFF11511B9D1B7D19F21E121AF61DFE1E77FF207F218F229F23AF24BF25CF26DF27EFFF28FF2A0F2B1F2C2F2D3F2E4F2F5F306FFF317F328F339F34AF35BF36CF37DF38EFFF39FF3B0F3C1F3D2F3E3F3F4F405F416FFF427F438F449F45AF46BF47CF48DF49EFFF4AFF4C0F4D1F4E2F4F3F504F515F526FF7537F548F557C6455751E05576F587FFF598F5A9F5BAF5CBF5DCF5EDF5FEF60FFF620F631F642F653F664F675F686F697FFF6A8F6B9F6CAF6DBF6ECF6DF70EF71FFF730F741F752F763F774F785F796F7A7FFF7B8F7C9F7DAF7EBF7FCF80DF81EF82FFF840F851F862F873F884F895F8A6F8B7FFF8C8F8D9F8EAF8FBF90CF91DF92EF93FF950F1E13139016011E6196B23734F510E43410A13619819732E6C09711FF1A4298FF9A0F9B1F9C2F9D3F115116221710A1956F569663D770643938B5A0D062A0F03313611320390F00EA6612706413016216D01F6FA2E635DC9034973032A19098B03661FFA16010701EFA5FFA70FA81FA92FAA3FFAB4FAC5FAD6F200FAF6CADEFB17FB28FFF39FB4AFB5BFB6CFB7DFB8EFB9FFBB0FFBFC1FBD2FAE4FBF4FB06FC16FC27FC38FFFC49FC5AFC6BFC7CFC8DFC9EFC AFFCC0FFFCDFBE3FCF3FC05FD15FD26FD37FD48F2F1CBE10A4D5750F7000D7A0
PidTagSensitivity	0
PidTagSubject	Lunch?

The following shows the resulting iCalendar file.

BEGIN:VCALENDAR

```

PRODID:-//Microsoft Corporation//Outlook 12.0 MIMEDIR//EN
VERSION:2.0
METHOD:REQUEST
X-MS-OLK-FORCEINSPECTOROPEN:TRUE
BEGIN:VEVENT
ATTENDEE;CN=sito@contoso.com;RSVP=TRUE:mailto:sito@contoso.com
CLASS:PUBLIC
CREATED:20080208T173955Z
DESCRIPTION:When: Friday\, February 08\, 2008 12:00 PM-12:30 PM (GMT-08:00)
Pacific Time (US & Canada).\nWhere: Fourth Coffee\n\n*~*~*~*~*~*~*~*~*~*\n\nI haven't had a raspberry scone in forever! Want to head down to Fourth Coffee for lunch?\n
DTEND:20080208T203000Z
DTSTAMP:20080208T173955Z
DTSTART:20080208T200000Z
LAST-MODIFIED:20080208T173955Z
LOCATION:Fourth Coffee
ORGANIZER;CN="Elizabeth Andersen":mailto:eandersen@contoso.com
PRIORITY:5
SEQUENCE:0
SUMMARY;LANGUAGE=en-us:Lunch?
TRANSP:OPAQUE
UID:040000008200E00074C5B7101A82E008000000010C4F838346AC80100000000000000001010000002009EB53F098B249AD66CBE6BB3B8B99
X-ALT-DESC;FMTTYPE=text/html:<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 3.2//EN">\n<HTML>\n<HEAD>\n<META NAME="Generator" CONTENT="MS Exchange Server version 08.00.0681.000">\n<TITLE></TITLE>\n</HEAD>\n<BODY>\n<!-- Converted f

```

```

rom text/rtf format -->\n\n<P DIR=LTR><SPAN LANG="en-us"><FONT FACE="Calibri">When: Friday\, February 08\, 2008 12:00 PM-12:30 PM (GMT-08:00) Pacific Time (US &amp\; Canada).</FONT></SPAN></P>\n\n<P DIR=LTR><SPAN LANG="en-us"><FONT FACE="Calibri">Where: Fourth Coffee</FONT></SPAN></P>\n\n<P DIR=LTR><SPAN LANG="en-us"><FONT FACE="Calibri">*****</FONT></SPAN></P>\n\n<P DIR=LTR><SPAN LANG="en-us"><FONT FACE="Calibri">I haven't had a raspberry scone in forever!&nbsp;\; Want to head down to Fourth Coffee for lunch?</FONT></SPAN><SPAN LANG="en-us"></SPAN></P>\n\n</BODY>\n</HTML>

```

```

X-MICROSOFT-CDO-BUSYSTATUS:TENTATIVE
X-MICROSOFT-CDO-IMPORTANCE:1
X-MICROSOFT-CDO-INTENDEDSTATUS:BUSY
X-MICROSOFT-DISALLOW-COUNTER:FALSE
X-MS-OLK-ALLOWEXTERNCHECK:TRUE
X-MS-OLK-AUTOSTARTCHECK:FALSE
X-MS-OLK-CONFTYPE:0
X-MS-OLK-SENDER;CN="Elizabeth Andersen":mailto:eandersen@contoso.com
BEGIN:VALARM
TRIGGER:-PT15M
ACTION:DISPLAY
DESCRIPTION:Reminder
END:VALARM
END:VEVENT
END:VCALENDAR

```

The following table lists the properties on the Calendar object that Shu receives.

Property name	Value
<b>PidLidAllowExternalCheck</b>	TRUE
<b>PidLidAppointmentDuration</b>	30
<b>PidLidAppointmentEndWhole</b>	08:30:00.000 PM 2/8/2008
<b>PidLidAppointmentNotAllowPropose</b>	FALSE
<b>PidLidAppointmentSequence</b>	0
<b>PidLidAppointmentStartW</b>	08:00:00.000 PM 2/8/2008



Property name	Value
hole	
PidLidAppointmentStateFlags	3
PidLidAppointmentSubType	FALSE
PidLidAutoStartCheck	FALSE
PidLidBusyStatus	1
PidLidCleanGlobalObjectId	cb: 56 lpb: 040000008200E00074C5B7101A82E008000000010C4F838346AC801000000000000000010000 0002009EB53F098B249AD66CBE6BB3B8B99
PidLidConflictingType	0
PidLidFInvited	TRUE
PidLidGlobalObjectId	cb: 56 lpb: 040000008200E00074C5B7101A82E008000000010C4F838346AC801000000000000000010000 0002009EB53F098B249AD66CBE6BB3B8B99
PidLidIntendedBusyStatus	2
PidLidLocation	Fourth Coffee
PidLidOwnerCriticalChange	05:39:55.000 PM 2/8/2008
PidLidReminderDelta	15
PidLidReminderSet	TRUE
PidLidReminderSignalTime	07:45:00.000 PM 2/8/2008

Property name	Value
<b>e</b>	
<b>PidLidReminderTime</b>	08:00:00.000 PM 2/8/2008
<b>PidLidResponseStatus</b>	5
<b>PidTagBody</b>	When: Friday\, February 08\, 2008 12:00 PM-12:30 PM (GMT-08:00) Pacific Time (US & Canada).\nWhere: Fourth Coffee\n~*~*~*~*~*~*~*~*~*~*~*~*\n\nI haven't had a raspberry scone in forever! Want to head down to Fourth Coffee for lunch?\n
<b>PidTagCreationTime</b>	05:43:51.254 PM 2/8/2008
<b>PidTagImportance</b>	1
<b>PidTagLastModificationTime</b>	05:43:53.051 PM 2/8/2008
<b>PidTagMessageClass</b>	IPM.Schedule.Meeting.Request
<b>PidTagMessageLocaleId</b>	1033
<b>PidTagReplyRequested</b>	TRUE
<b>PidTagResponseRequested</b>	TRUE
<b>PidTagRtfCompressed</b>	cb: 997 lpb: E10300008F0B00004C5A4675555055B303000A00726370673132358232034368746D6C310331F862696404000330010301F70A80FF02A403E40713028010830050045608559F07B211B50E510301020063680AC07073657432060006C311B533DB044614473012BF02003403C5165AF9074069620510028011C308EF09F7B63B1ABF0E303511B20C60630050330B090164333616E00BA534205910822A5C0EB20190671F603300203C21444F4354590050452048544D4C20005055424C49432022402D2F2F5733432220444454442134332E32222045F84E223E11C31FD720800AA323BCFC31392090214223AD14D024BF2471E31F70261045414423AD0EF1278F050E10360EF03C4D455441C507B0412BB03D224709F0049014617405B02216F04F4E544D2370542C4005E1457814616EF4676506527613112E9100900220402030382E30302F70367438312F7130239E2A1F25A337823720905449544C45266EA6340EF0250D383520902F32DF7F310F1FF53421357028EF273F200435C116E03C424F445923AD1EE14739DF20513B01212D2D16F16E552E91740980200352203EA078FC742F00213ED005B000C005403E102F3B7F3C8F412F20043628B15020804449523D4C545223A0BF1FE33F82000044E51EE144E65C2020CE720AB146A214605C7103214587051F9B3828B15350414E

Property name	Value
	201A4C4980472C4009F02D757347239144DF482E313438209046E12D21204641432C3119554A6CD3181047A9576809F03A4D300510506461792C4D3065199075BD0AC0792F41508001D02F50200E20A63A2F8021804D2D51C1335202C02028474D542D2F5051E1DE29218000D006900DE020076252D0865505F0485E26616D7002804D4A9726457819416E61505029F22E251C353635614CF24A794A87FD483D3914D035704962595F45CB0AA2FF5A080A8146270AB15ED8483D01C03561FE50405F42BF628F438F449F45AF46BFFF5FFF48DF49EF4AFF4C0F4D1F4E2F4F3AE71AC050010861746816F1012009E0FF57EF58FF5A0F5B1F73EF5D3F5E4F5F5FFF606F617F63DF7CCF64AF65BF66CF67DFFF68EF69FF6B0F80DF6D2F6E3F6F4F4EFBFC2A7E8BAF726F737F748F759F8E5FFF77BF78CF79DF7AEF7BFF7E5F973F7F2FFF803F814F825F836F847F858F9B4F87AFE788BF89CF4EFB492014702E900B909E279070054014703EC061202CA0F87370620490510104F002202E402B0B803FB2652E912154BF6E62B7A76055F9A68061014056C85700701705402CC0A62065A6F1646F77AF03A0AC31719B3FB2200A406E1460FE3F8CDF8DEF8EFF900FB03FB14F9F7FFFA08FB3BFB20FB31F924F935F946F957FDF968F98EFBF7F3A77A3112F3B3F398F2F200532A1386026337DC5E0
<b>PidTagSenderAddressType</b>	SMTP
<b>PidTagSenderEmailAddress</b>	eandersen@contoso.com
<b>PidTagSenderEntryId</b>	cb: 116 lpb: 00000000812B1FA4BEA310199D6E00DD010F5402000008045006C0069007A0061006200650074006800200041006E00640065007200730065006E00000053004D00540050000000650061006E00640065007200730065006E00400063006F006E0074006F0073006F002E0063006F006D000000
<b>PidTagSenderName</b>	Elizabeth Andersen
<b>PidTagSensitivity</b>	0
<b>PidTagSubject</b>	Lunch?

### 3.3.2 Attendee's Meeting Acceptance

Shu accepts Elizabeth's meeting request.

The following table lists the properties on the Calendar object that Shu sends.

Property name	Value
<b>PidLidAppointmentCounterProposal</b>	FALSE
<b>PidLidAppointmentDuration</b>	30
<b>PidLidAppointmentE</b>	08:30:00.000 PM 2/8/2008

Property name	Value
<b>ndWhole</b>	
<b>PidLidAppointmentSequence</b>	0
<b>PidLidAppointmentStartWhole</b>	08:00:00.000 PM 2/8/2008
<b>PidLidAppointmentStateFlags</b>	0
<b>PidLidAppointmentSubType</b>	FALSE
<b>PidLidAttendeeCriticalChange</b>	05:44:34.941 PM 2/8/2008
<b>PidLidAutoFillLocation</b>	FALSE
<b>PidLidBusyStatus</b>	2
<b>PidLidCleanGlobalObjectId</b>	cb: 56 lpb: 04000008200E00074C5B7101A82E008000000010C4F838346AC8010000000000000000002009EB53F098B249AD66CBE6BB3B8B99
<b>PidLidCollaborateDoc</b>	
<b>PidLidConferencingType</b>	0
<b>PidLidDirectory</b>	
<b>PidLidFInvited</b>	FALSE
<b>PidLidGlobalObjectId</b>	cb: 56 lpb: 04000008200E00074C5B7101A82E008000000010C4F838346AC8010000000000000000002009EB53F098B249AD66CBE6BB3B8B99
<b>PidLidIntendedBusyStatus</b>	4294967295
<b>PidLidLocation</b>	Fourth Coffee
<b>PidLidNetShowUrl</b>	
<b>PidLidOnlinePassword</b>	
<b>PidLidOrganizerAlias</b>	
<b>PidLidOwnerCriticalChange</b>	05:39:55.000 PM 2/8/2008
<b>PidLidReminderDelta</b>	0
<b>PidLidReminderSet</b>	FALSE
<b>PidLidReminderSign</b>	08:00:00.000 PM 2/8/2008

Property name	Value
<b>alTime</b>	
<b>PidLidReminderTime</b>	08:00:00.000 PM 2/8/2008
<b>PidLidResponseStatus</b>	0
<b>PidLidTimeZoneDescription</b>	(GMT-08:00) Pacific Time (US & Canada)
<b>PidTagCreationTime</b>	05:44:34.926 PM 2/8/2008
<b>PidTagImportance</b>	1
<b>PidTagLastModificationTime</b>	05:44:39.254 PM 2/8/2008
<b>PidTagMessageClass</b>	IPM.Schedule.Meeting.Resp.Pos
<b>PidTagMessageLocalId</b>	0
<b>PidTagSensitivity</b>	0
<b>PidTagSubject</b>	Accepted: Lunch?

The following shows the resulting iCalendar file.

```

BEGIN:VCALENDAR
PRODID:-//Microsoft Corporation//Outlook 12.0 MIMEDIR//EN
VERSION:2.0
METHOD:REPLY
X-MS-OLK-FORCEINSPECTOROPEN:TRUE
BEGIN:VEVENT
ATTENDEE;PARTSTAT=ACCEPTED:mailto:sito@contoso.com
CLASS:PUBLIC
CREATED:20080208T174434Z
DTEND:20080208T203000Z
DTSTAMP:20080208T174434Z
DTSTART:20080208T200000Z
LAST-MODIFIED:20080208T174439Z
LOCATION:Fourth Coffee
PRIORITY:5
SEQUENCE:0
SUMMARY:Accepted: Lunch?
TRANSP:OPAQUE
UID:040000008200E00074C5B7101A82E008000000010C4F838346AC80100000000000000
0100000002009EB53F098B249AD66CBE6BB3B8B99
X-MICROSOFT-CDO-BUSYSTATUS:BUSY
X-MICROSOFT-CDO-IMPORTANCE:1
X-MS-OLK-AUTOFILLLOCATION:FALSE
X-MS-OLK-CONFTYPE:0
END:VEVENT
END:VCALENDAR

```

The following table lists the properties on the Calendar object that Elizabeth receives.

Property name	Value
<b>PidLidAppointmentDuration</b>	30
<b>PidLidAppointmentEndWhole</b>	08:30:00.000 PM 2/8/2008
<b>PidLidAppointmentSequence</b>	0
<b>PidLidAppointmentStartWhole</b>	08:00:00.000 PM 2/8/2008
<b>PidLidAppointmentStateFlags</b>	3
<b>PidLidAppointmentSubType</b>	FALSE
<b>PidLidAttendeeCriticalChange</b>	05:44:34.000 PM 2/8/2008
<b>PidLidAutoFillLocation</b>	FALSE
<b>PidLidBusyStatus</b>	2
<b>PidLidCleanGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E008000000010C4F838346AC8010000000000000001 0000002009EB53F098B249AD66CBE6BB3B8B99
<b>PidLidConferencingType</b>	0
<b>PidLidFInvited</b>	FALSE
<b>PidLidGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E008000000010C4F838346AC8010000000000000001 0000002009EB53F098B249AD66CBE6BB3B8B99
<b>PidLidLocation</b>	Fourth Coffee
<b>PidLidReminderDelta</b>	1080
<b>PidLidReminderSet</b>	FALSE
<b>PidLidReminder</b>	02:00:00.000 AM 2/8/2008

Property name	Value
<b>derSignalTime</b>	
<b>PidLidReminderTime</b>	08:00:00.000 PM 2/8/2008
<b>PidLidResponseStatus</b>	3
<b>PidTagCreationTime</b>	05:47:43.269 PM 2/8/2008
<b>PidTagImportance</b>	1
<b>PidTagLastModificationTime</b>	05:47:43.769 PM 2/8/2008
<b>PidTagMessageClass</b>	IPM.Schedule.Meeting.Resp.Pos
<b>PidTagMessageLocaleId</b>	1033
<b>PidTagReplyRequested</b>	FALSE
<b>PidTagResponseRequested</b>	FALSE
<b>PidTagSenderAddressType</b>	SMTP
<b>PidTagSenderEmailAddress</b>	sito@contoso.com
<b>PidTagSenderEntryId</b>	cb: 84 lpb: 0000000812B1FA4BEA310199D6E00DD010F5402000001805300680075002000490074006 F00000053004D005400500000007300690074006F00400063006F006E0074006F0073006F0 02E0063006F006D000000
<b>PidTagSenderName</b>	Shu Ito
<b>PidTagSensitivity</b>	0
<b>PidTagSubject</b>	Accepted: Lunch?

### 3.3.3 Organizer's Cancellation

Elizabeth realizes that she has a conflicting meeting, so she cancels her lunch with Shu.

The following table lists the properties on the Calendar object that Elizabeth sends.

Property name	Value
<b>PidLidAllowExternalCheck</b>	TRUE
<b>PidLidAppointmentCounterProposed</b>	FALSE
<b>PidLidAppointmentDuration</b>	30
<b>PidLidAppointmentEndWhole</b>	08:30:00.000 PM 2/8/2008
<b>PidLidAppointmentNotAllowPropose</b>	FALSE
<b>PidLidAppointmentSequence</b>	1
<b>PidLidAppointmentStartWhole</b>	08:00:00.000 PM 2/8/2008
<b>PidLidAppointmentStateFlags</b>	7
<b>PidLidAppointmentSubType</b>	FALSE
<b>PidLidAppointmentSequenceTime</b>	05:48:33.676 PM 2/8/2008
<b>PidLidAttendeeCriticalChange</b>	05:52:48.957 PM 2/8/2008



Property name	Value
<b>PidLidAutoStartCheck</b>	FALSE
<b>PidLidBusyStatus</b>	0
<b>PidLidCalendarGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E008000000010C4F838346AC801000000000000000010000002009EB53F098B249AD66CBE6BB3B8B99
<b>PidLidCollaborateDoc</b>	
<b>PidLidConferenceType</b>	0
<b>PidLidDirectory</b>	
<b>PidLidInvited</b>	TRUE
<b>PidLidGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E008000000010C4F838346AC801000000000000000010000002009EB53F098B249AD66CBE6BB3B8B99
<b>PidLidIntendedBusyStatus</b>	0
<b>PidLidLocation</b>	Fourth Coffee
<b>PidLidNetShowUrl</b>	
<b>PidLidOnlinePassword</b>	
<b>PidLidOrganizerAlias</b>	
<b>PidLidOwnerCriticalChange</b>	05:52:48.957 PM 2/8/2008
<b>PidLidReminderDelta</b>	1525252321

Property name	Value
<b>PidLidReminderSet</b>	FALSE
<b>PidLidReminderSignalTime</b>	08:00:00.000 PM 2/8/2008
<b>PidLidReminderTime</b>	08:00:00.000 PM 2/8/2008
<b>PidLidResponseStatus</b>	5
<b>PidLidTimeZoneDescription</b>	(GMT-08:00) Pacific Time (US & Canada)
<b>PidTagBody</b>	When: Friday\, February 08\, 2008 12:00 PM-12:30 PM (GMT-08:00) Pacific Time (US & Canada).\nWhere: Fourth Coffee\n\n*~*~*~*~*~*~*~*~*~*\n\nOops! Forgot I have a meeting today. Maybe we can try again sometime next week.\n
<b>PidTagCreationTime</b>	05:52:48.926 PM 2/8/2008
<b>PidTagImportance</b>	2
<b>PidTagLastModificationTime</b>	05:52:49.301 PM 2/8/2008
<b>PidTagMessageClass</b>	IPM.Schedule.Meeting.Canceled
<b>PidTagMessageLocalId</b>	1033
<b>PidTagOwnerAppointmentId</b>	2758289368
<b>PidTagResponseRequested</b>	TRUE
<b>PidTagRt</b>	cb: 5760 lpb:

Property name	Value
fCompressed	7C160000AD5C00004C5A46759798928207000601010B606E6731303266350064007263700DD0 0E00321D0C60630D4401340131737473E26805706263681035090010C03433371044680EB011 8762699311910D773333131666651393F87468650780135714C7145001403914C7637301E802A 412D064698F0336020010C00AC073657402D150707271320002A0AA16E5A6F1940200DF01A9 13613A030383530341B1101D01B00347DF3076D02833334180F191F1A281B42C71B041AE21FE 17D436106D00721FD05D06114C01CD411A01D5603E31E2F3F19FB01301B621AA21B4020C66C 69FB21511CD4311B2017FF235F1A1F1B2FFF1C3E27010050275F286F297F2A8F2B9FFF0F202CCF 2DDF1F7F208F26A713C0323FFF334F2EEF2FFF310F1D3F381F392F3A3FFF3B4F3FA00E103C9F3D AF3EBF3FCF40DFFE36225F430F247F258F26982248428F6490F44AF45BF1CD4394C5F4D64321 433384DD420076D2043457F02834F90519F52A53C62535F546379CE7254C4321F4D5531362CA 156FFF503824709D16B54C4370F59E758D17B5AAF038254087054C43C7F59E637C722415E7F03 82284865215007D0FE2954C441EF6167532F6306071001A0E0EB063E54758597D384751662F0 382FA420740740EB054C44C4F59E75CA1CB6A2F6333560890746E21300790FE6563E41190518F 529F212A54965310FF552F563F72AC5855531058DF59EF72ABFF5BF853105CAF5DBF72AB5FC65 310685FF7696F72AB6B7A30708847FC720A2653FF54970DE082AF752F84C658560EF085DFF778 BF84C55BF9317B4889AE7CE884D4FF5FC75A508C7F7FFF84C56B7926F265F1FF7F0F52CF53DF2 6C5708F86DF955F7706FD2700312CAF8A1F5AFF7A989AB1779FFF8D7F5ECF7E469AB17B4F616F 6E5F638AFF9AA2605F656FA4EF678A9AA2645F90BFFF6A7F925B8F996CDFACDFEFA658933FF 7944F992F966731970F981FB5CF9A38DE329AEF9BFF9D0F9E1A329EEF9FFF7FA10FA218B520BF 6FA3EFA4FFA60C32FFA6FFA80FC55FAA2D0E01C78FAC5FAD6FFD927932AF3FB04FC98FB26FB2 1B3AFF7B4BF2126965832B77FB88FD6379A38DF26F0D77F8A2F21359E0B33BF5C06FFB2126A2 0933CB9FCCAF2126924CB532FFE1DFB4EFB5FFDA55D76FD87FE75F9A38FF85A0E91FBC7FBD8F 9E2958CFDF4FEFFFA2095C9FC43FF2FFA5EE604FC86FF6DFFFAA1E644FE2AFFB0F924C684FD0 AFF3FBFD2CFECA2E53FE64FEB2F966734E90FFFEA1F07CF9A389AC0098FEE0FEF1F9E29FFBB30 0D6FF20FF31F0CB8F4CFF5DF035FFFA5FDECC0154FFA1FFB2FAA3C0D30197FF7FE4FFF5F926A35 013F024F1B8F046FDF0D2105AF06BF0B9F966735097F0A8FFF283F9A380EE22A1F0E9F0FAF9E47 12E2FF2DFF129F13AF2D46153F164F23CFA5FDDE36196F1A7F37CFAA2D361D9F1EAFB1FBF925 B3621AF22BF3BF24DF2D91FF2618833F844F2D37829F2AFF87EE92F1DE372DC889AF8ABF9E29 37890F32DFFF8E8E4CF23E08904F915F926A3B62424F7F275F286F4CC529EF4AEF59CF9A3838FF 2DCF4E4F2FEF9E1A778F51BF616FA209EF7B3F36AF656FA5EE3839DF3AEF695FFDAA2D383E0F5 52F402F925B7ECF431F0771AF453C92B1636F6C6F72A074626C3B5C9E106485C01A679E116E85 C07830756530F5785F65CB8035798A7AA17A5F7B69FF79747B9279FF7DCF7D8D7D0F7B3F798F FA659ED038835A8471842F853979747F856283CF879F875D86DF850F88D4393F63508C248D81 85A38D8092A22A5C54646560517074113368D17325BF40208EC670618F61716C3F7410565078 A0E0A078A04DE06463B4746C90A07291A0AA30708F11C46175AE605C617390A09200A34E5093 026E756D96A06192C004746F9300646A757374F9E0A0676892F0E0A07015650790114697490B 03090105C6E6F867155D16E036F7465209A70A994C0796C6DB0689E20749A70FF90FF920F931F 942F953F836099006060C9604173317410616678A09E208B8FE19A106C6020673130CB807F982 19BE09D949D318F9698309EE333DB67309ED26685D0A11263896073E039A0B36E70A109A2A47 410736EE86578749D3173968078006E40B674A3D155E069780095E079A4427F97504E7073E0B B40D75054009DF04EFAA4A278408EC39DD19D319B9073F0AE708E7697009730B2E06D696873E 0A78F106E609730756EA8D1659BC0977880A4F99DF04499B420504E600661896090B06820466F 6E7A748EB4749DE05F50AC905FF0772BA2409BE066AC905773E07468DE4267309BE09A0A07F0 6C9F106D00E5AE2472AE98666CAE06AD70B007CA62B00772AE02636290A04EA0FFB1F29091B2 62783095507891B3249750047065AE017363656C6CEF98C1ADD0AD71B38173A8407810CEC1AF AC81C680AF20B5E66CB5F562B5F5F39940B6046467B6E6B860B7E69DA0FDB6047690DF98FF9A 0F9B1F9C2F9D3FFF8FA19E6F9F7FA08FA19FA2AFA3B7ACB0FFA86FA97AA486A6C475B0CAB0977 0A727BFC1A1A7E89D6DC1BCBC3077C06675A0FD973062BC707880AC00A7A2C6EFA9987DA5EC 48B411B6D09550DDA3A76336FFCA7FCB8FCC9A85E0CD6FCE7FCF8FA682FFABF0B4A0AD10788 0D0DF68B0D20F9DBEFFC1BFC2C4B2B0A442D53FD646A52AD0F11E73AC00C951973077D06D70 6F8B04E0D76F456E40696C539752DD68B03177838EF0F0107678219710E655D1409660776EE3 56A611E3F2F9E513363046705F41A609E5A468B007FD016B60A60238393830307F1D81A060285E 0E5F071202191E8A3342F68C0E5F0F0D0EC616DA4C1685057BB90EA63ABF2336B606DF8106B4 6429552EBA5537562EC1173E9A6F16C46FC3063EC1173F0BC80A3AAD15F506D6C4D4E6067EBF 36672EE778F114A63EE31BBB2493FB36078F04EA0F8E0EC119550744CA76D90EC1104A07279F 151318EC3FA78EE506EBE20E402F2749DF0BE70E074703A2F2FB47097A06E4074732ED610635F F0E080AD702E15E1012FF4F066FC60652F7F97800642F4B50C370F5D3EE507790D65C90A1B59 07785E032F0E1F713FE686B32EC11EE81AE80F0D3EE81AF30D7F8F6F0B5EE8162F0C367BDA096

Property name	Value
	F0FE729571BE3004E0BB407410BB11AD10C7BB40B6D1AD706E626ABC6078F0D9A7F06F63AD4 1ED706B96D0A840FF9DE0FD94A4940070C1518F00AC0096E1E3EBA07880737973A490F0A1836 1F46C79AC0076EE5078A0FF789591D46764A4D06178A266FD61E3D0FBF091B5317656410231A 410EE505F50BB9790AD1070C130B48004506CADC0DFA41295D0C4F07800D60178788077D0E7 AC10F09178A07361A84095500373FFF28106910451F281B5905FF04E705F504D966078C130F3B 06F7978F05CFDA410709790781060309660BC31B6D03BBC80FD8064AC107830F2B06264FFB76 09660BC81B480A491CD01A4929790C9BDE0655C0450727AFD62B86077F89295500D31680B73 7110013167FE760E090CC1BE50955011200E730F84DF0F330442FF510EA111136A09616020E5C 4A0764550776BB3516B601272BFB4705640C401F7B1FAA0B97265BDE0DF13D5A49096E0A5010 0C074E4909550FF0CA0FCC11567BE706E40BDA0BC809651FFF2A0BE70BDE17821CCF0255020D 0DE00FFF2A0C1110AB2B351BA8015701361BB40FF7830AD21156178217810B911F2A0EBB1DF0 BE10CA09660EBB1BBB07017D2A3F0FF90B0BD80C4729550B482C111D8A1F5909FB490D66100 00B490BBA17070A960FB8B40BC616960201AF6A6025FF096E0FB8E26A400777821A5D2BC304E 109660FF8960AD10BD92F590BC50A9C10591ECF0BF9750A4915650BE209651B3516EEBA17FAC 9025B0B4901AE1B490E3D0965163FE78BC8095F0C9A195D0B3600A41D8C0EF24C1093196609E 2063F2B117D29E20EF24B3BDA09550B6E06826231532F3C0F667BB72FF916307017137820EB C01F26E2743019B229320370747862FC785C1B10C5004E70A400BC501360FBF42106116C18617 41009F13D40E1112FA4D2C3F0A4308ED2770291666DF72A60E2B0FB4120F7900FF09642C3F0FF A4D034F04E9009A096E0BB5085D095D0BE6CA4906E4013601970F2A0759610FFDC42B871A3D 1FBD1A9F1FB959582A410FF78A0FD31A970B5900CA03233BC043140FF3223E72A0030FCD2971 18EF0BD20FBC1FC6C760411BD21F4B0BD5036B195F0FF78103732B351F09150A0F7B1A970C14 1CF9711BD202B3095F0202EE36436B6FF63503752DC5137BF38CF39DF37106730FBFD208F10F D803BAF3CBF3DCF6C6B60DFBD20DB003B6F403F4145293A2C6F90F73F0F43FF4125626E704CB 1452F36E3FF55B042CF479F48AF49BF370168D04B12FF379F4C7F4D8F459D6D004B1F50AF51BF FF52CF37015B704FAF554F565F5765F701FFB630F700C1309550DC33BB72BA5FBB6FFBFC7FBD8 FBE9FDADFC0CFDC5FC2EFC3FFFFC50FA3B16AF0D2CF650ADDA125B1ACF0C9E8B9205714406E3 AABE067B1A861792CABE065EBB075F1C14E20AEA06D60F631382085E03AD3E850AB404D2D6E A1336EE276B0B0474D542DAEA06EC129AB411C6369F59175B376B05553201826204374706120 61292EFC0D0A5C526C9278D06CE10A0078103DABD043F57178E0723572352A7EFFF4CF73EC5C 445D0F5E1F5F2F603F614F7F95B65C525960A619697F6A8F6B9F4F726F09802120ABE1EE9096E 020F649F39006C120419071202BF0FF21B6207B206D312E8190EE7079FFE0FA20D8C02013605C F07BA06DF0AB807F5CD2E0807120FF107121A402840165FE6B3A107E1F7F2F803EA7707A40B7 D07FA61976668ED208D10312975377F073F300008561617880C0C0A08C21D8A0FFFDD0D8D08F 1195718C31D607907130907F8C21A9688EA6C8958D86A526796139FE39EA408CF7A410B4801B E077E18DEAFFD3A28F0A9404C8956381910994048D24BF62C0A6C5932F943F954FA5443996CB BF144282F2E3409A0F9B1F9C2B329D0FBB9E1F9C1C33A01FA12F9C1C34A32FBBAA43F9C1C35A6 3FA74F9C1C36A94FBBAA5F9C1C37AC5FAD6F9C1C38AF6FDBB07F9C1C3997F3B39633B41C7B20 FF70E09CF4B5DFB6E8A004B7EFB6E8A314FFB9FFB6E8A624BC0FB6E8A934BE1FB6E8FFAC44C02 FB6E8AF54C23FB6E8B264C44FFFB6E8B574B2CF6C9364D296F813601BE0FFB3B0E4A0980F991F C84FB3B4DE7296E9FF71003061C60B95D49716EE0179927071FFED60029062A07360EB32CB1F CC2FCD3FFFC46D0CCECA1FF10FC6D35FD46FD57DFE1A0F780D6CC7BA0063067D81FD92F7 7DA3FDB4696BC452D607A407D607357DD0FDE1F910935B41C54257220DE4767B1E213DE5E97 165004962EF1FE540521E21FE68FDF2FD05F9754D7807F0B81FF21E94FEA5F910980D096CB4CF F7BC2D7800C71EE3FEF4FF05DD0CCF224FFF2202360F2FFF40FF08ADBCCF224E6375FF7AFF8BF F0D5695096DA4D2C6069BF7AB0F2769CE5FCOFFD1FF0D534FEAFFFFF9A00400CF01DFF0D5C9 CCF75F712FF005F062FF06C8120083F0945052F0ACFFDF07B370CBFFFB1E63209AF0F4FF06CFF 6E80115F12650E4F13EFF07BB41C121AAFA31417CF18DFB3B43796BC445960FE6BF70F1CCF1D DFD0CC73808D202E60FF79A0F27F20EF21FF1EB1DBCC2417201FFF25EF1DEEFE9C2417FB7F2A7 FF04FFA4FF1F267204163E8708B9012CF2F2FFFF4FF314F096332DF33EF34FFFA0FFB18FF37BF38 CF39DFFE5FFF6F3CAF3DBF3ECFF031F042F41FF430F441F07DF08EC474CE3E6CFD135526576E 1F0CAEF48BFFFB3FC639456C0963D2274F4F505F516FF3DB461A5C517581F0D80F55BF56CFFB C65796BC498B906CC04DB0593F5A4FFF499F0C9F0DA9474F5F7F608F10FF120CFF638F649F65A F158F169C68AF69BF6ACFF1A1F1B2C6DCF6EDF6FEF1EAF1FB872EFFF73FF750F22FF240F77CF7 8DF79EF27BFFF28CC7D1F7E2F7F3F2C4F2D5C823F834FFF845F30DF31EF8783176F88EF356F367 FFF82098CFF8E0F3A5F3B6F872991EF92FFF3F4F717F416F96DF97EF449F9A0F46BFFF9C2F9D3F 49EF9F5F4C0CA17FA28F610FFFA4AF632CA69FA7AF662FA9CF684CABBFFACCF6B4FAEEF6D6CB 0DFB1EF706FB40FFF728CB5FFB70F758F769F914FBB8FBC9FFF7ADF7BEF8C5FC06FC17F802F813 FC4DFFFC5EFC6FF857F868FCA2FCB3FB7DF8ACFF8BDF1BEFD08F8F0FD2AF81FAD4AFD5BFFF94

Property name	Value
	0F951F8729D99FDDAAF98FFB92F9B1FFFDE8FDF9F9E4FE1BFA06FE3DFE4EFA39FFFE70F4C0CE92F EA3FA8BFEC5F632CEE4FFFEF5FADDF17F684CF36FF47FB2FFF69FFF6D6CF88FF99FB81FFBFF72 8CFDAFFEBFFFB3FBE4FD8FF033F044FC28FC39FD40FFF081F092FC7DFC8EFC08F0D9F0EAFCD2 F3FCE3F11DF12EFFF8FD27FD38F2034FF174F185FD6DFD7EF82181C5F1D6FDBBFFDCCF872921 4F225FE0AF00DFE2CF263FFF274FE5FF296FE81F2B8F2C9FEB4F2EBFFF4C0C30DF31EFF06F340F 632C35FF370FFFF58F392F684C3B1F3C2FFAAF3E4F6D6CFF403F414FFFCF436F728C455F466F04 EFFF05FF20AF4AEF4BFF0A3F0B4F1BBF4FCFFF50DF0F8F109F543F554F565F14DF15EF9F598F5A9 F473F1A2F1B3F20355EFFFF600F1E8F1F9F8218640F651F236F247FFF872968FF6A0F285F488F2A 7F6DEF6EFFFF2DAF711F2FCF733F744F32FF766FA5BCFF788F799F381F7BBFAADC7DAF7EBF3D3 FFF80DAFFC82CF83DF425F85FFB51C87EFFF88FF477F8B1FBA3C8D0F8E1F4C9F4DAFFF685F929 F93AF51EF52FF636F977F988FFF573F584F9BEF9CFF9E0F5C8F5D9FA13FCFA24F8EEF61DF62EF2 036A6AFA7BFFF663F674FC9C8ABBFAACF6B1F6C2FCED9FFB0AFB1BF700F903F722FB59FB6AF75 5FFFB8CF777FBAEFBFF7AAFB1ED6CC03FFFC14F7FCFC36FF28CC55FC66F84EFC88FFFF7ACC A7FCB8F8A0FCDAFFCCCF9FD0AFF8F2FD2CF01ECD4BFD5CF944F955FB00FFFDA4FDB5F999F9 AAFAB1FDF2FE03F9EEFFF9FFFE39FE4AFE5BFA43FA54FE8EFE9FF89D6967166ED206D6174E1A4 05A8F631D7AC537562746CA06520456D702A80733520AFE5FEF6FF07FA90532E1AC491700BF1 6F0EAF0F34FF45FF56FF0FE33E1ACC1F2E5526566657216F016E0FFF96FFA7FFB8FFC96B39CF86 6FE6FFF7F47008F019FEC1C426F6F4E70541FA940F3200493FC87CD6C426962A26CA910677261 F9007904930706EFFCC3D7AC544F43204802652A933B7D7D7B5C2A6C5C64F0F0F92074ED20F8 C030D03130353010D23210D31090123811343464EC0037383608643663029032653533303431 3538133012103463FC3532C310AE90BDC0C310E6E012D0FE3313B014801134153EA97010D1B4 40006366313165306131726216D0616510A0179F188C330F16F0197110D0042066663039FF161 61AEF11711BBD1B9D1A121E321B16FF1E1E1E97209F21AF22BF23CF24DF25EFFF26FF280F291F 2A2F2B3F2C4F2D5F2E6FFF2F7F308F319F32AF33BF34CF35DF36EFFF37FF390F3A1F3B2F3C3F3D 4F3E5F3F6FFF40F418F429F43AF44BF45CF46DF47EFFF48FF4A0F4B1F4C2F4D3F4E4F4F5F506F DF517F528F539F54AF559C6455951E25FF578F589F59AF5ABF5BCF5CDF5DEF5EFFF600F611F62 2F633F644F655F666F677FFF688F699F6AAF6BBF6CCF6DDF6EEF6FFFFF710F721F732F743F754F7 65F776F787FFF798F7A9F7BAF7CBF7DCF7EDF7FEF80FFF820F831F842F853F864F875F886F897F FF8A8F8B9F8CAF8DBF8ECF8FD90EF91FFFF930F941F952F1E3313B016211E8196D2D43734110 43410C13619A19752FFE6E097311A62991F9A2F9B3F9C4F9D5F5F1171164210C1958F56B663D7 9064D43938A0F062A1103313811340AA390F206612906413216216F0331F8FA30662301340119 03662F037623661A18010901F1FA61FFFA72FA83FA94FAA5FAB6FAC7FAD8F202FFFAF8CAE0FB1 9FB2AFB3BFB4CFB5DFB6EFFF7FFB90FBA1FBB2FBC3FBD4FAE6FBF6FFF80FC18FC29FC3AFC4B FC5FC6DFC7EFFF8CFFCA0FCB1FCC2FCD3FBE5FCF5FC07FFFD17FD28FD39FD4AF1CDE10C4D59 50F900200D7C0
<b>PidTagSensitivity</b>	0
<b>PidTagSubject</b>	Canceled: Lunch?

The following shows the resulting iCalendar file.

```

BEGIN:VCALENDAR
PRODID://Microsoft Corporation//Outlook 12.0 MIMEDIR//EN
VERSION:2.0
METHOD:CANCEL
X-MS-OLK-FORCEINSPECTOROPEN:TRUE
BEGIN:VEVENT
ATTENDEE;CN=sito@contoso.com;RSVP=TRUE:mailto:sito@contoso.com
CLASS:PUBLIC
CREATED:20080208T175248Z
DESCRIPTION:When: Friday\, February 08\, 2008 12:00 PM-12:30 PM (GMT-08:00)
Pacific Time (US & Canada).\nWhere: Fourth Coffee\n\n*~*~*~*~*~*~*~*~*~*\n\nOops! Forgot I have a meeting today. Maybe we can try again sometime

```

```

next week.\n
DTEND:20080208T203000Z
DTSTAMP:20080208T175248Z
DTSTART:20080208T200000Z
LAST-MODIFIED:20080208T175249Z
LOCATION:Fourth Coffee
ORGANIZER;CN="Elizabeth Andersen":mailto:eandersen@contoso.com
PRIORITY:1
SEQUENCE:1
SUMMARY;LANGUAGE=en-us:Canceled: Lunch?
TRANSP:TRANSPARENT
UID:040000008200E00074C5B7101A82E008000000010C4F838346AC8010000000000000000
0100000002009EB53F098B249AD66CBE6BB3B8B99
X-ALT-DESC;FMTTYPE=text/html:





```

The following table lists the properties on the Calendar object that Shu receives.

Property name	Value
<b>PidLidAllowExternalCheck</b>	TRUE
<b>PidLidAppointmentDuration</b>	30
<b>PidLidAppointmentEndWhole</b>	08:30:00.000 PM 2/8/2008
<b>PidLidAppointmentNotAll</b>	FALSE

Property name	Value
<b>owPropose</b>	
<b>PidLidAppointmentSequence</b>	1
<b>PidLidAppointmentStartWhole</b>	08:00:00.000 PM 2/8/2008
<b>PidLidAppointmentStateFlags</b>	7
<b>PidLidAppointmentSubType</b>	FALSE
<b>PidLidAppointmentSequenceTime</b>	05:48:33.000 PM 2/8/2008
<b>PidLidAutoStartCheck</b>	FALSE
<b>PidLidBusyStatus</b>	0
<b>PidLidCleanGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E008000000010C4F838346AC801000000000000000010000 0002009EB53F098B249AD66CBE6BB3B8B99
<b>PidLidConferenceType</b>	0
<b>PidLidInvited</b>	TRUE
<b>PidLidGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E008000000010C4F838346AC801000000000000000010000 0002009EB53F098B249AD66CBE6BB3B8B99
<b>PidLidLocation</b>	Fourth Coffee
<b>PidLidOwnerCriticalChange</b>	05:52:48.000 PM 2/8/2008

Property name	Value
<b>PidLidReminderDelta</b>	1080
<b>PidLidReminderSet</b>	FALSE
<b>PidLidReminderSignalTime</b>	02:00:00.000 AM 2/8/2008
<b>PidLidReminderTime</b>	08:00:00.000 PM 2/8/2008
<b>PidLidResponseStatus</b>	5
<b>PidTagBody</b>	When: Friday\, February 08\, 2008 12:00 PM-12:30 PM (GMT-08:00) Pacific Time (US & Canada).\nWhere: Fourth Coffee\n\n*~*~*~*~*~*~*~*~*~*\n\nOops! Forgot I have a meeting today. Maybe we can try again sometime next week.\n
<b>PidTagCreationTime</b>	05:57:02.941 PM 2/8/2008
<b>PidTagImportance</b>	2
<b>PidTagLastModificationTime</b>	05:57:03.222 PM 2/8/2008
<b>PidTagMessageClass</b>	IPM.Schedule.Meeting.Canceled
<b>PidTagMessageLocalId</b>	1033
<b>PidTagReplyRequested</b>	TRUE
<b>PidTagResponseRequested</b>	TRUE
<b>PidTagRtfCompressed</b>	cb: 1001 lpb: E5030000B00B00004C5A4675FB3BB89A03000A00726370673132358232034368746D6C310331F862696404000330010301F70A80FF02A403E40713028010830050045608559F07B211B50E510



Property name	Value
	301020063680AC07073657432060006C311B533DB044614473012BF02003403C5165AF9074069620510028011C308EF09F7B63B1ABF0E303511B20C60630050330B090164333616E00BA534205910822A5C0EB20190671F603300203C21444F4354590050452048544D4C20005055424C49432022402D2F2F5733432220444454442134332E32222045F84E223E11C31FD720800AA323BCFC31392090214223AD14D024BF2471E31F70261045414423AD0EF1278F050E10360EF03C4D455441C507B0412BB03D224709F0049014617405B02216F04F4E544D2370542C4005E1457814616EF4676506527613112E9100900220402030382E30302F70367438312F7130239E2A1F25A337823720905449544C45266EA6340EF0250D383520902F32DF7F310F1FF53421357028EF273F200435C116E03C424F445923AD1EE14739DF20513B01212D2D16F16E552E91740980200352203EA078FC742F00213ED005B000C005403E102F3B7F3C8F412F20043628B15020804449523D4C545223A0BF1FE33F82000044E51EE144E65C2020CE720AB146A214605C7103214587051F9B3828B15350414E201A4C4980472C4009F02D757347239144DF482E313438209046E12D21204641432C3119554A6CD3181047A9576809F03A4D300510506461792C4D3065199075BD0AC0792F41508001D02F50200E20A63A2F8021804D2D51C1335202C02028474D542D2F5051E1DE29218000D006900DE020076252D0865505F0485E26616D7002804D4A9726457819416E61505029F22E251C353635614CF24A794A87FD483D3914D035704962595F45CB0AA2FF5A080A8146270AB15ED8483D01C03561FE50405F42BF628F438F449F45AF46BFFF5FFF48DF49EF4AFF4C0F4D1F4E2F4F3AE71AC050010861746816F1012009E0FF57EF58FF5A0F5B1F73EF5D3F5E4F5F5FFF606F617F63DF7CCF64AF65BF66CF67DFFF68EF69FF6B0F80DF6D2F6E3F6F4F4EFBFC2A7E8BAF726F737F748F759F8E5FFF77BF78CF79DF7AEF7BFF7E5F973F7F2FFF803F814F825F836F847F858F9B4F87AF0788BF89CF4EFB4F6F7073211154BF6E627355EA5C276147014056C8719072676F054049C62014702E90206120078014B0FD0B80673F200470506057DCA73FA84FAA4D5060622E40772E40630391CF9D10511020400B7120730370AA71CF54412C803F50AE71656B57DF8DDFFF8EEF8FFF8B23FB34F9F6FA07FB5BFB40FFFB51F923F934F945F956F967F98DFC17FFB3A68A3112F3B3F398F200532A138600526337DC7F0
<b>PidTagS enderAd dressTyp e</b>	SMTTP
<b>PidTagS enderEm ailAddre ss</b>	eandersen@contoso.com
<b>PidTagS enderEnt ryId</b>	cb: 116 lpb: 00000000812B1FA4BEA310199D6E00DD010F5402000008045006C0069007A0061006200650074006800200041006E00640065007200730065006E00000053004D00540050000000650061006E00640065007200730065006E00400063006F006E0074006F0073006F002E0063006F006D000000
<b>PidTagS enderNa me</b>	Elizabeth Andersen
<b>PidTagS ensitivit y</b>	0
<b>PidTagS ubject</b>	Canceled: Lunch?

### 3.4 Recurring Meeting Scenario

This subsection describes a multi-step scenario in which an organizer, Elizabeth, sets up a recurring meeting with Shu, Patrick, and Anne, but cancels an instance that coincides with the company picnic. Shortly thereafter, Elizabeth corrects a typo in the Location field.

This section also documents Shu's tentative acceptance of the meeting series.

#### 3.4.1 Organizer's Meeting Request

Elizabeth organizes a weekly status meeting for Project Northwind on Wednesdays at 2:00 P.M. with Shu, Patrick, and Anne.

The following table lists the properties on the Calendar object that Elizabeth sends.

Property name	Value
PidLidAllowExternalCheck	TRUE
PidLidAppointmentCounterProposal	FALSE
PidLidAppointmentDuration	30
PidLidAppointmentEndWhole	10:30:00.000 PM 2/13/2008
PidLidAppointmentNotAllowPropose	FALSE
PidLidAppointmentRecur	cb: 80 lpb: 043004300B2001000000C02100000100000000000000008000000232000000A000000000000000 00000000000000000000003FC30CDF80E95A0630000009300000480300006603000000000000000 000000
PidLidAppointmentSequence	0
PidLidAppointmentStartWhole	10:00:00.000 PM 2/13/2008

Property name	Value
<b>PidLidAppointmentStateFlags</b>	3
<b>PidLidAppointmentSubType</b>	FALSE
<b>PidLidAttendeeCriticalChange</b>	09:33:20.275 PM 2/8/2008
<b>PidLidAutoStartCheck</b>	FALSE
<b>PidLidBusyStatus</b>	1
<b>PidLidCleanGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E00800000003046642B576AC80100000000000000010000 000622C639E40D09342B747A1672730CBBA
<b>PidLidCollaborateDoc</b>	
<b>PidLidConferenceType</b>	0
<b>PidLidDirectory</b>	
<b>PidLidInvited</b>	TRUE
<b>PidLidGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E00800000003046642B576AC80100000000000000010000 000622C639E40D09342B747A1672730CBBA
<b>PidLidIntendedBusyStatus</b>	2
<b>PidLidLocation</b>	Conference Room 123
<b>PidLidNetShowUrl</b>	
<b>PidLidOn</b>	



Property name	Value
me	
PidTagMessageClass	IPM.Schedule.Meeting.Request
PidTagMessageLocalId	1033
PidTagOwnerAppointmentId	3249022936
PidTagResponseRequested	TRUE
PidTagRtfCompressed	cb: 5789 lpb: 99160000ED5C00004C5A4675DF873B2307000601010B606E6731303266350064007263700DD0 0E00321D0C60630D4401340131737473E26805706263681035090010C03433371044680EB011 8762699311910D773333131666651393F87468650780135714C7145001403914C7637301E802A 412D064698F0336020010C00AC073657402D1507072713200002A0AA16E5A6F1940200DF01A9 13613A030383530341B1101D01B00347DF3076D02833334180F191F1A281B42C71B041AE21FE 17D436106D00721FD05D06114C01CD411A01D5603E31E2F3F19FB01301B621AA21B4020C66C 69FB21511CD4311B2017FF235F1A1F1B2FFF1C3E27010050275F286F297F2A8F2B9FFF0F202CCF 2DDF1F7F208F26A713C0323FFF334F2EEF2FFF310F1D3F381F392F3A3FFF3B4F3FA00E103C9F3D AF3EBF3CF40DFFE36225F430F247F258F26982248428F6F490F44AF45BF1CD4394C5F4D64321 433384DD420076D2043457F02834F90519F52A53C62535F546379CE7254C4321F4D5531362CA 156FFF503824709D16B54C4370F59E758D17B5AAF038254087054C43C7F59E637C722415E7F03 82284865215007D0FE2954C441EF6167532F6306071001A0EF0EB063E54758597D384751662F0 382FA420740740EB054C44C4F59E75CA1CB6A2F6333560890746E21300790FE6563E41190518F 529F212A54965310FF552F563F72AC5855531058DF59EF72ABFF5BF853105CAF5DBF72AB5FC65 310685FF7696F72AB6B7A30708847FC720A2653FF54970DE082AF752F84C658560EF085DFF778 BF84C55BF9317B4889AE7CE884D4FF5FC75A508C7F7FFF84C56B7926F265F1FF7F0F52CF53DF2 6C5708F86DF955F770FD2700312CAF8A1F5AFF7A989AB1779FFF8D7F5ECF7E469AB17B4F616F 6E5F638AFF9AA2605F656FA4EF678A9AA2645F90BFFF6A7F925B8F996CDFACDF6EFA658933FF 7944F992F966731970F981FB5CF9A38DE329AEF9BFF9D0F9E1A329EEF9FFF7FA10FA218B520BF 6FA3EFA4FFA60C32FFA6FFA80FC55FAA2D0E01C78FAC5FAD6FFD927932AF3FB04FC98FB26FBB2 1B3AFF7B4BF2126965832B77FB88FD6379A38DF26F0D77F8A2F21359E0B33BF5FC06FFB2126A2 0933CB9FCCAF2126924CB532FFE1DFB4EFB5FFDA55D76FD87FE75F9A38FF85A0E91FBC7FBD8F 9E2958CFDF4FEFFFA2095C9FC43FF2FFA5EE604FC86FF6DFFFAA1E644FE2AFFB0F924C684FD0 AFF3FBFD2CFECA2E53FE64FEB2F966734E90FFFEA1F07CF9A389AC0098FEE0FEF1F9E29FFBB30 0D6FF20FF31F0CB8F4CFF5DF035FFFA5FDECC0154FFA1FFB2FAA3C0D30197FF7FE4FFF5F926A35 013F024F1B8F046FD0D2105AF06BF0B9F966735097F0A8FFF283F9A380EE22A1F0E9F0FAF9E47 12E2FF2DFF129F13AF2D46153F164F23CFA5FDDE36196F1A7F37CFAA2D361D9F1EAFB1FBF925 B3621AF22BF3BFF24DF2D91FF2618833F844F2D37829F2AFF87EE92F1DE372DC889AF8ABF9E29 37890F32DFFF8E8E4CF23E08904F915F926A3B62424F7F275F286F4CC529EF4AEF59CF9A3838FF 2DCF4E4F2FEF9E1A778F51BF616FA209EF7B3F36AF656FA5EE3839DF3AEF695FFDAA2D383E0F5 52F402F925B7ECF431F0771AF453C92B1636F6C6F72A074626C3B5C9E106485C01A679E116E85 C07830756530F5785F65CB8035798A7AA17A5F7B69FF79747B9279FF7DCF7D8D7D0F7B3F798F FA659ED038835A8471842F853979747F856283CF879F875D86DF850F88D4393F63508C248D81 85A38D8092A22A5C54646560517074113368D17325BF40208EC670618F61716C3F7410565078 A0E0A078A04DE06463B4746C90A07291A0AA30708F11C46175AE605C617390A09200A34E5093 026E756D96A06192C004746F9300646A757374F9E0A0676892F0E0A0915650790114697490B 03090105C6E6F867155D16E306F7465209A70A994C0796C6DB0689E20749A70FF90FF920F931F

Property name	Value
	<p>942F953F836099006060C9604173317410616678A09E208B8FE19A106C6020673130CB807F982  19BE09D949D318F9698309EE333DB67309ED26685D0A11263896073E039A0B36E70A109A2A47  410736EE86578749D3173968078006E40B674A3D155E069780095E079A4424797504E7073E03  9393068B039FE366DD0A4A278408EC39DD19D319B903B73F0AE707697009730B2E06D699E68  73E08F106E609730756EA8D15E659BC07880A4F99DF04499B4201A504E6061896090B0682046  E86F6E748EB4749DE05F50AC90AD5FF077A2409BE066AC905773E07874684267309BE090A0A7  F06C979F106D00AE2472AE98666CAE062BAD70B00762B00772AE026362FF90A04EA0B1F29091  B26278309550789113B32497507065AE01736365BC6C6C98C1ADD0AD71B38173A840BF7810C  EC1AC81C680AF20B5E66CB5F5CE62B5F59940B6046467B6E6B860F7B7E69DA0B6047690DF98F  F9A0F9B1FFF9C2F9D3F8FA19E6F9F7FA08FA19FA2AFFFA3B7ACB0A86FA97AA486A6C475B0CAB0  FF9770A727C1A1A7E89D6DC1BCBC3077C0F66675A0973062BC707880AC00A7A27FC6EFA998A  5E47530592049C0962048FFB411B6D09550DDA3A763A6A0CA8FCB9FFCC985E0CD6FCE7FCF8  FD092ABF0B4A0FFAD107880D0DF68B0D20F9DBEC1BFC2C4BFB2B0A442D53FD646A52AD0F173  AC00C7C951973077D06D706F04E0D76FE2456E40696C53975268B07783DB8E0F01076782197  1055D14096607C776EE346A611E3E2E50385E0307F4B606B51D019E503A645E715AE9137CA36  EC616DA4C16850BB90E8C395ABF2336B606DF8106B42955251EA05537562AE7173A6F16CFA46  FC3063EA7173F0BC80AAD15F50A86D6C4D4E6067EA5372ECD7D98F114A63EC91BBB249B3607  8F0CF4EA0F8E0EA719550744C6D90EA71A904A07279EFB1318EC378ECB03E6EBE20E3F2F0D49  DF0BE707470383A2F2FB47097A06E40732E5DD610635FF0E080AD702EE1012F45F35066FC6065  2F7780064BA2FE5F133F433ECB077905C90A1B5B5907785E032EF41F573686B32FFEA71ECE1A  E80EF33ECE1AF30F756EF15B5ECE162EF2367BDA096F0729571FFBE3004E0BB407410BB11AD10  BB40B6D171AD706E626ABC6078F0A7F06FF663AD41EBD06B96D0A8409DE0FBF4FFA4940070C  1518F00AC0096E1EA00788038737973A490EF0183616C793DAC0076ECB078A0FDD895916764F  5A4D06178A266FBC1E3C0EEF1B531FE7656410091A410ECB05F509790AD10EE70C130B48002B  06CADCOA41295D0F7C4F07800D60178788077D0AC10EEF1F978A07361A840955001D3F0E104F  17F02B1F0E1B5905FF04E705F5096607853C130F2106F7978F05CA41070FF9790781060309660B  C31B6D0BC80FBE0CE64AC107830F1106264B76096607FBC81B480A491CD01A4929790BDE065  F25C02B0727AFBC2B860F6F295509D0B916809D37110FF9167760C69FF0B21BE50955011200C  D30DE40D9302A277FDB10D010F736A07C16020C4A076F94550776BB3516B6010D2B4705640E  FC401F611F900B97265BDE01235A490F796E0A501FF2074E48095500B00FB21FF13C7BE706E40  BDA0BC809651F100BE70FFBDE17821CCF0255020D0DE00F100C111FF0912B351BA8013D011C1  BB407830AD21FF13C178217810B911F100EA110A410B00F79660EA11BBB0701632A3F090B0BD  B0FFC4729550B482C111D8A1F3F0B490D661E7FE60B490BBA17070A960BB40BC61FE69602019  56A6025FF096E0E8259650FF39107821A5D2BC304E1096608960AD10FFBD92F3F0BC50A9C103  F1EB509750A491EF5650BE209651B3516EEA01AC9025B09FB4901941B490E3C096516378BC80  FF95FC9A195D0B36008A1D8C023210791FB96609E2063F1116329E202313BDA0BB9550B6E0  6824831392F22067BB72FDFDF16301D015737820EA2025427430071812279201D0747862785C  FF1970C5004E70A400BC5011C0F2810471FE6C16C1741008513D40E111A4D2C3F0CBA4308ED2  7700F1666D28C0E2B0FDF9A120F5F00E509642C3F0A4D034F0BF4E90080096E0BB5085D095D0  6CA490EF6E4011C017D0F100759610DC42BB71FFA3D1FA31A9F1F9F59582A41078A0FB91FFA9  70B5900B003093BC042FA03083E7E93F9730FB2397118EF0BD20FA216C76FF0271BD21F310BD  50351195F078103592FFB351EEF150A0F611A970C1419711BD20F3299095F0202EE3543516635  035B2FFDC51361F372F383F35706730BD208F10EFFBE03A0F3B1F3C2F6C6B60BD20DB00F739C  F3E9F3FA529388C6F903D6F425FFD3F85626E704951438F354355B0412FFF45FF470F481F35616  8D0497235FF4ADFF4BEF43FD6D00497F4F0F501F512F3561FF5B704E0F53AF54BF55C5F561B6  30F560FFC1309550DC33BB72BA5FBB6FBC7FBD8FFFBE9FDADFC0CFDC5FC2EFC3FFC50FA3B17F  6AF0D2CF636ADDA12411ACF0E5B820025712A06E3A204F63637F2E406DC00151F0306AE07880  A400733F00906C008F2065805CE0A832322F6631F4C0E5F1382074322D703AB3E600AB404D20  5F506E41336E836028474D542D1EC06E612939AB416369F3F175B376B05553302026204374705  F806129782E0D0A5AB26AE278D06B30437FAC00658078D01B4176516E2185E033F371F571F52  A7E74EF740C5AA45B6FFF5C7F5D8F5E9F5FAF95B65AB257C0D0296767DF68EF69FE48656C00EB  812CC5740C4C2A5172717596E26BA0FB70E02A5020FD06BBF6ED1FE701B40FF83C2AC006EC0  12A0835095F02E306BA09BF35085D346C99066106B616E30BDE9106F105078D071E671F5543F  31D46B7381C64501F07AC9902E61FFE8917E5F7F6F6A1BA7707A60B7D0D029FF7686903207310  172975378106C707BB0E1EFC061783236DD309021D8A0FFFC30D8D0798195719031D60779812  EFOFF9021A96892A6C8959186A5267981A640FFE8A090F7A410B4801A40780191EAD3A2FF930A  9804C89561E19509980491246120DFA6C5972F983F994FA544399ACB12A2BFFD8173C09BF39E  4F9F5FA06732A10FBBA21FA01C33A41FA52FA01C34A72FBBA83FA01C35AA3FAB4FA01C36AD4F</p>

Property name	Value
	BFAE5FA01CE330B06FB17FA02B38B36FDBB47FA01C399BF3B79633B81C7B40FF70A0A0F4B9DF BAE8A404BBEFBAE8A714FFBDFBFAE8AA24C00FBAE8AD34C21FBAE8FFB044C42FBAE8B354C63F BAE8B664C84FFFBAE8B974B6CFCA9363329AF811C01A40FFB7B0E4909C0F9D1FCC4FB7B4DE72 9AE9FF70C02EC1CA0B99D49B16EC6179B27031F7EBC000F0610068D861EF90CF1FD02FFFD13F D246D4CCB01FD70D3C6D75FD86FBFD97FE1A0F5E0DACC7BC0049067DC1FEFDD2FDE3FDF46 9ABC452BC07A60E730AE73E10FE21F950935B81C5423D2BC20476611E613E25E9B165002F6FD 2D51540381E61FEA8FE32FD45F9B54BFD8009E1FD81ED4FEE5F9509369ABCFFE4C7BE2DB800A D1F23FF34FF45DD4CCFF624F62021C0F6FFF80FF48ADFCCF624BFEA37FBAFFCBFF4D567B09AD A4D2AC0FE697AD0F676A0E5000F011FF4D58130FF02BF03C8A40404CF05DFF4D5CDCC0375EFF B12045F0A2FF46C360C2F0D36092FFB0ECFF47B3710BF03B1EA320DAF134FFFF46CDE0155F16 65124F17EFF47BB81C5F161AA7141BCF1CDFB7B4379ABC44FD57C06BFB0F20CF21DFD4CC72D 09120FF2CC079C0F67F24EF25FF22B1DFCC2817FF241F29EF21EE029C2817FF7F2E7FF44FF3FE4 FF66720416B60586116CF332FFF8FF354F0D6336DF37EF38FFFE0FFF18FF3BBF3CCF3DDF025F0 36F40AF41BF42CFFF071F082F45FF470F481F0BDF0CEC4B4CFBEACFD535526BC0E5F0CEEFC4BF EF3FFFCA39496C0D63D627534F545F556FDF46FD1E5C51831258BF59CF5ADFC669ABCFE498F 906B1051B05D3F5E4F4D9F109FFF11A94B4F637F648F14FF160C678F689FFF69AF198F1A9C6CAF 6DBF6ECF1E1F1F2CFF71CF72DF73EF22AF23B876EF77FF790FFF26FF280F7BCF7CDF7DEF2BBF2 CCC811FFF822F833F304F315C863F874F885F34DFFF35EF8B831B6F8CE9396F3A7F860990FFFF9 20F3E5F3F6F8B2995EF96FF434F757FFF456F9ADF9BEF489F9E0F4ABFA02FA13FFF4DEFA35F500 CA57FA68F650FA8AF672CFFAA9FABAF6A2FADCF6C4CAFBF80CF6F4FFFB2EF716CB4DFB5EF746F B80F768CB9FFFBB0F798F7A9F954FBF8FC09F7EDF7FEFFF905FC46FC57F842F853FC8DFC92FCA FFFF897F8A8FCE2FCF3FBBDF8ECF8FDF1FEFFD48F930FD6AF85FAD8AFD9BF980F991FFF8B29D D9FDEAF9CF9FBD2F9F1FE28FE39FFFA24FE5BFA46FE7DFE8EFA79FEB0F500CFFED2FEE3FACBFF0 5F672CF24FF35FB1DFFFF57F6C4CF76FF87FB6FFFA9F716CFC8FFFD9FBC1FFFBF768C01AF02BF C13FC24FFDCFF073F084FC68FC79FD80F0C1F0D2FFFCBDFCCEFF108F119F12AFD12FD23F15DFC F16EF038FD67FD78F20341B4F1C5FFDADFDBEF8618205F216FDFBFE0CF8B29FF254F265FE4AF 04DFE6CF2A3F2B4FE9FFFF2D6FEC1F2F8F309FEF4F32BF500C34DFFF35EFF46F380F672C39FF3B 0FF98F3D2FFF6C4C3F1F402FFEAF424F716C443F454FFF03CF476F768C495F4A6F08EF09FF24AFF F4EEF4FFF0E3F0F4F1FBF53CF54DF138FFF149F583F594F5A5F18DF19EF5D8F5E9FE74B3F1E2F1F 3F203562FF640F228FFF239F8618680F691F276F287F8B296CFFF6E0F2C5F4C8F2E7F71EF72FF3 1AF751FFF33CF773F784F36FF7A6FA9BC7C8F7D9FFF3C1F7FBFAEDC81AF82BF413F84DFB3CFF 86CF87DF465F89FFB91C8BEF8CFF4B7FFF8F1FBE3C910F921F509F51AF6C5F969FFF97AF55EF56 FF676F9B7F9C8F5B3F5C4FFF9FEFA0FFA20F608F619FA53FA64F92EFF365DF66EF2036AAAFABBF 6A3F6B4FFFDC8AFBFB0CF6F1F702FD2D9B4AFB5BFFF740F943F762FB99FBAAF795FBCCF7B7FF FBEEFBFFF7EAF21FF16CC43FC54F83CFFFC76FF68CC95FCA6F88EFC8FFBACCE7FFFCF8BE0FD 1AF00CCD39FD4AF932FD6CFF05ECD8BFD9CF984F995FB40FDE4DF5FFF9D9F9EAF1F1E32FE4 3014D23214D31490381534043464F000373836643602630690326533334310C3538173016103 4633532BFC710B290C1C0C710EAE016D03317B03F18801534193EAD7014D1B84063668031316 5306131621AD0DC616514A01B9F1C8C331AF01D71C314D00820666630391A161EEFFF15711FB D1F9D1E1222321F16221E2297FF249F25AF26BF27CF28DF29EF2AFF2C0FFF2D1F2E2F2F3F304F3 15F326F337F348FFF359F36AF37BF38CF39DF3AEF3BFF3D0FFF3E1F3F2F403F414F425F436F447F 458FFF469F47AF48BF49CF4ADF4BEF4CFF4E0FFF4F1F502F513F524F535F546F557F568FF7579F5 8AF599C6459952255B8F5C9FFF5DAF5EBF5FCF60DF61EF62FF640F651FFF662F673F684F695F6 A6F6B7F6C8F6D9FFF6EAF6FBF70CF71DF72EF73FF750F761FFF772F783F794F7A5F7B6F7C7F7D8 F7E9FFF7FAF80BF81CF82DF83EF84FF860F871FFF882F893F8A4F8B5F8C6F8D7F8E8F89FFF90AF 91BF92CF93DF94EF95FF970F981F3F992F223317B01A2122819AD23734F515043414C1361DA19 B52EAE09B31FF1E629D1F9E2F9F3FA04FA15F15711A421714C1998F5AB663DB90643938B5A4F0 62A5103317811740391320EA661690641721621AF0238FA70622631A3036623211E03961FC366 1A5801490231FAA1FAB2FAC3FFFAD4FAE5FAF6FB07FB18F242FB38CB20FFF59FB6AFB7BFB8CF B9DFBAEFBFBFD0FFFBE1FBF2FC03FC14FB26FC36FB48FC58FFFC69FC7AFC8BFC9FCFCADFCBEFC CFFCE0FFFCF1FD02FD13FC25FD35FC47FD57FD68FBFD79FD8AF20DE14C4D995139000DBCO
PidTagS	0

Property name	Value
ensitivity	
PidTagSubject	Fabrikam Project Status Meeting

The following code shows the iCalendar generated to send over the wire.

```

BEGIN:VCALENDAR
PRODID:-//Microsoft Corporation//Outlook 12.0 MIMEDIR//EN
VERSION:2.0
METHOD:REQUEST
X-MS-OLK-FORCEINSPECTOROPEN:TRUE
BEGIN:VTIMEZONE
TZID:Pacific Time (US & Canada)
BEGIN:STANDARD
DTSTART:16011104T020000
RRULE:FREQ=YEARLY;BYDAY=1SU;BYMONTH=11
TZOFFSETFROM:-0700
TZOFFSETTO:-0800
END:STANDARD
BEGIN:DAYLIGHT
DTSTART:16010311T020000
RRULE:FREQ=YEARLY;BYDAY=2SU;BYMONTH=3
TZOFFSETFROM:-0800
TZOFFSETTO:-0700
END:DAYLIGHT
END:VTIMEZONE
BEGIN:VEVENT
ATTENDEE;CN=sito@contoso.com;RSVP=TRUE:mailto:sito@contoso.com
ATTENDEE;CN=pcook@contoso.com;RSVP=TRUE:mailto:pcook@contoso.com
ATTENDEE;CN=aweiler@contoso.com;RSVP=TRUE:mailto:aweiler@contoso.com
CLASS:PUBLIC
CREATED:20080208T213320Z
DESCRIPTION:When: Occurs every Wednesday effective 2/13/2008 from 2:00 PM t
o 2:30 PM (GMT-08:00) Pacific Time (US & Canada).\nWhere: Conference Room
123\n\n*~*~*~*~*~*~*~*~*~*\n\nHey all,\n\nLet's meet up every Wednesday
to sync up on the status of the Fabrikam Project.\n\nThanks,\n\nElizabeth\n
n
DTEND;TZID="Pacific Time (US & Canada)":20080213T143000
DTSTAMP:20080208T213320Z
DTSTART;TZID="Pacific Time (US & Canada)":20080213T140000
LAST-MODIFIED:20080208T213321Z
LOCATION:Conference Room 123
ORGANIZER;CN="Elizabeth Andersen":mailto:eandersen@contoso.com
PRIORITY:5
RRULE:FREQ=WEEKLY;BYDAY=WE
SEQUENCE:0
SUMMARY;LANGUAGE=en-us:Fabrikam Project Status Meeting
TRANSP:OPAQUE
UID:040000008200E00074C5B7101A82E008000000003046642B576AC8010000000000000000
010000000622C639E40D09342B747A1672730CBBA
X-ALT-DESC;FMTTYPE=text/html:<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 3.2//E
N">\n<HTML>\n<HEAD>\n<META NAME="Generator" CONTENT="MS Exchange Server ve
rsion 08.00.0681.000">\n<TITLE></TITLE>\n</HEAD>\n<BODY>\n<!-- Converted f
rom text/rtf format -->\n\n<P DIR=LTR><SPAN LANG="en-us"><FONT FACE="Calib

```



```

ri">When: Occurs every Wednesday effective 2/13/2008 from 2:00 PM to 2:30
PM (GMT-08:00) Pacific Time (US &amp; Canada).</FONT></SPAN></P>\n\n<P DI
R=LTR><SPAN LANG="en-us"><FONT FACE="Calibri">Where: Conference Room 123</
FONT></SPAN></P>\n\n<P DIR=LTR><SPAN LANG="en-us"><FONT FACE="Calibri">***
***~***~***~***~***</FONT></SPAN></P>\n\n<P DIR=LTR><SPAN LANG="en-us"><FONT
FACE="Calibri">Hey all\,</FONT></SPAN></P>\n\n<P DIR=LTR><SPAN LANG="en-us
"><FONT FACE="Calibri">Let's meet up every Wednesday to sync up on the s
tatus of the Fabrikam Project.</FONT></SPAN></P>\n\n<P DIR=LTR><SPAN LANG=
"en-us"><FONT FACE="Calibri">Thanks\,</FONT></SPAN></P>\n\n<P DIR=LTR><SPA
N LANG="en-us"><FONT FACE="Calibri">Elizabeth</FONT></SPAN><SPAN LANG="en-
us"></SPAN></P>\n\n</BODY>\n</HTML>

```

```

X-MICROSOFT-CDO-BUSYSTATUS:TENTATIVE
X-MICROSOFT-CDO-IMPORTANCE:1
X-MICROSOFT-CDO-INTENDEDSTATUS:BUSY
X-MICROSOFT-DISALLOW-COUNTER:FALSE
X-MS-OLK-ALLOWEXTERNCHECK:TRUE
X-MS-OLK-AUTOSTARTCHECK:FALSE
X-MS-OLK-CONFTYPE:0
X-MS-OLK-SENDER;CN="Elizabeth Andersen":mailto:eandersen@contoso.com
BEGIN:VALARM
TRIGGER:-PT15M
ACTION:DISPLAY
DESCRIPTION:Reminder
END:VALARM
END:VEVENT
END:VCALENDAR

```

The following table lists the properties on the Calendar object that Shu receives.

Property name	Value
<b>PidLidAllowExternalCheck</b>	TRUE
<b>PidLidAppointmentDuration</b>	30
<b>PidLidAppointmentEndWhole</b>	02:30:00.000 PM 2/13/2008
<b>PidLidAppointmentNotAllowPropose</b>	FALSE
<b>PidLidAppointmentRecur</b>	cb: 80 lpb: 043004300B2001000000C02100000100000000000000008000000232000000A000000000000000 00000000000000000000003FC30CDF80E95A0630000009300000480300006603000000000000000 000000

Property name	Value
PidLidAppointmentSequence	0
PidLidAppointmentStartWhole	02:00:00.000 PM 2/13/2008
PidLidAppointmentStateFlags	3
PidLidAppointmentSubType	FALSE
PidLidAutoStartCheck	FALSE
PidLidBusyStatus	1
PidLidGlobalObjectId	cb: 56 lpb: 04000008200E00074C5B7101A82E00800000003046642B576AC80100000000000000010000 000622C639E40D09342B747A1672730CBBA
PidLidConferencingType	0
PidLidInvited	TRUE
PidLidGlobalObjectId	cb: 56 lpb: 04000008200E00074C5B7101A82E00800000003046642B576AC80100000000000000010000 000622C639E40D09342B747A1672730CBBA
PidLidIntendedBusyStatus	2
PidLidLocation	Conference Room 123
PidLidOwnerCriticalChange	09:33:20.000 PM 2/8/2008
PidLidReminderD	15



Property name	Value
<b>PidTagResponseRequested</b>	TRUE
<b>PidTagRtfCompressed</b>	cb: 1170 lpb: 8E040000481000004C5A4675C5EB0C9A03000A00726370673132358232034368746D6C310331F862696404000330010301F70A80FF02A403E40713028010830050045608559F07B211B50E510301020063680AC07073657432060006C311B533DB044614473012BF02003403C5165AF9074069620510028011C308EF09F7B63B1ABF0E303511B20C60630050330B090164333616E00BA534205910822A5C0EB20190671F603300203C21444F4354590050452048544D4C20005055424C49432022402D2F2F5733432220444454442134332E32222045F84E223E11C31FD720800AA323BCFC31392090214223AD14D024BF2471E31F70261045414423AD0EF1278F050E10360EF03C4D455441C507B0412BB03D224709F0049014617405B02216F04F4E544D2370542C4005E1457814616EF4676506527613112E9100900220402030382E30302F70367438312F7130239E2A1F25A337823720905449544C45266EA6340EF0250D383520902F32DF7F310F1FF53421357028EF273F200435C116E03C424F445923AD1EE14739DF20513B01212D2D16F16E552E91740980200352203EA078FC742F00213ED005B000C005403E102F3B7F3C8F412F20043628B15020804449523D4C545223A0BF1FE33F82000044E51EE144E65C2020CE720AB146A214605C7103214587051F9B3828B15350414E201A4C4980472C4009F02D757347239144DF482E313438209046E12D21204641432C3119554A6C13181047A9576809F03A204FAC636308700420652E91794FB0E309802C8073646150D0011105901474692E9020234031332F6701D02F503ED4323A2F8021804D153F206F531133535328474DEC542D2F50533129218000D006906D0DE020076254405505F0485E26D8616D7002804A972645781941246E615150292E251C3536DF35614CF24A794A87483D3914D03570FF49625ACF45CB0AA25B780A8146270AB1EF6048483D01C0356150405F42BF63FFFF438F449F45AF46BF616F48DF49EF4AFFFF4C0F4D1F4E2F4F3A1AC050003E4151B0791AC06E632E4008003F010E2033FF595F5A6F5B7F5C8F75BF5EAF5FBF60CFFF61DF62EF654F7E9F661F672F683F694FFF6A5F6B6F6C7F82AF6E9F6FAF70BF4EFBFC2A7E8D7F743F754F765F776F902FFF798F7A9F7BAF7CBF7DCF802F990F80FFFF820F831F842F853F864F875F9D1F897F678A8F8B9F4EFB486550D007406CFE2C8EAF8FBF90CF91DFA9EF93FF950FFF961F972F983F9A9FB2CF9B6F9C7F9D8FFF9E9F9FAFA0BFA1CFB6DFA3EFA4FFA60FE54EFB4C14B05C27AC00042007803114B0207570508F53A17379777370C2722F2174FD0C3D00190746FBC20C4503FA0C4924601A005106BF75730218003606A51C1594FA96FAA7FFAB8FC83FADAFABFAFCFB0DFB1EFB44FFFD11FB51FB62FB73FB84FB95FBA6FBB7F5FD52FBD9FBEAFBFBF71BC542E016BFE73A85FC7CFC8DFC9EFE1EFCC0FCD1FFFCE2FCF3FD04FD2AFEACFD37FD48FD59FFFD6AFD7BFD8CFD9DFEEDFDBFFDD0FDE1FB571BC4519707A01A014B068E07FFF E18FE29FE3AFFBCFFCDFF31FF42FFF4FFFFD9FFEAFE5EFE6FFE80FE91FEA2FEC8FF70B0F3A77F6B12F3B3F398F200532A10B386026337D1170
<b>PidTagSenderAddressType</b>	SMTTP
<b>PidTagSenderEmailAddress</b>	eandersen@contoso.com
<b>PidTagSenderEntryId</b>	cb: 116 lpb: 00000000812B1FA4BEA310199D6E00DD010F54020000008045006C0069007A0061006200650074006800200041006E00640065007200730065006E00000053004D00540050000000650061006E00640065007200730065006E00400063006F006E0074006F0073006F002E0063006F006D000000
<b>PidTagSenderName</b>	Elizabeth Andersen

Property name	Value
PidTagSensitivity	0
PidTagSubject	Fabrikam Project Status Meeting

### 3.4.2 Organizer's Cancellation of an Instance

Elizabeth cancels the May 28th instance of the status meeting because it conflicts with the company picnic.

The following table lists the properties on the Calendar object that Elizabeth sends.

Property name	Value
PidLidAllowExternalCheck	TRUE
PidLidAppointmentCountProposal	FALSE
PidLidAppointmentDuration	30
PidLidAppointmentEndWhole	09:30:00.000 PM 5/28/2008
PidLidAppointmentNotAllowPropose	FALSE
PidLidAppointmentSequence	0
PidLidAppointmentStartWhole	09:00:00.000 PM 5/28/2008
PidLidAppointmentStateFI	7

Property name	Value
<b>ags</b>	
<b>PidLidAppointmentSubType</b>	FALSE
<b>PidLidAppointmentSequenceTime</b>	09:33:20.275 PM 2/8/2008
<b>PidLidAttendeeCriticalChange</b>	09:34:55.904 PM 2/8/2008
<b>PidLidAutoStartCheck</b>	FALSE
<b>PidLidBusyStatus</b>	0
<b>PidLidCleanGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E008000000003046642B576AC801000000000000000010000 000622C639E40D09342B747A1672730CBBA
<b>PidLidCollaborateDoc</b>	
<b>PidLidConferecingType</b>	0
<b>PidLidDirectory</b>	
<b>PidLidInvited</b>	TRUE
<b>PidLidGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E00807D8051C3046642B576AC80100000000000000001000 000622C639E40D09342B747A1672730CBBA
<b>PidLidIntendedBusyStatus</b>	0
<b>PidLidLocation</b>	Conference Room 123
<b>PidLidNetShowUrl</b>	

Property name	Value
<b>PidLidOnlinePassword</b>	
<b>PidLidOrganizerAlias</b>	
<b>PidLidOwnerCriticalChange</b>	09:34:56.904 PM 2/8/2008
<b>PidLidReminderDelta</b>	1525252321
<b>PidLidReminderSet</b>	FALSE
<b>PidLidReminderSignalTime</b>	09:00:00.000 PM 5/28/2008
<b>PidLidReminderTime</b>	09:00:00.000 PM 5/28/2008
<b>PidLidResponseStatus</b>	5
<b>PidLidTimeZoneDescription</b>	(GMT-08:00) Pacific Time (US & Canada)
<b>PidLidTimeZoneStruct</b>	cb: 48 lpb: E001000000000000C4FFFFFF00000000B000000010002000000000000000000000030000000 20002000000000000000
<b>PidTagBody</b>	When: Wednesday\, May 28\, 2008 2:00 PM-2:30 PM (GMT-08:00) Pacific Time (US & Canada).\nWhere: Conference Room 123\n*n~*~*~*~*~*~*~*~*~*\n\nCancelling the May 28th meeting due to a conflict with the Company Picnic.\n
<b>PidTagCreationTime</b>	09:34:55.888 PM 2/8/2008
<b>PidTagImportance</b>	2
<b>PidTagLastModificationTime</b>	09:34:56.013 PM 2/8/2008

Property name	Value
me	
PidTagMessageClass	IPM.Schedule.Meeting.Canceled
PidTagMessageLocalId	1033
PidTagOwnerAppointmentId	3249022936
PidTagResponseRequested	TRUE
PidTagRtfCompressed	cb: 5773 lpb: 891600001A5D00004C5A467533CC81F007000601010B606E6731303266350064007263700DD0 0E00321D0C60630D4401340131737473E26805706263681035090010C03433371044680EB011 8762699311910D773333131666651393F87468650780135714C7145001403914C7637301E802A 412D064698F0336020010C00AC073657402D1507072713200002A0AA16E5A6F1940200DF01A9 13613A030383530341B1101D01B00347DF3076D02833334180F191F1A281B42C71B041AE21FE 17D436106D00721FD05D06114C01CD411A01D5603E31E2F3F19FB01301B621AA21B4020C66C 69FB21511CD4311B2017FF235F1A1F1B2FFF1C3E27010050275F286F297F2A8F2B9FFF0F202CCF 2DDF1F7F208F26A713C0323FFF334F2EEF2FFF310F1D3F381F392F3A3FFF3B4F3FA00E103C9F3D AF3EBF3CF40DFFE36225F430F247F258F26982248428F6F490F44AF45BF1CD4394C5F4D64321 433384DD420076D2043457F02834F90519F52A53C62535F546379CE7254C4321F4D5531362CA 156FFF503824709D16B54C4370F59E758D17B5AAF038254087054C43C7F59E637C722415E7F03 82284865215007D0FE2954C441EF6167532F6306071001A0EF0EB063E54758597D384751662F0 382FA420740740EB054C44C4F59E75CA1CB6A2F6333560890746E21300790FE6563E41190518F 529F212A54965310FF552F563F72AC5855531058DF59EF72ABFF5BF853105CAF5DBF72AB5FC65 310685FF7696F72AB6B7A30708847FC720A2653FF54970DE082AF752F84C658560EF085DFF778 BF84C55BF9317B4889AE7CE884D4FF5FC75A508C7F7FFF84C56B7926F265F1FF7F0F52CF53DF2 6C5708F86DF955F7706FD2700312CAF8A1F5AFF7A989AB1779FFF8D7F5ECF7E469AB17B4F616F 6E5F638AFF9AA2605F656FA4EF678AA2645F90BFFF6A7F925B8F996CDFACDF6EFA658933FF 7944F992F966731970F981FB5CF9A38DE329AEF9BFF9D0F9E1A329EEF9FFF7FA10FA218B520BF 6FA3EFA4FFA60C32FFA6FFA80FC55FAA2D0E01C78FAC5FAD6FFD927932AF3FB04FC98FB26FBB2 1B3AFF7B4BF2126965832B77FB88FD6379A38DF26F0D77F8A2F21359E0B33BF5FC06FFB2126A2 0933CB9FCCAF2126924CB532FFE1DFB4EFB5FFDA55D76FD87FE75F9A38FF85A0E91FBC7FBD8F 9E2958CFDF4FEFFFA2095C9FC43FF2FFA5EE604FC86FF6DFFFAA1E644FE2AFFB0F924C684FD0 AFF3FBFD2CFECA2E53FE64FEB2F966734E90FFFEA1F07CF9A389AC0098FEE0FEF1F9E29FFBB30 0D6FF20FF31F0CB8F4CFF5DF035FFFA5FDECC0154FFA1FFB2FAA3C0D30197FF7FE4FFF5F926A35 013F024F1B8F046FD0D2105AF06BF0B9F966735097F0A8FFF283F9A380EE22A1F0E9F0FAF9E47 12E2FF2DFF129F13AF2D46153F164F23CFA5FDDE36196F1A7F37CFAA2D361D9F1EAFB1FBF925 B3621AF22BF3BFF24DF2D91FF2618833F844F2D37829F2AFF87EE92F1DE372DC889AF8ABF9E29 37890F32DFFF8E8E4CF23E08904F915F926A3B62424F7F275F286F4CC529EF4AEF59CF9A3838FF 2DCF4E4F2FEF9E1A778F51BF616FA209EF7B3F36AF656FA5EE3839DF3AEF695FFDAA2D383E0F5 52F402F925B7ECF431F0771AF453C92B1636F6C6F72A074626C3B5C9E106485C01A679E116E85 C07830756530F5785F65CB8035798A7AA17A5F7B69FF79747B9279FF7DCF7D8D7D0F7B3F798F FA659ED038835A8471842F853979747F856283CF879F875D86DF850F88D4393F63508C248D81 85A38D8092A22A5C54646560517074113368D17325BF40208EC670618F61716C3F7410565078 A0E0A078A04DE06463B4746C90A07291A0AA30708F11C46175AE605C617390A09200A34E5093 026E756D96A06192C004746F9300646A757374F9E0A0676892F0E0A0915650790114697490B 03090105C6E6F867155D16E306F7465209A70A994C0796C6DB0689E20749A70FF90FF920F931F



Property name	Value
	<p>942F953F836099006060C9604173317410616678A09E208B8FE19A106C6020673130CB807F982  19BE09D949D318F9698309EE333DB67309ED26685D0A11263896073E039A0B36E70A109A2A47  410736EE86578749D3173968078006E40B674A3D155E069780095E079A4424797504E7073E03  9393068B039FE366DD0A4A278408EC39DD19D319B903B73F0AE707697009730B2E06D699E68  73E08F106E609730756EA8D15E659BC07880A4F99DF04499B4201A504E6061896090B0682046  E86F6E748EB4749DE05F50AC90AD5FF077A2409BE066AC905773E07874684267309BE090A0A7  F06C979F106D00AE2472AE98666CAE062BAD70B00762B00772AE026362FF90A04EA0B1F29091  B26278309550789113B32497507065AE01736365BC6C6C98C1ADD0AD71B38173A840BF7810C  EC1AC81C680AF20B5E66CB5F5CE62B5F59940B6046467B6E6B860F7B7E69DA0B6047690DF98F  F9A0F9B1FFF9C2F9D3F8FA19E6F9F7FA08FA19FA2AFFFA3B7ACB0A86FA97AA486A6C475B0CAB0  FF9770A727C1A1A7E89D6DC1BCBC3077C0F66675A0973062BC707880AC00A7A27FC6EFA998A  5E47530592049C0962048FFB411B6D09550DDA3A763A6A0CA8FCB9FFCC985E0CD6FCE7FCF8  FD092ABF0B4A0FFAD107880D0DF68B0D20F9DBEC1BFC2C4BFB2B0A442D53FD646A52AD0F173  AC00C7C951973077D06D706F04E0D76F62456E40696C53975268B031B777838EF0F010767821  971055D140F99660776EE356A611E3F2E51385E0FE37F0D06F81A60209604B50E8D1E5133FD05  5E513A645E5A4A3B04B603030CA39EC616DA4C16850BB90E9A395ABF2336B606DF8106B42955  251EAE5537562EB5173A6F16CFA46FC3063EB5173F0BC80AAD15F50A86D6C4D4E6067EB3372E  DB7D98F114A63ED71BBB249B36078F0CF4EA0F8E0EB519550744C6D90EB51A904A07279F0913  18EC378ED903E6EBE20E402F1B49DF0BE707470383A2F2FB47097A06E40732E5DD610635FF0E  080AD702EE1012F45F43066FC60652F77780064BE2F4B50C370F513ED9077905C90A1B5B59077  85E032F021F653686B32FFEB51EDC1AE80F013EDC1AF30F836EFF5B5EDC162F00367BDA096F0  729571FFBE3004E0BB407410BB11AD10BB40B6D171AD706E626ABC6078F0A7F06FF663AD41EC  B06B96D0A8409DE0FCD4FFA4940070C1518F00AC0096E1EAE0788038737973A490EFE183616C  793DAC0076ED9078A0FEB895916764F5A4D06178A266FCA1E3D0EFD1B531FE7656410171A410  ED905F509790AD10EE70C130B48003906CADCOA41295D0F7C4F07800D60178788077D0AC10E  FD1F978A07361A840955002B3F1C105D17F0391F1C1B5905FF04E705F5096607853C130F2F06F  7978F05CA41070FF9790781060309660BC31B6D0BC80FCC0CE64AC107830F1F06264B7609660  7FBC81B480A491CD01A4929790BDE065F25C0390727AFCA2B860F7D295509D0C71680AB3711  0007167760D49FF0C01BE509550E6F00DB30EC40E73038277FE910DE110536A08A16020C4A07  6F94550776BB3516B6011B2B4705640EFC401F6F1F9E0B97265BDE01315A490F796E0A5010000  74E49095500BE0FC01FF14A7BE706E40BDA0BC809651F1E0BE70FFBDE17821CCF0255020D0DE  00F1E0C111FF09F2B351BA8014B012A1BB407830AD21FF14A178217810B911F1E0EAF10B210BE  0F79660EAF1BBB0701712A3F090B0BDB0FFC4729550B482C111D8A1F4D0B490D661E7FF40B49  0BBA17070A960BB40BC61FE6960201A36A6025FF096E0E8F69650FF39107821A5D2BC304E109  6608960AD10FFBD92F4D0BC50A9C104D1EC309750A491EF5650BE209651B3516EEAE1AC9025  B09FB4901A21B490E3D096516378BC80FF95F0C9A195D0B3600981D8C024110871FB96609E20  63F1F117129E202403BDA0BB9550B6E06825731472F30067BB72DFDF16302B016537820EB00  263274300718F2288202B0747862785CFF1A50C5004E70A400BC5012A0F3610551FE6C17A1741  009313D40E111A4D2C3F0CBA4308ED27701D1666D29B0E2B0FDF8120F6D00F309642C3FOA4  D034F0BF4E9008E096E0BB5085D095D06CA490EF6E4012A018B0F1E0759610DC42BB71FFA3D1  FB11A9F1FAD59582A41078A0FC71FFA970B5900BE03183BC0430903173E8BA3F9730FC0397118  EF0BD20FB016C76FF0351BD21F3F0BD50361195F078103692FFB351EFD150A0F6F1A970C14197  11BD20F32A8095F0202EE3643616635036B2FFDC51371F382F393F36706730BD208F10EFFCC03  B0F3C1F3D2F6C6B60BD20DB00F73ACF3F9F40A529398C6F903E6F435FFD4085626E704CB1448  F364355B0422FFF46FF480F491F366168D04A7236FF4BDFFF4CE44FD6D004A7F500F511F522F3  661FF5B704F0F54AF55BF56C5F641B630F640FFC1309550DC33BB72BA5FBB6FBC7FBD8FFFBE9F  DADFC0C5FC2EFC3FFC50FA3B17F6AF0D2CF646ADDA12501ACF0E68820725713806E3A6BE  07880A40073510170792C20EDB0792E60386B6CE0F571382E603AE940AB404D1E2D6DD0E9106  E1176B0474D54962DAF506DE129AB416369F4D10375B376B0555320262043837470608061292  E0D0A5BB2F76BE278D06C3043AC00668078D01C216B765176702085E033714571452AFE7E743  F735C5BA45C6F5D7F5E8F5F9FF60AF95B65BB258C0E8C968CF69DF6AEFF770C1B482FE6120AD  D097006D04E971FF7DBF7ECEA95D0F16AFDA77079B0B7D0DF7CDAADD0820F831F7FAF20703  02B40CD8122648CD081506F2040F00561FFAFE0F4E0A4E077F0ADD0815372202CB1DA6E6D205  0F4E014E063397086DFFF87EF849F85AE75D635D20811025297530F77606CA07B00F0A0617832  36FFDD3092F1D8A0FD10D8D078D17BB19301FFD60778D12FE092F1A9689576C8959456FFA526  78D1A640E98093C7A410B4801B20FF775194BAD3A295DA9AD4C89562E197D9FF9AD493F4622  0A6C599FF9B0F9C1FA544FF7D709DAA13828122E340A0DFA1EFA2FBEE32A3DFA4EFA2EC33A6E  FA7FFA2ECE34A9FFAB0FA2EC35AD0FAE1FA2ECE36B01FB12FA2EC37B32FB43FA2EC6E38B63</p>

Property name	Value
	FB74FA2EC399EC3BA6633FFBAEC7A906FF0A3C4BCAFBDB8A6D4BEBFFBDB8A9E4C0CFBDB8AC F4C2DFBDB8B004FFC4EFBDB8B314C6FFBDB8B624C90FBDB8FFB934CB1FBDB8B8C44B99FCD636 4329DC8FF12A01B20BA80E4A09EDF9FEFCF1FBA84FFDE729DB970102FB1CCDB9CA49DE6ED41 FF79026F81ECA001D062008BD0EA72D1EFFFD2FFD40FD516D79CEBE1FE50D696DA2F7FDB3FD C4F2070F6C0DD9C7B10057067DFDEEFDFFFE10FE2169D8C452CB079B05D1F0073E3DFE4EF97D 935BAEC547924C220476711E8E3E52E9DE650FB03D62E41540461E8EFED5FE5FFD72F7F9E24D E500AC1FE61F01FF12F97D936FD9D8C4C7B32DE500BB1F50FF61FF72DFFD79CF8F4F8F022B0F9 CFFADFF75AE29C7FF8F4ED07FE7FFF8FF7A568B09DAA4DFD2BB0697A20F946A3B502DF03EFF7 A5FE34057F0689A6D4079F08AFF7A5D09CDF0645FDE2072F0CFFF73C360EFF1006F70BFF119FF 74B37138F0681ED02107FFF161FF73C6DB0182F1935151F1ABFF74BBFBAEC18EAA9E41E9F1FAF BA84379D8CFA4458C06BFDDF239F24AFD79C7220FF93F02DB07910F94F27BF28CF2581E29CFF 2AE726EF2CBF24BE056C2AE7024F314FC7F71F011FF93720416372A09260FF199F35FFFBCF381F 103339AF3ABF3BCFFF00DF01E83E8F3F9F40AF052F063F437FFF448F459F09EFOAFF48CF49DF4A EF0EAF8F0FBC4E1CED9FD805526576E8C0FFD1BF4F8FF20FCD094C3C1033D8F7561F8F572F583 FE216BAEC51756F9240DF5B8F5C9F5DAFCD3625BC4992606C10FF5480600F611F506F136F1479 4E1F664FFF675F17CF18DC6A5F6B6F6C7F1C5F1D6CFF6F7F708F719F20EF21FC749F75AF76BFFF 257F268879BF7ACF7BDF29CF2ADF7E9FFF7FAF80BF2E8F2F9C83EF84FF860F331FFF342C890F8A 1F8B2F37AF38BF8E531E3FFF8FBF3C3F3D4F88D993CF94DF412F423FFF8DF998BF99CF461F784F 483F9DAF9EBFFF4B6FA0DF4D8FA2FFA40F50BFA62F52DCFFA84FA95F67DFAB7F69FCAD6FAE7F6 CFFFBF09F6F1CB28FB39F721FB5BF743CB7AFFB8BF773FBADF795CBCCFBDD7C5F7D6FFF981F C25FC36F81AF82BF932FC73FC84FFF86FF880FCBAFCCBFCDC8C4F8D5FD0FFFDD20FBEAF919F9 2AF22BFD75F95DFD97FFF88CADB7FDC8F9ADF9BEF8DF9E06FE17FFF9FCBFFFA1EFE55FE66FA5 1FE88FA73FFFEAAFEBBFAA6FEDDF52DCEFFFF10FAF8FFFF32F69FCF51FF62FB4AFF84F6F1CFA3F FFB4FB9CFFD6F743CFF5F006FBEEF028FFF795C047F058FC40FC51FDFCF0A0F0B1FFF95FCA6F DADF0EEF0FFCEAFCFBF135FFF146F157FD3FFD50F18AF19BF065FD94FF9DA5F20341E1F1F2FD DAFDEBF88E8FF232F243FE28FE39F8DF9281F292FE77FFF07AFE99F2D0F2E1FECCF303FEEEF325 FFF336FF21F358F52DC37AF38BFF73F3ADFFF69FC3CCF3DDFFC5F3FFF6F1C41EF42FFF017F451 F743C470F481F069F4A3F795CFF4C2F4D3F0BBF0CCF277F51BF52CF110FFF121F228F569F57AF1 65F176F5B0F5C1FFF5D2F1BAF1CBF605F616F4E0F20FF220FFC203565CF66DF255F266F88E86AD FFF6BEF2A3F2B4F8DF96FCF70DF2F2F4F5FFF314F74BF75CF347F77EF369F7A0F7B1FFF39CF7D3 FAC8C7F5F806F3EEF828FB1ACFF847F858F440F87AFB6CC899F8AAF492FFF8CCFBEC8EBF8CF 4E4F91EFC10C93DFFF94EF536F547F6F2F996F9A7F58BF59CFFF6A3F9E4F9F5F5E0F5F1FA2BFA3 CFA4DF7F635F646FA80FA91F95BF68AF69BF20FE36AD7FAE8F6D0F6E1FD098B28FB39FFF71EF7 2FFD5A9B77FB88F76DF970F78FFFFB6C6BD7F7C2FBF9F7E4FC1BFC2CF817FFFC4EFF43CC70FC8 1F869FCA3FF95CCC2FFFC3F8BBFCF5FFE7CD14FD25F90DFD47FFF039CD66FD77F95FFD99F08B CDB8FDC9FFF9B1F9C2FB6DFE11FE22FA06FA17FB1EFFFE5FFE70FA5BFA6CFEA6FEB7FEC8FAB0F 4FAC1FEFBFF0CFDD667166F3F06D2C6174E874AFC631DE7C53750062746C6520456D707D3150 733BF0F52FF63FF74FAFD532FDE87C491DD01DC0F1C0FA1FFB2FFC3F0DF7CE33E87CF9B552656 665FE721DC01DB0003F014F025F0366BA6C3FFF36053F064F075F086FF2EC426FFA6F554054B0 10F9F00B630357D43C104269626CAFE06772613DFFD0790B630DBF0393DE7C544F1043204865 31633B7D7D607B5C2A5C64F7C0FFF07483F3F0FF90303130353017A2963217A31760381804346 4F2D04037383664366309603280653533343135381A00E118E034633532C9E0B560C490F7C9E0 EDB019A0331A801B5018041C0E07B04017A1BB10636631316590306131621DA0616517707B1E 6F1F5C331DC0204117A00AF066F86630391CE621BF1841228D226DFF20E2250221E624EE25672 76F287F298FFF2A9F2BAF2CBF2DCF2EDF2FEF30FF320FFF331F342F353F364F375F386F397F3A8 FFF3B9F3CAF3DBF3ECF3FDF40EF41FF430FFF441F452F463F474F485F496F4A7F4B8FFF4C9F4DA F4EBF4FCF50DF51EF52FF540FFF551F562F573F584F595F5A6F5B7F5C6CF6E645C6524F55E5F5F6 F607F618F629FFF63AF64BF65CF66DF67EF68FF6A0F6B1FFF6C2F6D3F6E4F6F5F706F717F728F73 9FFF74AF75BF76CF77DF78EF79FF7B0F7C1FFF7D2F7E3F7F4F805F816F827F838F849FFF85AF86B F87CF88DF89EF8AFF8C0F8D1FFF8E2F8F3F904F915F926F937F948F959FFF96AF97BF98CF99DF9 AEF9BFF25031A80A71CF125519DA2373417D4341791FE3620719E22EDB09E0121329FEFA0FFFF A20FA31FA42F18411D1217919C5F5D86A263DE0643938A7C062A7E056331A511A103915F066 1960647D19F1621DC0265FA9D61DC09E3039C111603239613661A8501760FF25EFACFAFFAF 0FB01FB12FB23FB34FFFB45F26FFB65CB4DFB86FB97FBA8FBB9FFFBCAFBDBFBCECFBDFC0EFC1F FC30FC41FFF53FC63FB75FC85FC96FCA7FCB8FCC9FFFCDAFCEBFCFCFD0DFD1EFD2FFD40FC52 FFFD62FC74FD84FD95FDA6FDB7F23AE17940BDC65166000DE90
PidTagS	0

Property name	Value
ensitivity	
PidTagSubject	Canceled: Fabrikam Project Status Meeting

The following shows the resulting iCalendar file.

```

BEGIN:VCALENDAR
PRODID:-//Microsoft Corporation//Outlook 12.0 MIMEDIR//EN
VERSION:2.0
METHOD:CANCEL
X-MS-OLK-FORCEINSPECTOROPEN:TRUE
BEGIN:VTIMEZONE
TZID:Pacific Standard Time
BEGIN:STANDARD
DTSTART:16011104T020000
RRULE:FREQ=YEARLY;BYDAY=1SU;BYMONTH=11
TZOFFSETFROM:-0700
TZOFFSETTO:-0800
END:STANDARD
BEGIN:DAYLIGHT
DTSTART:16010311T020000
RRULE:FREQ=YEARLY;BYDAY=2SU;BYMONTH=3
TZOFFSETFROM:-0800
TZOFFSETTO:-0700
END:DAYLIGHT
END:VTIMEZONE
BEGIN:VEVENT
ATTENDEE;CN=sito@contoso.com;RSVP=TRUE:mailto:sito@contoso.com
ATTENDEE;CN=pcook@contoso.com;RSVP=TRUE:mailto:pcook@contoso.com
ATTENDEE;CN=awailer@contoso.com;RSVP=TRUE:mailto:awailer@contoso.com
CLASS:PUBLIC
CREATED:20080208T213455Z
DESCRIPTION:When: Wednesday\, May 28\, 2008 2:00 PM-2:30 PM (GMT-08:00) Pacific Time (US & Canada).\nWhere: Conference Room 123\n\n*****
*\n\nCancelling the May 28th meeting due to a conflict with the Company Picnic.\n
DTEND;TZID="Pacific Standard Time":20080528T143000
DTSTAMP:20080208T213456Z
DTSTART;TZID="Pacific Standard Time":20080528T140000
LAST-MODIFIED:20080208T213456Z
LOCATION:Conference Room 123
ORGANIZER;CN="Elizabeth Andersen":mailto:eandersen@contoso.com
PRIORITY:1
RECURRENCE-ID;TZID="Pacific Standard Time":20080528T140000
SEQUENCE:0
SUMMARY;LANGUAGE=en-us:Canceled: Fabrikam Project Status Meeting
TRANSP:TRANSPARENT
UID:040000008200E00074C5B7101A82E008000000003046642B576AC8010000000000000000
010000000622C639E40D09342B747A1672730CBBA
X-ALT-DESC;FMTTYPE=text/html:<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 3.2//EN"
">\n<HTML>\n<HEAD>\n<META NAME="Generator" CONTENT="MS Exchange Server version 08.00.0681.000">\n<TITLE></TITLE>\n</HEAD>\n<BODY>\n<!-- Converted from text/rtf format -->\n\n<P DIR=LTR><SPAN LANG="en-us"><FONT FACE="Calibri

```

```

ri">When: Wednesday\, May 28\, 2008 2:00 PM-2:30 PM (GMT-08:00) Pacific Ti
me (US & Canada).</FONT></SPAN></P>\n\n<P DIR=LTR><SPAN LANG="en-us">
<FONT FACE="Calibri">Where: Conference Room 123</FONT></SPAN></P>\n\n<P DI
R=LTR><SPAN LANG="en-us"><FONT FACE="Calibri">*****</FONT></
SPAN></P>\n\n<P DIR=LTR><SPAN LANG="en-us"><FONT FACE="Calibri">Cancelling
the May 28</FONT></SPAN><SPAN LANG="en-us"><SUP><FONT FACE="Calibri">th</
FONT></SUP></SPAN><SPAN LANG="en-us"><FONT FACE="Calibri"> meeting due to
a conflict with the Company Picnic.</FONT></SPAN><SPAN LANG="en-us"></SPAN
></P>\n\n</BODY>\n</HTML>
X-MICROSOFT-CDO-BUSYSTATUS:FREE
X-MICROSOFT-CDO-IMPORTANCE:2
X-MICROSOFT-DISALLOW-COUNTER:FALSE
X-MS-OLK-ALLOWEXTERNCHECK:TRUE
X-MS-OLK-APPTSEQTIME:20080208T213320Z
X-MS-OLK-AUTOSTARTCHECK:FALSE
X-MS-OLK-CONFTYPE:0
X-MS-OLK-SENDER;CN="Elizabeth Andersen":mailto:eandersen@contoso.com
END:VEVENT
END:VCALENDAR

```

The following table lists the properties on the Calendar object that Shu receives.

Property name	Value
<b>PidLidAllowExternalCheck</b>	TRUE
<b>PidLidAppointmentDuration</b>	30
<b>PidLidAppointmentEndWhole</b>	09:30:00.000 PM 5/28/2008
<b>PidLidAppointmentNotAllowPropose</b>	FALSE
<b>PidLidAppointmentSequence</b>	0
<b>PidLidAppointmentStartWhole</b>	09:00:00.000 PM 5/28/2008
<b>PidLidAppointmentStateFI</b>	7

Property name	Value
<b>ags</b>	
<b>PidLidAppointmentSubType</b>	FALSE
<b>PidLidAppointmentSequenceTime</b>	09:33:20.000 PM 2/8/2008
<b>PidLidAutoStartCheck</b>	FALSE
<b>PidLidBusyStatus</b>	0
<b>PidLidCleanGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E00800000003046642B576AC80100000000000000001000000622C639E40D09342B747A1672730CBBA
<b>PidLidReferencingType</b>	0
<b>PidLidExceptionReplaceTime</b>	09:00:00.000 PM 5/28/2008
<b>PidLidFInvited</b>	TRUE
<b>PidLidGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E00807D8051C3046642B576AC801000000000000000010000000622C639E40D09342B747A1672730CBBA
<b>PidLidLocation</b>	Conference Room 123
<b>PidLidOwnerCriticalChange</b>	09:34:56.000 PM 2/8/2008
<b>PidLidReminderDelta</b>	1080
<b>PidLidReminderSet</b>	FALSE
<b>PidLidReminderSignalTime</b>	03:00:00.000 AM 5/28/2008

Property name	Value
e	
PidLidReminderTime	09:00:00.000 PM 5/28/2008
PidLidResponseStatus	5
PidTagBody	When: Wednesday\, May 28\, 2008 2:00 PM-2:30 PM (GMT-08:00) Pacific Time (US & Canada).\nWhere: Conference Room 123\n\n*~*~*~*~*~*~*~*~*~*\n\nCancelling the May 28th meeting due to a conflict with the Company Picnic.\n
PidTagCreationTime	09:46:20.655 PM 2/8/2008
PidTagImportance	2
PidTagMessageClass	IPM.Schedule.Meeting.Canceled
PidTagMessageLocalId	1033
PidTagReplyRequested	TRUE
PidTagResponseRequested	TRUE
PidTagRtfCompressed	cb: 1049 lpb: 15040000430D00004C5A467505CAF70503000A00726370673132358232034368746D6C310331F862696404000330010301F70A80FF02A403E40713028010830050045608559F07B211B50E510301020063680AC07073657432060006C311B5335B044614473012BF02003403C643F9074069620510028011C308EF09F7B63B1A1F0E303511B20C60630050330B090164333616E00BA534205910822A5C0EB20190671EC03300203C21444F4354590050452048544D4C20005055424C49432022402D2F2F5733432180444454442094332E32218045F84E223E11C31F371FE00AA3231CFC31391FF020A2230D14D0241F23D1E31ED02570454144230D0EF126EF050E10360EF03C4D455441C507B0412B103D224709F0049014617405B02216F04F4E544D22D0542BA005E1457814616EF4676506527613112DF100900220402030382E30302ED0367438312ED13022FE297F25033782371FF05449544C4525CEA6340EF0246D38351FF02F323F7F306F1F55338134D0284F269F1F6435C116E03C424F4459230D1E4147393F1FB13A61212D2D16F16E552DF1740980200352203E0078FC742F00213E3005B000C005403D702F3ADF3BEF408F1F643628115020804449523D4C54522300BF1F433EE2000044451E4144465C1F80CE720AB1460214605C71032144E7051EFB3828115350414E201A4C48E0472BA009F02D75734722F1443F478E3134381FF046E12C81204641432B9118B549CD318104709576809F03A4F100980C12BE0736461792C05D04FF078203238501001D02EB050603A532EE020E04D2D5100335132206028474D542D2EB05111296F20E000D006900DE020076251F055C305F047BE26616D70028049F7262644D818A16E614FE0292EF9247C353634C14C5249D949E7479DFE3914D034D048C2587F452B0AA259287F0A8145870AB15DF8479D01C034C150FF3

Property name	Value
	FBF421F61AF42EF43FF450F461F5F1FFF483F494F4A5F4B6F4C7F4D8F4E9A1A20CB4F603DA16670616E632DA00800FB3E610E2033570F581F592F5A3F736FFF5C5F5D6F5E7F5F8F609F62FF7C4F63CFFF64DF65EF66FF680F691F6A2F805F6C4FE76D5F6E6F4E5B2A7E8B2F71EF72FFFF740F751F8DDF773F784F795F7A6F7B7FFF7DDF96BF7EAF7FBF80CF81DF82EF83FFF850F9ACF872F883F894F4E5B56817130FE6C18D02D803E804F3050258C5F8D6FFF8E7F8F8FA86FA97F9EFA00FABEFACF8C6559611AEB97375701311AF5FFFA21FA32FA43F9B93A640A6EFA7FFABCFFFAA1BB11BB93FAA1FBB4FBC5FAD4FAE5FFFBEFCB38FB49FB5AF5633078014B0A60286640A503E806F20612005A0FB70D018D063054003F0A640A6330850B754F000705050500DE003006356FFF8B1FBE9FBCEFCB6FCC7FC01FC12FCEEFFCD3FCE4F91BF92CF93DF94EF95FF985FF7DAAF39C8C3C12F3A9F38EF1F6532010B37C025937DE120
<b>PidTagSenderAddressType</b>	SMTp
<b>PidTagSenderEmailAddress</b>	eandersen@contoso.com
<b>PidTagSenderEntryId</b>	cb: 116 lpb: 00000000812B1FA4BEA310199D6E00DD010F54020000008045006C0069007A0061006200650074006800200041006E00640065007200730065006E00000053004D00540050000000650061006E00640065007200730065006E00400063006F006E0074006F0073006F002E0063006F006D000000
<b>PidTagSenderName</b>	Elizabeth Andersen
<b>PidTagSensitivity</b>	0
<b>PidTagSubject</b>	Canceled: Fabrikam Project Status Meeting

### 3.4.3 Organizer's Location Change of an Instance

Elizabeth realizes that she mistyped the Conference Room number, and sends out a meeting update.

The following table lists the properties on the Calendar object that Elizabeth sends.

Property name	Value
<b>PidLidAllowExternalCheck</b>	TRUE
<b>PidLidAppointmentCounterProposa</b>	FALSE

Property name	Value
I	
PidLidAppointmentDuration	30
PidLidAppointmentEndWhole	10:30:00.000 PM 2/13/2008
PidLidAppointmentNotAllowPropose	FALSE
PidLidAppointmentRecur	cb: 84 lpb: 043004300B2001000000C021000001000000000000008000000232000000A00000000000000 1000000A08DC50C00000000003FC30CDF80E95A063000000930000048030000660300000000 0000000000000000
PidLidAppointmentSequence	1
PidLidAppointmentStartWhole	10:00:00.000 PM 2/13/2008
PidLidAppointmentStateFlags	3
PidLidAppointmentSubType	FALSE
PidLidAppointmentSequenceTime	09:33:20.275 PM 2/8/2008
PidLidAttendeeCriticalChange	09:36:00.420 PM 2/8/2008
PidLidAutoStartCheck	FALSE
PidLidBu	1



Property name	Value
<b>syStatus</b>	
<b>PidLidGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E00800000003046642B576AC801000000000000000010000 000622C639E40D09342B747A1672730CBBA
<b>PidLidCollaborateDoc</b>	
<b>PidLidConferenceType</b>	0
<b>PidLidDirectory</b>	
<b>PidLidInvited</b>	TRUE
<b>PidLidGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E00800000003046642B576AC801000000000000000010000 000622C639E40D09342B747A1672730CBBA
<b>PidLidIntendedBusyStatus</b>	2
<b>PidLidLocation</b>	Conference Room 1234
<b>PidLidNetShowUrl</b>	
<b>PidLidOnlinePassword</b>	
<b>PidLidOrganizerAlias</b>	
<b>PidLidOwnerCriticalChange</b>	09:36:00.420 PM 2/8/2008
<b>PidLidReminderDelta</b>	1525252321
<b>PidLidReminderSet</b>	TRUE



Property name	Value
<b>PidTagResponseRequested</b>	TRUE
<b>PidTagRtfCompressed</b>	cb: 5832 lpb: C41600003D5D00004C5A46755D154F9907000601010B606E6731303266350064007263700DD0 0E00321D0C60630D4401340131737473E26805706263681035090010C03433371044680EB011 8762699311910D773333131666651393F87468650780135714C7145001403914C7637301E802A 412D064698F0336020010C00AC073657402D150707271320002A0AA16E5A6F1940200DF01A9 13613A030383530341B1101D01B00347DF3076D02833334180F191F1A281B42C71B041AE21FE 17D436106D00721FD05D06114C01CD411A01D5603E31E2F3F19FB01301B621AA21B4020C66C 69FB21511CD4311B2017FF235F1A1F1B2FFF1C3E27010050275F286F297F2A8F2B9FFF0F202CCF 2DDF1F7F208F26A713C0323FFF334F2EEF2FFF310F1D3F381F392F3A3FFF3B4F3FA00E103C9F3D AF3EBF3FCF40DFFE36225F430F247F258F26982248428F6F490F44AF45BF1CD4394C5F4D64321 433384DD420076D2043457F02834F90519F52A53C62535F546379CE7254C4321F4D5531362CA 156FFF503824709D16B54C4370F59E758D17B5AAF038254087054C43C7F59E637C722415E7F03 82284865215007D0FE2954C441EF6167532F6306071001A0EF0EB063E54758597D384751662F0 382FA420740740EB054C44C4F59E75CA1CB6A2F6333560890746E21300790FE6563E41190518F 529F212A54965310FF552F563F72AC5855531058DF59EF72ABFF5BF853105CAF5DBF72AB5FC65 310685FF7696F72AB6B7A30708847FC720A2653FF54970DE082AF752F84C658560EF085DFF778 BF84C55BF9317B4889AE7CE884D4FF5FC75A508C7F7FFF84C56B7926F265F1FF7F0F52CF53DF2 6C5708F86DF955F7706FD2700312CAF8A1F5AFF7A989AB1779FFF8D7F5ECF7E469AB17B4F616F 6E5F638AFF9AA2605F656FA4EF678A9AA2645F90BFFF6A7F925B8F996CDFACDF6EFA658933FF 7944F992F966731970F981FB5CF9A38DE329AEF9BFF9D0F9E1A329EEF9FFF7FA10FA218B520BF 6FA3EFA4FFA60C32FFA6FFA80FC55FAA2D0E01C78FAC5FAD6FFD927932AF3FB04FC98FB26FBB2 1B3AFF7B4BF2126965832B77FB88FD6379A38DF26F0D77F8A2F21359E0B33BF5FC06FFB2126A2 0933CB9FCCAF2126924CB532FFE1DFB4EFB5FFDA55D76FD87FE75F9A38FF85A0E91FBC7FBD8F 9E2958CFDF4FEFFFAA2095C9FC43FF2FFA5EE604FC86FF6DFFFAA1E644FE2AFFB0F924C684FD0 AFFF3FBFD2CFECA2E53FE64FEB2F966734E90FFFEA1F07CF9A389AC0098FEE0FEF1F9E29FFBB30 0D6FF20FF31F0CB8F4CFF5DF035FFFA5FDECC0154FFA1FFB2FAA3C0D30197FF7FE4FFF5F926A35 013F024F1B8F046DF0D2105AF06BF0B9F966735097F0A8FFF283F9A380EE22A1F0E9F0FAF9E47 12E2FF2DFF129F13AF2D46153F164F23CFA5FDDE36196F1A7F37CFAA2D361D9F1EAFB1FBF925 B3621AF22BF3BFF24DF2D91FF2618833F844F2D37829F2AFF87EE92F1DE372DC889AF8ABF9E29 37890F32DFFF8E8E4CF23E08904F915F926A3B62424F7F275F286F4CC529EF4AEF59CF9A3838FF 2DCF4E4F2FEF9E1A778F51BF616FA209EF7B3F36AF656FA5EE3839DF3AEF695FFDAA2D383E0F5 52F402F925B7ECF431F0771AF453C92B1636F6C6F72A074626C3B5C9E106485C01A679E116E85 C07830756530F5785F65CB8035798A7AA17A5F7B69FF79747B9279FF7DCFD8D7D0DF7B3F798F FA659ED038835A8471842F853979747F856283CF879F875D86DF850F88D4393F63508C248D81 85A38D8092A22A5C54646560517074113368D17325BF40208EC670618F61716C3F7410565078 A0E0A078A04DE06463B4746C90A07291A0AA30708F11C46175AE605C617390A09200A34E5093 026E756D96A06192C004746F9300646A757374F9E0A0676892F0E0A079015650790114697490B 03090105C6E6F867155D16E306F7465209A70A994C0796C6DB0689E20749A70FF90FF920F931F 942F953F836099006060C9604173317410616678A09E208B8FE19A106C6020673130CB807F982 19BE09D949D318F9698309EE333DB67309ED26685D0A11263896073E039A0B36E70A109A2A47 410736EE86578749D3173968078006E40B674A3D155E069780095E079A4424797504E7073E03 9393068B039FE366DD0A4A278408EC39DD19D319B903B73F0AE707697009730B2E06D699E68 73E08F106E609730756EA8D15E659BC07880A4F99DF04499B4201A504E6061896090B0682046 E86F6E748EB4749DE05F50AC90AD5FF077A2409BE066AC905773E07874684267309BE090A0A7 F06C979F106D00AE2472AE98666CAE062BAD70B00772AE026362FF90A04EA0B1F29091 B26278309550789113B32497507065AE01736365BC6C6C98C1ADD0AD71B38173A840BF7810C EC1AC81C680AF20B5E66CB5F5CE62B5F59940B6046467B6E6B860F7B7E69DA0B6047690DF98F F9A0F9B1FFF9C2F9D3F8FA19E6F9F7FA08FA19FA2AFFFA3B7ACB0A86FA97AA486A6C475B0CAB0 FF9770A727C1A1A7E89D6DC1BCBC3077C0F66675A0973062BC707880AC00A7A27FC6EFA998A 5E47530592049C0962048FFB411B6D09550DDA3A763A6A0CA8FCB9FFFC985E0CD6FCE7FCF8 FD092ABF0B4A0FFAD107880D0DF68B0D20F9DBEC1BFC2C4BFB2B0A442D53FD646A52AD0F173 AC00C7C951973077D06D706F04E0D76F62456E40696C53975268B031B777838EF0F010767821 971055D140F99660776EE356A611E3F2E513E8C0FD753039E8C0E513D055E66563405400FF6F9

Property name	Value
	0A609E51360D03DF08D800120EC61726DA4C16850BB90E9A3ABF233656B606DF8106B429552 EAE553947562EB5173A6F16C46FC303E63EB5173F0BC80AAD15F506D6C6A4D4E6067EB3372ED B78F114AF663ED71BBB249B36078F04EA0F8E073EB519550744C6D90EB5104A072AA79F09131 8EC378ED906EBE200FE402F1B49DF0BE7074703A2F4E2FB47097A06E40732ED61063575FF0E08 0AD702EE1012FF4306691FC60652F77800642F4B506FC370F513ED9077905C90A1B59077EF85 E0E94078A0F653686B32EB51EDC17FAE80F013EDC1AF30F836EFF5EDC162EDF00367BDA096F0 729571BE3004E07FBB407410BB11AD10BB40B6D1AD706E9C626ABC6078F0A7F06F63AD41FDE CB06B96D0A8409DE0FCD4A49400703FC1518F00AC0096E1EAE0788073794E73A490EFE183616 C79AC00764FED9078A0FEB895916764A4D061BD78A266FCA1E3D0EFD1B531765641BF0171A4 10ED905F509790AD1070C130FBB48003906CADC0A41295D0C4F078007DD60178788077D0AC1 0EFD178A073FE61A840955002B3F1C105D10391F1C1DFB5905FF04E705F50966078C130F2F0D4 6F7978F05CA4107097907810BF60309660BC31B6D0BC80FCC064AC10F37830F1F06264B76096 60BC81B4809FA491CD01A4929790BDE0655C03907C727AFCA2B860F7D295500C7168E70AB37 110007167760D490C01BE50FF955011200DB30EC40E730382FE910DE15D10536A08A16020C4A 076455077FE6BB3516B6011B2B4705640C401F6F1FBF9E0B97265BDE01315A49096E0A501FD0 00074E49095500BE0FC0114A7BE70FF6E40BDA0BC809651F1E0BE70BDE17821FFCCF025502D0 0DE00F1E0C11109F2B351FFBA8014B012A1BB407830AD2114A17821FF7810B911F1E0EAF10B2 10BE09660EAF1FDBBB0701712A3F090B0BD0C4729550FFB482C111D8A1F4D0B490D661FF40B 490B9BBA17070A960BB40BC61696020BF1A36A6025FF096E0E776A400777821FFA5D2BC304E1 096608960AD10BD92F4D0FFBC50A9C104D1EC309750A4915650BE20FB9651B3516EEAE1AC90 25B0B4901A21E7B490E3D096516378BC80950FC9A1FF95D0B3600981D8C02401087196609E20 FE63F1F117129E2023F3BDA09550B6E06E6825631472F30067BB72FED163FF02B016537820EB0 02622743018F22872C102B0747862785C1A50C500BF4E70A400BC5012A0F36105516C17A1FF74 1009313D40E111A4D2C3F0A4308ED2727701D1666D29A0E2B0FA8120FFE9400F309642C3F0A4 D034F04E9008E0EF96E0BB5085D095D06CA4906E4012A0FB18B0F1E0759610DC42BB71A3D1FB 11FFA9F1FAD59582A41078A0FC71A970B590FF0BE03173BC0430803163E73AFF70FC12CF97118 EF0BD20FB016C760351BD21FFF3F0BD5035F195F078103672B351EFD1FF50A0F6F1A970C14197 11BD202A7095F0FC202EE36435F663503692DC5136FFFF380F391F36506730BD208F10FCC03AE FFB3BFF3D0F6C6B60BD20DB003AAF3F77D408529396C6F903E4F433F406562FF6E704CB1446F 362355B0420F46DF47EFFF48FF364168D04A5236DF4BBF4CCF44DDFF6D004A5F4FEF50FF520F3 6415B704EEFFF548F559F56A5F641B630F640C1309550FFDC33BB72BA5FBB6FBC7FBD8FBE9FDA DFFFC0CFDC5FC2EFC3FFC50FA3B16AF0D2CF9F644ADDA124F1ACF0E8C920571380C06E3A204F 63632F206DC0DF0231F1106BD07880A4007301706CF08F8F2066605DC0A832322F31F5A0D9F5 71382074322E503AF580AB402C4D2060306F31336F732847584D542DAF506F5129AB41630E69 F4D175B376B0555320260C20437470606061292E0DDE0A5B926BD278D06C2043AC006660FF78 D01C2176516F1185E0EAB072E572E5FC2A7E75FE750C5B845C4F5D5F5E6FFF57F608F95B65B9 258A0D02968BF69CFDD6ADF2873C0B7D0FB11A9E140D0B4017F6FD05C21ADD0970073CE7BC1 FF2072B229750C48656CF0EC612C750CE24C2B3172717596E26C9071D0FD2B302030B06CAF6F C1FF501C2088B27FAC0083A358812F106C90F43083A346B3C99066F06B616F20E9F06F1130977 9D072D672E55440116B7386B6FA4502D07AC9902F41E9717F5F806FFF6AFCA7707B60B7D0D02 9778635B208113F0252975379106D607CB0F0A06178FC3236DD309521D8A0FD10D8D07A81FF7 D619531D6077A812FD09521A96897A6FFC8959686A5267A81A640E98095F7A410FFB4801B207 90196EAD3A2980A9D04C895FF62C19A099D0496246200A6C59C2F9D3FFB9E4FA544399FCB138 2FE6174B0A0F377A34FA45FA56732A60FA71FA51C3377A91FAA2FA51C34AC2FAD3FA51C3577A F3FB04FA51C36B24FB35FA51C3777B55FB66FA51C38B86FB97FA51C39FFA0F3BC96E6209FCB7C 407190A5F4BEDFFFBE8A904C0EFBFE8AC14C2FFBFE8AF24FFC50FBFE8B234C71FBFE8B5444C92 FBFE8FB854CB3FBFE8BB64CD4FBFE8BE74BBCFFFC9364129FF812A01B20BCB0E4A0A10FFFA2 1FD14FBCB4DE729FE971B02FA1CF0BFF9ED4A016ED417AB27121ECA001D061E0FE688BE00571 D41FD52FD63FD956D9CCFFEBE1FE50D8C6DC5FDD6FDE7F8330F6C0F7DFCC7CC0057067E11FE 22FE33FE446DD9FBC452CA07B601F0073E60FE71FCF9A096B80D7DC24B2204766F1EB13DBE75 EA0165003D62E31540461EB1FFFEF8FE82FD95FA054E0800AC1FE61F24FBE3F59A09369FBC4C 7CE2E0800BB1FFF73FF84FF95DD9CCFB24FB2022A0FBFFFFD0FF98AE4CCFB24EF3700AF01BFF 9D5EB68909FDA4D2BA0697BD0FB76A5E5F7050F061FF9D53407AF08B9A90409CFFF0ADFF9D5D 2CC08750012095F0F2FF96CBF6BC0113F12450E2F13CFF97B3715BFFF08B1EF3212AF184FF96C6 ED01A5F1B65FF174F1CEFF97BBD1C1B1AC4A420CF21DFD5BCB4379FBC4458A06B000F25CF2 6DFD9CC73C096207266DAE0FB7FFF29EF2AFF27B1E4CC2D17291F2EEF26EE7F079C2D17047F3 37FF94F034FFB6720FE416C5059411BCF382FFDFF3A4F1263FF3BDF3CEF3DFF030F041840BF41C F42DFFF075F086F45AF46BF47CF0C1F0D2F4AFF7F4C0F4D1F10DF11EC504CEFCFDA3552FF6CB0

Property name	Value
	EAF0D3EF51BFF43FCF394E6C1263BFDB27584F595F5A6FE446235C518802DF5DBF5ECF5FDFCF6 627EC4994906C00FF56B0623F634F529F159F16A9504F687FFF698F19FF1B0C6C8F6D9F6EAF1E8 F1F9CFF71AF72BF73CF231F242C76CF77DF78EFFF27AF28B87BEF7CFF7E0F2BFF2D0F80CFFF81D F82EF30BF31CC861F872F883F354FFF365C8B3F8C4F8D5F39DF3AEF9083206FFF91EF3E6F3F7F8 B0995FF970F435F446FFF90299AEF9BFF484F7A7F4A6F9FDFA0EFFF4D9FA30F4FBFA52FA63F52E FA85F550CFFAA7FAB8F6A0FADAF6C2CAF9FB0AF6F2FFF2CF714CB4BFB5CF744FB7EF766CB9DF FFBAEF796FBD0F7B8CBEFFC00F7E8F7F9FFF9A4FC48FC59F83DF84EF955FC96FCA7FFF892F8A3F CDDFCEEF3FF8E7F8F8FD32FFFD43FC0DF93CF94DF24EFD98F980FDBAFF8AFADDAFDEBFD9D0F 9E1F9029E29FE3AFFFA1FFC22FA41FE78FE89FA74FEABFA96FFFECDFEDEFAC9FF00F550CF22FF3 3FB1BFFFF55F6C2CF74FF85FB6DFFA7F714CFC6FFF7D7FBBFFFF9F766C018F029FC11F04BFFF7B 8C06AF07BFC63FC74FE1FF0C3F0D4FFFCB8FCC9FDD0F11F122FD0DFD1EF158FFF169F17AFD62 FD73F1ADF1BEF088FDB7FF9DC8F2034204F215FDFDFE0EF8B18FF255F266FE4BE5CF90292A4F 2B5FE9AFF09DFEBCF2F3F04FEEFF326FF11F348FFF359FF44F37BF550C39DF3AEFF96F3D0FFF6 C2C3EFF400FFE8F422F714C441F452FFF03AF474F766C493F4A4F08CF4C6F7B8CFF4E5F4F6F0DE F0EFF29AF53EF54FF133FFF144F24BF58CF59DF188F199F5D3F5E4FFF5F5F1DDF1EEF628F639F50 3F232F243FFC203567FF690F278F289F8B186D0FFF6E1F2C6F2D7F902971FF730F315F518FFF337 F76EF77FF36AF7A1F38CF7C3F7D4FFF3BFF7F6FAEBC818F829F411F84BFB3DCFF86AF87BF463F8 9DFB8FC8BCF8CDF4B5FFF8EFFBE1C90EF91FF507F941FC33C960FFF971F559F56AF715F9B9F9CA F5AEF5BFFFF6C6FA07FA18F603F614FA4EFA5FFA70F7F658F669FAA3FAB4F97EF6ADF6BEF20FE3 6AFAFB0BF6F3F704FD2C8B4BFB5CFFF741F752FD7D9B9AFBABF790F993F7B2FFFBE9FBFAF7E5F C1CF807FC3EFC4FF83AFFFC71FF66CC93FCA4F88CFCC6FFB8CCE5FFF6CF6F8DEFD18F00ACD37FD 48F930FD6AFF05CCD89FD9AF982FDBCF0AECDDBFDECF9D4F9E5FB90FE34FE45FA29FA3AFB 41FFF82FE93FA7EFA8FFEC9FEDAFEEBFAD3F4FAE4FF1EFF2FFDF967166F6206D2C6174EAA4B1F 631E0AC53750062746C6520456D707D3380733E20F75FF86FF97FB20532FDEAAC4920001FF0F3 F0FC4FFD5FFE6F0DF9FE33EAACFBE552656665FE721FF01FE0026F037F048F0596BC9C3F016607 6F087F098F0A9FF51C426FFA6F577054B240FC200D930587D66C104269626CB2106772613D020 0790D930FEF05C3E0AC544F104320486533933B7D7D607B5C2A5C64F9F002207483F62001C03 03130353019D2963219D31990381A343464F500403738366436630B903280653533343135381C 30E11B1034633532CC10B790C6C0F7CC10EFE01BD0331CB01D801A341E3E07B27019D1F0A063 6631316590306131621FD0616519A07B209F218C331FF0227119D00D2066F86630391F1623EF1 A7124BD249DFF231227322416271E2797299F2AAF2BBFFF2CCF2DDF2EEF2FFF310F321F332F34 3FFF354F365F376F387F398F3A9F3BAF3CBFFF3DC3EDF3FEF40FF420F431F442F453FFF464F475 F486F497F4A8F4B9F4CAF4DBFFF4ECF4FDF50EF51FF530F541F552F563FFF574F585F596F5A7F5 B8F5C9F5DAF5E9CFE645E952725608F619F62AF63BF64CFFF65DF66EF67FF690F6A1F6B2F6C3F6 D4FFF6E5F6F6F707F718F729F73AF74BF75CFFF76DF77EF78FF7A0F7B1F7C2F7D3F7E4FFF7F5F80 6F817F828F839F84AF85BF86CFFF87DF88EF89FF8B0F8C1F8D2F8E3F8F4FFF905F916F927F938F9 49F95AF96BF97CFFF98DF99EF9AFF9C0F9D1F9E2F27331CB0A71F2127819FD237341A043419C1 FE3622A1A052EFE0A0312362A21FA32FFFA43FA54FA65F1A711F4219C19E8F5FB6A263E090643 938A9F062AA1056331C811C40391820661B90647D1C21621FF0288FAC061A211FF139F1AD706 13661AA801990281FAF1FFF02FB13FB24FB35FB46FB57FB68F292FFF8B8CB70FBA9FBBAFBCBF BDCFBEFDFBEFFFC0FFC20FC31FC42FC53FC64FB76FC86FFF89FCA8FCB9FCCAFCD8FCECFDFD D0EFFF1FFD30FD41FD52FD63FC75FD85FC97FFFDA7FDB8FDC9FDDAF25DE19C4DE951890020 0E0C0
<b>PidTagSensitivity</b>	0
<b>PidTagSubject</b>	Fabrikam Project Status Meeting

The following shows the resulting iCalendar file.

```
BEGIN:VCALENDAR
PRODID:-//Microsoft Corporation//Outlook 12.0 MIMEDIR//EN
VERSION:2.0
METHOD:REQUEST
```

X-MS-OLK-FORCEINSPECTOROPEN:TRUE  
 BEGIN:VTIMEZONE  
 TZID:Pacific Time (US & Canada)  
 BEGIN:STANDARD  
 DTSTART:16011104T020000  
 RRULE:FREQ=YEARLY;BYDAY=1SU;BYMONTH=11  
 TZOFFSETFROM:-0700  
 TZOFFSETTO:-0800  
 END:STANDARD  
 BEGIN:DAYLIGHT  
 DTSTART:16010311T020000  
 RRULE:FREQ=YEARLY;BYDAY=2SU;BYMONTH=3  
 TZOFFSETFROM:-0800  
 TZOFFSETTO:-0700  
 END:DAYLIGHT  
 END:VTIMEZONE  
 BEGIN:VEVENT  
 ATTENDEE;CN=sito@contoso.com;RSVP=TRUE:mailto:sito@contoso.com  
 ATTENDEE;CN=pcook@contoso.com;RSVP=TRUE:mailto:pcook@contoso.com  
 ATTENDEE;CN=aweiler@contoso.com;RSVP=TRUE:mailto:aweiler@contoso.com  
 CLASS:PUBLIC  
 CREATED:20080208T213600Z  
 DESCRIPTION:When: Occurs every Wednesday effective 2/13/2008 from 2:00 PM t  
     o 2:30 PM (GMT-08:00) Pacific Time (US & Canada).\nWhere: Conference Room  
     1234\n\n\*~\*~\*~\*~\*~\*~\*~\*~\*~\*\n\n(Corrected a typo in the Conference Room nu  
     mber)\n\nHey all\,\n\nLet's meet up every Wednesday to sync up on the st  
     atus of the Fabrikam Project.\n\nThanks\,\n\nElizabeth\n  
 DTEND;TZID="Pacific Time (US & Canada)":20080213T143000  
 DTSTAMP:20080208T213600Z  
 DTSTART;TZID="Pacific Time (US & Canada)":20080213T140000  
 EXDATE;TZID="Pacific Time (US & Canada)":20080528T140000  
 LAST-MODIFIED:20080208T213600Z  
 LOCATION:Conference Room 1234  
 ORGANIZER;CN="Elizabeth Andersen":mailto:eandersen@contoso.com  
 PRIORITY:5  
 RRULE:FREQ=WEEKLY;BYDAY=WE  
 SEQUENCE:1  
 SUMMARY;LANGUAGE=en-us:Fabrikam Project Status Meeting  
 TRANSP:OPAQUE  
 UID:040000008200E00074C5B7101A82E008000000003046642B576AC8010000000000000000  
     010000000622C639E40D09342B747A1672730CBBA  
 X-ALT-DESC;FMTTYPE=text/html:<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 3.2//E  
   N">\n<HTML>\n<HEAD>\n<META NAME="Generator" CONTENT="MS Exchange Server ve  
   rsion 08.00.0681.000">\n<TITLE></TITLE>\n</HEAD>\n<BODY>\n<!-- Converted f  
   rom text/rtf format -->\n\n<P DIR=LTR><SPAN LANG="en-us"><FONT FACE="Calib  
   ri">When: Occurs every Wednesday effective 2/13/2008 from 2:00 PM to 2:30  
   PM (GMT-08:00) Pacific Time (US & Canada).</FONT></SPAN></P>\n\n<P DI  
   R=LTR><SPAN LANG="en-us"><FONT FACE="Calibri">Where: Conference Room 1234<  
   /FONT></SPAN></P>\n\n<P DIR=LTR><SPAN LANG="en-us"><FONT FACE="Calibri">\*~  
   \*~\*~\*~\*~\*~\*~\*~\*~\*~\*</FONT></SPAN></P>\n\n<P DIR=LTR><SPAN LANG="en-us"><FONT  
   FACE="Calibri">(Corrected a typo in the Conference Room number)</FONT></S  
   PAN></P>\n\n<P DIR=LTR><SPAN LANG="en-us"><FONT FACE="Calibri">Hey all\,</  
   FONT></SPAN></P>\n\n<P DIR=LTR><SPAN LANG="en-us"><FONT FACE="Calibri">Let  
   's meet up every Wednesday to sync up on the status of the Fabrikam Proj  
   ect.</FONT></SPAN></P>\n\n<P DIR=LTR><SPAN LANG="en-us"><FONT FACE="Calibr  
   i">Thanks\,</FONT></SPAN></P>\n\n<P DIR=LTR><SPAN LANG="en-us"><FONT FACE=  
   "Calibri">Elizabeth</FONT></SPAN><SPAN LANG="en-us"></SPAN></P>\n\n</BODY>  
   \n</HTML>  
 X-MICROSOFT-CDO-BUSYSTATUS:TENTATIVE

X-MICROSOFT-CDO-IMPORTANCE:1  
 X-MICROSOFT-CDO-INTENDEDSTATUS:BUSY  
 X-MICROSOFT-DISALLOW-COUNTER:FALSE  
 X-MS-OLK-ALLOWEXTERNCHECK:TRUE  
 X-MS-OLK-APPTSEQTIME:20080208T213320Z  
 X-MS-OLK-AUTOSTARTCHECK:FALSE  
 X-MS-OLK-CONFTYPE:0  
 X-MS-OLK-SENDER;CN="Elizabeth Andersen":mailto:eandersen@contoso.com  
 BEGIN:VALARM  
 TRIGGER:-PT15M  
 ACTION:DISPLAY  
 DESCRIPTION:Reminder  
 END:VALARM  
 END:VEVENT  
 END:VCALENDAR

The following table lists the properties on the Calendar object that Shu receives.

Property name	Value
<b>PidLidAllowExternalCheck</b>	TRUE
<b>PidLidAppointmentDuration</b>	30
<b>PidLidAppointmentEndWhole</b>	02:30:00.000 PM 2/13/2008
<b>PidLidAppointmentNotAllowPropose</b>	FALSE
<b>PidLidAppointmentRecur</b>	cb: 84 lpb: 043004300B2001000000C02100000100000000000000008000000232000000A000000000000000 1000000A08DC50C00000000003FC30CDF80E95A0630000009300000480300006603000000000 0000000000000000
<b>PidLidAppointmentSequence</b>	1
<b>PidLidAppointmentStartWhole</b>	02:00:00.000 PM 2/13/2008
<b>PidLidAppointment</b>	3

Property name	Value
<b>ntStateFlags</b>	
<b>PidLidAppointmentSubType</b>	FALSE
<b>PidLidAppointmentSequenceTime</b>	09:33:20.000 PM 2/8/2008
<b>PidLidAutoStartCheck</b>	FALSE
<b>PidLidBusyStatus</b>	1
<b>PidLidCleanGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E008000000003046642B576AC801000000000000000010000 000622C639E40D09342B747A1672730CBBA
<b>PidLidConferencingType</b>	0
<b>PidLidInvited</b>	TRUE
<b>PidLidGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E008000000003046642B576AC801000000000000000010000 000622C639E40D09342B747A1672730CBBA
<b>PidLidIntendedBusyStatus</b>	2
<b>PidLidLocation</b>	Conference Room 1234
<b>PidLidOwnerCriticalChange</b>	09:36:00.000 PM 2/8/2008
<b>PidLidReminderDelta</b>	15
<b>PidLidReminderSet</b>	TRUE
<b>PidLidReminderSi</b>	09:45:00.000 PM 2/13/2008





Property name	Value
<b>ssed</b>	F862696404000330010301F70A80FF02A403E40713028010830050045608559F07B211B50E510301020063680AC07073657432060006C311B533DB044614473012BF02003403C5165AF9074069620510028011C308EF09F7B63B1ABF0E303511B20C60630050330B090164333616E00BA534205910822A5C0EB20190671F603300203C21444F4354590050452048544D4C20005055424C49432022402D2F2F5733432220444454442134332E32222045F84E223E11C31FD720800AA323BCFC31392090214223AD14D024BF2471E31F70261045414423AD0EF1278F050E10360EF03C4D455441C507B0412BB03D224709F0049014617405B02216F04F4E544D2370542C4005E1457814616EF4676506527613112E9100900220402030382E30302F70367438312F7130239E2A1F25A337823720905449544C45266EA6340EF0250D383520902F32DF7F310F1FF53421357028EF273F200435C116E03C424F445923AD1EE14739DF20513B01212D2D16F16E552E91740980200352203EA078FC742F00213ED005B000C005403E102F3B7F3C8F412F20043628B15020804449523D4C545223A0BF1FE33F82000044E51EE144E65C2020CE720AB146A214605C7103214587051F9B3828B15350414E201A4C4980472C4009F02D757347239144DF482E313438209046E12D21204641432C3119554A6C13181047A9576809F03A204FAC636308700420652E91794FB0E309802C8073646150D0011105901474692E9020234031332F6701D02F503ED4323A2F8021804D153F206F531133535328474DEC542D2F50533129218000D006906D0DE020076254405505F0485E26D8616D7002804A972645781941246E615150292E251C3536DF35614CF24A794A87483D3914D03570FF49625ACF45CB0AA25B780A8146270AB1EF6048483D01C0356150405F42BF63FFFF438F449F45AF46BF616F48DF49EF4AFFFF4C0F4D1F4E2F4F3A1AC050003E4151B0F91AC06E632E4008003F010E2028A0FF595F5A6F5B7F5C8F75CF5EAF5FBF60CFFF61DF62EF654F7EAF661F672F683F694FFF6A5F6B6F6C7F82BF6E9F6FAF70BF4EFBFC2A7E8D8F744F755F766F777F903FFF799F7AAF7BBF7CCF7DDF803F991F810FFF821F832F843F854F865F876F9D2F898FD78A9F8BAF4EFB280850721AC051D0E53EB1613F20797053B00B803F20B34FD072FF6E7506D00490298EBFFF8FC90DF91EFAC7F940F951F962F973FFF984F9AAFB55F9B7F9C8F9D9F9EAF9FBF7FA0CFA1DFB96FA3FFA50FA61F4EFB48E66550D007406C2CAAFFAC0FAD1FFFAE2FC63FB04FB15FB26FB37FB48FB6EFFFCF1FB7BFB8CFB9DFBAEFBBFFBD0FBE1F5FD32FC03FC14FC25F4EFB4C14B05C1E27C8500420078014B0207570F3508F53A173797370DEC22F21A9427A73019074D870E0A03FA0A94246BB01A005106B5730218003606A51C1FF594FC5BFC6CFC7DFE48FC9FFCB0FCC1FFFCDD2FCE3FD09FED6FD16FD27FD38FD49FFFD5AFD6BFD7CFF17FD9EFD AFFDC0F71BCF2542E016B73C4AFE41FE52FE63FFFFE3FE85FE96FEA7FE8BFEC9FEFF071FFFECFF0DF1EFF2FFF40FF51FF62F0B2FAFF84FF95FFA6F71BC4514007AE210FDDE0068FCCFFDDFFEEFFFF181F192FFF0F6F107F1B9F19EF1AFF023F034F045F056F067F08DF275F3A7713012F3B3F8F398F2B5532A13860544D4C1460027D2DC0
<b>PidTagSenderAddressType</b>	SMTP
<b>PidTagSenderEmailAddress</b>	eandersen@contoso.com
<b>PidTagSenderEntryId</b>	cb: 116 lpb: 00000000812B1FA4BEA310199D6E00DD010F54020000008045006C0069007A0061006200650074006800200041006E00640065007200730065006E00000053004D00540050000000650061006E00640065007200730065006E00400063006F006E0074006F0073006F002E0063006F006D000000
<b>PidTagSenderName</b>	Elizabeth Andersen
<b>PidTagSensitivity</b>	0
<b>PidTagS</b>	Fabrikam Project Status Meeting

Property name	Value
subject	

### 3.4.4 Attendee's Tentative Acceptance of the Series

Shu tentatively accepts the recurring meeting.

The following table lists the properties on the Calendar object that Shu sends.

Property name	Value
<b>PidLidAppointmentCounterProposal</b>	FALSE
<b>PidLidAppointmentDuration</b>	30
<b>PidLidAppointmentEndWhole</b>	02:30:00.000 PM 2/13/2008
<b>PidLidAppointmentRecur</b>	cb: 84 lpb: 043004300B2001000000C021000001000000000000008000000232000000A000000000 0000001000000A08DC50C00000000003FC30CDF80E95A06300000093000004803000066 03000000000000000000000000000000
<b>PidLidAppointmentSequence</b>	1
<b>PidLidAppointmentStartWhole</b>	02:00:00.000 PM 2/13/2008
<b>PidLidAppointmentStateFlags</b>	0
<b>PidLidAppointmentSubType</b>	FALSE
<b>PidLidAttendeeCriticalChange</b>	09:51:51.956 PM 2/8/2008
<b>PidLidAutoFillLocation</b>	FALSE
<b>PidLidBusyStatus</b>	2
<b>PidLidCleanGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E008000000003046642B576AC80100000000000000 010000000622C639E40D09342B747A1672730CBBA
<b>PidLidCollaborateDoc</b>	
<b>PidLidConferencingType</b>	0

Property name	Value
<b>PidLidDirector y</b>	
<b>PidLidFInvited</b>	FALSE
<b>PidLidGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E008000000003046642B576AC80100000000000000 010000000622C639E40D09342B747A1672730CBBA
<b>PidLidIntendedBusyStatus</b>	4294967295
<b>PidLidLocation</b>	Conference Room 1234
<b>PidLidNetShowUrl</b>	
<b>PidLidOnlinePassword</b>	
<b>PidLidOrganizerAlias</b>	
<b>PidLidOwnerCriticalChange</b>	09:36:00.000 PM 2/8/2008
<b>PidLidReminderDelta</b>	0
<b>PidLidReminderSet</b>	FALSE
<b>PidLidReminderSignalTime</b>	02:00:00.000 PM 2/13/2008
<b>PidLidReminderTime</b>	02:00:00.000 PM 2/13/2008
<b>PidLidResponseStatus</b>	0
<b>PidLidTimeZoneDescription</b>	(GMT-08:00) Pacific Time (US & Canada)
<b>PidLidTimeZoneStruct</b>	cb: 48 lpb: E001000000000000C4FFFFFF000000000B000000010002000000000000000000000000300 000002000200000000000000
<b>PidTagCreationTime</b>	09:51:51.940 PM 2/8/2008
<b>PidTagImportance</b>	1
<b>PidTagLastModificationTime</b>	09:51:52.174 PM 2/8/2008
<b>PidTagMessageClass</b>	IPM.Schedule.Meeting.Resp.Tent

Property name	Value
<b>PidTagMessageLocaleId</b>	0
<b>PidTagSensitivity</b>	0
<b>PidTagSubject</b>	Tentative: Fabrikam Project Status Meeting

The following shows the resulting iCalendar file.

```

BEGIN:VCALENDAR
PRODID:-//Microsoft Corporation//Outlook 12.0 MIMEDIR//EN
VERSION:2.0
METHOD:REPLY
X-MS-OLK-FORCEINSPECTOROPEN:TRUE
BEGIN:VTIMEZONE
TZID:Pacific Time (US & Canada)
BEGIN:STANDARD
DTSTART:16011104T020000
RRULE:FREQ=YEARLY;BYDAY=1SU;BYMONTH=11
TZOFFSETFROM:-0700
TZOFFSETTO:-0800
END:STANDARD
BEGIN:DAYLIGHT
DTSTART:16010311T020000
RRULE:FREQ=YEARLY;BYDAY=2SU;BYMONTH=3
TZOFFSETFROM:-0800
TZOFFSETTO:-0700
END:DAYLIGHT
END:VTIMEZONE
BEGIN:VEVENT
ATTENDEE;PARTSTAT=TENTATIVE:mailto:sito@contoso.com
CLASS:PUBLIC
CREATED:20080208T215151Z
DTEND;TZID="Pacific Time (US & Canada)":20080213T143000
DTSTAMP:20080208T215151Z
DTSTART;TZID="Pacific Time (US & Canada)":20080213T140000
EXDATE;TZID="Pacific Time (US & Canada)":20080528T140000
LAST-MODIFIED:20080208T215152Z
LOCATION:Conference Room 1234
PRIORITY:5
RRULE:FREQ=WEEKLY;BYDAY=WE
SEQUENCE:1
SUMMARY:Tentative: Fabrikam Project Status Meeting
TRANSP:OPAQUE
UID:040000008200E00074C5B7101A82E008000000003046642B576AC801000000000000000
010000000622C639E40D09342B747A1672730CBBA
X-MICROSOFT-CDO-BUSYSTATUS:BUSY
X-MICROSOFT-CDO-IMPORTANCE:1
X-MS-OLK-AUTOFILLLOCATION:FALSE
X-MS-OLK-CONFTYPE:0
END:VEVENT
END:VCALENDAR

```

The following table lists the properties on the Calendar object that Elizabeth receives.

Property name	Value
<b>PidLidAppointmentDuration</b>	30
<b>PidLidAppointmentEndWhole</b>	02:30:00.000 PM 2/13/2008
<b>PidLidAppointmentRecur</b>	cb: 84 lpb: 043004300B2001000000C02100000100000000000000008000000232000000A00000000000 00001000000A08DC50C000000000003FC30CDF80E95A063000000930000048030000660300 0000000000000000000000
<b>PidLidAppointmentSequence</b>	1
<b>PidLidAppointmentStartWhole</b>	02:00:00.000 PM 2/13/2008
<b>PidLidAppointmentStateFlags</b>	3
<b>PidLidAppointmentSubType</b>	FALSE
<b>PidLidAttendeeCriticalChange</b>	09:51:51.000 PM 2/8/2008
<b>PidLidAutoFillLocation</b>	FALSE
<b>PidLidBusyStatus</b>	2
<b>PidLidCleanGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E008000000003046642B576AC8010000000000000001 0000000622C639E40D09342B747A1672730CBBA
<b>PidLidConferencingType</b>	0
<b>PidLidFInvited</b>	FALSE
<b>PidLidGlobalObjectId</b>	cb: 56 lpb: 040000008200E00074C5B7101A82E008000000003046642B576AC8010000000000000001 0000000622C639E40D09342B747A1672730CBBA
<b>PidLidLocation</b>	Conference Room 1234
<b>PidLidReminderDelta</b>	1080

Property name	Value
<b>PidLidReminderSet</b>	FALSE
<b>PidLidReminderSignalTime</b>	04:00:00.000 AM 2/13/2008
<b>PidLidReminderTime</b>	10:00:00.000 PM 2/13/2008
<b>PidLidResponseStatus</b>	2
<b>PidLidTimeZoneDescription</b>	(GMT-08:00) Pacific Time (US & Canada)
<b>PidLidTimeZoneStruct</b>	cb: 48 lpb: E001000000000000C4FFFFFF00000000B000000010002000000000000000000000030000 0002000200000000000000
<b>PidTagCreationTime</b>	09:56:53.622 PM 2/8/2008
<b>PidTagImportance</b>	1
<b>PidTagLastModificationTime</b>	09:56:53.810 PM 2/8/2008
<b>PidTagMessageClass</b>	IPM.Schedule.Meeting.Resp.Tent
<b>PidTagMessageLocaleId</b>	1033
<b>PidTagReplyRequested</b>	FALSE
<b>PidTagResponseRequested</b>	FALSE
<b>PidTagSenderAddressType</b>	SMTP
<b>PidTagSenderEmailAddress</b>	sito@contoso.com
<b>PidTagSenderEntryId</b>	cb: 84 lpb: 00000000812B1FA4BEA310199D6E00DD010F5402000001805300680075002000490074006 F00000053004D005400500000007300690074006F00400063006F006E0074006F0073006F0 02E0063006F006D000000
<b>PidTagSenderName</b>	Shu Ito

<b>Property name</b>	<b>Value</b>
<b>rName</b>	
<b>PidTagSensitivity</b>	0
<b>PidTagSubject</b>	Tentative: Fabrikam Project Status Meeting



## 4 Security

### 4.1 Security Considerations for Implementers

Authentication of the source of an iCalendar is not supported. As such, Calendar object(s) resulting from the import of an iCalendar are only as trustworthy as the source of an iCalendar. This has special implications with regard to spoofing the ORGANIZER and ATTENDEE properties.

The FMTTYPE parameter of the ATTACH property (section [2.1.3.1.1.20.1.2](#)) can be mislabeled and it is recommended that it be verified. See [\[MS-OXCMAIL\]](#) section 4.1.3. Furthermore, since the ATTACH property encodes binary files, it can contain malicious content. This is particularly interesting because virus scanners might not be able to parse iCalendar data.

### 4.2 Index of Security Parameters

None.

## 5 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft® Exchange Server 2003
- Microsoft® Exchange Server 2007
- Microsoft® Exchange Server 2010
- Microsoft® Exchange Server 2013
- Microsoft® Office Outlook® 2003
- Microsoft® Office Outlook® 2007
- Microsoft® Outlook® 2010
- Microsoft® Outlook® 2013

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

[<1> Section 2.1.3.1.1:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not support multiple VCALENDAR components in an iCalendar stream. Office Outlook 2007 and Outlook 2010 only support multiple VCALENDAR components when the METHOD property is PUBLISH.

[<2> Section 2.1.3.1.1.1:](#) Office Outlook 2003 and Exchange 2003 do not implement the 'COUNTER' value of METHOD. On export, both implementations will use the 'REPLY' value. On import, Office Outlook 2003 will treat the METHOD as 'PUBLISH', while Exchange 2003 will treat the METHOD as 'REPLY'.

[<3> Section 2.1.3.1.1.1:](#) Note that it is possible for a collection of two or more VEVENT components to represent a single appointment. However, Office Outlook 2003 has limited support for iCalendars with multiple VEVENT components. Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 have no support. Refer to the documentation on the RECURRENCE-ID Property in section [2.1.3.1.1.20.20](#) for additional information.

[<4> Section 2.1.3.1.1.1:](#) Office Outlook 2003 and Exchange 2003 do not implement the 'COUNTER' value of METHOD. On export, both implementations will use the 'REPLY' value. On import, Office Outlook 2003 will treat the METHOD as 'PUBLISH', while Exchange 2003 will treat the METHOD as 'REPLY'.

[<5> Section 2.1.3.1.1.4:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not support this property.

[<6> Section 2.1.3.1.1.4:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not support this property.

<7> [Section 2.1.3.1.1.5](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not support this property.

<8> [Section 2.1.3.1.1.5](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not support this property.

<9> [Section 2.1.3.1.1.6](#): Office Outlook 2007, Outlook 2010, and Outlook 2013 use this property for purposes outside the scope of this algorithm.

<10> [Section 2.1.3.1.1.6](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not support this property.

<11> [Section 2.1.3.1.1.7](#): Office Outlook 2007, Outlook 2010, and Outlook 2013 use this property for purposes outside the scope of this algorithm.

<12> [Section 2.1.3.1.1.7](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not support this property.

<13> [Section 2.1.3.1.1.8](#): Exchange 2003, Exchange 2007 (**WebDAV**), Office Outlook 2003, Office Outlook 2007, Outlook 2010, and Outlook 2013 do not support the X-MICROSOFT-CALSCALE property.

<14> [Section 2.1.3.1.1.8](#): Exchange 2003, Exchange 2007 (WebDAV), Office Outlook 2003, Office Outlook 2007, Outlook 2010, and Outlook 2013 do not support the X-MICROSOFT-CALSCALE property.

<15> [Section 2.1.3.1.1.8](#): Exchange 2003, Exchange 2007 (WebDAV), Office Outlook 2003, Office Outlook 2007, Outlook 2010, and Outlook 2013 do not support the X-MICROSOFT-CALSCALE property.

<16> [Section 2.1.3.1.1.8](#): Exchange 2003, Exchange 2007 (WebDAV), Office Outlook 2003, Office Outlook 2007, Outlook 2010, and Outlook 2013 do not support the X-MICROSOFT-CALSCALE property.

<17> [Section 2.1.3.1.1.8](#): Exchange 2003, Exchange 2007 (WebDAV), Office Outlook 2003, Office Outlook 2007, Outlook 2010, and Outlook 2013 do not support the X-MICROSOFT-CALSCALE property.

<18> [Section 2.1.3.1.1.9](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not support this property.

<19> [Section 2.1.3.1.1.9](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not support this property.

<20> [Section 2.1.3.1.1.10](#): Office Outlook 2007, Outlook 2010, and Outlook 2013 use this property for purposes outside the scope of this algorithm.

<21> [Section 2.1.3.1.1.10](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not support this property.

<22> [Section 2.1.3.1.1.11](#): Office Outlook 2007, Outlook 2010, and Outlook 2013 use this property for purposes outside the scope of this algorithm.

<23> [Section 2.1.3.1.1.11](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not support this property.

<24> [Section 2.1.3.1.1.12](#): Office Outlook 2007, Outlook 2010, and Outlook 2013 use this property for purposes outside the scope of this algorithm.

<25> [Section 2.1.3.1.1.12](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not support this property.

<26> [Section 2.1.3.1.1.13](#): Office Outlook 2007, Outlook 2010, and Outlook 2013 use this property for purposes outside the scope of this algorithm.

<27> [Section 2.1.3.1.1.13](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not support this property.

<28> [Section 2.1.3.1.1.13.1](#): Office Outlook 2007, Outlook 2010, and Outlook 2013 use this property for purposes outside the scope of this algorithm.

<29> [Section 2.1.3.1.1.13.1](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not support this property.

<30> [Section 2.1.3.1.1.14](#): Office Outlook 2007, Outlook 2010, and Outlook 2013 use this property for purposes outside the scope of this algorithm.

<31> [Section 2.1.3.1.1.14](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not support this property.

<32> [Section 2.1.3.1.1.15](#): Office Outlook 2007, Outlook 2010, and Outlook 2013 use this property for purposes outside the scope of this algorithm.

<33> [Section 2.1.3.1.1.15](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not support this property.

<34> [Section 2.1.3.1.1.16](#): Office Outlook 2007, Outlook 2010, and Outlook 2013 use this property for purposes outside the scope of this algorithm.

<35> [Section 2.1.3.1.1.16](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not support this property.

<36> [Section 2.1.3.1.1.16](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not support this property.

<37> [Section 2.1.3.1.1.16](#): Office Outlook 2007, Outlook 2010, and Outlook 2013 do not have logic to avoid splitting surrogate pairs.

<38> [Section 2.1.3.1.1.17](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not support this property.

<39> [Section 2.1.3.1.1.17](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not support this property.

<40> [Section 2.1.3.1.1.17](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not support this property.

<41> [Section 2.1.3.1.1.18](#): Office Outlook 2007, Outlook 2010, and Outlook 2013 use this property for purposes outside the scope of this algorithm.

<42> [Section 2.1.3.1.1.18](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not support this property.

<43> [Section 2.1.3.1.1.19](#): Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not support more than one VTIMEZONE component per iCalendar file.

<44> [Section 2.1.3.1.1.19](#): Office Outlook 2003, Office Outlook 2007, Exchange 2003, Exchange 2007, and the initial release version of Exchange 2010 do not export or import

**PidLidAppointmentTimeZoneDefinitionRecur**, **PidLidAppointmentTimeZoneDefinitionStartDisplay**, or **PidLidAppointmentTimeZoneDefinitionEndDisplay**. These implementations only use **PidLidTimeZoneDescription** and **PidLidTimeZoneStruct** when exporting or importing VTIMEZONE components and TZID parameters.

<45> [Section 2.1.3.1.1.19](#): Exchange 2010 SP1 and Exchange 2013 set the **wYear** field to 0x0001 for the first **TZRule** structure in the array.

<46> [Section 2.1.3.1.1.19](#): Office Outlook 2007, Outlook 2010, and Outlook 2013 use a case-sensitive TZID comparison function.

<47> [Section 2.1.3.1.1.19](#): Office Outlook 2003, Office Outlook 2007, Exchange 2003, Exchange 2007, and the initial release version of Exchange 2010 do not export or import

**PidLidAppointmentTimeZoneDefinitionRecur**, **PidLidAppointmentTimeZoneDefinitionStartDisplay**, or **PidLidAppointmentTimeZoneDefinitionEndDisplay**. These implementations only use **PidLidTimeZoneDescription** and **PidLidTimeZoneStruct** when exporting or importing VTIMEZONE components and TZID parameters.

<48> [Section 2.1.3.1.1.19.1](#): Office Outlook 2007, Outlook 2010, and Outlook 2013 use a case-sensitive TZID comparison function.

<49> [Section 2.1.3.1.1.19.1](#): Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not override **PidLidTimeZoneDescription**.

<50> [Section 2.1.3.1.1.19.2](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not parse the STANDARD component with the largest DTSTART.

<51> [Section 2.1.3.1.1.19.2](#): Office Outlook 2003 parses the first occurrence of the STANDARD component in the VTIMEZONE.

<52> [Section 2.1.3.1.1.19.2](#): Exchange 2010 SP1 and Exchange 2013 parse all STANDARD components in the VTIMEZONE that have unique years in their DTSTART subcomponents.

<53> [Section 2.1.3.1.1.19.2](#): Exchange 2003, Exchange 2007, and the initial release version of Exchange 2010 fail if more than one STANDARD component is present in a VTIMEZONE.

<54> [Section 2.1.3.1.1.19.2.1](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not set the fields of the **stStandardDate** field according to the table.

<55> [Section 2.1.3.1.1.19.2.1](#): Office Outlook 2003 imports RDATE if RRULE is not present.

<56> [Section 2.1.3.1.1.19.2.1](#): Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 import DTSTART if RRULE is not present.

<57> [Section 2.1.3.1.1.19.2.1](#): Office Outlook 2007, Outlook 2010, and Outlook 2013 use the year 1601.

<58> [Section 2.1.3.1.1.19.2.2](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not import VTIMEZONES with RRULEs that use BYMONTHDAY instead of BYDAY.

<59> [Section 2.1.3.1.1.19.2.2](#): For transitions between Daylight Saving Time and Standard Time based on a specific day of the month, Office Outlook 2003 instead omits the RRULE and exports

**PidLidTimeZoneStruct.stStandardDate** as an RDATE. Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 omit both the RRULE and RDATE, relying on DTSTART to convey the transition date.

<60> [Section 2.1.3.1.1.19.2.3](#): Office Outlook 2003 exports the TZNAME property with value 'Standard Time'.

<61> [Section 2.1.3.1.1.19.3](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not parse the DAYLIGHT component with the largest DTSTART.

<62> [Section 2.1.3.1.1.19.3](#): Office Outlook 2003 parses the first occurrence of the DAYLIGHT component in the VTIMEZONE.

<63> [Section 2.1.3.1.1.19.3](#): Exchange 2010 SP1 and Exchange 2013 parse all DAYLIGHT components in the VTIMEZONE that have unique years in their DTSTART subcomponents.

<64> [Section 2.1.3.1.1.19.3](#): Exchange 2003, Exchange 2007, and the initial release version of Exchange 2010 fail if more than one DAYLIGHT component is present in a VTIMEZONE.

<65> [Section 2.1.3.1.1.19.3](#): Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do export a DAYLIGHT component for time zones that do not observe DST. In this case, the TZOFFSETFROM and TZOFFSETTO properties for both the DAYLIGHT and STANDARD components are all set to the same value.

<66> [Section 2.1.3.1.1.19.3.3](#): Office Outlook 2003 exports the TZNAME property with value 'Daylight Saving Time'.

<67> [Section 2.1.3.1.1.20.1](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 ignore ATTACH properties.

<68> [Section 2.1.3.1.1.20.1](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 ignore ATTACH properties.

<69> [Section 2.1.3.1.1.20.1](#): Office Outlook 2003, Office Outlook 2007, Outlook 2010, Outlook 2013, Exchange 2007 (MIME), Exchange 2010, and Exchange 2013 ignore ATTACH properties specified as CID URIs and, instead, import all of the MIME attachments into the **Message object**, regardless of whether or not they are referenced in the iCalendar stream.

<70> [Section 2.1.3.1.1.20.1](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 ignore ATTACH properties.

<71> [Section 2.1.3.1.1.20.1](#): Prior to Exchange 2007 SP1, Exchange 2007 (MIME) does not export ATTACH properties specified as CID URIs.

<72> [Section 2.1.3.1.1.20.1](#): Prior to Exchange 2007 SP1, Exchange 2007 (MIME) does not export ATTACH properties specified as CID URIs.

<73> [Section 2.1.3.1.1.20.1](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not export ATTACH properties encoded with base64 encoding.

<74> [Section 2.1.3.1.1.20.1.2](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 ignore ATTACH properties.

<75> [Section 2.1.3.1.1.20.1.4](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 ignore ATTACH properties.

<76> [Section 2.1.3.1.1.20.1.4](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not export ATTACH properties encoded with base64 encoding.

- <77> [Section 2.1.3.1.1.20.2](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not parse attendee properties with value 'invalid:nomail'.
- <78> [Section 2.1.3.1.1.20.2](#): Office Outlook 2007 does not import attendees with a CUTYPE other than "RESOURCE" or "ROOM" and a ROLE of "NON-PARTICIPANT" to **PidLidNonSendableBcc**.
- <79> [Section 2.1.3.1.1.20.2](#): Office Outlook 2007 imports attendees with a CUTYPE other than "RESOURCE" or "ROOM" and a ROLE of "NON-PARTICIPANT" to **PidLidNonSendableCc**.
- <80> [Section 2.1.3.1.1.20.2](#): Office Outlook 2003 imports only one attendee property when the METHOD property has value 'REPLY'. For any other value of METHOD, Office Outlook 2003 does not import any attendee properties.
- <81> [Section 2.1.3.1.1.20.2](#): Office Outlook 2003 does not perform address book lookups on attendee properties. A one-off EntryID is always created.
- <82> [Section 2.1.3.1.1.20.2](#): Office Outlook 2003 does not set this property.
- <83> [Section 2.1.3.1.1.20.2](#): Office Outlook 2003 does not set this property.
- <84> [Section 2.1.3.1.1.20.2](#): Office Outlook 2003 does not set this property.
- <85> [Section 2.1.3.1.1.20.2](#): Office Outlook 2003 incorrectly adds the RECIPIENT\_ORGANIZER (0x00000002) bit to this property.
- <86> [Section 2.1.3.1.1.20.2](#): Office Outlook 2003 always uses MAPI\_TO (0x00000001).
- <87> [Section 2.1.3.1.1.20.2](#): Office Outlook 2003, Exchange 2003, Office Outlook 2007, Exchange 2007, Exchange 2010, and Exchange 2013 do not import the PARTSTAT parameter as **PidTagRecipientTrackStatus**.
- <88> [Section 2.1.3.1.1.20.2](#): Office Outlook 2003, Exchange 2003, Office Outlook 2007, Exchange 2007, Exchange 2010, and Exchange 2013 do not import the X-MS-OLK-RESPTIME parameter.
- <89> [Section 2.1.3.1.1.20.2](#): Office Outlook 2007 does not set **PidTagRecipientType** to 0x00000003 for attendees with a CUTYPE other than "RESOURCE" or "ROOM" and a ROLE of "NON-PARTICIPANT".
- <90> [Section 2.1.3.1.1.20.2](#): Office Outlook 2007 sets **PidTagRecipientType** to 0x00000002 for attendees with a CUTYPE other than "RESOURCE" or "ROOM" and a ROLE of "NON-PARTICIPANT".
- <91> [Section 2.1.3.1.1.20.2](#): Exchange 2007, Exchange 2010, and Exchange 2013 use this table.
- <92> [Section 2.1.3.1.1.20.2](#): Exchange 2007, Exchange 2010, and Exchange 2013 do not check **PidLidAppointmentStateFlags** before exporting attendee properties.
- <93> [Section 2.1.3.1.1.20.2](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 omit the attendee property if no SMTP address is available.
- <94> [Section 2.1.3.1.1.20.2](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not export **PidLidNonSendableTo**, **PidLidNonSendableCc**, or **PidLidNonSendableBcc**.
- <95> [Section 2.1.3.1.1.20.2.1](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not export **PidLidNonSendableTo**, **PidLidNonSendableCc**, or **PidLidNonSendableBcc**.



<96> [Section 2.1.3.1.1.20.2.2](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not export the CUTYPE parameter.

<97> [Section 2.1.3.1.1.20.2.2](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not export the CUTYPE parameter.

<98> [Section 2.1.3.1.1.20.2.3](#): Office Outlook 2003, Exchange 2003, Office Outlook 2007, Exchange 2007, Exchange 2010, and Exchange 2013 do not import the PARTSTAT parameter for calendars with a METHOD of PUBLISH.

<99> [Section 2.1.3.1.1.20.2.3](#): Office Outlook 2003, Exchange 2003, Office Outlook 2007, Exchange 2007, Exchange 2010, and Exchange 2013 do not export the PARTSTAT parameter for calendars with a METHOD of publish.

<100> [Section 2.1.3.1.1.20.2.3](#): Office Outlook 2003, Office Outlook 2007, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not export the PARTSTAT parameter for calendars with a METHOD of publish.

<101> [Section 2.1.3.1.1.20.2.4](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 export a ROLE of 'REQ-PARTICIPANT' instead of omitting the ROLE parameter.

<102> [Section 2.1.3.1.1.20.2.4](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not export **PidLidNonSendableTo**, **PidLidNonSendableCc**, or **PidLidNonSendableBcc**.

<103> [Section 2.1.3.1.1.20.2.6](#): Exchange 2003, Exchange 2007, Exchange 2010, Exchange 2013,, Office Outlook 2003, and Office Outlook 2007 do not import the X-MS-OLK-RESPTIME parameter.

<104> [Section 2.1.3.1.1.20.2.6](#): Exchange 2003, Exchange 2007, Exchange 2010, Exchange 2013, Office Outlook 2003, and Office Outlook 2007 do not export the X-MS-OLK-RESPTIME parameter from **PidLidAppointmentReplyTime**.

<105> [Section 2.1.3.1.1.20.3](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not apply this filter.

<106> [Section 2.1.3.1.1.20.3](#): Office Outlook 2007, Outlook 2010, and Outlook 2013 consider all of the following to be whitespace characters: U+0009, U+000A, U+000B, U+000C, U+000D, U+0020, U+0085, U+00A0, U+1680, U+2000, U+2001, U+2002, U+2003, U+2004, U+2005, U+2006, U+2007, U+2008, U+2009, U+200A, U+200B, U+2028, U+2029, U+202F, U+3000.

<107> [Section 2.1.3.1.1.20.3](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not apply this filter.

<108> [Section 2.1.3.1.1.20.3](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not apply this filter.

<109> [Section 2.1.3.1.1.20.3](#): Office Outlook 2007, Outlook 2010, and Outlook 2013 do not have logic to avoid splitting surrogate pairs.

<110> [Section 2.1.3.1.1.20.3](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not apply this filter.

<111> [Section 2.1.3.1.1.20.4](#): Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 map SENSITIVITY\_PERSONAL (0x00000001) to the 'PERSONAL' value of the CLASS property.



<112> [Section 2.1.3.1.1.20.4](#): Office Outlook 2003 does not support the 'X-PERSONAL' value of the CLASS property. SENSITIVITY\_PERSONAL (0x00000001) is exported as 'PRIVATE'.

<113> [Section 2.1.3.1.1.20.5](#): Exchange 2007 (WebDAV) and Office Outlook 2003 do not import or export the COMMENT property. For backwards compatibility, if the METHOD property of the VCALENDAR component is set to 'REPLY' or 'COUNTER', then Office Outlook 2007, Outlook 2010, and Outlook 2013 will export **PidTagBody** as both COMMENT and DESCRIPTION. In this same case, Office Outlook 2007, Outlook 2010, and Outlook 2013 will import **PidTagBody** from COMMENT, falling back on DESCRIPTION if a COMMENT is not specified. Regardless of the METHOD property of the VCALENDAR, Exchange 2007 (MIME) will always import **PidTagBody** from DESCRIPTION, falling back on the COMMENT property if no DESCRIPTION is specified. Exchange 2010 will always import PidTagBody from DESCRIPTION and ignore COMMENT. Exchange 2010 SP2 and Exchange 2013 will import **PidTagBody** from COMMENT only if the METHOD property is set to 'REPLY' or 'COUNTER' and the DESCRIPTION property is not specified.

<114> [Section 2.1.3.1.1.20.6](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not import or export the CONTACT property.

<115> [Section 2.1.3.1.1.20.6](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not apply this filter.

<116> [Section 2.1.3.1.1.20.6](#): Office Outlook 2007, Outlook 2010, and Outlook 2013 consider all of the following to be whitespace characters: U+0009, U+000A, U+000B, U+000C, U+000D, U+0020, U+0085, U+00A0, U+1680, U+2000, U+2001, U+2002, U+2003, U+2004, U+2005, U+2006, U+2007, U+2008, U+2009, U+200A, U+200B, U+2028, U+2029, U+202F, U+3000.

<117> [Section 2.1.3.1.1.20.6](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not apply this filter.

<118> [Section 2.1.3.1.1.20.6](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not apply this filter.

<119> [Section 2.1.3.1.1.20.6](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not apply this filter.

<120> [Section 2.1.3.1.1.20.6](#): Office Outlook 2007, Outlook 2010, and Outlook 2013 do not have logic to avoid splitting surrogate pairs.

<121> [Section 2.1.3.1.1.20.6](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not apply this filter.

<122> [Section 2.1.3.1.1.20.6](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not import or export the contact property.

<123> [Section 2.1.3.1.1.20.7](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not import or export the CREATED property.

<124> [Section 2.1.3.1.1.20.8](#): Regardless of the METHOD property of the VCALENDAR, Exchange 2003 and Office Outlook 2003 always map DTSTART and DTEND to **PidLidAppointmentStartWhole** and **PidLidAppointmentEndWhole**, respectively. Exchange 2003 and Office Outlook 2003 always ignore X-MS-OLK-ORIGINALSTART and X-MS-OLK-ORIGINALEND. Furthermore, Exchange 2003 and Office Outlook 2003 never export **PidLidAppointmentProposedStartWhole** or **PidLidAppointmentProposedEndWhole**.

<125> [Section 2.1.3.1.1.20.8](#): Regardless of the METHOD property of the VCALENDAR, Exchange 2003 and Office Outlook 2003 always map DTSTART and DTEND to **PidLidAppointmentStartWhole** and **PidLidAppointmentEndWhole**, respectively. Exchange

2003 and Office Outlook 2003 always ignore X-MS-OLK-ORIGINALSTART and X-MS-OLK-ORIGINALEND. Furthermore, Exchange 2003 and Office Outlook 2003 never export **PidLidAppointmentProposedStartWhole** or **PidLidAppointmentProposedEndWhole**.

<126> [Section 2.1.3.1.1.20.8](#): Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not set **PidLidAppointmentDuration**.

<127> [Section 2.1.3.1.1.20.8](#): Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 require that X-MICROSOFT-CDO-ALLDAYEVENT be set to 'TRUE' if the Calendar object is to be imported as all day. Office Outlook 2003 requires that a VALUE parameter be set to 'DATE' for both DTSTART and DTEND if the Calendar object is to be imported as all day.

<128> [Section 2.1.3.1.1.20.8](#): Office Outlook 2003 does not import or export the X-MICROSOFT-CDO-ALLDAYEVENT or X-MICROSOFT-MSNCALENDAR-ALLDAYEVENT properties.

<129> [Section 2.1.3.1.1.20.8](#): Regardless of the METHOD property of the VCALENDAR, Exchange 2003 and Office Outlook 2003 always map DTSTART and DTEND to **PidLidAppointmentStartWhole** and **PidLidAppointmentEndWhole**, respectively. Exchange 2003 and Office Outlook 2003 always ignore X-MS-OLK-ORIGINALSTART and X-MS-OLK-ORIGINALEND. Furthermore, Exchange 2003 and Office Outlook 2003 never export **PidLidAppointmentProposedStartWhole** or **PidLidAppointmentProposedEndWhole**.

<130> [Section 2.1.3.1.1.20.8](#): Regardless of the METHOD property of the VCALENDAR, Exchange 2003 and Office Outlook 2003 always map DTSTART and DTEND to **PidLidAppointmentStartWhole** and **PidLidAppointmentEndWhole**, respectively. Exchange 2003 and Office Outlook 2003 always ignore X-MS-OLK-ORIGINALSTART and X-MS-OLK-ORIGINALEND. Furthermore, Exchange 2003 and Office Outlook 2003 never export **PidLidAppointmentProposedStartWhole** or **PidLidAppointmentProposedEndWhole**.

<131> [Section 2.1.3.1.1.20.8](#): Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not export all day appointments in floating time.

<132> [Section 2.1.3.1.1.20.8](#): Office Outlook 2007 exports non-recurring, non-all day appointments in UTC time.

<133> [Section 2.1.3.1.1.20.8.1](#): Office Outlook 2003, Office Outlook 2007, Exchange 2003, Exchange 2007, and the initial release version of Exchange 2010 do not export or import **PidLidAppointmentTimeZoneDefinitionRecur**.

<134> [Section 2.1.3.1.1.20.8.1](#): Office Outlook 2003, Office Outlook 2007, Exchange 2003, Exchange 2007, and the initial release version of Exchange 2010 do not export or import **PidLidAppointmentTimeZoneDefinitionEndDisplay**.

<135> [Section 2.1.3.1.1.20.8.1](#): Office Outlook 2003, Office Outlook 2007, Exchange 2003, Exchange 2007, and the initial release version of Exchange 2010 do not export or import **PidLidAppointmentTimeZoneDefinitionRecur**.

<136> [Section 2.1.3.1.1.20.8.1](#): Office Outlook 2003, Office Outlook 2007, Exchange 2003, Exchange 2007, and the initial release version of Exchange 2010 do not export or import **PidLidAppointmentTimeZoneDefinitionEndDisplay**.

<137> [Section 2.1.3.1.1.20.8.2](#): Office Outlook 2003 requires that a VALUE parameter be set to 'DATE' for both DTSTART and DTEND if the Calendar object is to be imported as all day.

<138> [Section 2.1.3.1.1.20.9](#): Exchange 2003 and Exchange 2007 always import DTSTAMP as **PidLidAttendeeCriticalChange**.

[<139> Section 2.1.3.1.1.20.10:](#) Regardless of the METHOD property of the VCALENDAR, Exchange 2003 and Office Outlook 2003 always map DTSTART and DTEND to

**PidLidAppointmentStartWhole** and **PidLidAppointmentEndWhole**, respectively. Exchange 2003 and Office Outlook 2003 always ignore X-MS-OLK-ORIGINALSTART and X-MS-OLK-ORIGINALEND. Furthermore, Exchange 2003 and Office Outlook 2003 never export **PidLidAppointmentProposedStartWhole** or **PidLidAppointmentProposedEndWhole**.

[<140> Section 2.1.3.1.1.20.10:](#) Regardless of the METHOD property of the VCALENDAR, Exchange 2003 and Office Outlook 2003 always map DTSTART and DTEND to

**PidLidAppointmentStartWhole** and **PidLidAppointmentEndWhole**, respectively. Exchange 2003 and Office Outlook 2003 always ignore X-MS-OLK-ORIGINALSTART and X-MS-OLK-ORIGINALEND. Furthermore, Exchange 2003 and Office Outlook 2003 never export **PidLidAppointmentProposedStartWhole** or **PidLidAppointmentProposedEndWhole**.

[<141> Section 2.1.3.1.1.20.10:](#) Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not set **PidLidAppointmentDuration**.

[<142> Section 2.1.3.1.1.20.10:](#) Exchange 2003, Exchange 2007, and Exchange 2010 require that X-MICROSOFT-CDO-ALLDAYEVENT be set to 'TRUE' if the Calendar object is to be imported as all day. Office Outlook 2003 requires that a VALUE parameter be set to 'DATE' for both DTSTART and DTEND if the Calendar object is to be imported as all day. Exchange 2010 SP1 and Exchange 2013 import an appointment as an all day appointment if the VALUE parameter is set to 'DATE' for the DTSTART property and the DTEND and DURATION properties are missing.

[<143> Section 2.1.3.1.1.20.10:](#) Office Outlook 2003 does not import or export the X-MICROSOFT-CDO-ALLDAYEVENT or X-MICROSOFT-MSNCALENDAR-ALLDAYEVENT properties.

[<144> Section 2.1.3.1.1.20.10:](#) Exchange 2010 SP2 and Exchange 2013 uses the value of DTSTART to derive the end time if both the DTEND and DURATION properties are not specified.

[<145> Section 2.1.3.1.1.20.10:](#) Regardless of the METHOD property of the VCALENDAR, Exchange 2003 and Office Outlook 2003 always map DTSTART and DTEND to

**PidLidAppointmentStartWhole** and **PidLidAppointmentEndWhole**, respectively. Exchange 2003 and Office Outlook 2003 always ignore X-MS-OLK-ORIGINALSTART and X-MS-OLK-ORIGINALEND. Furthermore, Exchange 2003 and Office Outlook 2003 never export **PidLidAppointmentProposedStartWhole** or **PidLidAppointmentProposedEndWhole**.

[<146> Section 2.1.3.1.1.20.10:](#) Regardless of the METHOD property of the VCALENDAR, Exchange 2003 and Office Outlook 2003 always map DTSTART and DTEND to

**PidLidAppointmentStartWhole** and **PidLidAppointmentEndWhole**, respectively. Exchange 2003 and Office Outlook 2003 always ignore X-MS-OLK-ORIGINALSTART and X-MS-OLK-ORIGINALEND. Furthermore, Exchange 2003 and Office Outlook 2003 never export **PidLidAppointmentProposedStartWhole** or **PidLidAppointmentProposedEndWhole**.

[<147> Section 2.1.3.1.1.20.10:](#) Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not export all day appointments in floating time.

[<148> Section 2.1.3.1.1.20.10:](#) Office Outlook 2007 exports non-recurring, non-all day appointments in UTC time.

[<149> Section 2.1.3.1.1.20.10.1:](#) Office Outlook 2003, Office Outlook 2007, Exchange 2003, Exchange 2007, and the initial release version of Exchange 2010 do not export or import **PidLidAppointmentTimeZoneDefinitionRecur**.

[<150> Section 2.1.3.1.1.20.10.1:](#) Office Outlook 2003, Office Outlook 2007, Exchange 2003, Exchange 2007, and the initial release version of Exchange 2010 do not export or import **PidLidAppointmentTimeZoneDefinitionStartDisplay**.

[<151> Section 2.1.3.1.1.20.10.1:](#) Office Outlook 2003, Office Outlook 2007, Exchange 2003, Exchange 2007, and the initial release version of Exchange 2010 do not export or import **PidLidAppointmentTimeZoneDefinitionRecur**.

[<152> Section 2.1.3.1.1.20.10.1:](#) Office Outlook 2003, Office Outlook 2007, Exchange 2003, Exchange 2007, and the initial release version of Exchange 2010 do not export or import **PidLidAppointmentTimeZoneDefinitionStartDisplay**.

[<153> Section 2.1.3.1.1.20.10.2:](#) Office Outlook 2003 requires that a VALUE parameter be set to 'DATE' for both DTSTART and DTEND if the Calendar object is to be imported as all day.

[<154> Section 2.1.3.1.1.20.11.1:](#) For backwards compatibility, if the METHOD property of the VCALENDAR component is set to 'REPLY' or 'COUNTER', then Office Outlook 2007, Outlook 2010, and Outlook 2013 will export **PidTagBody** as both COMMENT and DESCRIPTION. In this same case, Office Outlook 2007, Outlook 2010, and Outlook 2013 will import **PidTagBody** from DESCRIPTION if a COMMENT is not specified. Regardless of the METHOD property of the VCALENDAR, Exchange 2007 (MIME) will always import **PidTagBody** from DESCRIPTION, falling back on the COMMENT property if no DESCRIPTION is specified. Exchange 2010 will always import **PidTagBody** from DESCRIPTION. Exchange 2010 SP2 and Exchange 2013 will import **PidTagBody** from COMMENT only if the METHOD property is set to 'REPLY' or 'COUNTER' and the DESCRIPTION property is not specified.

[<155> Section 2.1.3.1.1.20.11.1:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not import or export the LANGUAGE parameter.

[<156> Section 2.1.3.1.1.20.12:](#) Office Outlook 2003 does not import or export the DURATION property.

[<157> Section 2.1.3.1.1.20.13:](#) Exchange 2003, Exchange 2007, Exchange 2007 SP1, Exchange 2007 SP2, Exchange 2010, and Exchange 2013 ignore all instances of EXDATE except the last one in the VEVENT. Exchange 2003, Exchange 2007 SP2, Exchange 2010, and Exchange 2013 also ignore instances of EXDATE that have more than one value.

[<158> Section 2.1.3.1.1.20.13:](#) The initial release version of Exchange 2010 and Exchange 2010 SP1 ignore values of EXDATE that are specified in a time zone other than the time zone specified by **PidLidTimeZoneStruct**. Exchange 2010 SP2 and Exchange 2013 convert values of EXDATE to the time zone specified by **PidLidTimeZoneStruct**.

[<159> Section 2.1.3.1.1.20.13:](#) Exchange 2003, Exchange 2007 (WebDAV), Office Outlook 2003, Office Outlook 2007, Outlook 2010, and Outlook 2013 do not support the X-MICROSOFT-EXDATE property.

[<160> Section 2.1.3.1.1.20.13:](#) In certain cases, RecurrencePattern.DeletedInstanceDates will be exported as a X-MICROSOFT-EXDATE instead of an EXDATE. See section [2.1.3.1.1.20.39](#). Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 export EXDATEs with times set to noon in the time zone specified by **PidLidTimeZoneStruct**.

[<161> Section 2.1.3.1.1.20.13.2:](#) Office Outlook 2003 requires that a VALUE parameter be set to 'DATE' for both DTSTART and DTEND if the Calendar object is to be imported as all day.

[<162> Section 2.1.3.1.1.20.14:](#) Exchange 2003 and Exchange 2007 import LAST-MODIFIED as **PidLidAttendeeCriticalChange**.

[<163> Section 2.1.3.1.1.20.14:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not import or export the LAST-MODIFIED property.

[<164> Section 2.1.3.1.1.20.15:](#) Office Outlook 2003 does not apply this filter.

[<165> Section 2.1.3.1.1.20.15:](#) Office Outlook 2003 does not apply this filter.

[<166> Section 2.1.3.1.1.20.15:](#) Office Outlook 2007, Outlook 2010, and Outlook 2013 do not have logic to avoid splitting surrogate pairs.

[<167> Section 2.1.3.1.1.20.15.1:](#) Exchange 2007, Exchange 2010, and Exchange 2013 import the ALTREP parameter on the LOCATION property to the **PidNameLocationUrl** (section [2.2.3](#)) property.

[<168> Section 2.1.3.1.1.20.15.1:](#) Exchange 2007, Exchange 2010, and Exchange 2013 export the **PidNameLocationUrl** property to the ALTREP parameter on the LOCATION property.

[<169> Section 2.1.3.1.1.20.15.2:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not import or export the LANGUAGE parameter.

[<170> Section 2.1.3.1.1.20.16:](#) Office Outlook 2003 does not import the organizer property when the METHOD property has a value of 'REPLY'.

[<171> Section 2.1.3.1.1.20.16:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not export ATTACH properties encoded with base64 encoding.

[<172> Section 2.1.3.1.1.20.16:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not export ATTACH properties encoded with base64 encoding.

[<173> Section 2.1.3.1.1.20.16:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not export ATTACH properties encoded with base64 encoding.

[<174> Section 2.1.3.1.1.20.16:](#) If the METHOD property of the iCalendar is 'REPLY', Office Outlook 2003 exports the first entry in the recipient table as an organizer, ignoring the constraints specified in section [2.1.3.1.1.20.16](#). For other values of the METHOD property, Office Outlook 2003 exports the Address Book object specified by **PidTagSentRepresentingEntryId** as an organizer.

[<175> Section 2.1.3.1.1.20.16:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 omit the organizer property if no SMTP address is available.

[<176> Section 2.1.3.1.1.20.18:](#) Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not support RDATEs.

[<177> Section 2.1.3.1.1.20.18:](#) Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not support RDATEs.

[<178> Section 2.1.3.1.1.20.18:](#) Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not support RDATEs.

[<179> Section 2.1.3.1.1.20.18.2:](#) Office Outlook 2003 requires that a VALUE parameter be set to 'DATE' for both DTSTART and DTEND if the Calendar object is to be imported as all day.

[<180> Section 2.1.3.1.1.20.20:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 only import or export the RECURRENCE-ID property in the context of a VCALENDAR component with exactly one VEVENT child and with a METHOD property of value 'REQUEST', 'REPLY', or 'CANCEL'.

[<181> Section 2.1.3.1.1.20.20:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 only import or export the RECURRENCE-ID property in the context of a VCALENDAR component with exactly one VEVENT child and with a METHOD property of value 'REQUEST', 'REPLY', or 'CANCEL'.



[<182> Section 2.1.3.1.1.20.20:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 only import or export the RECURRENCE-ID property in the context of a VCALENDAR component with exactly one VEVENT child and with a METHOD property of value 'REQUEST', 'REPLY', or 'CANCEL'.

[<183> Section 2.1.3.1.1.20.20:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 only import or export the RECURRENCE-ID property in the context of a VCALENDAR component with exactly one VEVENT child and with a METHOD property of value 'REQUEST', 'REPLY', or 'CANCEL'.

[<184> Section 2.1.3.1.1.20.20:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 only import or export the RECURRENCE-ID property in the context of a VCALENDAR component with exactly one VEVENT child and with a METHOD property of value 'REQUEST', 'REPLY', or 'CANCEL'.

[<185> Section 2.1.3.1.1.20.20:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 only import or export the RECURRENCE-ID property in the context of a VCALENDAR component with exactly one VEVENT child and with a METHOD property of value 'REQUEST', 'REPLY', or 'CANCEL'.

[<186> Section 2.1.3.1.1.20.20.2:](#) Office Outlook 2003 requires that a VALUE parameter be set to 'DATE' for both DTSTART and DTEND if the Calendar object is to be imported as all day.

[<187> Section 2.1.3.1.1.20.21:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not import or export the RESOURCES property.

[<188> Section 2.1.3.1.1.20.21:](#) Exchange 2007, Exchange 2010, and Exchange 2013 consider all of the following to be whitespace characters: U+0009, U+000A, U+000B, U+000C, U+000D, U+0020, U+0085, U+00A0, U+1680, U+2000, U+2001, U+2002, U+2003, U+2004, U+2005, U+2006, U+2007, U+2008, U+2009, U+200A, U+200B, U+2028, U+2029, U+202F, U+3000.

[<189> Section 2.1.3.1.1.20.21:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not import or export the RESOURCES property.

[<190> Section 2.1.3.1.1.20.21:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not import or export the LAST-MODIFIED property.

[<191> Section 2.1.3.1.1.20.21:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not import or export the RESOURCES property.

[<192> Section 2.1.3.1.1.20.22:](#) Office Outlook 2003, Office Outlook 2007, Outlook 2010, Outlook 2013, Exchange 2003, and Exchange 2007 (WebDAV) import a **PidLidAppointmentSequence** of 0x00000000 if no SEQUENCE property is specified.

[<193> Section 2.1.3.1.1.20.23:](#) Office Outlook 2003 does not import or export the STATUS property.

[<194> Section 2.1.3.1.1.20.24:](#) Office Outlook 2003 does not apply these filters.

[<195> Section 2.1.3.1.1.20.24:](#) Office Outlook 2003 does not apply these filters.

[<196> Section 2.1.3.1.1.20.24:](#) Office Outlook 2007, Outlook 2010, and Outlook 2013 do not have logic to avoid splitting surrogate pairs.

[<197> Section 2.1.3.1.1.20.24:](#) Office Outlook 2003 leaves **PidTagSubject** unset when no SUMMARY is present.

[<198> Section 2.1.3.1.1.20.24:](#) Office Outlook 2003 omits the SUMMARY property if **PidTagSubject** is unset or empty.

[<199> Section 2.1.3.1.1.20.24.1:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not import or export the LANGUAGE parameter.

[<200> Section 2.1.3.1.1.20.24.1:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not import or export the LANGUAGE parameter.

[<201> Section 2.1.3.1.1.20.25:](#) Exchange 2003, Exchange 2007, and Exchange 2010 map the TRANSP property directly to **PidNameCalendarTransparent**. Update Rollup 7 for Exchange 2007 SP3, Update Rollup 2 for Exchange 2010 SP2, and Exchange 2013 import the TRANSP property into **PidLidBusyStatus** if the X-MICROSOFT-CDO-BUSYSTATUS and X-MICROSOFT-MSNCALENDAR-BUSYSTATUS properties are absent.

[<202> Section 2.1.3.1.1.20.25:](#) Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 map the TRANSP property directly to **PidNameCalendarTransparent**.

[<203> Section 2.1.3.1.1.20.25:](#) Exchange 2003, Exchange 2007, Exchange 2010, Office Outlook 2003, Office Outlook 2007, and Outlook 2010 do not support the value 0x00000004 for the **PidLidBusyStatus** property ([\[MS-OXOCAL\]](#) section 2.2.1.2).

[<204> Section 2.1.3.1.1.20.26:](#) The ByteArrayID is case-sensitive in Office Outlook 2007, Outlook 2010, and Outlook 2013.

[<205> Section 2.1.3.1.1.20.27:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not import or export the X-ALT-DESC property.

[<206> Section 2.1.3.1.1.20.27:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not import or export the X-ALT-DESC property.

[<207> Section 2.1.3.1.1.20.28:](#) Office Outlook 2007, Outlook 2010, and Outlook 2013 check to see if DTEND falls on midnight in the time zone specified by DTSTART.

[<208> Section 2.1.3.1.1.20.28:](#) Office Outlook 2003 does not import or export the X-MICROSOFT-CDO-ALLDAYEVENT or X-MICROSOFT-MSNCALENDAR-ALLDAYEVENT properties.

[<209> Section 2.1.3.1.1.20.28:](#) Office Outlook 2007, Outlook 2010, and Outlook 2013 do not have logic to avoid splitting surrogate pairs.

[<210> Section 2.1.3.1.1.20.28:](#) Office Outlook 2007, Outlook 2010, and Outlook 2013 do not have logic to avoid splitting surrogate pairs.

[<211> Section 2.1.3.1.1.20.28:](#) Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 export X-MICROSOFT-CDO-ALLDAYEVENT.

[<212> Section 2.1.3.1.1.20.29:](#) Office Outlook 2003, Office Outlook 2007, Outlook 2010, and Outlook 2013 do not import or export X-MICROSOFT-CDO-APPT-SEQUENCE.

[<213> Section 2.1.3.1.1.20.29:](#) Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 export **PidLidAppointmentSequence** as X-MICROSOFT-CDO-APPT-SEQUENCE.

[<214> Section 2.1.3.1.1.20.30:](#) Exchange 2003 and Exchange 2007 (WebDAV) import and export the X-MICROSOFT-CDO-ATTENDEE-CRITICAL-CHANGE property.

[<215> Section 2.1.3.1.1.20.30:](#) Exchange 2003 and Exchange 2007 (WebDAV) import and export the X-MICROSOFT-CDO-ATTENDEE-CRITICAL-CHANGE property.

<216> [Section 2.1.3.1.1.20.31](#): Office Outlook 2003 does not import or export the X-MICROSOFT-CDO-BUSYSTATUS property.

<217> [Section 2.1.3.1.1.20.33](#): Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 export an X-MICROSOFT-CDO-INSTTYPE with values: 0 if the appointment is non-recurring, 1 if the appointment is recurring, and 3 if the appointment is an exception of a recurring appointment.

<218> [Section 2.1.3.1.1.20.34](#): Office Outlook 2003 does not import or export the X-MICROSOFT-CDO-INTENDEDSTATUS or X-MICROSOFT-MSNCALENDAR-INTENDEDSTATUS properties.

<219> [Section 2.1.3.1.1.20.34](#): Update Rollup 2 for Exchange 2010 SP2 and Exchange 2013 set the value of **PidLidBusyStatus** to 0x00000001 if the METHOD property is REQUEST and the X-MICROSOFT-CDO-INTENDEDSTATUS property is present.

<220> [Section 2.1.3.1.1.20.34](#): Exchange 2010 does not copy the value of **PidLidBusyStatus** into the **PidLidIntendedBusyStatus** property. Update Rollup 2 for Exchange 2010 SP2 and Exchange 2013 do copy the value of **PidLidBusyStatus** into the **PidLidIntendedBusyStatus** property. Office Outlook 2003 does not import or export the X-MICROSOFT-CDO-INTENDEDSTATUS or X-MICROSOFT-MSNCALENDAR-INTENDEDSTATUS properties.

<221> [Section 2.1.3.1.1.20.34](#): Office Outlook 2003 does not import or export the X-MICROSOFT-CDO-INTENDEDSTATUS or X-MICROSOFT-MSNCALENDAR-INTENDEDSTATUS properties.

<222> [Section 2.1.3.1.1.20.34](#): Office Outlook 2003 does not import or export the X-MICROSOFT-CDO-INTENDEDSTATUS or X-MICROSOFT-MSNCALENDAR-INTENDEDSTATUS properties.

<223> [Section 2.1.3.1.1.20.35](#): Office Outlook 2003, Office Outlook 2007, Outlook 2010, and Outlook 2013 do not import or export the X-MICROSOFT-CDO-OWNERAPPTID property.

<224> [Section 2.1.3.1.1.20.36](#): Exchange 2003 and Exchange 2007 (WebDAV) import and export the X-MICROSOFT-CDO-OWNER-CRITICAL-CHANGE property.

<225> [Section 2.1.3.1.1.20.36](#): Exchange 2003 and Exchange 2007 (WebDAV) import and export the X-MICROSOFT-CDO-OWNER-CRITICAL-CHANGE property.

<226> [Section 2.1.3.1.1.20.37](#): If the METHOD property has value 'REPLY', Exchange 2003 and Exchange 2007 (WebDAV) will import X-MICROSOFT-CDO-REPLYTIME as **PidLidAttendeeCriticalChange** in addition to **PidLidAppointmentReplyTime**.

<227> [Section 2.1.3.1.1.20.37](#): Exchange 2003 and Exchange 2007 (WebDAV) import and export the X-MICROSOFT-CDO-REPLYTIME property.

<228> [Section 2.1.3.1.1.20.38](#): Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not import or export the X-MICROSOFT-DISALLOW-COUNTER property.

<229> [Section 2.1.3.1.1.20.39](#): Exchange 2003, Exchange 2007 (WebDAV), Office Outlook 2003, Office Outlook 2007, Outlook 2010, and Outlook 2013 do not import or export the X-MICROSOFT-EXDATE property.

<230> [Section 2.1.3.1.1.20.39](#): Exchange 2003, Exchange 2007 (WebDAV), Office Outlook 2003, Office Outlook 2007, Outlook 2010, and Outlook 2013 do not import or export the X-MICROSOFT-EXDATE property.

<231> [Section 2.1.3.1.1.20.40](#): Exchange 2003, Exchange 2007, Exchange 2010, Exchange 2013, Office Outlook 2003, and Office Outlook 2007 do not import or export the X-MICROSOFT-ISDRAFT property. Specifically, on import, those implementations always treat X-MICROSOFT-ISDRAFT as unset.



[<232> Section 2.1.3.1.1.20.40:](#) Exchange 2003, Exchange 2007, Exchange 2010, Exchange 2013, Office Outlook 2003, and Office Outlook 2007 do not import or export the X-MICROSOFT-ISDRAFT property. Specifically, on import, those implementations always treat X-MICROSOFT-ISDRAFT as unset.

[<233> Section 2.1.3.1.1.20.41:](#) Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not import or export the X-MICROSOFT-MSNCALENDAR-ALLDAYEVENT property.

[<234> Section 2.1.3.1.1.20.42:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not import or export the X-MICROSOFT-MSNCALENDAR-BUSYSTATUS property.

[<235> Section 2.1.3.1.1.20.43:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not import or export the X-MICROSOFT-MSNCALENDAR-IMPORTANCE property.

[<236> Section 2.1.3.1.1.20.44:](#) Office Outlook 2003 does not import or export the X-MICROSOFT-CDO-INTENDEDSTATUS or X-MICROSOFT-MSNCALENDAR-INTENDEDSTATUS properties.

[<237> Section 2.1.3.1.1.20.45.2:](#) Office Outlook 2003, Office Outlook 2007, Outlook 2010, Outlook 2013, Exchange 2003, and Exchange 2007 (WebDAV) do not import or export the X-MICROSOFT-RRULE property.

[<238> Section 2.1.3.1.1.20.46:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not import or export the X-MS-OLK-ALLOWEXTERNCHECK property.

[<239> Section 2.1.3.1.1.20.47:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not import or export the X-MS-OLK-APPTLASTSEQUENCE property.

[<240> Section 2.1.3.1.1.20.48:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not import or export the X-MS-OLK-APPTSEQTIME property.

[<241> Section 2.1.3.1.1.20.48:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not import or export the X-MS-OLK-APPTSEQTIME property.

[<242> Section 2.1.3.1.1.20.49:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not import or export the X-MS-OLK-AUTOFILLLOCATION property.

[<243> Section 2.1.3.1.1.20.50:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not import or export the X-MS-OLK-AUTOSTARTCHECK property.

[<244> Section 2.1.3.1.1.20.51:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not import or export the X-MS-OLK-COLLABORATEDOC property.

[<245> Section 2.1.3.1.1.20.52:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not import or export the X-MS-OLK-CONFHECK property.

[<246> Section 2.1.3.1.1.20.53:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not import or export the X-MS-OLK-CONFTYPE property.

[<247> Section 2.1.3.1.1.20.54:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not import or export the X-MS-OLK-DIRECTORY property.

[<248> Section 2.1.3.1.1.20.55:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not import or export the X-MS-OLK-MWSURL property.

[<249> Section 2.1.3.1.1.20.56:](#) Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not import or export the X-MS-OLK-NETSHOWURL property.

<250> [Section 2.1.3.1.1.20.57](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not import or export the X-MS-OLK-ONLINEPASSWORD property.

<251> [Section 2.1.3.1.1.20.58](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not import or export the X-MS-OLK-ORGALIAS property.

<252> [Section 2.1.3.1.1.20.59](#): Regardless of the METHOD property of the VCALENDAR, Exchange 2003 and Office Outlook 2003 always map DTSTART and DTEND to **PidLidAppointmentStartWhole** and **PidLidAppointmentEndWhole**, respectively. Exchange 2003 and Office Outlook 2003 always ignore X-MS-OLK-ORIGINALSTART and X-MS-OLK-ORIGINALEND. Furthermore, Exchange 2003 and Office Outlook 2003 never export **PidLidAppointmentProposedStartWhole** or **PidLidAppointmentProposedEndWhole**.

<253> [Section 2.1.3.1.1.20.59](#): Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not set **PidLidAppointmentDuration**.

<254> [Section 2.1.3.1.1.20.60](#): Regardless of the METHOD property of the VCALENDAR, Exchange 2003 and Office Outlook 2003 always map DTSTART and DTEND to **PidLidAppointmentStartWhole** and **PidLidAppointmentEndWhole**, respectively. Exchange 2003 and Office Outlook 2003 always ignore X-MS-OLK-ORIGINALSTART and X-MS-OLK-ORIGINALEND. Furthermore, Exchange 2003 and Office Outlook 2003 never export **PidLidAppointmentProposedStartWhole** or **PidLidAppointmentProposedEndWhole**.

<255> [Section 2.1.3.1.1.20.60](#): Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not set **PidLidAppointmentDuration**.

<256> [Section 2.1.3.1.1.20.61](#): Office Outlook 2003, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not import or export the X-MS-OLK-SENDER property.

<257> [Section 2.1.3.1.1.20.61](#): Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 export **PidLidAppointmentSequence** as X-MICROSOFT-CDO-APPT-SEQUENCE.

<258> [Section 2.1.3.1.1.20.61](#): Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 export **PidLidAppointmentSequence** as X-MICROSOFT-CDO-APPT-SEQUENCE.

<259> [Section 2.1.3.1.1.20.61](#): Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 export **PidLidAppointmentSequence** as X-MICROSOFT-CDO-APPT-SEQUENCE.

<260> [Section 2.1.3.1.1.20.61](#): Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 export **PidLidAppointmentSequence** as X-MICROSOFT-CDO-APPT-SEQUENCE.

<261> [Section 2.1.3.1.1.20.61](#): Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 export **PidLidAppointmentSequence** as X-MICROSOFT-CDO-APPT-SEQUENCE.

<262> [Section 2.1.3.1.1.20.61.1](#): Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 export **PidLidAppointmentSequence** as X-MICROSOFT-CDO-APPT-SEQUENCE

<263> [Section 2.1.3.1.1.20.62](#): Office Outlook 2003, Office Outlook 2007, Outlook 2010, Outlook 2013, and Exchange 2003 ignore TRIGGER properties that are specified as Date-Time.

<264> [Section 2.1.3.1.1.20.62](#): In this case, Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 set **PidLidReminderDelta** to 0x0000000F for all Calendar objects.

<265> [Section 2.1.3.1.1.20.62](#): Office Outlook 2003 does not set **PidLidReminderSignalTime**.

<266> [Section 2.1.3.1.1.20.62](#): Office Outlook 2003, Office Outlook 2007, Outlook 2010, Outlook 2013, and Exchange 2003 ignore TRIGGER properties that are specified as Date-Time.

<267> [Section 2.1.3.2.1.2](#): For Office Outlook 2003, the maximum INTERVAL of a YEARLY recurrence is 1.

<268> [Section 2.1.3.2.1.10](#): Office Outlook 2003 does not apply this filter.

<269> [Section 2.1.3.2.1.11](#): Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 export an X-MICROSOFT-CDO-INSTTYPE with values: 0 if the appointment is non-recurring, 1 if the appointment is recurring, and 3 if the appointment is an exception of a recurring appointment.

<270> [Section 2.1.3.2.2](#): Office Outlook 2003, Office Outlook 2007, Outlook 2010, Outlook 2013, Exchange 2003, and Exchange 2007 (WebDAV) do not import or export the X-MICROSOFT-RRULE property.

<271> [Section 2.1.3.2.2](#): Exchange 2003, Exchange 2007, and Exchange 2010 do not set the **PidLidClipStart** property ([\[MS-OXOCAL\]](#) section 2.2.1.14) or the **PidLidClipEnd** property ([\[MS-OXOCAL\]](#) section 2.2.1.15). Exchange 2010 SP2 and Exchange 2013 set the **PidLidClipStart** and **PidLidClipEnd** properties as specified.

<272> [Section 2.1.3.2.2.1](#): Office Outlook 2003 does not import or export the X-MICROSOFT-CDO-INTENDEDSTATUS or X-MICROSOFT-MSNCALENDAR-INTENDEDSTATUS properties.

<273> [Section 2.1.3.2.2.1](#): Office Outlook 2003 does not import or export the X-MICROSOFT-CDO-INTENDEDSTATUS or X-MICROSOFT-MSNCALENDAR-INTENDEDSTATUS properties.

<274> [Section 2.1.3.2.2.1](#): Exchange 2007 (MIME), Exchange 2010, and Exchange 2013 do not follow this guidance.

<275> [Section 2.1.3.2.2.1](#): Office Outlook 2003, Office Outlook 2007, Outlook 2010, and Outlook 2013 do not import or export the X-MICROSOFT-CDO-OWNERAPPTID property.

<276> [Section 2.1.3.2.2.1](#): Office Outlook 2007, Outlook 2010, and Outlook 2013 export 0x00002021 **EndType** values as a COUNT part instead of an UNTIL part.

<277> [Section 2.1.3.2.2.1](#): If **EndType** is 0x00002021, Exchange 2007, Exchange 2007 SP1, and Exchange 2007 SP2 set the UNTIL recurrence part to midnight on the date specified by **EndDate**.

<278> [Section 2.1.3.2.2.1](#): Office Outlook 2003 will export **FirstDOW** as the WKST recurrence part, regardless of whether or not it is relevant.

<279> [Section 2.1.3.2.2.2](#): Office Outlook 2003 does not import or export the X-MICROSOFT-CDO-INTENDEDSTATUS or X-MICROSOFT-MSNCALENDAR-INTENDEDSTATUS properties.

<280> [Section 2.1.3.2.2.2](#): Office Outlook 2003 does not import or export the X-MICROSOFT-CDO-INTENDEDSTATUS or X-MICROSOFT-MSNCALENDAR-INTENDEDSTATUS properties.

<281> [Section 2.1.3.2.2.2](#): Office Outlook 2007, Outlook 2010, and Outlook 2013 export 0x00002021 **EndType** values as a COUNT part instead of an UNTIL part.

<282> [Section 2.1.3.2.2.2](#): If **EndType** is 0x00002021, Exchange 2007, Exchange 2007 SP1, and Exchange 2007 SP2 set the UNTIL recurrence part to midnight on the date specified by **EndDate**.

<283> [Section 2.1.3.2.2.2](#): Office Outlook 2003 will export **FirstDOW** as the WKST recurrence part, regardless of whether it is relevant.

<284> [Section 2.1.3.2.2.3](#): Office Outlook 2003 does not import or export the X-MICROSOFT-CDO-INTENDEDSTATUS or X-MICROSOFT-MSNCALENDAR-INTENDEDSTATUS properties.

<285> [Section 2.1.3.2.2.3](#): Office Outlook 2007, Outlook 2010, and Outlook 2013 will promote MONTHLY recurrences with an INTERVAL of 12 to a YEARLY recurrence.

<286> [Section 2.1.3.2.2.3](#): Office Outlook 2003 imports BYMONTHDAY directly into **PatternTypeSpecific.Month.Day**.

<287> [Section 2.1.3.2.2.3](#): Office Outlook 2003 does not import or export the X-MICROSOFT-CDO-INTENDEDSTATUS or X-MICROSOFT-MSNCALENDAR-INTENDEDSTATUS properties.

<288> [Section 2.1.3.2.2.3](#): Office Outlook 2003 exports **PatternTypeSpecific.Month.Day** directly as BYMONTHDAY.

<289> [Section 2.1.3.2.2.3](#): Office Outlook 2007, Outlook 2010, and Outlook 2013 export 0x00002021 **EndType** values as a COUNT part instead of an UNTIL part.

<290> [Section 2.1.3.2.2.3](#): If **EndType** is 0x00002021, Exchange 2007, Exchange 2007 SP1, and Exchange 2007 SP2 set the UNTIL recurrence part to midnight on the date specified by **EndDate**.

<291> [Section 2.1.3.2.2.3](#): Office Outlook 2003 will export **FirstDOW** as the WKST recurrence part, regardless of whether it is relevant.

<292> [Section 2.1.3.2.2.4](#): Office Outlook 2003 does not import or export the X-MICROSOFT-CDO-INTENDEDSTATUS or X-MICROSOFT-MSNCALENDAR-INTENDEDSTATUS properties.

<293> [Section 2.1.3.2.2.4](#): Office Outlook 2007, Outlook 2010, and Outlook 2013 will promote MONTHLY recurrences with an INTERVAL of 12 to a YEARLY recurrence.

<294> [Section 2.1.3.2.2.4](#): Office Outlook 2003 does not import or export the X-MICROSOFT-CDO-INTENDEDSTATUS or X-MICROSOFT-MSNCALENDAR-INTENDEDSTATUS properties.

<295> [Section 2.1.3.2.2.4](#): Office Outlook 2007, Outlook 2010, and Outlook 2013 export 0x00002021 **EndType** values as a COUNT part instead of an UNTIL part.

<296> [Section 2.1.3.2.2.4](#): If **EndType** is 0x00002021, Exchange 2007, Exchange 2007 SP1, and Exchange 2007 SP2 set the UNTIL recurrence part to midnight on the date specified by **EndDate**.

<297> [Section 2.1.3.2.2.4](#): Office Outlook 2003 will export **FirstDOW** as the WKST recurrence part, regardless of whether or not it is relevant.

<298> [Section 2.1.3.2.2.5](#): Office Outlook 2003 does not import or export the X-MICROSOFT-CDO-INTENDEDSTATUS or X-MICROSOFT-MSNCALENDAR-INTENDEDSTATUS properties.

<299> [Section 2.1.3.2.2.5](#): Office Outlook 2003 does not support Yearly Recurrence with an INTERVAL other than 1.

<300> [Section 2.1.3.2.2.5](#): Office Outlook 2003 imports BYMONTHDAY directly into **PatternTypeSpecific.Month.Day**.

<301> [Section 2.1.3.2.2.5](#): Office Outlook 2003 does not import or export the X-MICROSOFT-CDO-INTENDEDSTATUS or X-MICROSOFT-MSNCALENDAR-INTENDEDSTATUS properties.

<302> [Section 2.1.3.2.2.5](#): Office Outlook 2003 exports **PatternTypeSpecific.Month.Day** directly as BYMONTHDAY.

<303> [Section 2.1.3.2.2.5](#): Office Outlook 2007, Outlook 2010, and Outlook 2013 export 0x00002021 **EndType** values as a COUNT part instead of an UNTIL part.

<304> [Section 2.1.3.2.2.5](#): If **EndType** is 0x00002021, Exchange 2007, Exchange 2007 SP1, and Exchange 2007 SP2 set the UNTIL recurrence part to midnight on the date specified by **EndDate**.

<305> [Section 2.1.3.2.2.5](#): Office Outlook 2003 will export **FirstDOW** as the WKST recurrence part, regardless of whether or not it is relevant.

<306> [Section 2.1.3.2.2.6](#): Office Outlook 2003 does not import or export the X-MICROSOFT-CDO-INTENDEDSTATUS or X-MICROSOFT-MSNCALENDAR-INTENDEDSTATUS properties.

<307> [Section 2.1.3.2.2.6](#): Office Outlook 2003 does not support Yearly Recurrence with an INTERVAL other than 1.

<308> [Section 2.1.3.2.2.6](#): Office Outlook 2003 does not import or export the X-MICROSOFT-CDO-INTENDEDSTATUS or X-MICROSOFT-MSNCALENDAR-INTENDEDSTATUS properties.

<309> [Section 2.1.3.2.2.6](#): Office Outlook 2007, Outlook 2010, and Outlook 2013 export 0x00002021 **EndType** values as a COUNT part instead of an UNTIL part.

<310> [Section 2.1.3.2.2.6](#): If **EndType** is 0x00002021, Exchange 2007, Exchange 2007 SP1, and Exchange 2007 SP2 set the UNTIL recurrence part to midnight on the date specified by **EndDate**.

<311> [Section 2.1.3.2.2.6](#): Office Outlook 2003 will export **FirstDOW** as the WKST recurrence part, regardless of whether it is relevant.

<312> [Section 2.1.3.2.4](#): Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not implement this compatibility fix for Office Outlook 2003.

<313> [Section 2.1.3.2.4](#): Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not implement this compatibility fix for Office Outlook 2003.

<314> [Section 2.1.3.2.4](#): Exchange 2003, Exchange 2007, Exchange 2010, and Exchange 2013 do not implement this compatibility fix for Office Outlook 2003.

<315> [Section 2.1.3.3](#): Exchange 2007 sets these additional properties.

## 6 Change Tracking

This section identifies changes that were made to the [MS-OXCICAL] protocol document between the July 2012 and October 2012 releases. Changes are classified as New, Major, Minor, Editorial, or No change.

The revision class **New** means that a new document is being released.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- An extensive rewrite, addition, or deletion of major portions of content.
- The removal of a document from the documentation set.
- Changes made for template compliance.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **Editorial** means that the language and formatting in the technical content was changed. Editorial changes apply to grammatical, formatting, and style issues.

The revision class **No change** means that no new technical or language changes were introduced. The technical content of the document is identical to the last released version, but minor editorial and formatting changes, as well as updates to the header and footer information, and to the revision summary, may have been made.

Major and minor changes can be described further using the following change types:

- New content added.
- Content updated.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.

- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.
- New content added for template compliance.
- Content updated for template compliance.
- Content removed for template compliance.
- Obsolete document removed.

Editorial changes are always classified with the change type **Editorially updated**.

Some important terms used in the change type descriptions are defined as follows:

- **Protocol syntax** refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.
- **Protocol revision** refers to changes made to a protocol that affect the bits that are sent over the wire.

The changes made to this document are listed in the following table. For more information, please contact [protocol@microsoft.com](mailto:protocol@microsoft.com).

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
<a href="#">1.2.2 Informative References</a>	Added the reference [MS-OXPROTO].	N	Content updated.
<a href="#">1.4 Relationship to Protocols and Other Algorithms</a>	Added informative reference information for overview of relationships between this and other protocols.	N	Content updated.
<a href="#">2.1.3.1.1 Component: VCALENDAR</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.4 Property: X-CALEND</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.5 Property: X-CALSTART</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.6 Property: X-CLIPEND</a>	Added Microsoft Exchange Server 2013 and Microsoft Outlook 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.7 Property: X-CLIPSTART</a>	Added Microsoft Exchange Server 2013 and Microsoft Outlook 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.8 Property: X-MICROSOFT-</a>	Added Microsoft Outlook 2013 to behavior note.	Y	Product behavior note



<b>Section</b>	<b>Tracking number (if applicable) and description</b>	<b>Major change (Y or N)</b>	<b>Change type</b>
<a href="#">CALSCALE</a>			updated.
<a href="#">2.1.3.1.1.9</a> <a href="#">Property: X-MS-OLK-FORCEINSPECTOROPEN</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.10</a> <a href="#">Property: X-MS-WKHRDAYS</a>	Added Microsoft Exchange Server 2013 and Microsoft Outlook 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.11</a> <a href="#">Property: X-MS-WKHREND</a>	Added Microsoft Exchange Server 2013 and Microsoft Outlook 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.12</a> <a href="#">Property: X-MS-WKHRSTART</a>	Added Microsoft Exchange Server 2013 and Microsoft Outlook 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.13</a> <a href="#">Property: X-OWNER</a>	Added Microsoft Exchange Server 2013 and Microsoft Outlook 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.13.1</a> <a href="#">Parameter: CN</a>	Added Microsoft Exchange Server 2013 and Microsoft Outlook 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.14</a> <a href="#">Property: X-PRIMARY-CALENDAR</a>	Added Microsoft Exchange Server 2013 and Microsoft Outlook 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.15</a> <a href="#">Property: X-PUBLISHED-TTL</a>	Added Microsoft Exchange Server 2013 and Microsoft Outlook 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.16</a> <a href="#">Property: X-WR-CALDESC</a>	Added Microsoft Exchange Server 2013 and Microsoft Outlook 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.17</a> <a href="#">Property: X-WR-CALNAME</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.18</a> <a href="#">Property: X-WR-RELCALID</a>	Added Microsoft Exchange Server 2013 and Microsoft Outlook 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.19</a> <a href="#">Component: VTIMEZONE</a>	Added Microsoft Exchange Server 2013 and Microsoft Outlook 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.19.1</a> <a href="#">Property: TZID</a>	Added Microsoft Exchange Server 2013 and Microsoft Outlook 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.19.2</a> <a href="#">Component: STANDARD</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note



Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
			updated.
<a href="#">2.1.3.1.1.19.2.1</a> <a href="#">Property: DTSTART</a>	Added Microsoft Exchange Server 2013 and Microsoft Outlook 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.19.2.2</a> <a href="#">Property: RRULE</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.19.3</a> <a href="#">Component: DAYLIGHT</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.1</a> <a href="#">Property: ATTACH</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.1.2</a> <a href="#">Parameter: FMTTYPE</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.1.4</a> <a href="#">Parameter: X-FILENAME</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.2</a> <a href="#">Property: ATTENDEE</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.2.1</a> <a href="#">Parameter: CN</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.2.2</a> <a href="#">Parameter: CUTYPE</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.2.3</a> <a href="#">Parameter: PARTSTAT</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.2.4</a> <a href="#">Parameter: ROLE</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.2.6</a> <a href="#">Parameter: X-MS-OLK-RESPTIME</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.3</a> <a href="#">Property: CATEGORIES</a>	Added Microsoft Exchange Server 2013 and Microsoft Outlook 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.4</a> <a href="#">Property: CLASS</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
			updated.
<a href="#">2.1.3.1.1.20.5</a> <a href="#">Property: COMMENT</a>	Added Microsoft Exchange Server 2013 and Microsoft Outlook 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.6</a> <a href="#">Property: CONTACT</a>	Added Microsoft Exchange Server 2013 and Microsoft Outlook 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.7</a> <a href="#">Property: CREATED</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.8</a> <a href="#">Property: DTEND</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.10</a> <a href="#">Property: DTSTART</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.11</a> <a href="#">Property: DESCRIPTION</a>	Added Microsoft Exchange Server 2013 and Microsoft Outlook 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.11.1</a> <a href="#">Parameter: LANGUAGE</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.13</a> <a href="#">Property: EXDATE</a>	Added Microsoft Exchange Server 2013 and Microsoft Outlook 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.14</a> <a href="#">Property: LAST-MODIFIED</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.15</a> <a href="#">Property: LOCATION</a>	Added Microsoft Outlook 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.15.1</a> <a href="#">Parameter: ALTREP</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.15.2</a> <a href="#">Parameter: LANGUAGE</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.16</a> <a href="#">Property: ORGANIZER</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.18</a> <a href="#">Property: RDATE</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
			updated.
<a href="#">2.1.3.1.1.20.20</a> <a href="#">Property: RECURRENCE-ID</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.21</a> <a href="#">Property: RESOURCES</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.22</a> <a href="#">Property: SEQUENCE</a>	Added Microsoft Outlook 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.24</a> <a href="#">Property: SUMMARY</a>	Added Microsoft Outlook 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.24.1</a> <a href="#">Parameter: LANGUAGE</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.25</a> <a href="#">Property: TRANSP</a>	Added Microsoft Exchange 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.25</a> <a href="#">Property: TRANSP</a>	Added Update Rollup 7 for Exchange 2007 SP3 to product behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.26</a> <a href="#">Property: UID</a>	Added Microsoft Outlook 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.27</a> <a href="#">Property: X-ALT-DESC</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.28</a> <a href="#">Property: X-MICROSOFT-CDO-ALLDAYEVENT</a>	Added Microsoft Exchange Server 2013 and Microsoft Outlook 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.29</a> <a href="#">Property: X-MICROSOFT-CDO-APPT-SEQUENCE</a>	Added Microsoft Exchange Server 2013 and Microsoft Outlook 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.33</a> <a href="#">Property: X-MICROSOFT-CDO-INSTTYPE</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.34</a> <a href="#">Property: X-MICROSOFT-CDO-INTENDEDSTATUS</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.35</a> <a href="#">Property: X-MICROSOFT-CDO-</a>	Added Microsoft Outlook 2013 to behavior note.	Y	Product behavior note

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
<a href="#">OWNERAPPTID</a>			updated.
<a href="#">2.1.3.1.1.20.38</a> Property: X-MICROSOFT-DISALLOW-COUNTER	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.39</a> Property: X-MICROSOFT-EXDATE	Added Microsoft Outlook 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.40</a> Property: X-MICROSOFT-ISDRAFT	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.41</a> Property: X-MICROSOFT-MSNCALENDAR-ALLDAYEVENT	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.42</a> Property: X-MICROSOFT-MSNCALENDAR-BUSYSTATUS	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.43</a> Property: X-MICROSOFT-MSNCALENDAR-IMPORTANCE	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.45.2</a> Parameter: X-MICROSOFT-ISLEAPMONTH	Added Microsoft Outlook 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.46</a> Property: X-MS-OLK-ALLOWEXTERNCHECK	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.47</a> Property: X-MS-OLK-APPTLASTSEQUENCE	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.48</a> Property: X-MS-OLK-APPTSEQTIME	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.49</a> Property: X-MS-OLK-AUTOFILLOCATION	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.50</a> Property: X-MS-OLK-AUTOSTARTCHECK	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.51</a> Property: X-MS-OLK-COLLABORATEDOC	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.52</a> Property: X-MS-OLK-	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note

<b>Section</b>	<b>Tracking number (if applicable) and description</b>	<b>Major change (Y or N)</b>	<b>Change type</b>
<a href="#">CONFHECK</a>			updated.
<a href="#">2.1.3.1.1.20.53</a> <a href="#">Property: X-MS-OLK-CONFTYPE</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.54</a> <a href="#">Property: X-MS-OLK-DIRECTORY</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.55</a> <a href="#">Property: X-MS-OLK-MWSURL</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.56</a> <a href="#">Property: X-MS-OLK-NETSHOWURL</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.57</a> <a href="#">Property: X-MS-OLK-ONLINEPASSWORD</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.58</a> <a href="#">Property: X-MS-OLK-ORGALIAS</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.59</a> <a href="#">Property: X-MS-OLK-ORIGINALEND</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.60</a> <a href="#">Property: X-MS-OLK-ORIGINALSTART</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.61</a> <a href="#">Property: X-MS-OLK-SENDER</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.61.1</a> <a href="#">Parameter: CN</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.1.1.20.62</a> <a href="#">Component: VALARM</a>	Added Microsoft Exchange Server 2013 and Microsoft Outlook 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.2.1.11</a> <a href="#">Recurrence Part: COUNT</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.2.2</a> <a href="#">Recurrence Templates</a>	Added Microsoft Exchange Server 2013 and Microsoft Outlook 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.2.2.1</a> <a href="#">Template: Daily Recurrences</a>	Added Microsoft Exchange Server 2013 and Microsoft Outlook 2013 to behavior	Y	Product behavior note

<b>Section</b>	<b>Tracking number (if applicable) and description</b>	<b>Major change (Y or N)</b>	<b>Change type</b>
	note.		updated.
<a href="#">2.1.3.2.2.2</a> <a href="#">Template: Weekly Recurrences</a>	Added Microsoft Outlook 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.2.2.3</a> <a href="#">Template: Monthly Recurrences</a>	Added Microsoft Outlook 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.2.2.4</a> <a href="#">Template: Monthly Nth Recurrences</a>	Added Microsoft Outlook 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.2.2.5</a> <a href="#">Template: Yearly Recurrences</a>	Added Microsoft Outlook 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.2.2.6</a> <a href="#">Template: Yearly Nth Recurrences</a>	Added Microsoft Outlook 2013 to behavior note.	Y	Product behavior note updated.
<a href="#">2.1.3.2.4</a> <a href="#">Legacy UNTIL Concerns</a>	Added Microsoft Exchange Server 2013 to behavior note.	Y	Product behavior note updated.

## 7 Index

### A

[Applicability](#) 10

### B

[Birthday Calendar for 2008 example](#) 110

### C

[Change tracking](#) 262

### E

Examples

[Birthday Calendar for 2008](#) 110

[overview](#) 110

[Recurring Meeting Scenario](#) 202

[Schedule for the Week of June 16 - 2008](#) 138

[Single Meeting Scenario](#) 177

### G

[Glossary](#) 7

### I

[Implementer - security considerations](#) 241

[Index of security parameters](#) 241

[Informative references](#) 9

[Introduction](#) 7

### N

[Normative references](#) 8

### O

[Overview \(synopsis\)](#) 9

### P

[Parameters - security index](#) 241

[Product behavior](#) 242

### R

[Recurring Meeting Scenario example](#) 202

References

[informative](#) 9

[normative](#) 8

### S

[Schedule for the Week of June 16 - 2008 example](#)

138

Security

[implementer considerations](#) 241

[parameter index](#) 241

[Single Meeting Scenario example](#) 177

[Standards assignments](#) 10

### T

[Tracking changes](#) 262